
THE WIGOONG PRIMER



COOKING, YENTILATION, PEFPIGEPATION, KITCHEN CLEANUP AND OUTDOOP PRODUCTS

FEBRUARY 2008



PROFEGGIONAL PERFORMANCE FOR THE HOME TH

TABLE OF CONTENTS

COOKING PRODUCTS

FREESTANDING RANGES

YGIC GAG 24", 90", 96" AND 46"W. PANGEG	PAGES 1-7
VAIC GAG 90", 96", AND 48"W. GEALED BUPNER PANGEG	PAGES 8-13
VAOC AAO OELF-CLEAN 90", 9G" AND 48"W. PANAEO	PAGES 14-17
VAGO GAG GELF OLEAN 90", 96", AND 46"W. GEALED BUPNEP PANGEG	PAGEG 18-22
VCPC GAG 96", 48" AND GO"W. PANGES	PAGES 23-27
NYCIPC GAG 96", 48" AND GO"W. PANGEG FOR COOKING GCHOOLG	PAGEG 28-92
YDGO DUAL FUEL 90", 96" AND 46"W. PANAEG	PAGE6 99-95
YDGO DUAL FUEL 90", 96" AND 46"W. GEALED BUPNER PANGE	PAGEG 96-41
VEGO ELECTRIO 90"W. PANCE AND ACCEGGORY	PAGE 42

BUILT-IN GUPFACE COOKING

YGRT 24", 90", 96", 42", 46" AND 60"W. PANGETOP6	PAGES 49-49
DART 24", 90", 96"W. RANAETOP9	PAGES 46
VGPT 90", 96", 48"W. GEALED BUPNEP PANGETOPS	PAGEG 50-59
VERT 90"W. ELECTRIC PANCIETOP AND ACCEGGORY	PAGE 54
YCRT 90"W. ELECTRIC INDUCTION/RADIANT RANGETOR	PAGE 55
YIRT 90"W. ELECTRIC ALL INDUCTION PANGETOP	PAGE 50
DEPT 90" AND 96" W. ELECTPIC PADIANT PANGETOP	PAGE 57
PANGE AND PANGETOP INSTALLATION ACCESSOPIES	PAGEG 58-59
PANGE AND PANGETOP SUPFACE COOKING ACCESSOPIES	PAGES 61-69
VGGU PROFEGGIONAL 90" AND 96"W. GAG COOKTOPG	PAGE 64
DG6U DE6KNER 90" AND 96"W. GA6 COOKTOP6	PAGE 05
DGCU DEGIGNER 90", 96" AND 45"W. GAG 600KTOPG	PAGE 66
VECU PROFEGGIONAL 90" AND 96"W. ELECTRIC RADIANT COOKTOP	PAGE 67
VCCU PPOFEGGIONAL 90" AND 96"W. ELECTPIC INDUCTION/PADIANT COOKTOPG	PAGE 68
YICU PP-OFE99IONAL 90" AND 96"W. ALL INDUCTION COOKTOP9	PAGE 69
DECU DEGICNEP 90", 96" AND 45"W. ELECTPIC PADIANT COOKTOPG	PAGE 70
PROFEGGIONAL COOKTOP ACCEGGORIEG	PAGE 71
DEGIGNER COOKTOP ACCEGGORIEG	PAGE 72

BUILT-IN WALL OVENS

YEGO ELECTPIC 27", 90" AND 96"W. GINGLE OVENG	PAGE 79, 74, 78
YEDO ELECTPIC 27", 90", AND 96"W. DOUBLE OVENO	PAGE 79, 74, 78
DEGO ELECTRIC 27" AND 90" W. GINGLE OVENG	PAGE 75,76,77,77
DEDO ELECTRIC 27" AND 90"W. DOUBLE OVENS	PAGE 76,76,77,78
ELECTRIC OVEN ACCESSORY	PAGE 80
VGOO GAO 96"W. GINGLE OVEN AND ACCEGGOPIEG	PAGE 81
VCGO COMBI GTEAM/CONVECTION OVENG AND ACCEGGOPIEG	PAGEG 82-89
VHGO HIGH GPEED CONVECTION OVEN AND TRIM FITG	PAGE 84
VMOG PROFEGGIONAL MICROWAVE OVENG AND TRIM KITG	PAGE 85
DMOG DEGIGNER MICROWAVE OVENG AND TRIM KITG	PAGE 85
VMOC PROFEGGIONAL CONVECTION MICROWAVE OVENG AND TRIM HITG	PAGE 86
DMOC DEGIGNER CONVECTION MICROWAVE OVENG AND TRIM HITG	PAGE 86
VMOR PROFEGGIONAL CONVECTION MICROWAVE HOODS	PAGE 87
DMOR DEGIGNER CONVECTION MICROWAVE HOODS	PAGE 87
VEWD PROFEGGIONAL 27", 90" AND 96"W. WARMING DRAWERG	PAGE 88
DEWD DEGIGNER 27" AND 90"W. WARMING DRAWERG	PAGE 88
DFWD FULL OVERLAY 27", AND 90"W. WARMING DRAWERG	PAGE 88
WARMING DRAWER ACCEGGORIEG	PAGE 89
YMWC PROFEGGIONAL 27", 90" AND 96"W. MULTI-UGE CHAMBERG	PAGE 90
DMWC DEGIGNER 27" AND 90"W. MULTI-UGE CHAMBERG	PAGE 90

TABLE OF CONTENTS CONT.

YENTILATION PRODUCTS

1	
PPOFEGGIONAL INTERIOR POWER 24", 90", AND 96"W./10"H. WALL HOOD	PAGE 92
DEGICNER 90" AND 96"W. I 2"H. INTERIOR POWER WALL HOODG	PAGE 99
PP-OFE6610NAL 24", 90", 96", 42", 48", 54", 60", AND 66"W. WALL HOOD	PAGE 94
PP-OFE9910NAL 90", 96", 42", 48", 54", 60", AND 66"W. CHIMNEY WALL HOODS	PAGE 95
DEGIGNER CLAGGIC CHIMNEY WALL HOODG	PAGE 96
PP-OFE9910NAL 19LAND H00D9 AND BUILT-IN CUSTOM VENTILATOR 9Y9TEM9	PAGE 97
PP-OFE9910NAL CHIMNEY 19LAND H00D9	PAGE 98
DEGIGNER WALL HOODG	PAGE 99
DEGIGNER CUGTOM VENTILATOR GYGTEMG	PAGE 100
HOOD ACCEGGOPIEG	PAGES 100-102
PP-OFE9910NAL AND DE91GNEP DOWNDP-AFT9	PAGE 104
DOWNDRAFT ACCEGGORIEG	PAGE 105
PROFEGGIONAL AND DEGIGNER HOOD/VENTILATOR FIT DATA	PAGES 106-108

PEFPIGEPATION PRODUCTS

21GEPATION PPODUCTO	
VCBB PROFESSIONAL, DDBB DESIGNER, DFBB FULL OVERLAY 96"W.	
BOTTOM-MOUNT PEFPIGEPATOP/FPEEZERG	PAGE 110
VCGB PROFEGGIONAL, DDGB DEGIGNER AND DFGB FULL OVERLAY	
42"W. ODE-BY-ODE REFRIGERATOR/FREEZERO	PAGEIII
VCOB PROFEOGIONAL, DOOB DEGIGNER, DFOB FULL OVERLAY 42"W. GIDE-BY-GIDE	
PEFPICEPATOR/FREEZERO WITH ICE AND WATER DIOPENOERO	PAGE 112
YOU'D PROFEGGIONAL, DOUBD DEGIONER AND DEOD FULL OVERLAY	
48"W. GIDE-BY-GIDE PEFPICEPATOR/FREEZERG	PAGE 112
VCGB PROFEGGIONAL, DDGB DEGIGNER, DFGB FULL OVERLAY 46"W.	
GIDE-BY-GIDE PEFFLICERATOR/FREEZERG WITH ICE AND WATER DIGPENGERG	PAGE 114
VCPB PROFESSIONAL, DCPB DESIGNER, DFRB FULL OVERLAY 90"W.	
ALL PEFPIGEPATORS	PAGE 115
VCPB PROFESSIONAL, DCPB DESIGNER, DFRB FULL OVERLAY 96"W. ALL REFRIGERATORS	PAGE 116
VCFB PROFEGGIONAL, DDFB DEGIGNER, DFFB FULL OVERLAY 90"W. ALL FREEZERG	PAGE 117
VCFB PROFEGGIONAL, DDFB DEGIGNER, DFFB FULL OVERLAY 96"W. ALL FREEZERG	PAGE 118
BUILT-IN PEFPICEPATOR/FREEZER ACCEGGORIEG	PAGES 119-120
VCBF PROFESSIONAL AND DDBF DESIGNER 96" FREESTANDING	
PEFPIGEPATOR/FPEE2ER6	PAGE 121
VCFF PROFEGGIONAL AND DOFF DEGIGNER 96" FREEGTANDING FRENCH-DOOR	
PEFPIGERATOR/FREEZERO	PAGE 122
VCGF PROFEGGIONAL AND DDGF DEGIGNER 9G" FREEGTANDING GIDE-BY-GIDER	
PEFPIGEPATOR/FREEZERG	PAGE 129
VCGF PROFEGGIONAL AND DDGF DEGIGNER 9G" FREEGTANDING GIDE-BY-GIDER	
WITH IOE AND WATER DISPENSERS REFRIGERATOR/FREEZERS	PAGE 124
FREESTANDING REFRIGERATOR ACCESSORIES	PAGE 124-126
VCWB PROFEGGIONAL, DDWB DEGIGNER, AND DFWB 90"W. FULL-HEIGHT WINE CELLARG	PAGE 127
BUILT-IN FULL HEIGHT WINE CELLAR ACCEAGORIEG	PAGE 128
VUAR PROFEGGIONAL, DUAR DEGIGNER, DFUR FULL OVERLAY I 5"W.	
UNDERCOUNTER/FREEGTANDING REFRIGERATED BEVERAGE CENTERG	PAGE 129
VUAR PROFEGGIONAL, DUAR DEGIGNER, DFUR FULL OVERLAY 2 4 "W.	
UNDEP-COUNTEP-/FP-EEGTANDING PEFP-IGEP-ATED BEYEP-AGE CENTEP-G	PAGE 190
VUPI PPOFEGGIONAL, DUPI DEGIGNEP, DFPI FULL OVEPLAY 2 4"W.	
UNDER-COUNTER/FREESTANDING REFRIGERATED BEVERAGE CENTER/ICE MAKERS	PAGE 191
VURD PROFEGGIONAL, DURD DEGIGNER, DFRD FULL OVERLAY 2 4"W.	
COMBINATION PEFPICIEPATED DPAWERG/ACCEGGOPIEG	PAGE 192
YUWC PROFEGGIONAL, DUWC DEGIGNER, DFWC FULL OVERLAY I 5"W.	
UNDER-COUNTER-PREESTANDING WINE CELLARS	PAGE 199
YUWO PROFEGGIONAL, DUWO DEGIGNER, DFWO FULL OVERLAY 24"W.	
UNDER-COUNTER/FREESTANDING WINE CELLARS	PAGE 194
YUIM PROFEGGIONAL, DUIM DEGIGNER UNDERCOUNTER/FREEGTANDING ICE MACHINE	PAGE 195
to allow the second of the second of a second of the secon	

PAGE 196


PEFPIGERATED BEVERAGE CENTER/WINE CELLAR ACCESSORIES

TABLE OF CONTENTS CONT.

FITCHEN CLEANUP

1 1 0 1 - 1 0 - 2 1 1 1	
DFUD PROFEGGIONAL, DEGIGNER AND FULL OVERLAY	
UNDERCOUNTER DIGHWAGHERG	PAGE 198
UNDERCOUNTER DIGHWAGHER ACCEGGORIEG	PAGE 199
YUC PROFEGGIONAL, DUC DEGIGNER AND DFC FULL OVERLAY	
TRAGH COMPACTORG	PAGE 140
TRAGH COMPACTOR ACCEGGORIEG	PAGE 141
YOFW AND YEFW HEAVY FOOD WAGTE DIGPOGERG	PAGE 142
HEAVY DUTY FOOD WASTE DISPOSED ACCESSOPIES	PAGE 149
OUTDOOR PRODUCTS	
T-GERIEG 90", 41" AND 59" OUTDOOK GAS GRILLS	PAGE 145
T-GERIEG 4 1" AND 57" OUTDOOR GAS GRILLS	
TRUGEAR INFRARED BURNER	PAGE 146
E-GERIEG 90", 41" AND 59" OUTDOOR GAG GRILLG	PAGE 147
E-9EPIEG 4 1" AND 59" OUTDOOP GAG GPILLG	
TRUGEAR INFRARED BURNER	PAGE 148
T-GERIEG 90"W. OUTDOOR PREMIUM GAG CRILL	PAGE 149
CRILL CARTO	PAGE 150
59"W. GRILL CART WITH GAS OVEN	PAGE 151
GAG GRILL ACCEGGORIEG	PAGE 152-155
VC96 C4 TM OUTDOOR COOKER AND CARTE	PAGE 150
C4 OUTDOOR COOKER ACCESSORIES	PAGE 157
VEOG 90"W. ELECTRIC GMOKER OVEN AND VAGO OUTDOOR GAG OVEN	PAGE 158
BUILT-IN SIDE BURNERS/INFRARED ARILLERS	PAGE 159
VEWO 27", 90" AND 96"W. OUTDOOR WARMING DRAWERG	
AND ACCEGGORY	PAGE 160
BUILT-IN 27", 90" AND 96"W. OUTDOOR STORAGE DRAWERS	
AND ACCESS DOORS	PAGE 161
OUTDOOK GTAINLEGG GTEEL CABINETG	PAGE 162
OUTDOOR GTAINLEGG GTEEL CABINETG INGTALLATION ACCEGGORIEG	PAGE 169
OUTDOOR OVEN GTORAGE BAGEG AND REFRIGERATION BAGEG	PAGE 164
VWH OUTDOOR WALL HOODS AND ACCESSORY	PAGE 165-160
BUILT-IN AND PORTABLE 2 4" AND 4 I "W. PEFREGHMENT CENTERG	PAGE 167
YUAP 15" AND 24"W. OUTDOOR PEFPIGERATED BEVERAGE CENTERS	PAGE 168
VUIM 15"W. OUTDOOR UNDERCOUNTER/FREEGTANDING ICE MACHINE	
AND ACCEOGORY	PAGE 168
VRBO 2 4"W. PORTABLE REFRIGERATED BEVERAGE DIGPENGERG	PAGE 169
YUBO 2 4 "W. UNDERGOUNTER PEFRIGERATED BEVERAGE DIGPENGERG	PAGE 170
PEVERAGE DISPENSER ACCESSORIES	PAGE 171

VIOSOONG



PROFEGGIONAL AND DEGIGNER GOOKING PRODUCTS

Y416245-45

- · 4-15,000 BTU 66 BUPNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · DPIP TRAY WITH POLLER BEARING GLIDES \$ 2 QT. DRIP PAN
- · EXCLUSIVE COMBINATION OF SINGLE BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · GIX FUNCTIONO NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRA-PED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROOT
- · LAPGE CONVECTION OVEN
 - · OVERALL 18"W. X 16 1/8"H. X 1834"D. 3.1 CUBIC FEET
 - · AHAM 18"W. X 161/8"H. X 175/8"D. 9.0 CUBIC FEET
 - · THREE HEAVY-DUTY RACKO/GIX POGITIONG
- · GHIPPED WITH 6"H. GG BACKGUARD
- · STANDARD KICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY SURFACE/TUBE BURNERS


V4162454

- · 2 4"W. THEPMOSTATICALLY CONTPOLLED STEEL APIDDLE/SIMMEP PLATE (SEPARATE BURNER/CONTROL FOR THE LEFT AND PIGHT SIDE)
- · DPIP TRAY WITH POLLER BEARING GLIDEG \$ 2 AT. DRIP PAN
- · EXCLUSIVE COMBINATION OF SINGLE BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · SIX FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRA-PED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · LAPGE CONVECTION OVEN
 - · OYERALL 18"W. X 161/0"H. X 1834"D. 9.1 CUBIC FEET
 - · AHAM 18"W. X 161/8"H. X 175/8"D. 3.0 CUBIC FEET
 - · THREE HEAVY-DUTY RACKO/OIX POOITIONS
- · GHIPPED WITH 6"H. GG BACKGUAPD
- · GTANDARD FICKOPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORGELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFAGE/TUBE BURNERG


V416245A

- · 2 4 "W. APILL WITH FLAYOR GENERATOR PLATED AND AUTOMATIC IGNITION/RE-IGNITION
- · DPIP TRAY WITH POLLER BEARING GLIDES \$ 2 AT. DRIP PAN
- · EXCLUSIVE COMBINATION OF SINGLE BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · GIX FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHY-DRATE AND CONVECTION DEFROST
- · LAPGE CONVECTION OVEN
 - · OYEPALL 18"W. X 161/8"H. X 1834"D. 9.1 CUBIC FEET
 - · AHAM 18"W. X 161/6"H. X 175/6"D. 9.0 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG
- · GHIPPED WITH 6"H. GG BACKGUAPD
- · OTANDARD FICKOPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG

24"
WIDE
-VGICFREESTANDING
GAS RANGES
(24" DEPTH)



24" GRIDDLE/SIMMER



2 4" WIDE GEILL




V416245K

- · 27,500 BTU PORCELAIN/CAST IRON BURNER WITH AUTOMATIC IGNITION/RE-IGNITION
 - · 20" STEEL WOK/TOP STANDARD
 - · EXCLUDIVE AGENCY CERTIFIED CENTER-TRIVET

ALLOWS USE OF LARGE STOCK POTS

- · DPIP TRAY WITH POLLER BEARING GLIDES \$ 2 9T. DRIP PAN
- · EXCLUSIVE COMBINATION OF SINGLE BAKE BURNERS AND INFRARED BROIL BURNER. ALL WITH AUTOMATIC IGNITION
- · SIX FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRA-PED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · LAPGE CONVECTION OVEN
 - · OVERALL 18"W. X 161/8"H. X 18%"D. 9.1 CUBIC FEET
 - · AHAM 18"W. X 101/0"H. X 175/0"D. 2.0 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONS
- · SHIPPED WITH 6"H. SS BACKGUARD
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORGELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFAGE/TUBE BURNERG



YAIC SEPIES PANAES

- · 6"H. 90 BACKGUARD 10 OHPPED AUTOMATICALLY WITH 24"

 AND 90" PANGEO, BUT NOT WITH 96"W. OP 46"W. PANGEO.

 EITHER A BACKGUARD, HIGH-OHELF, OR 10LAND TRIM MUOT

 BE UDED FOR ALL INOTALLATIONO.
- · OHIPPED OTANDARD FOR NATURAL GAO; FIELD CONVERT TO LP/PROPANE WITH ACCEGOORY FIT (LPFRR/LPFOBER)
 - · 4 FOOT CORD INCLUDED WITH PANGE
 - · 2 WIPE WITH GROUND/9 PRONG PLUG
 - · 120 V/60 HZ

OPEN AND SEALED BUPNER MODELS - MAXIMUM AMPS

- · 24"W. PANGEO: 45 4.9; 4-11.5; 9-4.9; K-4.9
- · 90"W. PANGES: 45 8.2
- · 96"W. PANGEO: 6B 8.5; 44 11.8; 49 8.5
- · 40"W. FANGEO: 64-16; 69-12.4; 44-19.7; 449-16; 49-12.4

FINIOH DETAILS

NOTE: PARTO LIOTED BELOW MAY NOT BE
APPLICABLE TO ALL MODELO. OTAINLEGO OTEEL (OO), BLACK
(BK), ALMOND (AL), BIOCUIT (BT), OTONE CRAY (OC), CRAPHITE
CRAY (CA), BURGUNDY (BU), LEMONADE (LE), MINT JULEP (MJ),
FOREOT CREEN (FA), VIKING BLUE (VB), COBALT BLUE (CB) AND
ECCPLANT (EP).

- · FINIGH DEGICNATEG DOOR FRONT, LOWER FRONT PANEL, GIDE PANELG AND PORCELAIN TOP/GRATE GUPPORTG AND BURNER BOWLG
- · BLACK PORCELAIN TOP/GRATE SUPPORT ON 24"W. WOR RANGE
- · OTAINLEOO OTEEL AND BURGUNDY UNITO HAVE BLACK PORCELAIN TOP/GRATE OUPPORTO AND BURNER BOWLO
- · ALL FINIOHEO HAVE BLACK PORCELAIN CRATEO, BLACK PORCELAIN BURNER CAPO, AND BLACK KNOBO/OWITCHEO.
- · WHITE (WH)

· FINIOH DEOLGNATEO DOOR FRONT, LOWER FRONT PANEL, OIDE PANELO,

KNOBO/OWITCHEO, PORCELAIN TOP/CRATE OUPPORTO AND BURNER

BOWLS

· HAS DARK CRAY PORCELAIN CRATES AND DARK CRAY PORCELAIN BURNER

CAPO.

- · ALL FINIOHEO HAVE OTAINLEOO OTEEL

 HANDLE/CHPOME PLATED BRACKETO, DRIP TRAY PULL/
 TRIM, CONTROL PANEL AND LANDING LEDGE.
- · BPAGG TPIM OPTION (BP) INCLUDEG

 NAMEPLATE, WINDOW TPIM, DOOP HANDLE, DPIP TPAY

 PULL/TPIM BELOW CONTROL PANEL, MOB BEZELG,

 THERMAL-CONVECTION GWITCH BEZEL AND CRATE

 GUPPORT GIDE TRIM. GUPER DURABLE, LONG LAGTING

 BPAGG FINIGH ON ALL "HIGH TRAFFIC" PARTG (HANDLE

 AND DRIP TRAY PULL/TRIM BELOW CONTROL PANEL); ALL


 OTHER PARTG HAVE A DURABLE PROTECTIVE COAT
 ING. ALL PARTG DEGICNED FOR MAINTENANCE-FREE


 NORMAL UGE
- · ALL MODELO AVAILABLE AO LP (ADD LP AFTER COLOR CODE)

Y416306-4B


- · 4-1 5,000 BTU 66 BUPNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUDIVE YAPIGIMMERTM SETTING FOR ALL BURNERS
- · CENTER ARATE ALLOWS MOVEMENT OF COOKING VESSELS ACROSS ENTIRE TOP SURFACE
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DRIP TRAY WITH ROLLER BEARING GLIDES \$ 2 9T. DRIP PAN
- · EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRA-PED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · OIX FUNCTIONO NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEFROOT
- · EXTREMELY LARGE CONVECTION OVEN
 - · OVERALL 2 7"W. X 1 6 1/8"H. X 1 8 34"D. 4.1 CUBIC FEET
 - · AHAM 27"W. X 16 1/0"H. X 17"D. 7.7 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG
 - · TWO HALOGEN LIGHTS
- · SHIPPED WITH 6"H. SS BACKGUARD
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAP LIMITED WAPPANTY POPGELAIN OVEN; FIVE-YEAP LIMITED WAPPANTY - GUPFAGE/TUBE BUPNERG


30"
WIDE
WIDE
VGIC
FREESTANDING
GAS RANGE
(24" DEPTH)





36TE WIDE WIDE WGICFREESTANDING FREESTANDING GAS RANGES GAS RANGES (24T DEPTH)






V416966-63

- · 6-1 5,000 BTU 66 BUPNERS WITH POPCELAIN/CAST IPON CAPS AND AUTOMATIC IGNITION/PE-IGNITION
- · EXOLUGIVE VARIGIMMERTM GETTING FOR ALL BURNERG
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TPAY WITH POLLER BEARING GLIDEG \$ 2 9T. DPIP PAN
- · EXOLUGIVE COMBINATION OF DUAL BAKE BUPNEPS AND INFRAPED BROIL BUPNEP, ALL WITH AUTOMATIC IGNITION
- · OIX FUNCTIONO NATUPAL AIRFLOW BAKE, CONVECTION BAKE, INFRAPED BROIL, CONVECTION INFRAPED BROIL, CONVECTION DEHYDRATE AND

CONVECTION DEFPOST

- · LAPGE CONVECTION OVEN
- · OYEPALL 29"W. X 16 1/8"H. X 18 3"D. 5.1 CUBIC FEET
- · AHAM 29"W. X 10 1/0"H. X 17"D. 4.0 CUBIC FEET
- · THREE HEAVY-DUTY RACKG/GIX POGITIONG
- · TWO HALOGEN LIGHTS
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY - GURFACE/TUBE BURNERG






V416766-44

THERMOSTATICALLY
CONTROLLED STEEL
CRIDDLE/SIMMER PLATE

1416766-44 \$ 1416766-49

- · 4-15,000 BTU 90 BURNERO WITH PORCELAIN/ CAOT IRON CAPO AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUDIVE VARIOIMMERM DETTING FOR ALL BURN-
- · PEMOVABLE POPCELAIN BUPNER BOWLG
- · DPIP TRAY WITH POLLER BEARING GLIDES \$ 2 9T. DRIP PAN
- · EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTO-MATIC ICNITION
- · OIX FUNCTIONO NATURAL AIRFLOW BAKE, CON-VECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROOT
- · LAPGE CONVECTION OVEN
- · OYEPALL 29"W. X | 6 1/6"H. X | 6 3"D. 5. | CUBIC FEET
- · AHAM 29"W. X 16 1/8"H. X 17"D. 4.6 CUBIC FEET
- · THREE HEAVY-DUTY RACKG/GIX POGITIONG
- · TWO HALOGEN LIGHTS
- · STANDARD KICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORGELAIN OVEN; FIVE-YEAR LIMITED WARRANTY - SURFAGE/TUBE BURNERS





VAIC 9 66-49
1 2 "W. APILL WITH
FLAYOR GENERATOR
PLATE &
AUTOMATIC IGNITION

48" WIDE -VGICFREESTANDING GAS RANGES (24" DEPTH)

1416486-64


- · G- I 5,000 BTU 66 BUPNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2 "W. THEPMOSTATICALLY CONTROLLED STEEL CRIDDLE/SIMMER PLATE
- · EXCLUSIVE VARISIMMERTM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH ROLLER BEARING GLIDES \$ 2 GT. DRIP PAN
- · PICHT OVEN EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · OIX FUNCTIONO NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRA-PED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROOT
- · PIGHT OVEN LAPGE CONVECTION CAVITY
 - · OYEPALL 27"W. X 16 1/8"H. X 18 34"D. 4.0 CUBIC FEET
 - · AHAM 20"W. X 10 1/0"H. X 17"D. 2.7 CUBIC FEET
 - · THREE HEAVY-DUTY RACKS/GIX POSITIONS AND TWO HALOGEN


LIGHTS


- · LEFT BAKE OVEN (AUTO. IGNITION)
 - · OVERALL 12 1/0"W. X 16 1/0"H. X 18 3"D. 2.1 CUBIC FEET
 - · AHAM | 2 1/0"W. X | 6 1/0"H. X | 8 1/0"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKO/GIX POGITIONG AND TWO HALOGEN

LIGHTS

- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG









VUICA86-60

- · G- I 5,000 BTU 66 BUPNEP6 WITH POPCELAIN/CAST IPON CAPS AND AUTOMATIC IGNITION/PE-IGNITION
- · I 2"W. APILL WITH FLAVOR AENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUSIVE VARISIMMERM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNEP BOWLG
- · DPIP TRAY WITH ROLLER BEARING GLIDEG \$ 2 AT. DRIP PAN
- · PIGHT OVEN EXCLUGIVE COMBINATION OF DUAL BAKE BURNERG AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · OIX FUNCTIONO NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRA-PED BROIL, CONVECTION INFRAPED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROOT
- · PIGHT OVEN LAPGE CONVECTION CAVITY
 - · OVERALL 29"W. X 16 1/0"H. X 18 4"D. 4.0 CUBIC FEET
 - · AHAM 2 7"W. X 1 6 1/0"H. X 1 7"D. 7.7 CUBIC FEET
 - · THREE HEAVY-DUTY RACKO/GIX POGITIONG AND TWO HALOGEN

LIGHTS


- · LEFT BAKE OVEN (AUTO. IGNITION)
 - · OVERALL 13% 8"W. X 161/8"H. X 184"D. 2.1 CUBIC FEET
 - · AHAM 19% (8"W. X 161/6"H. X 1834"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKS/GIX POSITIONS
- · GTANDARD KICKGPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORGELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFAGE/TUBE BURNERG


V416486-44


- · 4-15,000 BTU 66 BUPNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 2 4"W. THERMOSTATICALLY CONTROLLED STEEL ARIDDLE/SIMMER PLATE (GEPARATE BURNER/CONTROL FOR THE LEFT AND PIGHT SIDE)
- · EXCLUSIVE YAPISIMMERTM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DRIP TRAY WITH ROLLER BEARING GLIDEG \$ 2 QT. DRIP PAN
- · PIGHT OVEN EXCLUSIVE COMBINATION OF DUAL BAKE
- BUPNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · OIX FUNCTIONO NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROOT
- · PIGHT OVEN LAPGE CONVECTION CAVITY
 - · OYEPALL 27"W. X 16 1/8"H. X 18 4"D. 4.0 CUBIC FEET
 - · AHAM 2 3"W. X 1 6 1/0"H. X 1 7"D. 3.7 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG AND TWO HALOGEN


LIGHTS

- · LEFT BAKE OYEN (AUTO. IGNITION)
 - · OYEPALL 13% 8"W. X 161/8"H. X 1834"D. 2.1 CUBIC FEET
 - · AHAM 199/0"W. X 101/0"H. X 1834"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG
- · STANDARD KICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARPANTY PORCELAIN OYEN; FIVE-YEAR LIMITED WAR-PANTY - GURFACE/TUBE BURNERG









V416486-449

- · 4-15,000 BTU 66 BURNERO WITH PORCELAIN/CAGT IRON CAPO AND AUTO-MATIC IGNITION/RE-IGNITION
- · I 2"W. THEPMOGTATICALLY CONTROLLED GTEEL GRIDDLE/GIMMER PLATE
- · 1 2 "W. APILL WITH FLAYOR GENERATOR PLATED AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUGIVE YAPIGIMMERM GETTING FOR ALL BURNERG
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH POLLER BEARING GLIDES \$ 2 9T. DRIP PAN
- · PIGHT OVEN EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · OIX FUNCTIONO NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROOT
- · PIGHT OVEN LAPGE CONVECTION CAVITY
 - · OVERALL 27"W. X 1 6 1/0"H. X 1 8 34"D. 4.0 CUBIC FEET
 - · AHAM 20"W. X 16 1/0"H. X 17"D. 9.7 CUBIC FEET
 - · THPEE HEAVY-DUTY PACKG/GIX POGITIONG AND TWO HALOGEN LIGHTG
- · LEFT BAKE OVEN (AUTO. IGNITION)
 - · OYEPALL 199/8"W. X 161/8"H. X 1834"D. 2.1 CUBIC FEET
 - · AHAM 199/8"W. X 161/8"H. X 184"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG
- · OTANDAPD FICKOPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WAR-RANTY - GURFACE/TUBE BURNERG

Y416308-4B

· EXCLUGIVE YOHM PRO GEALED BURNER GYGTEM (VARIGIMMERM TO HIGH) - COM-BINATION OF UNIQUE PATENTED BURNER AND TOP DEGIGN PROVIDE CLEANABIL-ITY PLUG GUPERIOR

PERFORMANCE AT SIMMER AND HIGH

- · 4-15,000 BTU BRAGG GEALED BURNERG WITH POPCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/PE-IGNITION
- · EXCLUSIVE VARISIMMER SETTING FOR ALL BURNERS
- · EXCLUSIVE ONE-PIECE TOOLED AND POPCELAINIZED
- COOKING SUPFACE CONTAINS SPILLS FOR EASY CLEANING
- · CENTER ARATE ALLOWS MOVEMENT OF COOKING VESSELS ACROSS ENTIRE TOP SURFACE
- · EXCLUGIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · GIX FUNCTIONG NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL,


CONVECTION DEHYDRATE AND


CONVECTION DEFPOST

- · EXTREMELY LARGE CONVECTION OVEN
 - · OVERALL 20"W. X 161/8"H. X 18 3"D. 4.1 CUBIC FEET
 - · AHAM 20"W. X 16 1/0"H. X 17"D. 9.7 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG
 - · TWO HALOGEN LIGHTS
- · GHIPPED WITH 6"H. GG BACKGUARD
- · STANDARD KICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORGELAIN OVEN; FIVE-YEAR LIMITED WARRANTY - GURFAGE/TUBE BURNERG

WIDE

-VGICFREESTANDING GAS
SEALED BURNER
RANGE
(24" DEPTH)





V416968-61

· EXCLUSIVE YOUTH PRO SEALED BURNER SYSTEM (VARISHMERT TO HIGH) COMBINATION OF UNIQUE PATENTED BURNER AND TOP DESIGN PROVIDE
CLEANABILITY PLUS SUPERIOR


PERFORMANCE AT SIMMER AND HIGH

- · 6- I 5,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUSIVE VARISIMMER SETTING FOR ALL BURNERS
- · EXCLUGIVE ONE-PIECE TOOLED AND POPCELAINIZED

 COOKING GUPFACE CONTAING SPILLS FOR EAGY CLEANING
- · EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · GIX FUNCTIONG NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL,

CONVECTION DEHYDRATE AND CONVECTION DEFROST

- · EXTREMELY LARGE CONVECTION OVEN
 - · OVERALL 29"W. X 161/0"H. X 18 3"D. 5.1 CUBIC FEET
 - · AHAM 29"W. X 16 1/0"H. X 17"D. 4.6 CUBIC FEET
 - · THREE HEAVY-DUTY RACKO/GIX POGITIONG
 - · TWO HALOGEN LIGHTS
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WAR-RANTY - GURFACE/TUBE BURNERG



V416768-44


· EXOLUGIVE YOHM PRO SEALED BURNER SYSTEM (VARISIMMERM TO HIGH) -COMBINATION OF UNIQUE PATENTED BURNER AND TOP DESIGN PROVIDE CLEANABILITY PLUS SUPERIOR


PERFORMANCE AT SIMMER AND HIGH

- · 4-15,000 BTU BRAGG GEALED BURNERG WITH ORGELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2 "W. THERMOSTATICALLY CONTROLLED STEEL GRIDDLE/SIMMER PLATE
- · DPIP TPAY WITH POLLER BEAPING GLIDEG \$ 2 AT. DPIP PAN
- · EXCLUGIVE YAPIGIMMER GETTING FOR ALL BURNERS
- · EXCLUSIVE ONE-PIECE TOOLED AND POPCELAINIZED

 COOKING SUPFACE CONTAINS SPILLS FOR EASY CLEANING
- · EXCLUGIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · GIX FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL,
- CONVECTION DEHYDRATE AND CONVECTION DEFROGT
- · EXTREMELY LARGE CONVECTION OVEN
 - · OVERALL 29"W. X 161/0"H. X 184"D. 5.1 CUBIC FEET
 - · AHAM 29"W. X 101/0"H. X 17"D. 4.0 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG
 - · TWO HALOGEN LIGHTS
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG

36 PERIODE WIDE GAS GAS EREESTANDING GAS BURNER SEALED BURNER RANGES RAN





V416768-49

- · EXCLUGIVE YOUTH PRO GEALED BURNER GYGTEM (VARIGIMMERTH TO HIGH) -COMBINATION OF UNIQUE PATENTED BURNER AND TOP DEGIGN PROVIDE CLEANABILITY PLUG GUPERIOR
- PERFORMANCE AT SIMMER AND HIGH
- · 4-15,000 BTU BRAGG GEALED BURNERG WITH POPCELAIN/CAGT IPON CAPG AND AUTOMATIC IGNITION/PE-IGNITION
- · 1 2"W. APILL WITH FLAYOR GENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION
- · DPIP TRAY WITH POLLER BEARING GLIDEG \$ 2 QT. DRIP PAN
- · EXOLUGIVE VARIGIMMER GETTING FOR ALL BURNERG
- · EXCLUGIVE ONE-PIECE TOOLED AND POPCELAINIZED

 COOKING GUPFACE CONTAING SPILLS FOR EAGY CLEANING
- · EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- \cdot 6IX FUNCTION6 NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL,
- CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · EXTREMELY LARGE CONVECTION OVEN
 - · OVERALL 29"W. X 161/0"H. X 1834"D. 5.1 CUBIC FEET
 - · AHAM 29"W. X 101/0"H. X 17"D. 4.6 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG
 - · TWO HALOGEN LIGHTS
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WAR-RANTY - GURFACE/TUBE BURNERG

36"
WIDE
-VGICFREESTANDING GAS
SEALED BURNER
RANGES
(24" DEPTH)





48" WIDE -VGIC-

FREESTANDING GAS SEALED BURNER RANGES

V416488-64

- · EXCLUDIVE YOH™ PRO DEALED BURNER DYOTEM

 (VARIBINMER™ TO HIGH) COMBINATION OF UNIQUE


 PATENTED BURNER AND TOP DEDIGN PROVIDE


 CLEANABILITY PLUD DUPERIOR PERFORMANCE AT DIMMER


 AND HIGH
- · 6-15,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2 "W. THEPMOSTATICALLY CONTROLLED STEEL CRIDDLE/SIMMER PLATE
- · EXOLUGIVE VARIGIMMER GETTING FOR ALL BURNERS
- · EXCLUGIVE ONE-PIECE TOOLED AND POPCELAINIZED COOKING GURFACE CONTAING SPILLS FOR EASY CLEANING
- · DPIP TRAY WITH ROLLER BEARING GLIDES \$ 2 9T. DRIP PAN
- · EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · SIX FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRA-PED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · PIGHT OVEN LAPGE CONVECTION OVEN
 - · OVERALL 29"W. X 161/0"H. X 1834"D. 4.0 CUBIC FEET
 - · AHAM 2 9"W. X 1 61/6"H. X 1 7"D. 9.7 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG AND TWO HALOGEN


LIGHTS

- · LEFT BAKE OVEN (AUTO. IGNITION)
 - · OVERALL 121/8"W. X 161/8"H. X 184"D. 2.1 CUBIC FEET
 - · AHAM | 21/8"W. X | 61/8"H. X | 81/8"D. 2.0 CUBIC FEET
- · TWO HEAVY-DUTY PACKG/GIX POGITIONG
- · STANDARD KICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARPANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARPANTY - GURFACE/TUBE BURNERG









Val6488-60

- · EXCLUGIVE YOUTH PRO SEALED BURNER SYSTEM (VARISHMERT TO HIGH) -COMBINATION OF UNIQUE PATENTED BURNER AND TOP DESIGN PROVIDE CLEANABILITY PLUS SUPERIOR
- PERFORMANCE AT SIMMER AND HIGH
- · G- 1 5,000 BTU BRAGE GEALED BURNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2 "W. APILL WITH FLAYOR AENERATOR PLATED AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUSIVE VARISIMMER SETTING FOR ALL BURNERS
- · EXCLUSIVE ONE-PIECE TOOLED AND PORCELAINIZED COOKING SURFACE CONTAINS SPILLS FOR EASY CLEANING
- · DRIP TRAY WITH POLLER BEARING GLIDEG \$ 2 AT. DRIP PAN
- · EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · OIX FUNCTIONO NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROOT
- · PIGHT OVEN LAPGE CONVECTION OVEN
 - · OYERALL 27"W. X 161/6"H. X 1834"D. 4.0 CUBIC FEET
 - · AHAM 2 7"W. X 161/8"H. X 17"D. 9.7 CUEIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG AND TWO HALOGEN

LIGHTS


- · LEFT BAKE OVEN (AUTO. IGNITION)
 - · OYEPALL | 2 1/8"W. X | 61/8"H. X | 84"D. 2.1 CUBIC FEET
 - · AHAM | 2 1/0"W. X | 61/0"H. X | 81/0"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG AND TWO HALOGEN LIGHTG
- · STANDARD KICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WAR-RANTY GURFACE/TUBE BURNERG


48" WIDE -VGIC-

FREESTANDING GAS SEALED BURNER RANGES

Val6488-44

- · EXCLUGIVE YOHTH PRO GEALED BURNER GYGTEM (VARIGIMMERTH TO HIGH) -COMBINATION OF UNIQUE PATENTED BURNER AND TOP DEGIGN PROVIDE CLEANABILITY PLUG GUPERIOR PERFORMANCE AT GIMMER AND HIGH
- · 4-15,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 2 4"W. THERMOGTATICALLY CONTROLLED GTEEL GRIDDLE/GIMMER PLATE (GEPARATE BURNER/CONTROL FOR THE LEFT AND RIGHT GIDE)
- · EXCLUGIVE VARIGIMMER GETTING FOR ALL BURNERS
- · EXCLUGIYE ONE-PIECE TOOLED AND PORCELAINIZED COOKING GURFACE CONTAINS SPILLS FOR EASY CLEANING
- · DPIP TPAY WITH POLLER BEAPING GLIDEG \$ 2 QT. DPIP PAN
- · EXCLUGIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · OIX FUNCTIONO NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROOT
- · PIGHT OVEN LAPGE CONVECTION OVEN
 - · OYERALL 20"W. X 161/0"H. X 184"D. 4.0 CUBIC FEET
 - · AHAM 2 7"W. X 1 6 1/0"H. X 1 7"D. 3.7 CUBIC FEET
 - · THEEE HEAVY-DUTY PACKE/GIX POGITIONG AND TWO HALOGEN LIGHTG
- · LEFT BAKE OVEN (AUTO. IGNITION)
 - · OYEPALL | 2 1/0"W. X | 61/0"H. X | 83"D. 2.1 CUBIC FEET
 - · AHAM | 2 1/0"W. X | 61/0"H. X | 81/0"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKE/GIX POGITIONS AND TWO HALOGEN LIGHTS
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARPANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WAR-PANTY - GURFACE/TUBE BURNERG





Val6488-49


- · EXCLUGIVE YOHTM PRO GEALED BURNER GYGTEM (VARIGIMMERTM TO HIGH)


 COMBINATION OF UNIQUE PATENTED BURNER AND TOP DEGIGN

 PROVIDE CLEANABILITY PLUG GUPERIOR PERFORMANCE AT GIMMER AND HIGH
- · 4-15,000 BTU 66 BUPNERS WITH POPCELAIN/CAST IPON CAPS AND AUTOMATIC IGNITION/PE-IGNITION
- · 2 4"W. APILL WITH FLAVOR GENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION (SEPARATE BURNER/CONTROL FOR LEFT AND RIGHT SIDE)
- · EXCLUSIVE YAPISIMMERTM SETTING FOR ALL BURNERS
- · EXCLUSIVE ONE-PIECE TOOLED AND PORCELAINIZED COOKING SURFACE CONTAINS SPILLS FOR EASY CLEANING
- · DPIP TRAY WITH POLLER BEARING GLIDEG \$ 2 QT. DRIP PAN
- · EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · PIGHT OVEN EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRA-PED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · 61X FUNCTION6 NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · PIGHT OVEN LAPGE CONVECTION OVEN
 - · OYEPALL 29"W. X 161/6"H. X 184"D. 4.0 CUBIC FEET
 - · AHAM 2 7"W. X 1 6 1/8"H. X 1 7"D. 9.7 CUBIC FEET
 - · THREE HEAVY-DUTY RACKO/GIX POGITIONG AND TWO HALOGEN

LIGHTO

- · LEFT BAKE OVEN (AUTO. IGNITION)
 - · OVERALL 121/8"W. X 161/8"H. X 184"D. 2.1 CUBIC FEET
 - · AHAM | 21/8"W. X | 61/8"H. X | 81/8"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG AND TWO HALOGEN LIGHTG
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WAR-RANTY - GURFACE/TUBE BURNERG





Y416488-449


- · EXCLUGIVE YOHTM PRO SEALED BURNER SYSTEM (VARISIMMERTM TO HIGH) -COMBINATION OF UNIQUE PATENTED BURNER AND TOP DESIGN PROVIDE CLEANABILITY PLUS SUPERIOR PERFORMANCE AT SIMMER AND HIGH
- · 4-15,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · I 2"W. THEPMOSTATICALLY CONTROLLED STEEL GRIDDLE/SIMMER PLATE
- · I 2"W. APILL WITH FLAYOR AENERATOR PLATED AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUSIVE VARISIMMER SETTING FOR ALL BURNERS
- · EXCLUGIVE ONE-PIECE TOOLED AND POPCELAINIZED COOKING SUPFACE CONTAINS SPILLS FOR EASY CLEANING
- · DPIP TRAY WITH POLLER BEARING GLIDEO \$ 2 QT. DRIP PAN
- · EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · OIX FUNCTIONO NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROOT
- · PIGHT OVEN LAPGE CONVECTION OVEN
 - · OVERALL 27"W. X 161/8"H. X 184"D. 4.0 CUBIC FEET
 - · AHAM 20"W. X 101/8"H. X 17"D. 9.7 CUBIL FEET
 - · THREE HEAVY-DUTY PACKG/GIX POGITIONG AND TWO HALOGEN


LIGHTS

- · LEFT BAKE OVEN (AUTO. IGNITION)
 - · OYEPALL | 2 1/0"W. X | 61/0"H. X | 84"D. 2.1 CUBIC FEET
 - · AHAM 121/8"W. X 101/8"H. X 181/8"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG AND TWO HALOGEN

LIGHTS


- · OTANDAPD FICKOPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY SURFACE/TUBE BURNERS





1496706-4B

- · 4-15,000 BTU 66 BUPNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUDIVE VARIOIMMERTM DETTING FOR ALL BURNERS
- · CENTER CRATE ALLOWS MOVEMENT OF COOKING VESSELS ACROSS ENTIRE TOP SURFACE
- · PEMOYABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH POLLER BEARING GLIDEG \$ 2 AT. DRIP PAN
- · EXCLUGIVE COMBINATION OF GINCLE U-GHAPED BAKE BURNER AND INFRARED BROIL BURNER, BOTH WITH ELECTRIC GRAPK ICNITION AND "FLAME GENGOR" GHUT-OFF
- · SIX FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRA-PED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · EXTREMELY LARGE GELF-CLEAN, CONVECTION OVEN
 - · OYERALL 184"W. X 161/8"H. X 152/8"D. 4.0 CUBIC FEET
 - · AHAM 2 7"W. X 1 61/8"H. X 1 57/8"D. 7.7 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG
 - · FOUR HALOGEN LIGHTS
- · GHIPPED WITH G/H. GG BACKGUARD
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG



30" WIDE -VGSCFREESTANDING GAS SELF-CLEAN RANGE (24" DEPTH)

VAGO GEPIEG PANAEG

- · G"H. 99 BACKQUARD 19 9HPPED AUTOMATICALLY WITH EACH 90"W. PANGE, BUT NOT WITH 96"W. OR 48"W. PANGEO. EITHER A BACKGUARD, HIGH-GHELF, OR 19LAND TRIM MUST BE
- USED FOR ALL INSTALLATIONS.
- · OHIPPED OTANDARD FOR NATURAL GAO; FIELD CONVERT

LP /PROPANE WITH ACCESSORY FIT (LPFPR/LPFSBRR)

- · 4 FOOT CORD INCLUDED WITH PANGE
 - · 2 WIFE WITH APOUND/9 PRONG PLUG
 - · 1204/60 HZ


MAXIMUM AMPO


- · 30"W. PANGES: 4B 2.3
- · 96"W. PANGES: 6B 2.7; 44 6.0; 49 2.4
- · 48"W. PANGEO: 64 6.4; 69 2.4; 44 10.0; 449 - 6.4

FINIOH DETAILS

- · OTAINLEOO OTEEL (OO), BLACK (BK), ALMOND (AL), BIOCUIT (BT), OTONE GRAY (OG), GRAPHITE GRAY (GG), BURGUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREOT GREEN (FG), VIKING BLUE (YB), COBALT BLUE (CB) AND EGGPLANT (EP).
 - · FINICH DECIGNATES DOOR FRONT, LOWER FRONT PANEL, SIDE PANELS, AND PORCELAIN GRATE SUPPORTS/BURNER BOWLS.
 - · GTAINLEGG GTEEL AND BURGUNDY UNITG HAVE BLACK PORCELAIN TOP/GRATE GUPPORTG AND BURNER KNOBG
- · ALL FINIOHEO HAVE BLACK PORCELAIN CRATEO, BLACK PORCELAIN BURNER CAPO, AND BLACK KNOBO/OWITCHEO.
- · WHITE (WH)
 - · FINICH DECIGNATES DOOR FRONT, LOWER FRONT PANEL, SIDE PANELS, PORCELAIN GRATE SUPPORTS / BURNER BOWLS, PORCELAIN CENTER WORKTOP, AND KNOBS/SWITCHES.
 - · HAS DARK CIRAY PORCELAIN CIRATES AND DARK CIRAY PORCELAIN BURNER CAPS.
- · ALL FINIOHEO HAVE OTAINLEOO OTEEL HANDLE/CHROME PLATED BRACKETO AND OTAINLEOO OTEEL DRIP TRAY PULL, CONTROL PANEL, AND LANDING LEDGE.
- · BPAGG TPIM OPTION (BP) INCLUDEG NAMEPLATE, WINDOW TPIM, DOOP HANDLE, DPIP TPAY PULL, FNOB BEZELG, THEPMAL-CONVECTION GWITCH BEZEL, AND CRATE GUPPOPT GIDE TPIM. GUPEP DUPABLE, LONG LAGTING BPAGG FINIGH ON ALL "HIGH TPAFFIC" PAPTG (HANDLE AND DPIP TPAY PULL); ALL OTHEP PAPTG HAVE A DUPABLE PROTECTIVE COATING. ALL PAPTG DEGICNED FOR MAINTENANCE-FREE NORMAL LOGE.
- · ALL MODELO AVAILABLE AO LP (ADD LP AFTER COLOR-CODE)

36 TO TO THE SELF-CLEAN DEPTHI






1496766-60

- · G- I 5,000 BTU 66 BURNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUDIVE VARIOIMMERTH DETTING FOR ALL BURNERS
- · PEMOYABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH POLLER BEARING GLIDES \$ 2 AT. DRIP PAN
- · EXCLUGIYE COMBINATION OF DUAL U-GHAPED BAKE BUPNEP AND INFRAPED BROIL BUPNEP, BOTH WITH ELECTRIC GPAPK IGNITION AND "FLAME GENGOP" GHUT-OFF
- · SIX FUNCTIONS NATURAL AIRFLOW BAKE,

 CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND

CONVECTION DEFEOST

- · EXTREMELY LARGE SELF-CLEAN, CONVECTION OVEN
- · OYEPALL 29"W. X 161/8"H. X 18%"D. 5.1 CUBIC FEET
- · AHAM 29"W. X 161/8"H. X 157/8"D. 4.2 CUBIC FEET
- · THREE HEAVY-DUTY RACKS/9IX POSITIONS
- · FOUR HALOGEN LIGHTS
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORGELAIN OVEN; FIVE-YEAR LIMITED WARRANTY - GURFAGE/TUBE BURNERG






V406966-44 1 2" W. THERMOSTATICALLY

THERMOOTATICALLY CONTROLLED OTEEL GRIDDLE/OIMMER PLATE

- · 4-15,000 BTU 66 BUPNERS WITH POPCELAIN/CAST IFON CAPS AND AUTOMATIC ICNITION/RE-ICNITION
- · EXCLUSIVE VARISIMMERTH SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNEP BOWLG
- · 66 DPIP TRAY WITH POLLER BEARING GLIDEG \$ 2 AT. DRIP PAN
- · EXGLUGIVE COMBINATION OF DUAL U-GHAPED BAKE BURNER AND INFRARED BROIL BURNER, BOTH WITH ELECTRIC GRARK ICNITION AND "FLAME GENGOR" GHUT-OFF
- · OIX FUNCTIONO NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRA-PED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROOT
- · EXTREMELY LARGE GELF-CLEAN, CONVECTION OVEN
 - · OYEPALL 29"W. X 161/6"H. X 184"D. 5.1 CUBIC FEET
 - · AHAM 29"W. X 161/0"H. X 15%0"D. 4.2 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG
 - FOUR HALOGEN LIGHTS
- · OTANDARD KICKOPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG





1496766-

40


I 2" W. APILL WITH FLAVOR GENERATOR PLATEO AND AUTOMATIC IGNITION/ REIGNITION


48" WIDE -VGSC-

FREESTANDING GAS SELF-CLEAN RANGES (24" DEPTH)

1496486-64


- · 6-15,000 BTU 66 BUPNERS WITH PORCELAIN/CAST IRON CAPS AND AUTO-MATIC IGNITION/RE-IGNITION
- · I 2"W. THEPMOGTATICALLY CONTROLLED GTEEL GRIDDLE/GIMMER PLATE
- · EXCLUSIVE YAPISIMMERTH SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH ROLLER BEARING GLIDES \$ 2 9T. DRIP PAN
- · PIGHT OVEN EXCLUSIVE COMBINATION OF SINGLE U-SHAPED BAKE BURNER AND INFRARED BROIL BURNER, BOTH WITH ELECTRIC SPARK IGNITION AND "FLAME SENSOR" SHUT OFF
- · PIGHT OVEN 91X FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · PIGHT OVEN EXTREMELY LARGE SELF-CLEAN, CONVECTION OVEN
 - · OYERALL 2 9"W. X 1 6 1/8"H. X 1 8 34"D. 4.0 CUBIC FEET
 - · AHAM 2 9"W. X 101/8"H. X 159/8"D. 9.9 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONS
 - · FOUR HALOGEN LIGHTS
- · LEFT BAKE OVEN (ELECTRIC SPARK IGNITION AND "FLAME SENSOR" SHUT-OFF)
 - · OYEPALL | 2 1/0"W. X | 61/0"H. X | 83"D. 2.1 CUBIC FEET
 - · AHAM | 2 1/6"W. X | 61/6"H. X | 7 1/4"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG
 - · TWO HALOGEN LIGHTS
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARPANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARPANTY GURFACE/TUBE BURNERG





V496486-60


- · G- I 5,000 BTU GG BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2 "W. APILL WITH FLAVOR AENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUSIVE YAPISIMMERM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DRIP TRAY WITH ROLLER BEARING GLIDEG \$ 2 AT. DRIP PAN
- · PIGHT OVEN EXOLUGIVE COMBINATION OF GINGLE U-GHAPED BAKE BURNER AND INFRARED BROIL BURNER, BOTH WITH ELEC-TRIC GPARK IGNITION AND "FLAME GENGOR" GHUT OFF
- · PICHT OVEN 61X FUNCTION6 NATURAL AIRFLOW BAKE,
 CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · PIGHT OVEN EXTREMELY LARGE GELF-CLEAN, CONVECTION OVEN
 - · OYEPALL 27"W. X 161/6"H. X 184"D. 4.0 CUBIC FEET
 - · AHAM 2 9"W. X 1 61/6"H. X 1 59/6"D. 9.9 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG
 - · FOUR HALOGEN LIGHTS
- · LEFT BAKE OVEN (ELECTRIC SPARK IGNITION AND "FLAME SENSOR" SHUT-OFF)
 - · OYERALL | 2 1/8"W. X | 61/8"H. X | 834"D. 2.1 CUBIC FEET
 - · AHAM 121/0"W. X 101/0"H. X 174"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG
 - · TWO HALOGEN LIGHTS
- · STANDAPD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WAR-RANTY - GURFACE/TUBE BURNERG








1496486-44

- · 4-15,000 BTU 66 BUPNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 2 4"W. THERMOSTATICALLY CONTROLLED STEEL GRIDDLE/SIMMER PLATE (SEPARATE BURNER/CONTROL FOR LEFT AND RIGHT SIDE)
- · EXOLUGIVE VARIGIMMERTM GETTING FOR ALL BURNERS
- · PEMOYABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH POLLER BEARING GLIDEG \$ 2 AT. DRIP PAN
- · PIGHT OVEN EXCLUSIVE COMBINATION OF SINGLE U-SHAPED BAKE BURNER AND INFRARED BROIL BURNER, BOTH WITH ELECTRIC SPARK IGNITION AND "FLAME SENSOR" SHUT OFF
- · PIGHT OVEN 91X FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · PIGHT OVEN EXTREMELY LARGE GELF-CLEAN, CONVECTION OVEN
- · PIGHT OVEN EXTREMELY LARGE SELF-CLEAN, CONVECTION OVEN
 - · OYEPALL 29"W. X 161/8"H. X 1834"D. 4.0 CUBIC FEET
 - · AHAM 2 7"W. X (61/8"H. X (57/8"D. 3.7 CUBIC FEET
 - · THREE HEAVY-DUTY RACKS/GIX POSITIONS
 - · FOUR HALOGEN LIGHTS
- · LEFT BAKE OVEN (ELECTRIC SPARK IGNITION AND "FLAME SENSOR" SHUT-OFF)
 - · OVERALL | 2 1/0"W. X | 61/0"H. X | 63/10. 2.1 CUBIC FEET
 - · AHAM | 2 1/0"W. X | 61/0"H. X | 71/4"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG
 - · TWO HALOGEN LIGHTS
- · STANDARD KICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORGELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFAGE/TUBE BURNERG










1496486-449


- · 4-1 5,000 BTU 66 BURNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2"W. THERMOSTATICALLY CONTROLLED GRIDDLE/SIMMER PLATE
- · I 2"W. APILL WITH FLAVOR GENERATOR PLATES AND AUTOMATIC IGNITION/PE-IGNITION
- · EXCLUGIVE VARIGIMMERTM GETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH POLLER BEARING GLIDEO \$ 2 9T. DRIP PAN
- · PIGHT OVEN EXCLUSIVE COMBINATION OF SINGLE U-SHAPED BAKE BUPN-EP AND INFRAPED BROIL BUPNER, BOTH WITH ELECTRIC SPARK IGNITION AND "FLAME SENSOP" SHUT OFF
- · PIGHT OYEN 61X FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · PIGHT OVEN EXTREMELY LARGE GELF-CLEAN, CONVECTION OVEN
 - · OYERALL 27"W. X 161/0"H. X 1834"D. 4.0 CUBIC FEET
 - · AHAM 29"W. X 161/6"H. X 15%/6"D. 9.9 CUBIC FEET
 - · THREE HEAVY-DUTY PACKO/OIX POOITIONS
 - FOUR HALOGEN LIGHTS
- · LEFT BAKE OVEN (ELECTRIC SPARK ICNITION AND "FLAME SENSOR" SHUT-OFF)
 - · OYERALL 12 1/0"W. X 161/0"H. X 184"D. 2.1 CUBIC FEET
 - · AHAM 121/0"W. X 101/0"H. X 17/4"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG
 - · TWO HALOGEN LIGHTS
- · STANDARD KICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG

- · EXCLUDIVE YOHTH PRO GEALED BURNER GYGTEM (YARIGIMMERTH TO HIGH) COMBINATION OF UNIQUE PATENTED BURNER AND TOP DEGICN PROVIDE
- CLEANABILITY PLUG GUPERIOR PERFORMANCE AT GIMMER AND HIGH
- · 4-15,000 BTU 66 BUPNERS WITH POPCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/PE-IGNITION
- · EXCLUSIVE VARISIMMERM SETTING FOR ALL BURNERS
- · EXCLUGIYE ONE-PIECE TOOLED AND POPCELAINIZED

 COOKING GUPFACE CONTAING SPILLS FOR EAGY CLEANING
- · CENTER CRATE ALLOWS MOVEMENT OF COOKING VESSELS ACROSS ENTIRE TOP SURFACE
- · EXCLUGIVE COMBINATION OF GINALE U-GHAPED BAKE BURNER AND INFRARED
- BROIL BURNER, BOTH WITH ELECTRIC SPARK IGNITION AND "FLAME SENSOR" SHUT-OFF
- · SIX FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEFROST
- · EXTREMELY LARGE SELF-CLEAN, CONVECTION OVEN
 - · OVERALL 27"W. X 161/8"H. X 184"D. 4.0 CUBIC FEET
 - · AHAM 20"W. X 101/0"H. X 150/0"D. 3.7 CUBIC FEET
- · THREE HEAVY-DUTY RACKG/GIX POGITIONG
- · FOUR HALOGEN LIGHTS
- · GHIPPED WITH G/H. GG BACKGUAPD
- · STANDARD KICKSPACE HEIGHT
- · TEN-YEAP LIMITED WAPPANTY POPGELAIN OVEN;
 FIVE-YEAP LIMITED WAPPANTY SUPFAGE/TUBE BUPNERS

30 PE WIDE WIDE WIDE WIDE FREESTANDING GAS SEALED BURNER SEALED BURNER SELF-CLEAN RANGES (24" DEPTH)







36" WIDE VGSC FREESTANDING GAS SEALED BURNER SEALED BURNER SELF-CLEAN RAINGES (24" DEPTH)

1496767-6B

· EXCLUGIVE YOHTH PRO GEALED BURNER GYGTEM

(VARIGIMMERTH TO HIGH) - COMBINATION OF UNIQUE PATENTED BURNER AND TOP DEGIGN PROVIDE CLEANABILITY PLUG

GUPERIOR


PERFORMANCE AT SIMMER AND HIGH

- · 6-15,000 BTU 99 BUPNERS WITH POPCELAIN/CAST
 IPON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUSIVE VARISIMMERTM SETTING FOR ALL BURNERS
- · EXCLUGIVE ONE-PIECE TOOLED AND POPCELAINIZED COOK-ING GUPFACE CONTAINS SPILLS FOR EASY CLEANING
- · EXCLUGIVE COMBINATION OF DUAL U-GHAPED BAKE BURN-ER AND INFRARED BROIL BURNER, BOTH WITH ELECTRIC GRARK IGNITION AND "FLAME GENGOR" GHUT-OFF
- · OIX FUNCTIONO NATURAL AIRFLOW BAKE,

 CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND
- · EXCLUGIVE YOUTH PRO GEALED BURNER GYGTEM
 (VARIGIMMERT TO HIGH) COMBINATION OF UNIQUE PATENTED BURNER AND TOP DEGICN
 PROVIDE CLEANABILITY PLUG GUPERIOR
 PERFORMANCE AT GIMMER AND HIGH
- · 4-1 5,000 BTU 60 BUPNERO WITH PORCELAIN/CAST IPON CAPO AND AUTOMATIC IGNITION/RE-IGNITION
- · DPIP TPAY WITH POLLEP BEAPING GLIDEG \$ 2 9T. DPIP PAN
- · EXCLUSIVE VARISIMMERT SETTING FOR ALL BURNERS
- · EXCLUGIVE ONE-PIECE TOOLED AND POPCELAINIZED COOKING GUPFACE CONTAINS SPILLS FOR EAGY CLEANING
- · EXCLUDIVE COMBINATION OF DUAL U-OHAPED BAKE BURNER AND INFRARED BROIL BURNER, BOTH WITH ELECTRIC OPARK IGNITION AND "FLAME DENGOR" OHUT-OFF
- · OIX FUNCTIONO NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROOT
- · EXTREMELY LARGE SELF-CLEAN, CONVECTION OVEN
- · OVERALL 29"W. X [61/e"H. X [83"D. 5. [CUBIC FEET
- · AHAM 29"W. X 161/0"H. X 15%/0"D. 4.2 CUBIC FEET
- · THREE HEAVY-DUTY RACKG/GIX POGITIONG
- · FOUR HALOGEN LIGHTS
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED
 - WAPPANTY GUPFACE/TUBE BUPNEPG


CONVECTION DEFPOST

- · EXTREMELY LARGE SELF-CLEAN, CONVECTION OVEN
 · OVERALL 29"W. X 161/2"H. X 18%"D. 5.1 CUBIC
 FEET
- · AHAM 29"W. X [σ^{1}/e^{0} H. X [$5^{\circ}/e^{0}$ D. 4.2 CUBIC FEET
- · THREE HEAVY-DUTY RACKO/OIX POOITIONS
- · FOUR HALOGEN LIGHTS
- · STANDARD KICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY - GURFACE/TUBE BURNERG



YGOCOGT-49
I 2" W. GRILL WITH
FLAVOR GENERATOR
PLATES AND
AUTOMATIC
IGNITION/ REIGNITION





VGOLOGT-4G I 2" W. THERMOSTATICALLY CONTROLLED STEEL GRIDDLE/SIMMER PLATE





48" WIDE -VGSC-

FREESTANDING GAS SEALED BURNER SELF-CLEAN RANGES (24" DEPTH)

V496487-64

- · EXCLUGIVE YOUTH PRO GEALED BURNER GYGTEM (VARIGIMMERT TO HIGH) COMBINATION OF UNIQUE
 - PATENTED BUPNER AND TOP DEGICN PROVIDE CLEANABILITY PLUG SUPERIOR PERFORMANCE AT SIMMER AND HIGH
- · G- I 5,000 BTU GG BUPNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · I 2"W. THEPMOGTATICALLY CONTROLLED GTEEL CRIDDLE/GIMMER PLATE
- · EXOLUGIVE VARIGIMMERTM GETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BURNER BOWLS
- · DPIP TRAY WITH ROLLER BEARING GLIDES \$ 2 9T. DRIP PAN
- · PIGHT OYEN EXCLUDIVE COMBINATION OF DINGLE U-DHAPED BAKE BURNER AND INFRARED BROIL BURNER, BOTH WITH ELECTRIC SPARK IGNITION AND "FLAME DENGOR" DHUT OFF
- · PIGHT OVEN 61X FUNCTIONS NATURAL AIRFLOW BAKE,
 CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL,
 CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · PIGHT OVEN EXTREMELY LARGE SELF-CLEAN, CONVECTION OVEN
 - · OVERALL 20"W. X 161/8"H. X 184"D. 4.0 CUBIC FEET
 - · AHAM 29"W. X 161/6"H. X 150/6"D. 9.9 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG
 - · FOUR HALOGEN LIGHTS
- · LEFT BAKE OVEN (ELECTRIC SPARK IGNITION AND "FLAME SENSOR" SHUT-OFF)
 - · OVERALL 12 1/0"W. X 161/0"H. X 184"D. 2.1 CUBIC FEET
 - · AHAM | 2 1/8"W. X | 61/8"H. X | 74"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG
 - · TWO HALOGEN LIGHTS
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFACE/TUBE BURNERO





1496487-69

- · EXCLUGIVE VOHTM PRO GEALED BURNER GYGTEM (VARIGIMMERTM TO HIGH) COMBINATION OF UNIQUE PATENTED BURNER AND TOP DEGIGN PROVIDE CLEANABILITY
 PLUG GUPERIOR PERFORMANCE AT GIMMER AND HIGH
- · G- I 5,000 BTU 66 BUPNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2"W. APILL WITH FLAYOR GENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION
- · EXOLUGIVE YAPIGIMMERTM GETTING FOR ALL BURNERS
- · PEMOYABLE POPOELAIN BUPNER BOWLS
- · DPIP TRAY WITH POLLER BEARING GLIDEG \$ 2 QT. DRIP PAN
- · PIGHT OVEN EXCLUGIVE COMBINATION OF GINGLE U-GHAPED BAKE BURNER AND INFRARED BROIL BURNER, BOTH WITH ELECTRIC GRARK IGNITION AND "FLAME GENGOR" GHUT OFF
- · PICHT OVEN 61X FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE


 AND CONVECTION DEFROST
- · PIGHT OVEN EXTREMELY LARGE GELF-CLEAN, CONVECTION OVEN
 - · OVERALL 29"W. X 161/8"H. X 1834"D. 4.0 CUBIC FEET
 - · AHAM 2 7"W. X 1 6 1/0"H. X 1 5 7/0"D. 3.7 CUBIC FEET
 - · THREE HEAVY-DUTY RACKO/GIX POGITIONG
 - · FOUR HALOGEN LIGHTS
- · LEFT BAKE OVEN (ELECTRIC SPARK ICNITION AND "FLAME SENSOR" SHUT-OFF)
 - · OVERALL | 2 1/0"W. X | 61/0"H. X | 84"D. 2.1 CUBIC FEET
 - · AHAM | 2 1/0"W. X | 61/0"H. X | 74"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG
 - · TWO HALOGEN LIGHTS
- · OTANDARD FICKOPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORGELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFAGE/TUBE BURNERG






1496487-44


- · EXCLUGIVE YOHTH PRO SEALED BURNER SYSTEM (VARISIMMERTH TO HIGH)COMBINATION OF UNIQUE PATENTED BURNER AND TOP DESIGN PROVIDE CLEANABILITY
 PLUS SUPERIOR PERFORMANCE AT SIMMER AND HIGH
- · 4-15,000 BTU 66 BUPNERG WITH POPCELAIN/CAGT IPON CAPG AND AUTOMATIC ICNITION/PE-ICNITION
- · 2 4"W. THERMOGTATICALLY CONTROLLED GTEEL GRIDDLE/GIMMER PLATE (GEPARATE BURNER/CONTROL FOR LEFT AND RIGHT GIDE)
- · EXOLUGIVE VARIGIMMERM SETTING FOR ALL BURNERS
- · PEMOVABLE POPOELAIN BUPNER BOWLS
- · DPIP TRAY WITH ROLLER BEARING GLIDEG \$ 2 QT. DRIP PAN
- · PIGHT OVEN EXCLUSIVE COMBINATION OF SINGLE U-SHAPED BAKE BURNER AND INFRARED BROIL BURNER, BOTH WITH ELECTRIC SPARK IGNITION AND "FLAME SEN-SOR" SHUT OFF
- · PICHT OVEN 61X FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · PIGHT OVEN EXTREMELY LARGE GELF-CLEAN, CONVECTION OVEN
 - · OYERALL 2 9"W. X 1 6 1/0"H. X 1 8 34"D. 4.0 CUBIC FEET
 - · AHAM 20"W. X 161/0"H. X 15%/0"D. 9.9 CUBIC FEET
 - · THREE HEAVY-DUTY RACKO/GIX POGITIONG
 - · FOUR HALOGEN LIGHTS
- · LEFT BAKE OVEN (ELECTPIC SPARK IGNITION AND "FLAME SENSOR" SHUT-OFF)
 - · OVERALL 121/8"W. X 101/8"H. X 1834"D. 2.1 CUBIC FEET
 - · AHAM | 2 1/6"W. X | 61/6"H. X | 71/4"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONS
 - · TWO HALOGEN LIGHTS
- · OTANDARD FICKOPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORGELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GUR-FAGE/TUBE BURNERG






1496486-49


- · EXCLUGIVE YOHTM PRO GEALED BURNER GYGTEM (VARIGIMMERTM TO HIGH) COMBINATION OF UNIQUE PATENTED BURNER AND TOP DEGIGN PROVIDE CLEANABILITY PLUG GUPERIOR PERFORMANCE AT GIMMER AND HIGH
- · 4-15,000 BTU 66 BUPNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 2 4"W. APILL WITH FLAVOR GENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUSIVE YAPISIMMERTM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNEP BOWLS
- · DPIP TRAY WITH ROLLER BEARING GLIDEG \$ 2 9T. DRIP PAN
- · PIGHT OVEN EXCLUSIVE COMBINATION OF SINGLE U-SHAPED BAKE BURNER AND INFRARED BROIL BURNER, BOTH WITH ELECTRIC SPARK IGNITION AND "FLAME SENSOR" SHUT OFF
- · PIGHT OVEN 61X FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRA-PED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · PICHT OVEN EXTREMELY LARGE GELF-CLEAN, CONVECTION OVEN
 - OVERALL 2 7"W. X 161/8"H. X 184"D. 4.0 CUBIC FEET
 - · AHAM 27"W. X 161/6"H. X 157/6"D. 9.9 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG
 - · FOUR HALOGEN LIGHTS
- · LEFT BAKE OVEN (ELECTPIC SPARK ICNITION AND "FLAME SENSOR" SHUT-OFF)
 - · OVERALL | 2 1/0"W. X | 61/0"H. X | 834"D. 2.1 CUBIC FEET
 - · AHAM | 2 1/0"W. X | 61/0"H. X | 71/4"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG
 - · TWO HALOGEN LIGHTS
- · OTANDARD FICKOPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG






V496487-44A


- · EXCLUSIVE YOHTH PRO SEALED BURNER SYSTEM (VARISIMMERTH TO HIGH) COMBINATION OF UNIQUE PATENTED BURNER AND TOP DESIGN PROVIDE CLEANABILITY PLUS SUPERIOR PERFORMANCE AT SIMMER AND HIGH
- · 4-15,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · I 2"W. THEPMOSTATICALLY CONTROLLED STEEL GRIDDLE/SIMMER PLATE
- · 1 2 "W. APILL WITH FLAYOR GENERATOR PLATED AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUSIVE VARISIMMER SETTING FOR ALL BURNERS
- · EXCLUGIVE ONE-PIECE TOOLED AND PORCELAINIZED COOPING GURFACE CONTAINS SPILLS FOR EASY CLEANING
- · DPIP TPAY WITH POLLER BEAPING GLIDEG \$ 2 QT. DPIP PAN
- · EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURN-ER, ALL WITH AUTOMATIC IGNITION
- · 91X FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · PIGHT OVEN EXTREMELY LARGE SELF-CLEAN, CONVECTION OVEN
 - · OYEPALL 27"W. X 161/8"H. X 189/4"D. 4.0 CUBIC FEET
 - · AHAM 20"W. X (61/8"H. X (50/8"D. 0.0 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG
 - · FOUR HALOGEN LIGHTS
- · LEFT BAKE OVEN (ELECTIPIC SPARK IGNITION AND "FLAME SENSOR" SHUT-OFF)
 - · OVERALL 12 1/0"W. X 161/0"H. X 184"D. 2.1 CUBIC FEET
 - · AHAM | 2 1/0"W. X | 61/0"H. X | 74"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG
 - · TWO HALOGEN LIGHTS
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY
 - SUPFACE/TUBE BUPNERS










- · EXCLUGIVE YOUTH PRO GEALED BURNER GYGTEM (VARIGIMMERT TO HIGH) COM-BINATION OF UNIQUE PATENTED BURNER AND TOP DEGICN PROVIDE CLEANABILITY PLUG GUPERIOR PERFORMANCE AT GIMMER AND HIGH
- · 4-15,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 2 4"W. 27,000 BTU WOK WITH 20" STEEL WOK/TOP
- · EXCLUGIVE VARIGIMMER GETTING FOR ALL BURNERG
- · EXCLUSIVE ONE-PIECE TOOLED AND PORCELAINIZED COOKING SURFACE CONTAINS SPILLS FOR EASY CLEANING
- · DPIP TRAY WITH POLLER BEARING GLIDEG \$ 2 9T. DRIP PAN
- · EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · SIX FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEFROST
- · PIGHT OVEN EXTREMELY LARGE GELF-CLEAN, CONVECTION OVEN
 - · OYEPALL 27"W. X 161/8"H. X 184"D. 4.0 CUBIC FEET
 - · AHAM 20"W. X 161/0"H. X 150/0"D. 2.2 CUBIC FEET
 - · THREE HEAVY-DUTY PACKO/OIX POOITIONS
 - · FOUR HALOGEN LIGHTS
- · LEFT BAKE OVEN (ELECTRIC SPARK IGNITION AND "FLAME SENSOR" SHUT-OFF)
 - · OVERALL | 2 1/6"W. X | 61/6"H. X | 834"D. 2.1 CUBIC FEET
 - · AHAM | 2 1/0"W. X | 61/0"H. X | 71/4"D. 2.0 CUEIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG
 - · TWO HALOGEN LIGHTS
- · OTANDARD KICKOPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG





36TE WIDE WGRC FREESTANDING GAS FRANGES (27TH DEPTH) RANGES (27TH DEPTH)





YUP6965-650


- · G- 1 5,000 BTU GG BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUGIVE YAPIGIMMERTM GETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLG
- · DPIP TPAY WITH POLLEP BEAPING GLIDEG \$ 2 QT. DPIP PAN
- · EXCLUDIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · GIX FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL,

CONVECTION DEHYDRATE AND CONVECTION DEFROST


- · LAPGE CONVECTION OVEN
 - · OYERALL 30 1/0"W. X | 4 1/0"H. X 2 1/4"D. 5.2 CUBIC

FEET

- · AHAM 301/6"W. X 141/6"H. X 194"D. 4.7 CUBIC FEET
- · THREE HEAVY-DUTY RACKO/FIVE POOITIONO; TWO
- · STANDARD KICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OYEN; FIVE-YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG



VAPLOOGS-44D I 2" W. THERMOGTATICALLY CONTROLLED GTEEL GRIDDLE/GIMMER PLATE



VARCOOD-4AD

1 2" W. APILL WITH FLAVOR AENERATOR PLATES AND
AUTOMATIC IGNITION/ REIGNITION

- \cdot 4-15,000 BTU 66 BUPNER6 WIT PORCELAIN/CAST IRON CAP6 AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUSIVE YAPISIMMERTM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNEP BOWLS
- · DPIP TRAY WITH POLLER BEARING GLIDEG \$ 2 9T. DRIP PAN
- · EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · GIX FUNCTIONG NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL,

 CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROGT
- · LAPGE CONVECTION OVEN
 - · OYEPALL 901/8"W. X 141/8"H. X 211/4"D. 5.2 CUBIC FEET
 - · AHAM 901/6"W. X 141/6"H. X 194"D. 4.7 CUBIC FEET
 - · THREE HEAVY-DUTY RACKO/FIVE POSITIONS; TWO LIGHTS
- · STANDARD KICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY SURFACE/TUBE BURNERS


48" WIDE -VGRCFREESTANDING GAS RANGES (27" DEPTH)


YUP6485-64D


- · G- I 5,000 BTU GG BUPNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2 "W. THEPMOSTATICALLY CONTROLLED STEEL CRIDDLE/SIMMER PLATE
- · EXCLUSIVE VARISIMMERTM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNEP BOWLS
- · DPIP TRAY WITH POLLER BEARING GLIDEG \$ 2 AT. DRIP PAN
- · PIGHT OVEN EXCLUSIVE COMBINATION OF DUAL BAKE BUPNERS AND INFRARED BROIL BUPNER, ALL WITH AUTOMATIC IGNI-TION
- · PIGHT OVEN 91X FUNCTION9 NATURAL AIRFLOW BAKE,


 CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL,

 CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · PIGHT OVEN LAPGE CONVECTION OVEN
 - · OVERALL 241/8"W. X 141/8"H. X 211/4"D. 4.2 CUBIC FEET
 - · AHAM 241/8"W. X 141/8"H. X 1914"D. 7.8 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/FIVE POGITIONG; TWO LIGHTS
- · LEFT BAKE OVEN (AUTO. IGNITION)
 - · OYEPALL 199/8"W. X 141/8"H. X 211/4"D. 2.9 CUBIC FEET
 - · AHAM 199/8"W. X 141/8"H. X 211/4"D. 2.9 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/FIVE POGITIONG
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG











YUP 6485-690


- · G- 1 5,000 BTU GG BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2"W. APILL WITH FLAYOR GENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUDIVE YAPIOIMMERTM DETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNEP BOWLS
- · DPIP TRAY WITH POLLER BEARING GLIDES \$ 2 QT. DPIP PAN
- · PIGHT OVEN EXCLUSIVE COMBINATION OF DUAL BAKE BUPNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · PIGHT OVEN 61X FUNCTIONS NATURAL AIRFLOW BAKE, CON-VECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · PIGHT OVEN LAPGE CONVECTION OVEN
 - · OVERALL 241/8"W. X 141/8"H. X 214"D. 4.2 CUBIC FEET
 - · AHAM 2 4 1/6"W. X 1 4 1/6"H. X 1 94"D. 7.8 CUBIC FEET
 - · THREE HEAVY-DUTY PACKG/FIVE POGITIONG; TWO
- · LEFT BAKE OVEN (AUTO. IGNITION)
 - · OVERALL 199/8"W. X 141/8"H. X 214"D. 2.9 CUBIC FEET
 - · AHAM 1 3 % 0 "W. X 1 4 1/0 "H. X 2 1 1/4" D. 2.9 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/FIVE POGITIONS
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY SURFACE/TUBE BURNERS


YUP6485-44D

- · 4-15,000 BTU 66 BUPNERS WITH POPCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 2 4"W. THERMOSTATICALLY CONTROLLED STEEL GRIDDLE/SIMMER PLATE (SEPARATE BURNER/CONTROL FOR LEFT AND RIGHT SIDE)
- · EXOLUGIVE VARIGIMMERTM GETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNEP BOWLS
- · DPIP TRAY WITH ROLLER BEARING GLIDES \$ 2 9T. DRIP PAN
- · PIGHT OVEN EXCLUDIVE COMBINATION OF DUAL BAKE BUPNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · PIGHT OVEN 61X FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEFROST
- · PIGHT OVEN LAPGE CONVECTION OVEN
 - · OYEPALL 241/0"W. X 141/0"H. X 211/4"D. 4.2 CUBIC FEET
 - · AHAM 241/8"W. X 141/8"H. X 194"D. 3.8 CUBIC FEET
 - · THREE HEAVY-DUTY PACKG/FIVE POGITIONG; TWO LIGHTS
- · LEFT BAKE OVEN (AUTO. IGNITION)
 - · OVERALL 199/8"W. X 141/8"H. X 211/4"D. 2.9 CUBIC FEET
 - · AHAM 199/0"W. X 141/0"H. X 214"D. 2.9 CUBIC FEET
 - · TWO HEAVY-DUTY PACKO/FIVE POSITIONS
- · OTANDARD KICKOPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMIT-ED WARRANTY - GURFACE/TUBE BURNERG









YUP6485-449D

- · 4-15,000 BTU 66 BURNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2 "W. THERMOSTATICALLY CONTROLLED GRIDDLE/SIMMER PLATE
- · 1 2"W. APILL WITH FLAVOR GENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUGIVE VARIGIMMERTM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH POLLER BEARING GLIDES \$ 2 AT. DRIP PAN
- · PIGHT OVEN EXCLUDIVE COMBINATION OF DUAL BAKE BUPNERS AND INFRARED BROIL BUPNER, ALL WITH AUTOMATIC IGNI-TION
- · PICHT OVEN 61X FUNCTIONS NATURAL AIRFLOW BAKE, CON-VECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · PIGHT OVEN LAPGE CONVECTION OVEN
 - · OYEPALL 241/8"W. X 141/8"H. X 21/4"D. 4.2 CUBIC FEET
 - · AHAM 241/0"W. X 141/0"H. X 194"D. 9.8 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/FIVE POGITIONG; TWO LIGHTS
- · LEFT BAKE OVEN (AUTO. IGNITION)
 - · OYEPALL 199/8"W. X 141/8"H. X 211/4"D. 2.9 CUBIC FEET
 - · AHAM 1 9 % 6 W. X 1 4 1/6 H. X 2 1 4 D. 2.9 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/FIVE POGITIONG
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMIT-ED WARRANTY - GURFACE/TUBE BURNERG


YUP6605-449D


- · G- I 5,000 BTU 66 BURNERG WITH PORCELAIN/CAGT IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 2 4"W. THEPMOSTATICALLY CONTPOLLED STEEL APIDDLE/SIMMER PLATE (SEPARATE BURNER/CONTROL FOR LEFT AND PIGHT SIDE)
- · EXCLUSIVE YAPISIMMERTM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAYO WITH ROLLER BEARING GLIDEG \$ 2 AT. DRIP PAN
- · PIGHT OYEN EXCLUDIVE COMBINATION OF DUAL BAKE BUPNERS AND INFRARED BROIL BUPNER, ALL WITH AUTOMATIC IGNITION
- · PIGHT OVEN 61X FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · LEFT OVEN DUAL BAKE BURNERS WITH AUTOMATIC IGNITION
- · LEFT OVEN FOUR FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, CONVECTION DEHYDRATE AND

 CONVECTION DEFROST
- · BOTH OVENS LAPGE CONVECTION OVEN
 - · OYEPALL 241/8"W. X 141/8"H. X 211/4"D. 4.2 CUBIC FEET
 - · AHAM 241/6"W. X 141/6"H. X 1914"D. 3.8 CUBIC FEET
 - · 2.8 CUEIC FEET
 - · THREE HEAVY-DUTY RACKG/FIVE POGITIONG; TWO
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARPANTY PORCELAIN OYEN; FIVE-YEAR LIMITED WARPANTY SURFACE/TUBE BURNERS

60" WIDE

FREESTANDING GAS RANGES (27" DEPTH)







YUP6605-449D

- · G- I 5,000 BTU GO BUPNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- \cdot I 2 "W. THEPMOSTATICALLY CONTPOLLED STEEL OPIDDLE/SIMMER PLATE
- · I 2"W. APILL WITH FLAYOR GENERATOR PLATES AND AUTOMATIC IGNITION/PE-IGNITION
- · EXCLUDIVE YAPIGIMMERTH SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TPAYO WITH POLLEP BEAPING GLIDEO \$ 2 QT. DPIP PAN
- · PIGHT OVEN EXCLUDIVE COMBINATION OF DUAL BAKE BUPNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · PICHT OVEN GIX FUNCTIONG NATURAL AIRFLOW BAKE,
 CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEFROGT
- · LEFT OVEN DUAL BAKE BURNERS WITH AUTOMATIC IGNITION
- · LEFT OVEN FOUR FUNCTION O NATURAL AIRFLOW BAKE,

 CONVECTION BAKE, CONVECTION DEHYDRATE AND CONVECTION DEFROOT
- · BOTH OVENS LAPGE CONVECTION OVEN
 - · OVERALL 241/8"W. X 141/8"H. X 21/4"D. 4.2 CUBIC FEET
 - · AHAM 241/0"W. X 141/0"H. X 1914"D. 9.8 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/FIVE POGITIONG; TWO LIGHTS
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARPANTY PORCELAIN OYEN; FIVE-YEAR LIMITED WARPANTY GURFACE/TUBE BURNERG





YARO SEPIES PANGES

- · A BACKQUARD 16 NOT PACKAGED OR SHIPPED AUTOMATICALLY WITH EACH RANGE
- · EITHER A BACKQUARD, HIGH-GHELF, OR IGLAND TRIM MUST BE USED FOR ALL INSTALLATIONS.
- · SHIPPED STANDARD FOR NATURAL GAS; FIELD CONVERT TO LP /PROPANE WITH ACCESSORY KIT (LPKRR)
- · 4 FOOT CORD INCLUDED WITH PANGE
 - · 2 WIPE WITH APOUND/3 PRONG PLUG
 - · 1204/60 HZ


MAXIMUM AMPO


- · 96"W. PANGES: 65 8.5; 44 11.8; 49 8.5
- · 48"W. PANGES: 8B 12.4; 6G 16.0; 6G 12.4; 4G 19.9; 4GQ 16.0
- · 60"W. PANGES: 64 27.6; 649 20.0

FINIOH DETAILS

- · STAINLESS STEEL (SS), BLACK (BK), ALMOND (AL), BISCUIT (BT), STONE GRAY (SG), GRAPHITE GRAY (GG), BURGUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREST GREEN (FG), VIKING BLUE (VB), COBALT BLUE (CB) AND EGGPLANT (EP).
 - · FINIGH DEGIGNATEG DOOR FRONT, LOWER FRONT PANEL, GIDE PANELG, AND PORCELAIN GRATE GUPPORTG/BURNER BOWLG.
 - · OTAINLEGG OTEEL AND BURGUNDY UNITO HAVE BLACK PORCELAIN GRATE GUPPORTO AND BURNER BOWLO
 - · ALL FINICHEO HAVE BLACK PORCELAIN CRATEO, BLACK PORCELAIN BURNER CAPO, AND BLACK KNOBO/OWITCHEO.
 - · ALL FINIOHEO HAVE OTAINLEOO OTEEL HANDLE/CHPOME PLATED BPACKETO AND OTAINLEOO OTEEL DPIP TPAY PULL, CONTPOL PANEL, AND LANDING LEDGE.
- · WHITE (WH)
 - · FINIGH DEGIGNATEG DOOR FRONT, LOWER FRONT PANEL, GIDE PANELG, PORCELAIN GRATE
 - SUPPORTS / BURNER BOWLS, PORCELAIN CENTER WORKTOP, AND KNOBS/SWITCHES.
 - · HAG DARK ORAY PORGELAIN GRATEG AND DARK ORAY PORGELAIN BURNER GAPG.
- · BPAGG TRIM OPTION (BP) INCLUDEG NAMEPLATE, WINDOW TRIM, DOOR HANDLE, DRIP TRAY PULL, FNOB BEZELG, THERMAL-CONVECTION GWITCH BEZEL, AND GRATE GUPPORT GIDE TRIM. GUPER DURABLE, LONG LAGTING BRAGG FINIGH ON ALL "HIGH TRAFFIC" PARTO (HANDLE AND DRIP TRAY PULL); ALL OTHER PARTO HAVE A DURABLE PROTECTIVE COATING. ALL PARTO DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.
- · ALL MODELO AVAILABLE AO LP (ADD LP AFTER COLOR CODE)

36" WIDE NVGRC FREESTANDING GAS FREESTANDING COOKING RANGES FOR COOKING SCHOOLS (27" DEPTH)






NYGP6965-680


- · MEETS NOF REQUIREMENTS FOR COOKING SCHOOL USE
- · NON-PUGH TO TURN VALVEG AG A CONVERGION KIT KIT FOR 96", 48" OR GO"W. PANGEG. MUST BE INSTALLED BY A CERTIFIED INSTALLER
- · NOF MARKING ON THE RATING PLATE AND INSTALLATION INSTRUCTIONS
- · G- I 5,000 BTU 66 BUPNERG WITH POPCELAIN/CAGT IPON CAPS AND AUTOMATIC IGNITION/PE-IGNITION
- · EXCLUSIVE YAPISIMMERM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH ROLLER BEARING GLIDES \$ 2 9T. DRIP PAN
- · EXCLUDIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · SIX FUNCTIONS NATURAL AIRFLOW BAKE,

CONVECTION BAKE, INFRARED BROIL, CONVECTION
INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROOT

- · LAPGE CONVECTION OVEN
- · OVERALL 901/e"W. X [41/e"H. X 2 [4"D. 5.2 CUBIC FEET
- · AHAM 901/8"W. X 141/8"H. X 1914"D. 4.7 CUBIC FEET
- · THREE HEAVY-DUTY RACKO/FIVE POOITIONO; TWO
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY - GURFACE/TUBE BURNERG

NYAPU 965-44D I 2" W. THERMOOTATICALLY CONTROLLED OTEEL ARIDDLE/OMMER PLATE





NYARO905-49D 12" W. ARILL WITH FLAYOR AENERATOR PLATEO AND AUTOMATIC IGNITION/ REIGNITION


- · MEETO NOF PEQUIPEMENTO FOR COOKING OCHOOL USE
- · NON-PUGH TO TURN VALVEG AG A CONVERGION HIT HIT FOR 96", 48" OR GO"W. RANGEG. MUGT BE INGTALLED BY A CERTIFIED INGTALLER
- · NOF MARKING ON THE RATING PLATE AND INSTALLATION INSTRUCTIONS
- · 4- I 5,000 BTU 99 BURNER9 WITH PORCELAIN/CAST IRON CAP9 AND AUTOMATIC ICNITION/RE-ICNITION
- · EXCLUSIVE YAPISIMMERTM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DRIP TRAY WITH ROLLER BEARING GLIDEG \$ 2 GT. DRIP PAN
- · EXCLUGIVE COMBINATION OF DUAL BAKE BURNERG AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · GIX FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · LAPGE CONVECTION OVEN
 - · OYERALL 201/8"W. X 141/8"H. X 21/4"D. 5.2 CUBIC FEET
 - · AHAM 201/0"W. X 141/0"H. X 1914"D. 4.7 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/FIVE POSITIONS; TWO LIGHTS
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG


48" WIDE -NVGRC-


FREESTANDING GAS RANGES FOR COOKING SCHOOLS (27" DEPTH)


NYGE6485-64D

- · MEETS NOF PEQUIPEMENTS FOR COOKING SCHOOL USE
- ·NON-PUGH TO TURN VALVEG AG A CONVERGION KIT KIT FOR
- 96", 48" OF 60"W. PANGEO. MUOT BE INSTALLED BY A CEPTIFIED INSTALLER
- · NOF MARKING ON THE PATING PLATE AND INOTALLATION INOTPUCTIONS
- · G-15,000 BTU 66 BUPNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · I 2"W. THEPMOSTATICALLY CONTPOLLED STEEL APIDDLE/SIMMEP PLATE
- · EXCLUSIVE VARISIMMERTM SETTING FOR ALL BURNERS
- · PEMOYABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH ROLLER BEARING GLIDEG \$ 2 AT. DRIP PAN
- · PIGHT OYEN EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · PICHT OVEN 61X FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRA-PED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · PIGHT OVEN LAPGE CONVECTION OVEN
 - · OVERALL 24 1/8"W. X 14 1/8"H. X 2 1/4"D. 4.2 CUBIC FEET
 - · AHAM 241/0"W. X 141/0"H. X 1914"D. 3.8 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/FIVE POSITIONS; TWO LIGHTS
- · LEFT BAKE OVEN (AUTO. IGNITION)
 - · OVERALL 199/8"W. X 141/8"H. X 21/4"D. 2.9 CUBIC FEET
 - · AHAM 1 2 3/6"W. X 1 4 1/6"H. X 2 1 1/4"D. 2.3 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/FIVE POGITIONS
- · OTANDARD FICKOPACE HEIGHT
- · TEN-YEAP LIMITED WAPPANTY POPOELAIN OVEN; FIVE-YEAP LIMITED WAPPANTY - SUPFACE/TUBE BUPNEPS










NYGE 6485-690


- · MEETO NOF PEQUIPEMENTS FOR COOKING SCHOOL USE
- · NON-PUGH TO TUPN VALVEG AG A CONVERGION FIT FIT FOR 96", 46" OR GO"W. PANGEG. MUGT BE INGTALLED BY A CERTIFIED INGTALLER
- · NOF MARKING ON THE RATING PLATE AND INSTALLATION INSTRUCTIONS
- · G- I 5,000 BTU GG BUPNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2"W. APILL WITH FLAYOR GENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUSIVE VARISIMMERTM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNEP BOWLG
- · DPIP TRAY WITH ROLLER BEARING GLIDES \$ 2 9T. DRIP PAN
- · PIGHT OVEN EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRA-PED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · PIGHT OVEN GIX FUNCTIONG NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROGT
- · PIGHT OVEN LAPGE CONVECTION OVEN
 - · OVERALL 241/8"W. X 141/8"H. X 211/4"D. 4.2 CUBIC FEET
 - · AHAM 241/0"W. X 141/0"H. X 1914"D. 9.8 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/FIVE POGITIONG; TWO LIGHTS
- · LEFT BAKE OVEN (AUTO. IGNITION)
 - · OVERALL 199/0"W. X 141/0"H. X 2 14"D. 2.9 CUBIC FEET
 - · AHAM 1 3 % 6"W. X 1 4 1/6"H. X 2 1 1/4"D. 2.3 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/FIVE POGITIONS
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG

NYGE6485-4GD

- · MEETS NOF PEQUIPEMENTS FOR COOKING SCHOOL USE
- · NON-PUOH TO TURN VALVES AS A CONVERSION FIT FIT FOR 96", 48"

 OR GO"W. PANGES. MUST BE INSTALLED BY A CERTIFIED INSTALLER
- · NOF MARKING ON THE RATING PLATE AND INOTALLATION INOTRUCTIONS
- · 4-15,000 BTU 66 BUPNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 2 4"W. THERMOGTATICALLY CONTROLLED GTEEL GRIDDLE/GIMMER PLATE (GEPARATE BURNER/CONTROL FOR LEFT AND RIGHT GIDE)
- · EXCLUSIVE VARISIMMERTM SETTING FOR ALL BURNERS
- · PEMOYABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH ROLLER BEARING GLIDEG \$ 2 OT. DRIP PAN
- · PIGHT OVEN EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · PICHT OVEN 61X FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRA-PED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVEC-TION DEFROST
- · PIGHT OVEN EXTREMELY LARGE GELF-CLEAN, CONVECTION OVEN
 - · OVERALL 241/6"W. X 141/6"H. X 211/4"D. 4.2 CUBIC FEET
 - · AHAM 241/6"W. X 141/6"H. X 194"D. 2.8 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG
- · FOUR HALOGEN LIGHTS
- · LEFT BAKE OYEN (ELECTRIC SPARK ICNITION AND "FLAME SENSOR" SHUT-OFF)
 - · OYEPALL 1 3 %/0"W. X 1 4 1/0"H. X 2 1 1/4"D. 2.7 CUBIC FEET
 - · AHAM 1 3 %/6"W. X 1 4 1/6"H. X 2 1 1/4"D. 2.7 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG
 - · TWO HALOGEN LIGHTS
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY - SURFACE/TUBE BURNERS






NYGE 6485-4690

- · MEETS NOF REQUIREMENTS FOR GOOKING SCHOOL USE
- · NON-PUGH TO TUPN VALVEG AG A CONVERGION FIT FIT FOR 96", 48" OR GO"W. PANGEG. MUGT BE INGTALLED BY A CEPTIFIED INGTALLER
- · NOF MARKING ON THE RATING PLATE AND INOTALLATION INOTRUCTIONS
- · 4-15,000 BTU 66 BUPNERS WITH POPCELAIN/CAST IPON CAPS AND AUTO-MATIC IGNITION/PE-IGNITION
- · 1 2 W. THERMOSTATICALLY CONTROLLED GRIDDLE/SIMMER PLATE
- · 1 2"W. APILL WITH FLAYOR GENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUSIVE VARISIMMERTM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH POLLER BEARING GLIDEG \$ 2 9T. DRIP PAN
- · PIGHT OVEN EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · PIGHT OVEN 61X FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRARED BROIL, CONVECTION INFRARED BROIL, CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · PIGHT OVEN EXTREMELY LARGE SELF-CLEAN, CONVECTION OVEN
 - · OYEPALL 241/8"W. X 141/8"H. X 211/4"D. 4.2 CUBIC FEET
 - · AHAM 241/0"W. X 141/0"H. X 1914"D. 3.8 CUBIC FEET
 - · THREE HEAVY-DUTY RACKO/GIX POGITIONG
 - · FOUR HALOGEN LIGHTS
- · LEFT BAKE OVEN (ELECTPIC SPARK IGNITION AND "FLAME SENSOR" SHUT-OFF)
 - · OVEPALL 19%/e"W. X 141/e"H. X 21/4"D. 2.9 CUBIC FEET
 - · AHAM 13% 6"W. X 141/6"H. X 214"D. 2.9 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG
 - · TWO HALOGEN LIGHTS
- · GTANDARD KICKGPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG







60" WIDE -NVGRC-FREESTANDING GAS RANGES FOR COOKING SCHOOLS (27" DEPTH)

NYUP6605-46D

- · MEETS NOF REQUIREMENTS FOR COOKING SCHOOL USE
- · NON-PUGH TO TUPN VALVES AS A CONVERSION FIT FIT FOR 96", 48" OR GO"W. PANGES. MUST BE INSTALLED BY A CERTIFIED INSTALLER
- · NOF MARKING ON THE RATING PLATE AND INSTALLATION
- · 6-15,000 BTU 90 BUPNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 2 4"W. THERMOSTATICALLY CONTROLLED STEEL GRIDDLE/SIMMER PLATE (GEPAPATE BUPNEP/CONTPOL FOR LEFT AND PIGHT GIDE)
- · EXCLUSIVE VARISIMMERTM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DEIP TRAYO WITH ROLLER BEARING GLIDEO \$ 2 AT. DRIP PAN
- · PIGHT OVEN EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- PIGHT OVEN GIX FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFRAPED BROIL, CONVECTION INFRAPED BROIL CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · LEFT OVEN DUAL BAKE BURNERS WITH AUTOMATIC IGNITION
- · LEFT OVEN FOUR FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, CONVECTION DEHYDRATE AND CONVECTION DEFPOST
- · BOTH OVENS LAPGE CONVECTION OVEN
 - · OVERALL 241/8"W. X 141/8"H. X 214"D. 4.2 CUBIC FEET
 - · AHAM 241/8"W. X 141/8"H. X 1914"D. 7.8 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/FIVE POGITIONG; TWO LIGHTS
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARPANTY - SURFACE/TUBE BURNERS







NY4P6605-449D

- · MEETS NOT REQUIREMENTS FOR COOKING SCHOOL USE
- · NON-PUGH TO TUPN VALVEG AG A CONVERGION FIT FIT FOR 96", 48" OF GO"W. PANGEO. MUOT BE INOTALLED BY A CEPTIFIED INOTALLER
- · NOF MARKING ON THE RATING PLATE AND INSTALLATION INSTRUCTIONS
- · 6-15,000 BTU 99 BUPNERS WITH POPCELAIN CAST IRON CAPS AND AUTOMATIC IGNITION/PE-IGNITION
- · I 2"W. THEPMOGTATICALLY CONTROLLED STEEL GRIDDLE/SIMMER PLATE
- · I 2"W. GPILL WITH FLAYOR GENERATOR PLATED AND AUTOMATIC IGNITION/ PE-IGNITION



- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAYO WITH ROLLER BEARING GLIDEO \$ 2 AT. DRIP PAN
- · PIGHT OYEN EXCLUSIVE COMBINATION OF DUAL BAKE BUPNERS AND INFRAPED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · PIGHT OVEN SIX FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE, INFPAPED BPOIL, CONVECTION INFPAPED BPOIL, CONVECTION DEHYDPATE AND CONVECTION DEFPOST
- · LEFT OYEN DUAL BAKE BURNERS WITH AUTOMATIC IGNITION
- · LEFT OVEN FOUR FUNCTIONS NATURAL AIRFLOW BAKE, CONVECTION BAKE. CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · BOTH OVENS LAPGE CONVECTION OVEN
 - · OYEPALL 241/8"W. X 141/8"H. X 21/4"D. 4.2 CUBIC FEET
 - · AHAM 241/8"W. X 141/8"H. X 194"D. 3.8 CUBIC FEET
 - · THREE HEAVY-DUTY RACKS/FIVE POSITIONS: TWO LIGHTS
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRAN-TY - GUPFACE/TUBE BUPNERS





NYAPO SEPIES PANAES

- · A BACKGUARD IO NOT PACKAGED OR GHIPPED AUTOMATICALLY WITH EACH RANGE. EITHER A BACKGUARD, HIGH-GHELF, OR IOLAND TRIM MUOT BE UGED FOR ALL INGTALLATIONS.
- · SHIPPED STANDARD FOR NATURAL GAS; FIELD CONVERT TO LP/PROPANE WITH ACCESSORY HIT (LPKPR)
- · 4 FOOT CORD INCLUDED WITH PANGE
 - · 2 WIFE WITH GROUND/9 PRONG PLUG
 - · 120 V/60 HZ
 - · NYGE 6965 MAXIMUM AMPG: 615-8.5; 44-11.8; 49-8.5
 - ·NYGRG485 MAXIMUM AMPG: 88-12.4; 6G-16.0; 69-12.4; 4G-19.9; 4G9-16.0
 - · NVGP6605 MAXIMUM AMP6: 66-29.6; 669-20.0

FINIOH DETAILS

- · STAINLESS STEEL (SS)
 - · FINIOH DEGIGNATEG DOOP FRONT, LOWER FRONT PANEL AND GIDE PANELG.
 - · HAO BLACK PORCELAIN CRATEO, BLACK PORCELAIN BURNER CAPO, BLACK PORCELAIN CRATE SUPPORTO/BURNER BOWLO AND BLACK KNOBO/OWITCHEO.
 - · HAG STAINLEGG STEEL HANDLE(G)/CHROME PLATED BRACKETG AND GTAINLEGG GTEEL DRIP TRAY PULL(G),CONTROL PANEL, AND LANDING LEDGE.
- · ALL MODELO AVAILABLE AG LP (ADD LP AFTER COLOR CODE)


· G-15,000 BTU 66 BURNERG WITH
PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE
IGNITION

- · EXOLUGIYE YARIGIMMERT SETTING FOR ALL BURNERS
- · PEMOYABLE POPOELAIN BUPNER BOWLS
- · 66 DPIP TRAY WITH ROLLER BEARING GLIDEG \$ 2 QT. DRIP PAN
- · EIGHT OVEN FUNCTIONS TWO ELEMENT BAKE, CONVECTION BAKE, MINI-BROIL, MAXI-BROIL, CONVECTION BROIL, TRUCONVECTION COOKING (ELEMENT AROUND FAN), CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · LAPGE GELF-CLEAN CONVECTION OVEN
- · OYERALL 29"W. X 161/8"H. X 184"D. 5.1 CUBIC FEET
- · AHAM 29"W. X 161/8"H. X 157/8"D. 4.2 CUBIC FEET
- · THREE HEAVY-DUTY RACKO/GIX POGITIONG
- · TWO LIGHTS
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY - SURFACE BURNERS/OVEN ELEMENTS

36" WIDE -VDSCFREESTANDING DUAL FUEL RANGES


(24" DEPTH)






YD66365-44


- · 4-15,000 BTU 66 BUPNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2 "W. THEPMOSTATICALLY CONTROLLED STEEL GRIDDLE/SIMMER PLATE
- · EXCLUDIVE YAPIOIMMERTH DETTING FOR ALL BURNERS
- · PEMOVABLE PORCELAIN BURNER BOWLS
- · 60 DPIP TRAY WITH POLLER BEARING GLIDEO \$ 2 QT. DRIP PAN
- · EIGHT OVEN FUNCTIONS TWO ELEMENT BAKE, CONVECTION BAKE, MINI-BROIL, MAXI-BROIL, CONVECTION BROIL, TRUCONVECTION COOKING (ELEMENT AROUND FAN), CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · LAPGE GELF-CLEAN CONVECTION OVEN
 - · OVERALL 29"W. X 161/0"H. X 183"D. 5.1 CUBIC FEET
 - · AHAM 29"W. X 161/0"H. X 157/0"D. 4.2 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG
 - · TWO LIGHTS
- · OTANDAPO FICKOPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY - GURFACE BURNERG/OVEN ELEMENTS





YD66765-49

- · 4-15,000 BTU 66 BUPNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2"W. APILL WITH FLAVOR GENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION
- · EXOLUGIVE VARIGIMMERM GETTING FOR ALL BURNERG
- · PEMOVABLE POPCELAIN BUPNER BOWLG
- · 66 DPIP TRAY WITH POLLER BEARING GLIDEG \$ 2 QT. DRIP PAN
- · EIGHT OVEN FUNCTIONS TWO ELEMENT BAKE, CONVECTION BAKE, MINI-BROIL, MAXI-BROIL, CONVECTION BROIL, TRUCONVECTION CONVECTION CONVECTION CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · LAPGE SELF-CLEAN CONVECTION OVEN
 - · OYEPALL 29"W. X 101/0"H. X 1834"D. 5.1 CUBIC FEET
 - · AHAM 29"W. X [61/6"H. X [57/6"D. 4.2 CUBIC FEET
 - THEEE HEAVY-DUTY PACKO/OIX POOITIONS
 - · TWO LIGHTS
- · OTANDARD KICKOPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY SURFACE BURNERS/OVEN ELEMENTS






48" WIDE -VDSC-

FREESTANDING DUAL FUEL RANGES (24" DEPTH)


VD96485-64


- · G- I 5,000 BTU GO BUPNERO WITH PORCELAIN/CAGT IRON CAPO AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2"W. THERMOSTATICALLY CONTROLLED GRIDDLE/SIMMER PLATE
- · EXCLUSIVE VARISIMMERM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH POLLER BEARING GLIDEO \$ 2 QT. DRIP PAN
- · PIGHT OVEN EIGHT OVEN FUNCTIONS TWO ELEMENT BAKE, CON-VECTION BAKE, MINI-BPOIL, MAXI-BPOIL, CONVECTION BPOIL TPUCONVECTION COOKING (ELEMENT APOUND FAN), CONVECTION DEHYDPATE AND CONVECTION DEFPOST
- · LEFT OVEN THREE OVEN FUNCTIONS TWO ELEMENT BAKE, BROIL, PROOF (SEPARATE LOW WATTACE ELEMENT)
- · PIGHT OVEN LAPGE SELF-CLEAN CONVECTION OVEN
 - · OVERALL 20"W. X 161/8"H. X 184"D. 4.0 CUBIC FEET
 - · AHAM 2 7"W. X 1 61/8"H. X 1 57/8"D. 9.9 CUBIC FEET
 - · THREE HEAVY-DUTY RACKS/SIX POSITIONS; TWO LIGHTS
- · LEFT OVEN GELF-CLEAN OVEN
 - · OVERALL 121/8"W. X 161/8"H. X 184"D. 2.1 CUBIC FEET
 - · AHAM | 2 1/0"W. X | 61/0"H. X | 74"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG; ONE LIGHT
- · STANDARD KICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORGELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFAGE BURNERG/OVEN ELEMENTG



YD96485-60

- · G- I 5,000 BTU GG BUPNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2 "W. APILL WITH FLAVOR GENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION
- · EXOLUGIVE VARISIMMERTM SETTING FOR ALL BURNERS
- PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH POLLER BEARING GLIDEG \$ 2 AT. DRIP PAN
- · PIGHT OVEN EIGHT OVEN FUNCTIONO TWO ELEMENT BAKE, CON-VECTION BAKE, MINI-BPOIL, MAXI-BPOIL, CONVECTION BPOIL TPUCONVECTM CONVECTION COOKING (ELEMENT APOUND FAN), CONVECTION DEHYDPATE AND CONVECTION DEFPOOT
- · LEFT OVEN THREE OVEN FUNCTIONS TWO ELEMENT BAKE, BROIL, PROOF (SEPARATE LOW WATTAGE ELEMENT)
- · PIGHT OVEN LAPGE GELF-CLEAN CONVECTION OVEN
 - · OVERALL 29"W. X 161/0"H. X 1834"D. 4.0 CUBIC FEET
 - · AHAM 27"W. X 161/8"H. X 157/8"D. 3.7 CUBIC FEET
 - · THREE HEAVY-DUTY RACKS/GIX POGITIONS; TWO LIGHTS
- · LEFT OVEN GELF-GLEAN OVEN
 - · OYEPALL | 2 1/6"W. X | 6 1/6"H. X | 834"D. 2.1 CUBIC FEET
 - · AHAM | 2 1/0"W. X | 61/0"H. X | 74"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG; ONE LIGHT
- · OTANDARD KICKOPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY SURFACE BURNERS/OVEN ELEMENTS







VD96485-44

- · 4-15,000 BTU 66 BUPNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 2 4"W. THERMOGTATICALLY CONTROLLED GTEEL GRIDDLE/GIMMER PLATE (GEPARATE BURNER/CONTROL FOR LEFT AND RIGHT GIDE)
- · EXCLUSIVE YAPISIMMERTM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH POLLER BEARING GLIDEG \$ 2 AT. DRIP PAN
- · PIGHT OVEN EIGHT OVEN FUNCTIONS TWO ELEMENT BAKE,

 CONVECTION BAKE, MINI-BROIL, MAXI-BROIL, CONVECTION BROIL

 TRUCONVECT CONVECTION COOKING (ELEMENT AROUND FAN), CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · LEFT OVEN THREE OVEN FUNCTIONS TWO ELEMENT BAKE, BROIL, PROOF (SEPARATE LOW WATTACE ELEMENT)
- · PIGHT OVEN LAPGE SELF-GLEAN CONVECTION OVEN
 - · OYERALL 29"W. X 161/0"H. X 184"D. 4.0 CUBIC FEET
 - · AHAM 20"W. X 101/0"H. X 150/0"D. 2.7 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG; TWO LIGHTS
- · LEFT OVEN GELF-GLEAN OVEN
 - · OVERALL | 2 1/0"W. X | 61/0"H. X | 84"D. 2.1 CUBIC FEET
 - · AHAM | 2 1/6"W. X | 61/6"H. X | 71/4"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG; ONE LIGHT
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARPANTY PORCELAIN OYEN; FIVE-YEAR LIMITED WARPANTY GURFACE BURNER-6/OYEN ELEMENTO






VD96485-469


- · 4-15,000 BTU 66 BUPNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2 "W. THERMOSTATICALLY CONTROLLED STEEL GRIDDLE/SIMMER PLATE
- · I 2"W. APILL WITH FLAYOR GENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUDIVE YAPIDIMMERTM DETTING FOR ALL BURNERS
- · PEMOVABLE POPOELAIN BURNER BOWLS
- · DPIP TPAY WITH POLLEP BEAPING GLIDEG \$ 2 9T. DPIP PAN
- · PIGHT OVEN EIGHT OVEN FUNCTIONO TWO ELEMENT BAKE,

 CONVECTION BAKE, MINI-BROIL, MAXI-BROIL, CONVECTION BROIL

 TRUCONVECT CONVECTION COOKING (ELEMENT AROUND FAN),

 CONVECTION DEHYDRATE AND CONVECTION DEFROGT
- · LEFT OVEN THREE OVEN FUNCTIONS TWO ELEMENT BAKE, BROIL, PROOF (SEPARATE LOW WATTAGE ELEMENT)
- · PIGHT OVEN LAPGE GELF-CLEAN CONVECTION OVEN
 - · OYERALL 2 9"W. X 1 61/6"H. X 1 834"D. 4.0 CUBIC FEET
 - · AHAM 2 3"W. X (6 1/6"H. X (5 % 6"D. 3.3 CUE) C FEET
 - · THREE HEAVY-DUTY RACKO/GIX POGITIONG; TWO LIGHTG
- · LEFT OVEN GELF-CLEAN OVEN
 - · OYEPALL 121/0"W. X 161/0"H. X 184"D. 2.1 CUBIC FEET
 - · AHAM | 2 1/6"W. X | 61/6"H. X | 71/4"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG; ONE LIGHT
- · STANDARD KICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY - SURFACE BURNERS/OVEN ELE-MENTS







YD66530-45

- · YOHTM PRO SEALED BURNER SYSTEM (VARI-SIMMER TO HIGH) -COMBINATION OF PATENTED BURNER AND TOP DESIGN PROVIDE CLEANABILITY PLUS SUPERIOR PERFORMANCE AT SIMMER AND HIGH
- · THREE 15,000 BTU BURNERS
- ONE 18,500 BTU TRUPOWERTH PLUG BURNER (FRONT LEFT BURNER)
- · ALL BURNERS EQUIPPED WITH VARISIMMERM SETTING AND SURESPARKM IGNITION SYSTEM
- PATENT PENDING VARI-OPEED DUAL FLOWTH CONVECTION OYOTEM HAO THE LARGEOT CONVECTION FAN IN THE INDUOTRY; THE O 1/2" FAN WORKO BI-DIRECTIONALLY FOR MAXIMUM AIRFLOW AND EXCELLENT COOKING REGULTO
- · CONCEALED IO PAGG DUAL BAKE ELEMENT
- · EXTPA LAPAE AOUPMET-ALOTH ALAGG ENGLOGED INFPAPED BROILER
- · PAPID PEADYTM PREHEAT GYGTEM PROVIDEG GUPER FAGT PREHEAT TIMEG
- · HIGH PERFORMANCE COOKING MODES INCLUDE BAKE,
 CONVECTION BAKE, TRUCONVECTM CONVECTION COOKING,
 CONVECTION ROAST, HI, MED AND LOW BROIL, CONVECTION
 BROIL, CONVECTION DEHYDRATE, CONVECTION DEFROST AND
 SELF-CLEAN
- · THREE STRATEGICALLY LOCATED HALOGEN LIGHTS
- · THREE HEAVY-DUTY PACKO/OIX PORCELAIN COATED PACK POOITIONO INCLUDING ONE TRUGLIDEM FULL EXTENSION PACK
- · LAPGEST SELF-CLEAN CONVECTION OVEN
- · OVERALL 25 5/16"W. X 1 6 ½"H. X 1 9 ½"D. 4.7 CUBIC FEET
- AHAM OTANDARD 25 5/16"W. X 16 1/2"H. X 16 19/16"D. 4.1
 CUBIC FEET
- · GHIPPED GTANDARD WITH 8"H. GG BACKGUARD
- · STANDARD FICKSPACE HEIGHT

30 WIDE
WIDE
WIDE
WIDE
FREESTANDING DUAL
FUEL
SELF-CLEAN
SELF-CLEA





VD96767-68

- · EXCLUSIVE YOUTH PRO SEALED BURNER SYSTEM (VARISHMERTH TO HIGH) COMBINATION OF PATENTED BURNER AND TOP DESIGN PROVIDE CLEANABILITY PLUS SUPERIOR PERFORMANCE AT SIMMER AND HIGH
- · 6- I 5,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/ CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUSIVE VARISIMMER SETTING FOR ALL BURNERS
- · EXCLUSIVE ONE-PIECE TOOLED AND PORCELAINIZED COOKING SURFACE CONTAINS SPILLS FOR EASY CLEANING
- · EIGHT OVEN FUNCTIONS TWO ELEMENT BAKE,


 CONVECTION BAKE, MINI-BROIL, MAXI-BROIL,

 CONVECTION BROIL, TRUCONVECT CONVECTION COOKING (ELE
 MENT AROUND FAN), CONVECTION DEHYDRATE AND

 CONVECTION DEFROST
- · LAPGE SELF-CLEAN CONVECTION OVEN
 - · OVERALL 29"W. X 161/8"H. X 1834"D. 5.1 CUBIC FEET
 - · AHAM 29"W. X 161/0"H. X 15%/0"D. 4.2 CUBIC FEET
 - · THREE HEAVY-DUTY PACKG/GIX POGITIONG
 - · TWO LIGHTS
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORGELAIN OVEN; FIVE-YEAR LIMITED WARRANTY - GURFAGE BURNERG/OVEN ELEMENTO

36 VOSC VOSC FREESTANDING DUAL FUEL SEALED BURNER SEALED BURNER RANGES (24" DEPTH)







YD66367-44

- · EXCLUGIVE YOUTH PRO GEALED BURNER GYGTEM (VARIGIMMERTH TO HIGH) COMBINATION OF PATENTED BURNER AND TOP DEGICN PROVIDE CLEANABILITY PLUG GUPERIOR PERFORMANCE AT GIMMER AND HIGH
- · 4-15,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/ CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2"W. THEPMOSTATICALLY CONTROLLED STEEL GRIDDLE/SIMMER PLATE
- · DRIP TRAY WITH ROLLER BEARING GLIDEG \$ 2 AT. DRIP PAN
- · EXCLUSIVE YAPISIMMER SETTING FOR ALL BURNERS
- · EXCLUGIVE ONE-PIECE TOOLED AND PORCELAINIZED

 COOKING GURFACE CONTAING GPILLG FOR EAGY CLEANING
- · EIGHT OVEN FUNCTIONS TWO ELEMENT BAKE, CONVECTION BAKE, MINI-BROIL, MAXI-BROIL, CONVECTION BROIL, TRUCONVECTION CONVECTION CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · LAPGE GELF-CLEAN CONVECTION OVEN
 - · OVERALL 29"W. X 161/0"H. X 1834"D. 5.1 CUBIC FEET
 - · AHAM 29"W. X 161/0"H. X 157/0"D. 4.2 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG
 - · TWO LIGHTS
- · OTANDAPD KICKOPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORGELAIN OVEN; FIVE-YEAR LIMITED WARRANTY - GURFAGE BURNERG/OVEN ELE-MENTG







YD96367-49

- · EXCLUSIVE YOUTH PRO SEALED BURNER SYSTEM (VARISHMERTH TO HIGH) COMBINATION OF PATENTED BURNER AND TOP DESIGN PROVIDE CLEANABILITY PLUS SUPERIOR PERFORMANCE AT SIMMER AND HIGH
- · 4- I 5,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2"W. APILL WITH FLAYOR GENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION
- · DPIP TPAY WITH POLLER BEARING GLIDEG \$ 2 9T. DPIP PAN
- · EXOLUGIVE VARIGIMMER GETTING FOR ALL BURNERG
- · EXCLUSIVE ONE-PIECE TOOLED AND PORCELAINIZED

 COOKING SURFACE CONTAINS SPILLS FOR EASY CLEANING
- · EIGHT OVEN FUNCTIONS TWO ELEMENT BAKE, CONVECTION BAKE, MINI-BROIL, MAXI-BROIL, CONVECTION BROIL, TRUCONVECTION CONVECTION DEHY-DRATE AND CONVECTION DEFROST
- · LAPGE GELF-CLEAN CONVECTION OVEN
 - · OVERALL 29"W. X 161/8"H. X 1834"D. 5.1 CUBIC FEET
 - · AHAM 29"W. X 101/8"H. X 157/8"D. 4.2 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG
 - · TWO LIGHTS
- · STANDARD KICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY - SURFACE BURNERS/OVEN ELE-MENTS

36 VOSC VOSC FREESTANDING DUAL FUEL SEALED BURNER RANGES (24" DEPTH)







YD96487-64

- · EXCLUGIVE YOUTH PRO SEALED BURNER SYSTEM (VARISIMMERT TO HIGH) COMBINATION OF PATENTED BURNER AND TOP DESIGN PRO-VIDE CLEANABILITY PLUS SUPERIOR
- PERFORMANCE AT SIMMER AND HIGH
- · 6- I 5,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT
 IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · I 2"W. THEPMOSTATICALLY CONTROLLED GPIDDLE/SIMMER PLATE
- · EXOLUGIVE VARIGIMMER GETTING FOR ALL BURNERS
- · EXCLUDIVE ONE-PIECE TOOLED AND POPCELAINIZED

 COOKING GURFACE CONTAINS SPILLS FOR EASY CLEANING
- · DPIP TRAY WITH POLLER BEARING GLIDES \$ 2 9T. DRIP PAN
- · PIGHT OVEN EIGHT OVEN FUNCTIONS TWO ELEMENT BAKE, CON-VECTION BAKE, MINI-BROIL, MAXI-BROIL, CONVECTION BROIL, TRUCONVECT CONVECTION COOKING (ELEMENT AROUND FAN), CON-VECTION DEHYDRATE AND CONVECTION DEFROST
- · LEFT OVEN THREE OVEN FUNCTIONS TWO ELEMENT BAKE, BROIL, PROOF (SEPARATE LOW WATTAGE ELEMENT)
- · PIGHT OVEN LAPGE SELF-CLEAN CONVECTION OVEN
 - · OYERALL 27"W. X 161/0"H. X 184"D. 4.0 CUBIC FEET
 - · AHAM 20"W. X 101/0"H. X 150/0"D. 2.7 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG; TWO LIGHTS
- · LEFT OVEN GELF-GLEAN OVEN
 - · OVERALL 121/8"W. X 161/8"H. X 184"D. 2.1 CUBIC FEET
 - · AHAM 121/8"W. X 161/8"H. X 174"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG; ONE LIGHT
- · STANDARD KICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY - SURFACE BURNERS/OVEN ELE-MENTS








YD96487-69


- · EXCLUGIVE YOHTM PRO GEALED BURNER GYGTEM (VARIGIMMERTM TO HIGH) COM-BINATION OF PATENTED BURNER AND TOP DEGIGN PROVIDE CLEANABILITY PLUG GUPERIOR PERFORMANCE AT GIMMER AND HIGH
- · 6- I 5,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2"W. APILL WITH FLAVOR GENERATOR PLATES AND AUTOMATIC IGNITION/ RE-IGNITION
- · EXCLUGIVE YAPIGIMMER GETTING FOR ALL BURNERS
- · EXCLUSIVE ONE-PIECE TOOLED AND POPCELAINIZED COOKING SUPFACE CONTAINS SPILLS FOR EASY CLEANING
- · DRIP TRAY WITH ROLLER BEARING GLIDEG \$ 2 AT. DRIP PAN
- · PIGHT OVEN EIGHT OVEN FUNCTIONS TWO ELEMENT BAKE,

 CONVECTION BAKE, MINI-BROIL, MAXI-BROIL, CONVECTION BROIL, TRUCONVECTM

 CONVECTION COOKING (ELEMENT AROUND FAN), CONVECTION DEHYDRATE AND

 CONVECTION DEFROST
- · LEFT OVEN THREE OVEN FUNCTIONS TWO ELEMENT BAKE, BROIL, PROOF (GEPARATE LOW WATTAGE ELEMENT)
- · PIGHT OVEN LAPGE GELF-CLEAN CONVECTION OVEN
 - · OVERALL 27"W. X 1 61/6"H. X 1 834"D. 4.0 CUBIC FEET
 - · AHAM 20"W. X 101/0"H. X 15%0"D. 9.9 CUBIC FEET
 - · THREE HEAVY-DUTY RACKS/GIX POGITIONG; TWO LIGHTS
- · LEFT OVEN GELF-CLEAN OVEN
 - · OYERALL | 2 1/0"W. X | 6 1/0"H. X | 8 %"D. 2. | CUBIC FEET
 - · AHAM | 2 1/0"W. X | 61/0"H. X | 74"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG; ONE LIGHT
- · STANDARD KICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFACE BURNERG/OYEN ELEMENTO






YD96487-44

- · EXCLUGIVE YOUTH PRO SEALED BURNER SYSTEM (VARISHMERT TO HIGH) -COMBINATION OF PATENTED BURNER AND TOP DESIGN PROVIDE CLEANABILI-TY PLUS SUPERIOR PERFORMANCE AT SIMMER AND HIGH
- · 4- I 5,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 2 4 "W. THERMOGTATICALLY CONTROLLED CRIDDLE/GIMMER PLATE (GEPARATE BURNER/CONTROL FOR LEFT AND PICHT GIDE)
- · DRIP TRAY WITH POLLER BEARING GLIDEG \$ 2 AT. DRIP PAN
- · EXOLUGIVE VARIGIMMER GETTING FOR ALL BURNERG
- · EXCLUGIYE ONE-PIECE TOOLED AND PORCELAINIZED COOKING GURFACE CONTAINS SPILLS FOR EASY CLEANING
- · PIGHT OVEN EIGHT OVEN FUNCTIONS TWO ELEMENT BAKE, CONVECTION BAKE, MINI-BROIL, MAXI-BROIL, CONVECTION BROIL, TRUCONVECTM CONVECTION CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · LEFT OVEN THREE OVEN FUNCTIONS TWO ELEMENT BAKE, BROIL, PROOF (SEPARATE LOW WATTAGE ELEMENT)
- · PIGHT OVEN LAPGE GELF-CLEAN CONVECTION OVEN
 - · OYERALL 29"W. X 161/8"H. X 184"D. 4.0 CUBIC FEET
 - · AHAM 20"W. X 101/8"H. X 15%/8"D. 3.7 CUBIC FEET
 - · THREE HEAVY-DUTY RACKO/OIX POOITIONO; TWO LIGHTS
- · LEFT OVEN GELF-CLEAN OVEN
 - · OYEPALL | 2 1/0"W. X | 61/0"H. X | 84"D. 2.1 CUBIC FEET
 - · AHAM | 2 1/0"W. X | 61/0"H. X | 71/0"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG; ONE LIGHT
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WAR-RANTY - GURFACE BURNERG/OVEN ELEMENTG


VD96487-49


- · EXCLUGIVE YOHTH PRO SEALED BURNER SYSTEM (VARISIMMERTH TO HIGH) -COMBINATION OF PATENTED BURNER AND TOP DESIGN PROVIDE CLEANABILITY PLUS SUPERIOR PERFORMANCE AT SIMMER AND HIGH
- · 4- I 5,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 2 4"W. APILL WITH FLAYOR GENERATOR PLATES AND AUTOMATIC IGNITION/
 PE-IGNITION (SEPARATE BURNER/CONTROL FOR LEFT AND RIGHT SIDE)
- · DPIP TRAY WITH ROLLER BEARING GLIDEG \$ 2 AT. DRIP PAN
- · EXCLUSIVE YAPISIMMER SETTING FOR ALL BURNERS
- · EXCLUGIVE ONE-PIECE TOOLED AND POPCELAINIZED COOKING GUPFACE CONTAINS SPILLS FOR EASY CLEANING
- · PIGHT OVEN EIGHT OVEN FUNCTIONS TWO ELEMENT BAKE,
 CONVECTION BAKE, MINI-BROIL, MAXI-BROIL, CONVECTION BROIL, TRUCONVECTM
 CONVECTION COOKING (ELEMENT AROUND FAN), CONVECTION DEHYDRATE AND
 CONVECTION DEFROST
- · LEFT OVEN THREE OVEN FUNCTIONS TWO ELEMENT BAKE, BROIL, PROOF (SEPARATE LOW WATTAGE ELEMENT)
- · PIGHT OVEN LAPGE SELF-CLEAN CONVECTION OVEN
 - · OYEPALL 2 9"W. X 161/6"H. X 184"D. 4.0 CUBIC FEET
 - · AHAM 20"W. X 161/6"H. X 150/6"D. 0.0 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG; TWO LIGHTS
- · LEFT OVEN GELF-CLEAN OVEN
 - · OVERALL 121/8"W. X 161/8"H. X 184"D. 2.1 CUBIC FEET
 - · AHAM | 2 1/0"W. X | 61/0"H. X | 71/4"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG; ONE LIGHT
- · STANDARD KICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARPANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARPAN-TY - GURFACE BURNERG/OVEN ELEMENTG



YD96487-449

- · EXCLUDIVE YOUTH PRO SEALED BURNER SYSTEM (VARISHMERT TO HIGH) COMBINATION OF PATENTED BURNER AND TOP DESIGN
 PROVIDE CLEANABILITY PLUS SUPERIOR PERFORMANCE AT SIMMER AND
- · 4-15,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2 "W. THERMOSTATICALLY CONTROLLED ARIDDLE/SIMMER PLATE (GEPARATE BURNER/CONTROL FOR LEFT AND RIGHT SIDE)
- · 1 2 "W. APILL WITH FLAVOR AENERATOR PLATED AND AUTOMATIC IGNITION/RE-IGNITION (GEPARATE BURNER/CONTROL FOR LEFT AND RIGHT GIDE)
- · DPIP TRAY WITH POLLER BEARING GLIDEO \$ 2 AT. DRIP PAN
- · EXCLUSIVE VARISIMMER SETTING FOR ALL BURNERS
- · EXCLUGIVE ONE-PIECE TOOLED AND PORCELAINIZED COOKING SURFACE CONTAINS SPILLS FOR EASY CLEANING
- · PIGHT OVEN EIGHT OVEN FUNCTIONS TWO ELEMENT BAKE,
 CONVECTION BAKE, MINI-BROIL, MAXI-BROIL, CONVECTION BROIL,
 TRUCONVECTM CONVECTION COOKING (ELEMENT AROUND FAN),
 CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · LEFT OVEN THREE OVEN FUNCTIONS TWO ELEMENT BAKE, BROIL, PROOF (SEPARATE LOW WATTAGE ELEMENT)
- · PIGHT OVEN LAPGE SELF-CLEAN CONVECTION OVEN
 - · OVERALL 23"W. X 161/8"H. X 1834"D. 4.0 CUBIC FEET
 - · AHAM 20"W. X 101/0"H. X 157/0"D. 2.2 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITIONG; TWO LIGHTS
- · LEFT OVEN GELF-GLEAN OVEN
 - · OYEPALL | 2 1/0"W. X | 61/0"H. X | 8%"D. 2.1 CUBIC FEET
 - · AHAM | 2 1/0"W. X | 61/0"H. X | 74"D. 2.0 CUBIC FEET
 - · TWO HEAVY-DUTY PACKG/GIX POGITIONG; ONE LIGHT
- · OTANDAPD FICKOPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY - SURFACE BURNERS/OVEN ELEMENTS






- · OTPONG, WEAR REGIOTANT GLAGO CERAMIC TOP
- · QUICKCOOKTH GURFACE ELEMENTG UTILIZE PIBBON ELEMENT TECHNOLOGY PEACH FULL POWER IN ABOUT 9 GECONDS
 - · PIGHT FRONT 7" I 800 WATT ELEMENT
 - · PIGHT PEAP 7" 1800 WATT ELEMENT
 - · 600 WATT "BPIDGE" ELEMENT BETWEEN PIGHT FRONT AND PIGHT PEAP ELEMENTS
 - · LEFT FRONT 61/2" 1500 WATT ELEMENT
 - · LEFT PEAP DUAL ELEMENT 9" 2400 WATT/6" 1000 WATT ELE-


MENT

- · EIGHT OVEN FUNCTIONS TWO ELEMENT BAKE, CONVECTION BAKE, MINI-BROIL, MAXI-BROIL, CONVECTION BROIL, TRUCONVECT CONVECTION COOKING (ELEMENT AROUND FAN), CONVECTION DEHYDRATE AND CONVECTION DEFROST
- · LAPGE GELF-CLEAN CONVECTION OVEN
 - · OVERALL 29"W. X 161/8"H. X 184"D. 4.0 CUBIC FEET
 - · AHAM 2 7"W. X 1 61/8"H. X 1 5 7/8"D. 3.7 CUBIC FEET
 - · THREE HEAVY-DUTY RACKG/GIX POGITION
 - · TWO LIGHTS
- · GHIPPED WITH 6"H GG BACKGUARD
- · STANDARD FICKSPACE HEIGHT
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVEN; FIVE-YEAR LIMITED WARRANTY GURFACE BURNER6/OVEN ELEMENTO

-VESCFREESTANDING ELECTRIC RANGE (24" DEPTH)

30" WIDE





PORTABLE ARIDDLE AC-PAD



- · CAST ALUMINUM WITH PUGGED COMMERCIAL GRADE NO-STICK FINISH ON COOKING SURFACE
- · APEAGE TROUGH
- · PLACE OVER TWO PIGHT ELEMENTS WITH BRIDGE ELEMENT
- · CAN ALGO BE UGED TO QUICKLY DEFPOGT FROZEN FOODG

VEGO GEPIEG PANGEG

- · 99 BACKGUARD 19 9HIPPED AUTOMATICALLY WITH 90" W. PANGE. EITHER A BACKGUARD, HIGH-9HELF, OR 19LAND TRIM MUST BE USED FOR ALL INSTALLATIONS.
- · USA MODEL HARD WIRE DIRECT WITH 9 WIRE WITH AROUND OR USE AGENCY CERTIFIED, LOCALLY SUPPLIED POWER CORD/PLUG
- · CANADA MODEL FACTORY INSTALLED, AGENCY CERTIFIED 4 FOOT POWER CORD 9 WIRE WITH GROUND/4 PRONG PLUG - INCLUDED
 - · 240-208/120 V, 60 HZ
 - · MAXIMUM AMPG (2 40 VOLTG) 59.5
 - · MAXIMUM AMPS (208 VOLTS) 52.4

- · STAINLESS STEEL (SS), BLACK (BK), ALMOND (AL), BISCUIT (BT), STONE GRAY, (SG), CRAPHITE GRAY (GG), BURGUNDY (BU), LEMONADE, (LE), MINT JULEP (MJ), FOREST GREEN (FG), VIKING BLUE, (VB), COBALT BLUE (CB) AND EGGPLANT (EP).
- · FINIGH DEGIGNATES DOOR FRONT, LOWER FRONT PANEL AND SIDE PANELS.
 - · ALL FINIOHEO, EXCEPT WHITE, HAVE BLACK KNOBO/OWITCH.
 - · ALL FINIOHEO, EXCEPT WHITE, HAVE DARK RED GLAGO CERAMIC TOP WITH GRAY GRAPHICO, OTAINLEGO OTEEL
- HANDLE/CHROME PLATED BRACKETS AND STAINLESS STEEL CONTROL PANEL BOTTOM TRIM AND LANDING LEDGE.
- · WHITE (WH)
 - · INCLUDES WHITE GLASS CEPAMIC TOP WITH GRAY GRAPHICS.
 - · FINIGH DEGIGNATEG DOOR FRONT, LOWER FRONT PANEL, GIDE PANELG AND KNOBG/GWITCH.
- · BRAGG TRIM OPTION (BP) FOR ANY FINIGH; INCLUDEG NAMEPLATE, WINDOW TRIM, DOOR HANDLE/BRACKETG AND FNOB BEZELG. PARTG HAVE A DURABLE PROTECTIVE COATING. ALL PARTG DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.

APIDDLE PANGETOP VGGT 2 40

- · 2 4"W. THEPMOSTATICALLY CONTROLLED STEEL GRIDDLE/SIM-MER PLATE (SEPARATE BURNER/CONTROL FOR LEFT AND PIGHT SIDE)
- · FIVE-YEAR LIMITED WARRANTY GURFACE/TUBE BURNERS

APILL PANAETOP VAAT 2 40

- · 2 4"W. APILL WITH SMOKE AENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION (SEPARATE BURNER/CON-TROL FOR LEFT AND RIGHT SIDE)
- · DPIP TRAY WITH POLLER BEARING GLIDES
- · FIVE-YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG

WOK PANGETOP VGWT 2 40

- · I 2 7,500 BTU POPCELAIN/CAST IPON BUPNER WITH AUTOMATIC IGNITION/PE-IGNITION
- · 20" STEEL WOK/TOP STANDAPD
- · HEAVY-DUTY TWO-PIECE POPCELAIN/CAGT IPON GPATE
- · EXCLUGIVE AGENCY CERTIFIED CENTER TRIVET ALLOWG UGE OF LARGE STOCK POTS
- · DRIP TRAY WITH ROLLER BEARING GLIDES
- · FIVE-YEAR LIMITED WARRANTY GURFACE/TUBE BURNERS

BUILT-IN GURFACE UNITO

- · A BACKQUARD IO NOT PACKAGED OR OHIPPED AUTOMATICAL-LY WITH EACH RANGETOP. EITHER A BACKQUARD OR IOLAND TRIM MUOT BE USED FOR ALL INSTALLATIONS.
- · GHIPPED STANDARD FOR NATURAL GAS; FIELD CONVERT TO LP/PROPANE WITH ACCESSORY FIT (LPKRR)
- · 4 FOOT GORD INCLUDED WITH PANGET OP
 - · 2 WIFE WITH GROUND/9 PRONG PLUG
 - · 120 V/60 HZ
 - · YGGT 2 40 MAXIMUM AMPG: 0.5
 - · YGAT 2 40 MAXIMUM AMPG: 7.2
 - · YGWT 2 40 MAXIMUM AMPO: O. I

FINIOH DETAILS

4PIDDLE

- · OTAINLEGG STEEL (GG), BLACK (BK) AND WHITE (WH)
 - · OTAINLEGO OTEEL UNITO HAVE OTAINLEGO OTEEL
 - CONTROL PANEL AND BLACK KNOBG
 - · BLACK UNITO HAVE BLACK ENAMEL CONTROL
 - PANEL AND BLACK KNOBG
 - · WHITE UNITO HAVE WHITE ENAMEL CONTROL
 - PANEL AND WHITE KNOBS

CHAP-UPILL

- · STAINLESS STEEL (SS), BLACK (BK) AND WHITE (WH)
 - · STAINLESS STEEL UNITS HAVE BLACK PORCELAIN CRATES, CRATE SUPPORTS, STAINLESS STEEL CONTROL PANEL AND BLACK KNOBS.
 - · BLACK UNITO HAVE BLACK POPCELAIN CPATEO, CPATE GUPPOPTO, BLACK ENAMEL CONTPOL PANEL AND BLACK KNOBO.
 - · WHITE UNITO HAVE DARK GRAY PORCELAIN


 GRATED, WHITE PORCELAIN GRATE GUPPORTO,

 WHITE ENAMEL CONTROL PANEL AND WHITE KNOBD.
- · ALMOND (AL), BIGCUIT (BT), STONE GRAY (GG), GRAPHITE GRAY (GG), LEMONADE (LE), MINT JULEP (MJ), FOREST GREEN (FG), VIKING BLUE (VB), COBALT BLUE (CB) AND EGGPLANT (EP).
 - · UNITO HAVE BLACK POPCELAIN GRATES;

24" WIDE-VGRT-

BUILT-IN GAS

RANGETOPS
(24" DEPTH)







PORCELAIN ARATE SUPPORTS IN
DESIGNATED COLOR; STAINLESS STEEL
CONTROL PANEL, AND BLACK MOBS.

- · ALL FINIGHEO HAVE OTAINLEOO OTEEL DRIP TRAY PULL(O) AND LANDING LEDGE.
- · BPAGG TPIM OPTION (BP) FOR ANY FINIGH; INCLUDEG DPIP TPAY PULL(G), NAMEPLATE, KNOB BEZELG, AND CIPATE GUPPORT GIDE TRIM. GUPER DURABLE, LONG LAGTING BRAGG FINIGH ON ALL "HIGH TRAFFIC" PARTO (DRIP TRAY PULL); ALL OTHER PARTO HAVE A DURABLE PROTECTIVE COATING. ALL PARTO ARE DEGICNED FOR MAINTENANCE FREE NORMAL UGE.
- · ALL MODELO AVAILABLE AO LP (ADD LP AFTER COLOR

WOY/COOKER

- · OTAINLEGO OTEEL (GG)
 - · STAINLESS STEEL UNITS HAVE BLACK PORCELAIN CRATES, CRATE SUPPORTS, STAINLESS STEEL CONTROL PANEL AND BLACK KNOBS.
 - · OTAINLEOO OTEEL DEIP TEAY PULL(O) AND LANDING LEDGE.
- · BRAGO TRIM OPTION (BR) FOR ANY FINIOH; INCLUDED DRIP TRAY PULL(G), NAMEPLATE, KNOB BEZELO, AND GRATE OUPPORT GIDE TRIM. GUPER DURABLE, LONG LAGTING BRAGO FINIOH ON ALL "HIGH TRAFFIC" PARTO (DRIP TRAY PULL); ALL OTHER PARTO HAYE A DURABLE PROTECTIVE COATING. ALL PARTO ARE DEGIGNED FOR MAINTENANCE FREE NORMAL UGE.

YUPT900-4B

- · 4-15,000 BTU 66 BUPNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC ICNITION/RE-IGNITION
- · EXCLUDIVE YAPIGIMMERTM SETTING FOR ALL BURNERS
- · CENTER ARATE ALLOWS MOVEMENT OF COOKING VESSELS ACROSS ENTIRE TOP SURFACE
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DRIP TRAY WITH ROLLER BEARING GLIDES
- · FIVE YEAR LIMITED WARRANTY GURFACE BURNERS

30" WIDE -VGRT-

BUILT-IN GAS RANGETOPS (24" DEPTH)

YORT SEPIES PANCETOPS

- · A BACKQUARD IO NOT PACKAGED OR GHIPPED AUTOMATICALLY WITH EACH PANGETOP. EITHER A BACKQUARD, HIGH-GHELF, OR IGLAND TRIM MUGT BE UGED FOR ALL OTHER INSTALLATIONS.
- · SHIPPED STANDARD FOR NATURAL GAS; FIELD CONVERT SEALED BURNERS TO LP/PROPANE WITH ACCESSORY KIT (LPKSBRR)
- · 4 FOOT CORD INCLUDED WITH PANGET OP
 - · 2 WIPE WITH GROUND/9 PRONG PLUG
 - · 120 V/60 HZ


OPEN AND SEALED BURNER MODELS - MAXIMUM AMPS

- · 24"W. PANGETOPG: 4-5; 9-7.2; W-0.1
- · クロ"W. PANGETOPG: .ク
- · 96"/42"W. PANGETOPS: 615-.6; 44-9.9; 49-.6
- · 48"W. PANGETOPS: 64-4.2; 69-.6; 44-7.5; 449-4.2
- · 60"W. PANGETOPO: 64-7.8; 649-4.2

FINIOH DETAILS

NOTE - PARTO LIGTED BELOW MAY NOT BE APPLICABLE TO ALL MODELO


- · OTAINLEGG OTEEL (GG), BLACK (BK), AND WHITE (WH)
- · BLACK UNITO HAVE BLACK PORCELAIN GRATES AND TOP/GRATE SUPPORTS
- AND BURNER BOWLG, BURNER CAPG, BLACK ENAMEL CONTROL PANEL AND BLACK KNOBG.
- · WHITE UNITO HAVE DARK GRAY PORCELAIN GRATEO AND BURNER CAPO, WHITE PORCELAIN TOP/GRATE OUP PORTO AND BURNER BOWLO, WHITE ENAMEL CONTROL PANEL AND WHITE KNOBO
- · STAINLESS STEEL UNITS HAVE BLACK PORCELAIN TOP/CRATE SUPPORTS
- AND BURNER BOWLG AND GRATEG, AND BURNER CAPG, STAINLEGG STEEL CONTROL PANEL AND BLACK KNOBG.
- · ALMOND (AL), BIGCUIT (BT), STONE CIPAY (GC), CIPAPHITE CIPAY (CIC), LEMONADE (LE), MINT
- JULEP (MJ), FOREST GREEN (FG), VIKING BLUE (VB), COBALT BLUE (CB)AND EGGPLANT (EP)
- · UNITO HAVE BLACK PORCELAIN CRATED AND BURNER CAPD; OTAINLEDG OTEEL CONTROL PANEL AND BLACK KNOBO.
- · FINIGH DEGIGNATEG POPCELAIN TOP/GPATE GUPPOPTG AND BUPNEP BOWLG.
- · ALL FINIGHEG HAVE STAINLEGG STEEL DRIP TRAY PULL/TRIM, CONTROL PANEL AND LANDING LEDGE.
- · BPAGG TPIM OPTION (BP) FOR ANY FINIGH; INCLUDEG DRIP TRAY PULL/TRIM BELOW
 LANDING LEDGE, NAMEPLATE, KNOB BEZELG, AND GRATE GUPPORT GIDE TRIM. GUPER DURABLE, LONG
 LAGTING BRAGG FINIGH ON ALL "HIGH TRAFFIC" PARTG (DRIP TRAY PULL); ALL OTHER PARTG HAYE A
 DURABLE PROTECTIVE COATING. ALL PARTG DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.
- · ALL MODELO AVAILABLE AO LP (ADD LP AFTER COLOR CODE)



BUILT-IN GAS RANGETOPS (24" DEPTH)


YUPT960-615

- · 6-15,000 BTU 66 BURNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC
 - IGNITION/RE-IGNITION
- · EXCLUGIVE VARIGIMMERTH GETTING FOR ALL BURNERS
- · PEMOYABLE POPCELAIN BUPNEP BOWLG
- · DRIP TRAY WITH ROLLER BEARING GLIDEG
- · FIVE YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG




YGRT760-44

- · 4-15,000 BTU 60 BUPNERO WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2"W. THERMOGTATICALLY CONTROLLED STEEL GRIDDLE/SIMMER PLATE
- · EXCLUSIVE VARISIMMERTH SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH POLLER BEARING GLIDES
- · FIVE YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG



YURT760-49


- · 4-15,000 PTU 99 BURNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2 "W. APILL WITH FLAVOR GENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUGIVE VARIGIMMERM GETTING FOR ALL BURNERG
- · PEMOYABLE POPCELAIN BUPNEP BOWLS
- · 66 DPIP TRAY WITH POLLER BEARING GLIDES
- · FIVE YEAR LIMITED WARRANTY GURFACE/TUBE BURNERS



BUILT-IN GAS RANGETOPS (24" DEPTH)


YURT421-615

- · 6-1 5,000 BTU 66 BURNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC
- · EXCLUGIVE VARIGIMMERTM GETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH ROLLER BEARING GLIDES
- · FIVE YEAR LIMITED WARRANTY SURFACE/TUBE BURNERS




YGRT421-4G

- · 4-15,000 BTU 66 BUPNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 16"W. THERMOGTATICALLY CONTROLLED GTEEL GRIDDLE/GIMMER PLATE
- · EXCLUSIVE VARISIMMERTM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH ROLLER BEARING GLIDES
- · FIVE YEAR LIMITED WARRANTY GURFACE/TUBE BURNERS



YGRT421-49

- · 4-15,000 BTU GO BURNERO WITH PORCELAIN/CAGT IRON CAPO AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2 "W. CIPILL WITH FLAYOR GENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUSIVE VARISIMMERM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · 66 DPIP TRAY WITH POLLER BEARING GLIDES
- FIVE YEAR LIMITED WARRANTY SURFACE/TUBE BURNERS



BUILT-IN GAS RANGETOPS (24" DEPTH)

YURT 480-64

- · G- I 5,000 BTU GO BUPNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2 "W. THEPMOGTATICALLY CONTROLLED GTEEL APIDDLE/GIM-MER PLATE
- · EXCLUSIVE VARISIMMERTM SETTING FOR ALL BURNERS
- · PEMOYABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH POLLER BEARING GLIDES
- · FIVE YEAR LIMITED WARRANTY GURFACE/TUBE BURNERS

YUPT480-69


- · G- I 5,000 BTU GG BUPNERG WITH POPCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2"W. APILL WITH FLAVOR GENERATOR PLATED AND AUTOMATIC GNITION/RE-IGNITION
- · EXCLUSIVE VARISIMMERTM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH ROLLER BEARING GLIDES
- · FIVE YEAR LIMITED WARRANTY GURFACE/TUBE BURNERS

YUPT480-44

- · 4-15,000 BTU 66 BURNERS WITH PORCELAIN/CAST IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 2 4"W. THERMOSTATICALLY CONTROLLED STEEL GRIDDLE/SIMMER PLATE (SEPARATE BURNER/CONTROL FOR LEFT AND RIGHT SIDE)
- · EXOLUGIVE VARIGIMMERTM GETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH ROLLER BEARING GLIDES
- · FIVE YEAR LIMITED WARRANTY GURFACE/TUBE BURNERS


YURT480-449

- · 4-15,000 BTU 66 BUPNERG WITH POPCELAIN/CAGT IPON CAP6 AND AUTOMATIC IGNITION/PE-IGNITION
- · 1 2 "W. THEPMOSTATICALLY CONTROLLED STEEL APIDDLE/SIM-MEP PLATE
- · 1 2"W. APILL WITH FLAVOR AENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUGIVE VARIGIMMERTM GETTING FOR ALL BURNERS
- · PEMOYABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH POLLER BEARING GLIDES
- · FIVE YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG



YGRT 480-4K


- · YCRT 480-44 4-15,000 BTU 99 BURNERO WITH PORCELAIN/CAST IRON CAPS AND AUTOMÁTIC IGNITION/RE-IGNITION
- \cdot 1 2 7,500 BTU PORCELAIN/CAGT IRON BURNER WITH AUTOMATIC IGNITION/RE-IGNITION
- · 20" STEEL WOK/TOP STANDAPD
- · TWO-PIECE POPCELAIN/CAST IPON CRATE
- · EXOLUGIVE AGENCY CERTIFIED CENTER TRIVET ALLOWG USE OF LARGE STOCK POTG
- · EXCLUSIVE VARISIMMERTM SETTING FOR ALL BURNERS
- · PEMOVABLE POPCELAIN BUPNER BOWLS
- · DPIP TRAY WITH POLLER BEARING GLIDES
- · FIVE YEAR LIMITED WARRANTY GURFACE/TUBE BURNERS



BUILT-IN GAS RANGETOPS (24" DEPTH)


VART600-64

- · G- I 5,000 BTU GG BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 2 4"W. THEPMOOTATICALLY CONTPOLLED OTEEL CRIDDLE/OIMMER PLATE (OEPARATE BURNER/CONTROL FOR LEFT AND PIGHT OIDE)
- · EXOLUGIVE VARIOIMMERTH GETTING FOR ALL BURNERS
- · PEMOYABLE POPCELAIN BUPNER BOWLG
- · DPIP TRAYO WITH POLLER BEARING GLIDEG
- · FIVE YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG



YGRT600-669


- · 1 2 "W. THERMOSTATICALLY CONTROLLED STEEL CRIDDLE/SIM-MER PLATE (SEPARATE BURNER/CONTROL FOR LEFT AND RIGHT SIDE)
- \cdot 1 2 "W. APILL WITH FLAVOR AENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION
- · EXOLUGIVE VARIGIMMERTM GETTING FOR ALL BURNERG
- · PEMOVABLE POPCELAIN BUPNEP BOWLS
- · DPIP TRAYS WITH POLLER BEARING GLIDES
- · FIVE YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG



BUILT-IN GAS SEALED BURNER RANGETOP (24" DEPTH)

YUPT242-41

- · EXCLUDIVE YOHTH PRO GEALED BURNER GYGTEM (VARIGIMMERTH TO HIGH) COMBINATION OF PATENTED BURNER AND TOP DEGICN PROVIDE CLEANABILITY PLUG GUPERIOR PERFORMANCE AT GIMMER AND HIGH
- · 4- I 5,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · EXOLUGIVE VARIGIMMER GETTING FOR ALL BURNERG
- · EXCLUGIYE TOOLED AND PORCELAINIZED COOKING GURFACE CONTAING SPILLS FOR EASY CLEANING




30" WIDE -VGRT-

BUILT-IN GAS SEALED BURNER RANGETOP (24" DEPTH)

YUPT902-415


- · EXOLUGIVE YOHM PRO GEALED BURNER GYGTEM (VARIGIMMERM TO HIGH) COMBINATION OF PATENTED BURNER AND TOP DEGIGN PROVIDE CLEANABILITY PLUG GUPERIOR PERFORMANCE AT GIMMER AND HIGH
- · 4-15,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · CENTER CRATE ALLOWS MOVEMENT OF COOKING VESSELS ACROSS ENTIRE TOP SURFACE
- · EXCLUSIVE VARISIMMER SETTING FOR ALL BURNERS
- · EXCLUGIVE TOOLED AND POPCELAINIZED COOKING GUPFACE CONTAINS SPILLS FOR EASY CLEANING
- · FIVE YEAR LIMITED WARRANTY GURFACE BURNERS



BUILT-IN GAS SEALED BURNER RANGETOPS (24" DEPTH)


YURT362-615

- · EXCLUGIVE YOUTH PRO GEALED BURNER GYGTEM (VARIGIMMERT TO HIGH) COMBINATION OF PATENTED BURNER AND TOP DEGIGN PRO-VIDE CLEANABILITY PLUG GUPERIOR PERFORMANCE AT GIMMER AND HIGH
- · 6- I 5,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUSIVE VARISIMMER SETTING FOR ALL BURNERS
- · EXCLUGIVE TOOLED AND POPCELAINIZED COOKING GUPFACE CONTAINS SPILLS FOR EASY CLEANING
- · FIVE YEAR LIMITED WARRANTY GURFACE/TUBE BURNERS




YGRT762-44

- · EXCLUDIVE YOUTH PRO DEALED BURNER DYDTEM (VARIDIMMERT TO HIGH) COMBINATION OF PATENTED BURNER AND TOP DEDICN PRO-VIDE CLEANABILITY PLUD DUPERIOR PERFORMANCE AT DIMMER AND HIGH
- · 4-15,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2"W. THEPMOSTATICALLY CONTPOLLED STEEL APIDDLE/SIMMER PLATE
- · 60 DPIP TRAY WITH POLLER BEARING GLIDES
- · EXCLUDIVE VARIDIMMER DETTING FOR ALL BURNERS
- · EXCLUGIVE TOOLED AND POPCELAINIZED COOKING GUPFACE CONTAINS SPILLS FOR EASY CLEANING
- · FIVE YEAR LIMITED WARRANTY GURFACE/TUBE BURNERS



YURT362-49


- · EXOLUGIVE YOHM PRO GEALED BURNER GYGTEM (VARIGIMMERM TO HIGH) COMBINATION OF PATENTED BURNER AND TOP DEGIGN PROVIDE CLEANABILITY PLUG GUPERIOR PERFORMANCE AT GIMMER AND HIGH
- · 4-15,000 BTU BRAGG GEALED BURNERG WITH PORGELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- \cdot 1 2"W. APILL WITH FLAYOR AENERATOR PLATED AND AUTOMATIC IGNITION/RE-IGNITION
- · 66 DRIP TRAY WITH ROLLER BEARING GLIDES
- EXCLUGIVE VARIGIMMER GETTING FOR ALL BURNERS
- · EXCLUGIVE TOOLED AND POPCELAINIZED COOKING GUPFACE CONTAING SPILLS FOR EAGY CLEANING
- · FIVE YEAR LIMITED WARRANTY GURFACE/TUBE BURNERS



BUILT-IN GAS SEALED BURNER RANGETOPS (24" DEPTH)

YURT482-64

- · EXCLUGIVE YOHTM PRO GEALED BURNER GYGTEM (VARIGIMMERTM TO HIGH) COMBINATION OF PATENTED BURNER AND TOP DEGICN PROVIDE CLEANABILITY PLUG GUPERIOR PERFORMANCE AT GIMMER AND HIGH
- · G- I 5,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · I 2"W. THEPMOOTATICALLY CONTROLLED OTEEL GRIDDLE/OIMMER PLATE
- · EXCLUSIVE VARISIMMER SETTING FOR ALL BURNERS
- · EXCLUSIVE TOOLED AND POPCELAINIZED COOKING SUPFACE CONTAINS SPILLS FOR EASY CLEANING
- · DRIP TRAY WITH ROLLER BEARING GLIDES
- · FIVE YEAR LIMITED WARRANTY GURFACE/TUBE BURNERS




YGRT 482-69

- · EXCLUGIVE VOHTH PRO GEALED BURNER GYGTEM (VARIGIMMERTH TO HIGH) COMBINATION OF PATENTED BURNER AND TOP DEGICN PROVIDE CLEANABILITY PLUG GUPERIOR PERFORMANCE AT GIMMER AND HIGH
- · G- I 5,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 1 2"W. APILL WITH FLAYOR GENERATOR PLATES AND AUTOMATIC IGNITION/RE-IGNITION
- · EXOLUGIVE VARIGIMMER GETTING FOR ALL BURNERS
- · EXCLUGIVE TOOLED AND PORCELAINIZED COOKING GURFACE CONTAING SPILLS FOR EAGY CLEANING
- · DEIP TRAY WITH ROLLER BEARING GLIDES
- · FIVE YEAR LIMITED WARRANTY GURFACE/TUBE BURNERG


YGRT482-4G

- · EXCLUGIVE YOHM PRO SEALED BURNER SYSTEM (VARISIMMERM TO HIGH) COMBINATION OF PATENTED BURNER AND TOP DESIGN PROVIDE CLEANABILITY PLUS SUPERIOR PERFORMANCE AT SIMMER AND HIGH
- · 4-15,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPS AND AUTOMATIC IGNITION/RE-IGNITION
- · 2 4"W. THERMOSTATICALLY CONTROLLED STEEL ARIDDLE/SIMMER PLATE (SEPARATE BURNER/CONTROL FOR LEFT AND RIGHT SIDE)
- · EXCLUDIVE VAPIDIMMER DETTING FOR ALL BUPNERS
- · EXCLUGIVE TOOLED AND POPCELAINIZED COOKING GUPFACE CONTAING SPILLG FOR EAGY CLEANING
- · DRIP TRAY WITH POLLER BEARING GLIDES
- · FIVE YEAR LIMITED WARRANTY GURFACE/TUBE BURNERS




YGPT482-49

- · EXCLUGIVE YOHTH PRO SEALED BURNER SYSTEM (VARISIMMERTH TO HIGH) -COMBINATION OF PATENTED BURNER AND TOP DESIGN PROVIDE CLEANABILITY PLUS SUPERIOR PERFORMANCE AT SIMMER AND HIGH
- · 4-15,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · 2 4"W. APILL WITH FLAVOR GENERATOR PLATES AND AUTOMATIC IGNITION/ PE-IGNITION (SEPARATE BURNER/CONTROL FOR LEFT AND RIGHT SIDE)
- · EXCLUSIVE VARISIMMER SETTING FOR ALL BURNERS
- · EXCLUSIVE TOOLED AND POPCELAINIZED COOPING SUPFACE CONTAINS SPILLS FOR EASY CLEANING
- · DPIP TRAY WITH ROLLER BEARING GLIDES
- · FIVE YEAR LIMITED WARRANTY GURFACE/TUBE BURNERS



YGPT482-4G9

- · EXOLUGIVE YOHM PRO GEALED BURNER GYGTEM (VARIGIMMERM TO HIGH) -COMBINATION OF PATENTED BURNER AND TOP DEGICN PROVIDE CLEANABILITY PLUG GUPERIOR PERFORMANCE AT GIMMER AND HIGH
- · 4-15,000 BTU BRAGG GEALED BURNERG WITH PORCELAIN/CAGT IRON CAPG AND AUTOMATIC IGNITION/RE-IGNITION
- · I 2"W. THEPMOSTATICALLY CONTROLLED STEEL UPIDDLE/SIMMER PLATE
- · 1 2"W. APILL WITH FLAYOR GENERATOR PLATED AND AUTOMATIC IGNITION/RE-IGNITION
- · EXCLUSIVE YAPISIMMER SETTING FOR ALL BURNERS
- · EXOLUGIYE TOOLED AND PORCELAINIZED COOKING SURFACE CONTAINS SPILLS FOR EASY CLEANING
- · DPIP TRAY WITH POLLER BEARING GLIDEG
- · FIVE YEAR LIMITED WARRANTY GURFACE/TUBE BURNERS




30" AND 36" WIDE -DGRT-


BUILT-IN GAS RANGETOPS

DART900-4B (90"W.) DART960-5B (96"W.) APPROX. GHIPPING WEIGHT LEG(KG)
APPROX. GHIPPING WEIGHT LEG(KG)

49 (22.0) 74 (33.3)

- · GEALED BURNERG WITH BRAGG FLAME PORTG AND PORCELAIN/CAGT IRON CAPG
- · CONTINUOUS GRATE COOKING SURFACE
- · ONE-PIECE TOOLED TOP WITH LARGE SPILL COLLECTION AREA AROUND BURNERS
- · HEAVY-DUTY OTAINLEGO OTEEL CONTROL KNOBO WITH PUGH-TO-TURN GAFETY FEATURE
- · 90"W. PANGET OP 4 BUPNER
- · LEFT FRONT 16,000 BTU HIGH/9,400 BTU LOW
- · LEFT PEAP 12,000 BTU HIGH/1,700 BTU LOW
- · PIGHT FRONT 6,000 BTU HIGH/950 BTU LOW
- · PIGHT PEAR 8,000 BTU HIGH/ 1,200 BTU LOW
- · 96"W. PANGETOP 5 BUPNER
- · LEFT FRONT 12,000 BTU HIGH/1,700 BTU LOW
- · LEFT PEAP 10,000 BTU HIGH/1,500 BTU LOW
- · CENTER 16,000 BTU HIGH/9,400 BTU LOW
- · PIGHT FRONT 6,000 BTU HIGH/950 BTU LOW
- · PIGHT PEAP 8,000 BTU HIGH/ 1,200 BTU LOW
- · FIVE YEAR LIMITED WARRANTY GURFACE BURNERS





DURT960-55

DURT SEPIES GAS PANGETOPS


- · GHIPPED STANDARD FOR NATURAL GAS; FIELD CONVERT TO LP/PROPANE WITH
- ACCESSORY FIT (DLPF)
- · 4 FOOT CORD INCLUDED WITH PANGETOP
- · 2 WIPE WITH GROUND/9 PRONG PLUG
- · 1204/60HZ
- · MAX AMPG 2.0 (ALL UNITG)

- · BLACK (BK), WHITE (WH), OTAINLEGO (GG) BIGCUIT (BT), OTONE GRAY (GG) AND GRAPHITE GRAY (GG)
- · FINIOH DEOIGNATEO TOP. ALL UNITO EXCEPT WHITE HAVE BLACK POPCELAIN GPATEO, BLACK POPCELAIN BUPNER CAPO, AND BLACK KNOB GRIPO.
- · BRAGG TRIM OPTION BRAGG FINIGH KNOBG
- · ALL MODELO AVAILABLE AG LP (ADD LP AFTER COLOR CODE)




YERTOO1-45

- · OTRONG, WEAR REGIOTANT GLAGO CERAMIC TOP
- · QUICKGOOKM SURFACE ELEMENTS UTILIZE PIBBON ELEMENT TECHNOLOGY PEACH FULL POWER IN ABOUT 9 SECONDS
- · PIGHT FRONT 7" 1800 WATT ELEMENT
- · PIGHT PEAP 7" 1800 WATT ELEMENT
- \cdot 800 WATT "BRIDGE" ELEMENT BETWEEN PIGHT FRONT AND PIGHT PEAR BURNERS
- · LEFT FRONT 61/2" 1500 WATT ELEMENT
- · LEFT PEAP DUAL ELEMENT 9" 2400 WATT/6" 1000 WATT ELEMENT
- · FIVE YEAR LIMITED WARRANTY GURFACE ELEMENTO



PORTABLE APIDDLE FOR ELECTRIC PANAETOP

- · CAST ALUMINUM WITH PUGGED COMMERCIAL GRADE NO-STICK FIN-19H ON COOKING SURFACE
- · OPEAGE TROUGH
- · PLACE OVER TWO RIGHT ELEMENTS WITH BRIDGE ELEMENT
- · CAN ALGO BE UGED TO QUICKLY DEFROGT FROZEN FOODS



VERT SEPIES PANGETOPS

- · A BACKGUARD IO NOT PACKAGED OR GHIPPED AUTOMATICALLY WITH EACH RANGETOP. EITHER A BACKGUARD, HIGH-GHELF OR IGLAND TRIM MUGT BE UGED FOR ALL INSTALLATIONS.
- · 9 WIFE WITH UPOUND
- · 4 FOOT FLEXIBLE CONDUIT INCLUDED WITH PANCET OP
- · 240-208/120 Y, 60 HZ
- · MAXIMUM AMP6 (2 40 VOLT6) 37.1
- · MAXIMUM AMPG (208 YOLTG) 30.0

- $\cdot \text{ GTAINLEGG GTEEL (GG), BLACK (BK), WHITE (WH)}\\$
 - · BLACK UNITO HAVE BLACK GLAGG CERAMIC TOP, BLACK ENAMEL CONTROL PANEL AND BLACK KNOBG.
 - · WHITE UNITO HAVE WHITE GLAGO CEPAMIC TOP, WHITE ENAMEL CONTROL PANEL AND WHITE FNOBO.
 - · OTAINLEOG OTEEL UNITO HAVE BLACK CERAMIC TOP, OTAINLEOG OTEEL CONTROL PANEL AND BLACK KNOBG.
- · BRAGG TRIM OPTION (BR) FOR ANY FINIGH; INCLUDEG DRIP TRAY PULL/TRIM, NAMEPLATE AND KNOB BEZELG. PARTG HAVE A DURABLE PROTECTIVE COATING. ALL PARTG DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.

BUILT-IN ELECTRIC INDUCTION/RADIANT GLASS CERAMIC RANGETOP

YORT701-4B

- · MAGNEQUICKTM INDUCTION POWER GENERATORS UTILIZE MAGNETIC ENERGY FOR SUPERIOR POWER, RESPONSIVENESS AND EFFICIENCY
- · QUICKCOOKTH GUPFACE ELEMENTO UTILIZE PIBBON ELEMENT TECHNOLOGY TO PEACH FULL POWER IN ABOUT 9 SECONDS
- · STRONG, WEAR RESISTANT GLASS CERAMIC TOP
- · COMMERCIAL-TYPE STYLING
- · 90"W. MODELS
 - · LEFT FRONT (PADIANT) 9" 6"/2,500 1,000 WATT
 - · LEFT PEAP (PADIANT) 7"/1,500 WATT
 - · PIGHT FRONT (INDUCTION) 7"/1,200 WATT
 - · PIGHT PEAR (INDUCTION) 9"/9,900 WATT
- · FIVE YEAR LIMITED WARRANTY GURFACE ELEMENTS



YORT SEPIES PANGETOPS

- · A BACKAROUND 16 NOT PACKAGED OR GHIPPED AUTOMATICALLY WITH EACH RANGETOP. EITHER A BACKAROUND, HIGHGHELF, OR 1GLAND TRIM MUST BE USED FOR ALL APPLICATIONS.
 - · 9 WIFE CONDUIT WITH NO. 10 APOUND WIFE
 - · 240-208/120 V, 60 HZ
- · YORT701:
 - · MAXIMUM AMPO (2 40 YOLTO) 37.9
 - · MAXIMUM AMPG (208 VOLTG) 35.4

- · BLACK (BK), WHITE (WH), STAINLESS STEEL (SS)
- · BLACK UNITO HAVE BLACK GLAGO CERAMIC TOP, BLACK ENAMEL CONTROL PANEL AND BLACK KNOBO.
- · WHITE UNITY HAVE WHITE GLASS CEPAMIC TOP, WHITE ENAMEL CONTPOL PANEL AND WHITE FNORS.
- · STAINLESS STEEL UNITS HAVE BLACK GLASS CERAMIC TOP, STAINLESS STEEL CONTROL PANEL AND BLACK KNOBS.
- · BRAGG TRIM OPTION (BR) FOR ANY FINIOH; INCLUDED DRIP TRAY PULL/TRIM, NAMEPLATE AND KNOB BEZELD.

 PARTO HAVE A PROTECTIVE COATING. ALL PARTO DEGICNED FOR MAINTENANCE-FREE NORMAL UGE.

BUILT-IN ELECTRIC ALL INDUCTION GLASS CERAMIC RANGETOP

YORT301-45

- · MAGNEQUICK™ INDUCTION POWER GENERATORS UTILIZE MAGNETIC ENERGY FOR SUPERIOR POWER, RESPONSIVENESS AND EFFICIENCY
- · OTRONG, WEAR REGIOTANT GLAGO CERAMIC TOP
- · COMMERCIAL-TYPE STYLING
- · 90"W. MODELO
 - · LEFT FRONT (PADIANT) 9"/2,700 WATT
 - · LEFT PEAP (PADIANT) 7"/1,800 WATT
 - · PIGHT FRONT (INDUCTION) 7"/1,200 WATT
 - · PIGHT PEAP (INDUCTION) 9"/7,700 WATT
- · FIVE YEAR LIMITED WARRANTY GURFACE ELEMENTS



YORT GERIEG RANGETOPG

- · A BACKAROUND 10 NOT PACKAGED OR GHIPPED AUTOMATICALLY WITH EACH RANGETOP. EITHER A BACKAROUND, HIGHOHELF, OR 10LAND TRIM MUST BE USED FOR ALL APPLICATIONS.
 - · 9 WIPE CONDUIT WITH NO. 10 APOUND WIPE
 - · 240-208/120 V, 60 HZ
- · YCRT901:
 - MAXIMUM AMPS (2 40 VOLTS) 37.5
 - · MAXIMUM AMPG (208 YOLTG) 97.5

- · BLACK (BK), WHITE (WH), STAINLESS STEEL (SS)
- · BLACK UNITO HAVE BLACK GLAGO CEPAMIC TOP, BLACK ENAMEL CONTROL PANEL AND BLACK KNOBO.
- · WHITE UNITO HAVE WHITE GLAGG CERAMIC TOP, WHITE ENAMEL CONTROL PANEL AND WHITE KNOBG.
- · STAINLESS STEEL UNITS HAVE BLACK GLASS CERAMIC TOP, STAINLESS STEEL CONTROL PANEL AND BLACK KNOBS.
- · BRAGG TRIM OPTION (BR) FOR ANY FINIGH; INCLUDEG DRIP TRAY PULL/TRIM, NAMEPLATE AND KNOB BEZELG.
 PARTO HAVE A PROTECTIVE COATING. ALL PARTO DEGICNED FOR MAINTENANCE-FREE NORMAL UGE.

30" AND 36" WIDE -DERT-

BUILT-IN ELECTRIC RADIANT RANGETOPS


DEPT901-4B (90"W.)
DEPT961-5B (96"W.)

APPROX. SHIPPING WEIGHT LEG(KG)
APPROX. SHIPPING WEIGHT LEG(KG)

52 (23.4) 60 (27.0)

- · STONG, WEAR RESISTANT GLASS CERAMIC TOP
- · QUICKCOOK GURFACE ELEMENTG UTILIZE RIBBON ELECTRIC
- TECHNOLOGY PEACH FULL POWER IN ABOUT 9 SECONDS
- · HEAVY-DUTY OTAINLEGG OTEEL CONTROL FNODO WITH PUGH-TO-TURN GAPETY FEATURE
- · 90"W. PANGETOP 4 ELEMENT
- · LEFT FRONT 7 IN. 1,800 WATT ELEMENT; 800 WATT BRIDGE
- · LEFT PEAP 7 IN. 1,800 WATT ELEMENT
- · PIGHT FRONT 6.5 IN. 1,500 WATT ELEMENT
- · PIGHT PEAR 9 IN.-6 IN. 2,500 1,000 WATT ELEMENT
- · 96"W. PANGETOP 5 ELEMENT
- · LEFT FRONT 7 IN. 1,800 WATT ELEMENT; 800 WATT ERIDGE
- · LEFT PEAP 7 IN. 1,800 WATT ELEMENT
- · CENTER 12 IN. 2,700 -8.5 IN. 1,700 WATT ELEMENT
- · PIGHT FRONT 6.5 IN. 1,500 WATT ELEMENT
- PIGHT PEAR 8.25 IN. -4.75 IN. 2,200 750 WATT ELEMENT
- · FIVE YEAR LIMITED WARRANTY GURFACE BURNERG





DERTOGI-55

DERT SERIES RANGETOPS

- · 4 FOOT FLEXIBLE CONDUIT INCLUDED WITH PANGET OP
- · 9 WIPE WITH UPOUND
- · 240/2084,60 HZ
- · MAX AMP USAGE
- · DEPT901 95/90.9
- · DEPT961 44.2/40.0

- · OTAINLEGG OTEEL/BLACK (GB) OTAINLEGG OTEEL TRIM/CONTROL PANEL AND KNOBG; BLACK GLAGG AND KNOB GRIP
- · OTAINLEGO OTEEL/WHITE (OW) OTAINLEGO OTEEL TRIM/CONTROL PANEL AND KNOBO; WHITE GLAGO AND GRAY KNOB GRIP
- · BRAGG TRIM OPTION BRAGG FINIGH KNOBG

RANGE/RANGETOP INSTALLATION ACCESSORIES


6"H. BACKGUARD

· OTAINLEGG (GG) ONLY

APPROX. GHIPPING WT. LEG(KG)

· COOPDINATES WITH ALL FINISHES

·T24B46(FOP24"W./24"D.PAN4E6/PAN4ETOP6)	しし(ち.の)
·Tクのわ40(FOP クロ"W./24"D. PANAEの/PANAETOPの)	14(6.7)
·TクのやGの(FOR クの"W./24"D. PANGEの/PANGETOPの)	(7(7.7)
· T42BGG (FOR 42"W./24"D. PANGETOPS)	21(9.5)
· T48BGG (FOR 48"W./24"D. PANGEG/PANGETOPG)	24 (10.8)
· TGOBGG (FOR GO"W./24"D. PANGETOPS)	21(14.0)
· BOOBGG (FOR SEALED BURNER 20"W./24"D. PANGES/	, ((1.0)
PANGETOPS)	11(62)
	14(6.3)
· BOGBGG (FOR GEALED BURNER OG"W./24"D. PANGEG/	/>
PANGETOPO)	(7 (7 . 7)
B48BGG (FOR SEALED BURNER 48"W./24"D. PANGES/	
PANGETOPS)	24(10.8)
· 690646 (FOR 4A6 6/6 90"W./24"D. PANGE6)	14(6.9)
· 696046 (FOR 446 6/6 96"W./24"D. PANGE6)	(フ (フ.フ)
· 948BGG (FOR GAG 6/C 48"W./24"D. PANGEG)	24(10.8)
- 670BGG (FOR GAG G/C GEALED BURNER 90"W/24"D	
PANGEO)	14(6.3)
676846 (FOR GAG 6/6 SEALED BURNER 96"W/24"D	(7(7.7)
PANGEO)	
· 6481946 (FOR GAS S/C SEALED BURNER 48"W./24"D	24(12.2)
PANGEO)	2 2 . 2 ,
· P26BG6 (FOR 26"W./27"D. PANGES)	20(9.0)
· P48BG6 (FOR 48"W./27"D. PANGE9)	27(12.2)
·	
· P60B46 (FOR 60"W./27"D. PANGES)	76(16.2)




10"H. BACKGUARD

- · STAINLESS (SS) ONLY
- · COOPDINATES WITH ALL FINISHES

APPROX. GHIPPING WT. LEG(KG)

· T 9 6 B 4 1 0 (FOR 9 6 "W./2 4"D. PANGE 9/PANGET 0P 6)	20 (9.0)
T48BG10(FOR 48"W/24"D. RANGE9/RANGETOP9)	27(12.2)
· わりのわら10(FOR SEALED BURNER 96"W/24"D. RANGES/	
PANGETOPS)	20 (9.0)
B48BG10 (FOR SEALED BURNER 48"W./24"D. PANGES/	
PANGETOPO)	27(12.2)
· 6966410 (FOR UAG 6/6 96"W./24"D. PANGEG)	20 (9.0)
· 948P410(FOR 4A9 9/6 48"W./24"D. PANGE9)	27(12.2)
· 6960410 (FOR GAG 6/6 GEALED BURNER 96"W/24"D RAN	
E9)	20 (9.0)
· 6488410 (FOR GAS 5/6 SEALED BUPNER 48"W./24"D PAN	
E(0)	27(12.2)
·P96B410(F0P96"W./27"D.PANGE6)	29(10.4)
· P 4 8 PG 1 0 (FOR 48"W./27"D. PANGEO)	クロ(1カ.5)
· PGOBGIO (FOR GO"W./27"D. PANGES)	99(17.6)




HIGH SHELF

- · GELF-ATTACHED TO 2 4"H. BACKGUAPD
- · STAINLESS STEEL (SS) ONLY
- · COOPDINATES WITH ALL FINISHES

APPROX. GHIPPING WT. LEG(KG)

· T 2 4HG 2 4 (FOR 2 4"W./2 4"D. PANGE/PANGETOPG)	40 (18.0)
· TOOHO 2 4 (FOR 50"W./24"D. PANGEO/PANGETOPO)	45 (20.7)
· T 9 GHG 2 4 (FOR 9 G"W./2 4"D. PANGEG/RANGETOPG)	50(22.5)
· T 4 2 H 6 2 4 (FOR 4 2 "W./ 2 4"D. PANGETOPS)	与与(24.8)
· T48H024 (FOR 48"W./24"D. PANGEO/PANGETOPO)	60 (27.0)
· TGOHG 2 4 (FOR GO"W./2 4"D. RANGETOPG)	7 0 (カ1.5)
· 1590H624 (FOR GEALED BURNER 90"W./24"D. PANGEG/	
PANGETOPO)	45 (20.7)
· BOOHO24 (FOR SEALED BURNER OG"W./24"D. PANGES/	
PANGETOPG)	50(22.5)
· 15484624 (FOR GEALED BURNER 48"W./24"D. PANGEG/	
PANGETOPO)	60 (27.0)
· 690H624 (FOR GAG 6/6 90"W./24"D. PANGEG)	45 (20.7)
· 696H624 (FOR GA66/6 96"W./24"D. PANGE6)	50(22.5)
· 648H624 (FOR GAG 6/6 48"W./24"D. PANGEG)	60 (27.0)
· 670H024 (FOR GAG G/6 GEALED BURNER 70"W/24"D	
PANGEO)	45.5 (2 <i>0</i> .カ)
· 6964624 (FOR GAS S/6 SEALED BURNER 96"W./24"D	
PANGEO)	ラ <i>O</i> (22.5)
· 6484624 (FOR GAG G/6 GEALED BURNER 48"W./24"D	
PANGES)	60 (27/0)
· P 9 GHO 2 4 (FOP 9 G "W./27"D. PANGEO)	ラク(2 ク.9)
· P48H624 (FOP 48"W./27"D. PANGEG)	69 (28.4)
· PGOHO 2 4 (FOP GO"W./27"D. PANGEO)	75 (カカ.8)



16LAND TRIM

- · FOR IOLAND/PENINGULA INGTALLATION
- · CAN PEPLACE BACKGUAPO IF WALL 16 NON-COMBUSTIBLE
- · GTAINLEGG GTEEL (GG) ONLY
- · COOPDINATES WITH ALL FINISHES

APPROX. GHIPPING WT. LEG(KG)



COUNTERTOP SIDE TRIM

- · ONE PAIR OF TRIM
- · INSTALLS ON SIDE OF UNIT; OVERLAPS COUNTERTOP
- · STAINLESS STEEL (SS) ONLY
- · COOPDINATES WITH ALL FINISHES

APPROX. GHIPPING WT. LEG(KG)

· COOPDINATES WITH ALL FINISHES

CT 2 40T (FOP VAIC GAO 2 4"W./2 4"D. PANAEO) 02 4 COT (FOP VAOC GAO 0/C 2 4"D. PANAEO) P 2 4 COT (FOP VAIC/VDOC GAO/DUAL FUEL 2 4"D. OPEN BUPNEP PANAEO) P 2 7 COT (FOP VAIC/VDOC 2 4"D. PANAEO) P E 2 4 COT (FOP VAIC/VDOC 2 4"D. OEALED BUPNEP AND FOP VEOC ELECTRIC 2 4"D. PANAEO) P E 2 4 COT (FOP VAIC/VDOC 2 4"D. OEALED BUPNEP AND FOP VEOC ELECTRIC 2 4"D. PANAEO)	2 (.9)	
· OE 2 4 COT (FOR VAOC AAO O/C 2 4"D. OEALED BURNER 2 4"D. PANAEO) · T 2 4 COT (FOR VART AAO 2 4"D. OPEN BURNER PANAETOPO AND VAWT WOK/COOKER · TE 2 4 COT (FOR VART 2 4"D. OEALED BURNER PANAETOPO, VERT ELECTRIC 2 4"D. PANAETOPO, VAAT 2 4"W. ARIDDLE AND VAAT 2 4"W. ARILL)	2 (.9) 2 (.9) 2 (.9)	

CUPB BAGE FRONT AND CUSTOM CUPB BAGE

FRONT

AG CUPB BAGE FRONT

- · FRONT ONLY
- · STAINLESS STEEL (SS) ONLY
- · CONCEALS PANGE LEGS
- · COMPLETELY AGGEMBLED
- · EAGILY CLIPS ONTO PANGE LEGS AFTER PANCE 16 INSTALLED

AG CUPB BAGE FRONT

- PEMOVE OTAINLEGO FRONT AND PECYCLE ATTACH LOCALLY OUP-
- PLIED TRIM
- CONCEALS PANGE LEGO
- · COMPLETELY AGGEM-
- BLED
- · EAGILY CLIPS ONTO
- PANGE LEGG AFTER PANGE 16
- INSTALLED
- · PROVIDES DROP-IN
- PANGE LOOK

APPROX. SHIPPING WT. LEG(KG)

· PG246BF4 (FOR 24"W./24"D. PANGEG)	8 (2.6)
· PG906BF4 (FOR 90"W./24"D. PANGEG)	9 (4.1)
· PG966BF4 (FOP 96"W./24"D. PANGEG)	10(4.5)
· P64866F4 (FOP 48"W./24"D. PANGEG)	11(5.0)
· P7665 (FOR 76"W./27"D. PANGEG)	10(4.5)
· P486BF (FOR 48"W./27"D. PANGEG)	11(5.0)
· PGOCBF (FOP GO"W./27"D. PANGEG)	19(5.9)
	() ())

CASTER KIT

- · FOR YORG RANGES WITH 6" TO 8"H. LEGS ONLY
- · AGENCY CERTIFIED FOR REGIDENTIAL INGTALLATION
- · INCLUDES 4 LOCKING CASTER AND GAS LINE QUICK CONNECT/DIS-CONNECT FIT WITH FLEXIBLE HOSE, PESTPAINING CABLE, FITTINGS AND HAPDWAPE

APPROX. GHIPPING WT. LEG(KG)

21(9.5)



DESIGNER RANGETOP INSTALLATION ACCESSORIES

6"H. BACKGUARD

- · STAINLESS (SS) ONLY
- · GOOPDINATES WITH ALL FINISHES



D30B46 (FOR 30"W./24"D. PANGETOPS) D96BG6 (FOR 96"W./24"D. PANGETOPS) APPROX. SHIPPING WT. LEG(KG) APPROX. GHIPPING WT. LEG(KG) 14(16.9) 17(7.7)

10"H. BACKGUARD

- · STAINLESS (SS) ONLY
- · COOPDINATES WITH ALL FINISHES



D96BG10(FOR 96"W./24"D. PANGETOPS) APPROX. SHIPPING WT. LB(KG)

20 (9.0)

HIGH-GHELF

- · SHELF ATTACHED TO 2 4"H. BACKGUARD
- · STAINLESS (SS) ONLY
- · COOPDINATES WITH ALL FINISHES



D90H624 (FOR 90"W./24"D. PANGETOPG) APPROX. GHIPPING WT. LEG(KG) D96H624 (FOR 96"W./24"D. PANGETOPG) APPROX. SHIPPING WT. LE(KG)

45 (20.3) 50(22.5)

16LAND TRIM

- · FOR IOLAND/PENINGULA INGTALLATION
- · CAN PEPLACE BACKGUARD IF WALL IS NON-COMBUSTIBLE
- · STAINLESS (SS) ONLY
- · COOPDINATES WITH ALL FINISHES

D90T11 (FOR 90"W./24"D. PANGETOPG)	APPROX. GHIPPING WT. LEG(KG)	10(4.5)
D96T11 (FOR 96"W./24"D. PANGETOPG)	APPROX. GHIPPING WT. LEG(KG)	11(5.0)

RANGE/RANGETOP SURFACE COOKING ACCESSORIES

"Y" GRATEG

CTY (FÖR OPEN BURNER RANGEO/RANGETOPO) APPROX (CRATEO)

APPROX GHIPPING WT. LEG(KG)

19(5.9)

(2

- · TWO POPUELAIN/CAST IPON OPATES PER CAPTON
- · PEPLACEO OTANDARD OURFACE GRATEO
- · PROVIDES DIFFERENT LOOK
- · EAGY GLIDING OF POTG/PANG FROM BURNER TO BURNER (ALGO POGGIBLE WITH GTANDARD GURFAGE GRATEG)
- · AVAILABLE IN BLACK (BK) OF GRAY (GY)



WOY UPATE

WAT (FOR OPEN BURNER RANGEO/RANGETOPO)

APPROX GHIPPING WT. LB(KG)


G(2.7)

GBWAT (FOR GEALED BURNER RANGEO/RANGETOPO)

APPROX GHIPPING WT. LB(KG)

G(2.7)

- · POPCELAIN/CAST IPON
- · USE IN PLACE OF SURFACE GRATE (FRONT BURNERS RECOMMENDED)
- · WAT AVAILABLE IN BLACK (BK) OF GRAY (GY)
- · OBWAT AVAILABLE IN BLACK (BK) ONLY



WOY PING (FOR SEALED AND OPEN BURNER PANGES/RANGETOPS) PWRGG APPROX SHIPPING WT. LEKG) ((.5)

- · STAINLESS STEEL
- · UNIVERGALLY DEGIGNED TO GEOURELY FIT ON ANY VIKING PROFEGGIONAL RANGE/ RANGETOP GURFACE GRATE (FRONT BURNERG RECOMMENDED)
- · 61X (6) PER CAGE




PORTABLE GRIDDLE

PAD 4 (FOR OPEN BURNER RANGES/RANGETOPS)
98-PAD 4 (FOR SEALED BURNER RANGES/RANGETOPS)

APPROX SHIPPING WT. LEG(FG)
APPROX SHIPPING WT. LEG(FG)

40 (18.0) 40 (18.0)

- · CAST ALUMINUM WITH PUGGED COMMEPCIAL GPADE NO-STICK FINISH ON COOKING SUPFACE
- · APEASE TROUGH IN FRONT
- · FITO OVER OTANDARD OURFACE GRATES
- · CAN ALGO BE UGED TO QUICKLY DEFROST FROZEN FOODS
- · FOUR (4) PER CAGE



HAPDWOOD GOVER

CCHG (FOR OPEN BURNER RANGES/RANGETOPS) APPROX SHIPPING WT. LB(FG) 48 (2 1.6) SB-CCHG (FOR SEALED BURNER RANGES/RANGETOPS) APPROX SHIPPING WT. LB(FG) 48 (2 1.6)

- · MAPLE HAPDWOOD "BUTCHER BLOCK" CONSTRUCTION
- · CAN ALGO BE UGED AG CUTTING BOAPD
- · FITO OVER OTANDARD OURFACE GRATEO, (NOT "Y" GRATEO), GRIDDLE, OR GRILL
- · [15/8"W. X 2211/16"L. X 2"H.
- · GIX PEP CAGE



HAPDWOOD CUTTING BOAPD

HOBO APPROX OHIPPING WT. LB(KG) 90 (19.5)

- · MAPLE HAPDWOOD "BUTCHER BLOCK" CONSTRUCTION
- · PEVERGIBLE USE BOTH SIDES
- · 104"W. X 204"L. X 34" THICK
- · GIX PER CAGE



HAPDWOOD GUTTING BOARD FOR (18"W. GRIDDLE)

HOBIO APPROX GHIPPING WT. LEG(FG) B(9.6)

- · MAPLE HAPDWOOD "BUTCHER BLOCK" CONSTRUCTION
- · FOR USE WITH GAS 42"W. PANGETOPS WITH AN 18"W.

 THERMOSTATICALLY CONTROLLED STEEL GRIDDLE/SIMMER PLATE
- · PEVERGIBLE USE BOTH SIDES
- · FITS GRIDDLE PLATE
- · 169/0"W. X 19"L. X 34" THICK



STAINLESS STEEL COVERS (12"W. GRIDDLE / 12"W. GRILL)

664 | 266-06 (QPIDDLE) APPROX 6HIPPING WT. LE(KG) 21 (9.5) 669 | 266-06 (QPILL) APPROX 6HIPPING WT. LE(KG) 21 (9.5)

- · OTAINLEGG OTEEL COVER WITH VIKING PROFEGGIONAL HANDLE
- · FOR USE WITH GAS/DUAL FUEL RANGES AND RANGETOPS WITH A I 2 "W. THERMOSTATICALLY CONTROLLED STEEL GRIDDLE/SIMMER PLATE OR I 2 "W. GRILL
- · SEPARATE COVERS FOR CRIDDLE AND CRILL NOT INTER-CHANGEABLE
- · FITO OVER ARIDDLE/GIMMER PLATE OR OVER STANDARD ARILL ARATEG
- · APILL COVER CAN BE USED OVER OPEN AND SEALED SUPFACE BURNERS TO PREVENT SPLATTERS WHEN APILLINA
- · DOES NOT HAVE TO BE PEMOVED WHEN OPEPATING ADJACENT SUPFACE BUPNERS
- · 61X (6) PEP CAGE

STAINLESS STEEL COVERS

964186-66(18"W. GPIDDLE COVER)

664246-66(24"W. 2-PIECE GRIDDLE COVER)

664246-66(24"W. 2-PIECE GRILL COVER)

APPROX 6HIPPING WT. LEKG)

APPROX 6HIPPING WT. LEKG)

7.2(2.9)

APPROX 6HIPPING WT. LEKG)

7.2(2.9)

APPROX 6HIPPING WT. LEKG)

7.2(2.9)

- · STAINLESS STEEL COVER WITH VIKING PROFESSIONAL HANDLE
- · 964 | 86-66 FOR USE WITH GAS 42"W. PANGETOPS WITH A | 8"W. THERMOSTATICALLY CONTROLLED STEEL GRIDDLE/SIMMER PLATE
- · 9642 46-66 FOR USE WITH GAS/DUAL FUEL PANGES AND GAS PANGETOPS WITH A 2 4"W. THEPMOSTATICALLY CONTROLLED STEEL GRIDDLE/SIMMER PLATE
- · OCQ 2 4C-66 FOR USE WITH GAS/DUAL FUEL PANGES AND GAS PANGETOPS WITH A 24"W. GPILL
- · DOEG NOT HAVE TO BE PEMOVED WHEN OPEPATING ADJACENT GUPFACE BUPNERG



EPOILER PAN AND TRAY

おPT APPROX SHIPPING WT. LE(KG) ちち(2.5)

- · FOR USE WITH ALL VIKING BUILT-IN AND PANGE OVENS
- · HEAVY-DUTY POPCELAINIZED CONGTPUCTION
- · TRAY ALLOWS DRIPPINGS TO FALL THROUGH TO BROILER PAN
- · TRAY 10 REMOVABLE FOR EAGY CLEANING



Y-PACK AND DEIP PAN

CVD APPROX. GHIPPING WEIGHT LEY(KG) 4 (1.8)

- · NO STICK Y-PACK CAN BE USED FOR COOKING POASTS, HAMS, PIBS, ETC.
- · DPIP PAN CATCHEO DPIPPINGO FROM ITEMO COOKED IN V-PACK TO GENERATE FLAYOR AND PREVENT FLARE-UPO



BROILER PAN RACK

BPR APPROX OHIPPING WT. LPO(KG) 1 (.45)

- · FOR USE WITH VIKING BROILER PAN
- · PROVIDED BETTER BROILING AND ROADTING OPTIONS IN CONVECTION MODES



GEIDDLE GLEANING FIT

GCK APPROX SHIPPING WT. LB(KG) 5.7 (2.6)

- · FAGT AND EAGY COMMERCIAL GRADE CLEANING GYGTEM
- · SAME SYSTEM USED IN COMMERCIAL KITCHENS
- · CONTAINS ENOUGH FOR 25+ CLEANINGS
- · FOR USE ON STEEL GRIDDLES ONLY
- FIT INGLUDES:
- · 9 2 02. QUICK CLEAN SMALL APPLIANCE CLEANER
- · PAD HOLDER (1)
- · GRIDDLE POLIGHING PADS (1 PACK OF 10)
- · GQUEEGEE (1)
- · CLEANING INSTRUCTION SHEET

QUICK CLEAN SMALL APPLIANCE CLEANER CACKS APPROX SHIPPING WT. LE(KG) 1 8.4 (8.9)


- · PEPLACEMENT FOR LIQUID CLEANER SUPPLIED WITH CRIDDLE CLEANING FIT
- · 61X (6) 9 2 02. CONTAINERS PER CASE



PAD HOLDER

HACK APPROX SHIPPING WT. LEG(KG) 0.66 (0.9)

- · PEPLACEMENT FOR PAD HOLDER GUPPLIED WITH APIDDLE CLEANING KIT
- · CONSISTS OF ONE PAD HOLDER



GRIDDLE POLIGHING PADG

PACKG APPROX GHIPPING WT. LB(KG)

2.4(1.8)

- · PEPLACEMENT PADO FOR PAD HOLDER GUPPLIED WITH GRIDDLE CLEANING FIT
- · GIX (G) PACKG PER CAGE CONTAIN TEN (10) PADG EACH



GAUEEGEE

94CK

APPROX GHIPPING WT. LEG(KG)

1.1 (0.5)

- · PEPLACEMENT FOR GQUEEGEE GUPPLIED WITH GRIDDLE CLEANING KIT
- · CONGISTS OF ONE SQUEEGEE



PEPLACEMENT BLADEG

BUCK

APPROX SHIPPING WT. LEG(FG)

与(2.9)

- · PEPLACEMENT FOR GQUEEGEE BLADE GUPPLIED WITH GPIDDLE CLEANING KIT
- · CONGIGTS OF SIX (6) BLADES

BUILT-IN GAG 90" AND 96"W. COOKTOPG

V46UIO2-4B APPROX GHIPPING WT. LB(FG) 67 (90.2) V46UIO2-4B-LP (ADD LP AFTER COLOR CODE) V46UI62-6B APPROX GHIPPING WT. LB(FG) 80 (96) V46UI62-6B-LP (ADD LP AFTER COLOR CODE)




COOKTOPS (24" DEPTH)


· UPDATED COMMERCIAL-TYPE GTYLING INCORPORATEG REFINED DETAILING

· SEALED BURNERS WITH BRASS FLAME PORTS, PORCELAIN/CAST IRON CAPS, AND AUTOMATIC IGNITION/RE-IGNITION

· METAL KNOBO WITH CHILD PROOF, PUOH-TO-TURN GAFETY FEATURE

- · 90"W. COOKTOP 4 BURNER
- · LEFT FRONT 16,000 BTU HIGH/9,400 BTU LOW
- · LEFT PEAP 12,000 BTU HIGH/1,700 BTU LOW
- · PIGHT FRONT 6,000 BTU HIGH/950 BTU LOW
- · PIGHT PEAP 8,000 BTU HIGH/ 1,200 BTU LOW
- · DIMENSIONED TO FIT YIRTUALLY ALL 30"W. COOKTOP CUTOUTS
- · TWO GEPERATE GPILL COLLECTION AREAG EACH HOLDG 9.5 CUPG OF LIQUID GPILLG
- · 36"W. COOKTOP 6 BURNER
- · DIMENGIONED TO FIT VIRTUALLY ALL 36"W. COOKTOP CUTOUTS
- · ONLY "COUNTERTOP CUTOUT" SIX BURNER COOKTOP IN 96" WIDTH
- · LEFT FRONT 16,000 BTU HIGH/9,400 BTU LOW
- · LEFT PEAP, CENTER FRONT, CENTER PEAR 12,000 BTU HIGH/1,700 BTU LOW
- · PIGHT FRONT 6,000 BTU HIGH/950 BTU LOW
- · PIGHT PEAP 8,000 BTU HIGH/ 1,200 BTU LOW
- · TWO GEPARATE GPILL COLLECTION AREAG
- · NATURAL GAG GTANDARD; FOR LP/PROPANE, RECOMMEND FACTORY CONVERGION
- · FIVE YEAR LIMITED WARRANTY GURFACE BURNERS





YGOU SEPIES COOKTOP

- · FIELD CONVERGION (FROM NATURAL GAG TO LP) ORDER LPK9-V4GU CONVERGION KIT
- · FIELD CONVERSION (FROM LP TO NATURAL GAS) ORDER NF2 VGSU CONVERSION FIT
- · 4 FOOT CORD INCLUDED WITH COOKTOP
- · 2 WIPE WITH APOUND/9 PRONG PLUG
- · 120 V/60H2
- · Y46U 1 0 2/Y46U 1 62 MAXIMUM AMP6 2.0

- · OTAINLEOO OTEEL (OO) AND BLACK (BK) HAVE OTAINLEOO OTEEL TRIM/FRAME AND CONTROL PANEL.
- · HAG BLACK PORCELAIN CRATEG, BLACK PORCELAIN BURNER CAPG, AND BLACK KNOBG.
- · WHITE HAG STAINLEGG STEEL TRIM/FRAME AND CONTROL PANEL.
- ·HAG DARK ORAY PORGELAIN ORATEG, DARK ORAY PORGELAIN BURNER CAPG, AND WHITE KNOBG.
- · BRAGG TRIM OPTION (BR) FOR ANY FINIGH; INCLUDEG KNOB BEZELG, CONTROL PANEL FRAMEG AND NAME-PLATE. ALL PARTG DEGIGNED FOR MAINTAINANCE-FREE NORMAL UGE.

DESIGNER 30" & 36" WIDE -DGSU-

BUILT-IN GAS DESIGNER COOKTOPS (24" DEPTH)


BUILT-IN 90"W. CONTINUOUS GRATE DESIGNER GAS COOKTOP

DAGU 100-45

APPEOX GHIPPING WT. LEGICA) 49 (22.0)
DAGU 100-45-LP

APPEOX GHIPPING WT. LEGICA) 49 (22.0)
(ADD LP AFTER COLOR CODE)

- · GEALED BUPNERG WITH BRAGG FLAME PORTS AND PORCELAIN/CAGT IRON CAPS
- · ONE-PIECE TOOLED TOP WITH LAPGE SPILL COLLECTION APEA APOUND BUPNERS
- · HEAVY-DUTY OTAINLEGG OTEEL CONTROL KNOBG WITH PUGH-TO-TURN GAFETY FEATURE
- · 90"W. GOOKTOP 4 BURNER
- · LEFT FRONT 14,000 BTU HIGH/2,000 BTU LOW
- · LEFT PEAP 12,000 BTU HIGH/1,700 BTU LOW
- · PIGHT PEAP 8,000 BTU HIGH/ 1 200 BTU LOW
- · PIGHT FRONT 6,000 BTU HIGH/950 BTU LOW
- · OVERALL/BURNER BOX DIMENGIONG DEGIGNED TO FIT THE MAJORITY OF GIMILARLY GIZED COOKTOP CUTOUTG
- · FIVE YEAR LIMITED WARRANTY GURFACE BURNERS




BUILT-IN 36"W. CONTINUOUS GRATE DESIGNER GAS COOKTOP

D490 1 60-58 APPROX SHIPPING WT. LB(KG) 74 (99.9)

DUGU (60-55-LP APPROX SHIPPING WT. LB(FG) 74 (99.9)
(ADD LP AFTER COLOR CODE)

- · SEALED BUPNERS WITH BRAGG FLAME PORTS AND PORCELAIN/CAST IRON CAPS
- · ONE-PIECE TOOLED TOP WITH LAPGE SPILL COLLECTION APEA APOUND BUPNERS
- · HEAVY-DUTY GTAINLEGG GTEEL CONTROL FNOBG WITH PUGH-TO-TURN GAFETY FEATURE
- · 96"W. COOKTOP 5 BUPNER
- · LEFT FRONT 12,000 BTU HIGH/1,700 BTU LOW
- · LEFT PEAP 10,000 BTU HIGH/1,500 BTU LOW
- · CENTER 14,000 BTU HIGH/2,000 BTU LOW
- · PIGHT PEAP 8,000 BTU HIGH/ 1 200 BTU LOW
- · PIGHT FRONT 6,000 BTU HIGH/950 BTU LOW
- · OVERALL/BURNER BOX DIMENGIONG DEGIGNED TO FIT THE MAJORITY OF GIZED COOKTOP CUTOUTG
- · FIVE YEAR LIMITED WARRANTY GURFACE BURNERS



DAGU GERIEG AAG COOKTOPG

- · HIGHLY PECOMMENDED OPDEPING NAT. OP LP MODELS
- · 4 FOOT CORD INCLUDED WITH COOKTOP
- · 2 WIPE WITH APOUND/9 PRONG PLUG
- · 1204/60 HZ
- · MAX AMPO 2.0 (ALL UNITO)

- · BLACK (BK), WHITE (WH), STAINLESS (SS), BISCUIT (BT), STONE CRAY (SC), AND CRAPHITE CRAY (AG)
- · FINICH DECICNATEO TOP. ALL UNITO EXCEPT WHITE HAVE BLACK PORCELAIN CRATEO, BLACK PORCELAIN BURNER
 CAPO, AND BLACK FNOB CRIPG. WHITE UNITO HAVE CRAY PORCELAIN CRATEO, CRAY PORCELAIN BURNER CAPO, AND
 CRAY FNOB CRIPG
- · BRAGG TRIM OPTION KNOBG

BUILT-IN DEGIGNER GAG GOOKTOPG

20"W.

DGCU 1 05-45 APPROX SHIPPING WT. LB(FG) 67 (90.2)
DGGU 1 05-45-LP APPROX SHIPPING WT. LB(FG) 67 (90.2)
(ADD LP AFTER COLOR CODE)

96"W.

DGOU 1 65-55 APPROX SHIPPING WT. LB(KG) 80 (96.0)
DGOU 1 65-55-LP APPROX SHIPPING WT. LB(KG) 80 (96.0)
(ADD LP AFTER COLOR CODE)

45"₩.

 DGCU 155-66
 APPROX GHIPPING WT. LB(KG)
 99 (41.9)

 DGGU 155-66-LP
 APPROX GHIPPING WT. LB(KG)
 99 (41.9)

(ADD LP AFTER COLOR CODE)

DESIGNER

30", 36", & 45"


WIDE


DGCU=

BUILT-IN GAS DESIGNER

COOKTOPS (24" DEPTH)

- · SEALED BURNERS WITH BRASS FLAME PORTS AND PORCELAIN/CAST IRON BURNER CAPS
- · BUPNEPO MOUNTED IN DUPABLE, EAGY TO CLEAN CEPAMIC GLAGO
- · HEAVY-DUTY OTAINLEGG OTEEL CONTROL KNOBG WITH PUGH-TO-TURN GAFETY FEATURE
- · 90"W. COOKTOP 4 BURNER
- · LEFT FRONT 14,000 BTU HIGH/2,000 BTU LOW
- · LEFT PEAP 12,000 BTU HIGH/1,700 BTU LOW
- · PIGHT PEAR 8,000 BTU HIGH/ 1 200 BTU LOW
- · PIGHT FRONT 6,000 BTU HIGH/950 BTU LOW
- · 96"W. COOKTOP 5 BURNER
- · LEFT FRONT 12,000 BTU HIGH/1,700 BTU LOW
- · LEFT PEAR 10,000 BTU HIGH/1,500 BTU LOW
- · CENTER 1 4,000 BTU HIGH/2,000 BTU LOW
- · PIGHT PEAR 8,000 BTU HIGH/ 1 200 BTU LOW
- · PIGHT FRONT 6,000 BTU HIGH/950 BTU LOW
- · 45"W. GOOKTOP 6 BUPNER
- · LEFT FRONT 12,000 BTU HIGH/1,700 BTU LOW
- · LEFT PEAR 8,000 BTU HIGH/ 1 200 BTU LOW
- · LEFT CENTER 10,000 BTU HIGH/1,500 BTU LOW
- · PIGHT CENTER 1 4,000 BTU HIGH/2,000 BTU LOW
- · PIGHT FRONT 8,000 BTU HIGH/ 1 200 BTU LOW
- · PIGHT PEAP 6,000 BTU HIGH/950 BTU LOW
- · OVERALL/BURNER BOX DIMENGIONG DEGIGNED TO FIT THE MAJORITY OF SIMILARLY SIZED COOKTOP CUTOUTS
- · FIVE YEAR LIMITED WARRANTY GURFACE BURNERS






DUCU GERIEG UAG COOKTOPG

- · 4 FOOT CORD INCLUDED WITH COOKTOP
- · 2 WIFE WITH GROUND/9 PRONG PLUG
- · 1204/60 HZ
- · MAX AMPG 2.0 (ALL UNITG)

- · STAINLESS STEEL/BLACK(SB) STAINLESS STEEL TRIM/CONTROL PANEL AND KNOBS; BLACK CLASS, CRATES, AND KNOB CRIP
- · OTAINLEGO OTEEL/WHITE(OW) OTAINLEGO OTEEL

 TRIM/CONTROL PANEL AND KNOBO; WHITE CLAGO, CRAY CRATEG


 AND KNOB CRIP
- · BRAGG TRIM OPTION BRAGG FINIGH KNOBG




BUILT-IN ELECTRIC PADIANT GLAGO CEPAMIC COOKTOPS

20"W. - VECU I OG-4BAPPEOX GHIPPING WT. LB(KG) 52 (27.4) 76"W. - VECU I GG-GBAPPEOX GHIPPING WT. LB(KG) 67 (28.4)


- · UPDATED COMMERCIAL-TYPE STYLING INCORPORATES REFINED DETAILING
- · DEGIGNED TO FIT THE MAJORITY OF GIMILARLY GIZED GOOKTOP CUTOUTG
- · OTRONG, WEAR REGIOTANT GLAGO CERAMIC TOP
- · METAL KNOBS WITH CHILD PROOF, PUSH-TO-TURN FEATURE
- · QUICKGOOKM SURFACE ELEMENTS UTILIZE PIBBON ELEMENT TECHNOLOGY PEACH FULL POWER IN ABOUT 9 SECONDS
- · 90"W. MODELS
- · LEFT FRONT 7" 1800 WATT
- · LEFT PEAR 7" 1800 WATT; 800 WATT BPIDGE
- · PIGHT FRONT 61/2" 1,500 WATT
- · PIGHT PEAP 9" 6"/2,500 1,000 WATT
- · 96"W. MODELO
- · LEFT FRONT 84" 44"/2,200 750 WATT
- · LEFT PEAP 61/2" 1500 WATT
- · CENTER FRONT 7" 1800 WATT
- · CENTER REAR 7" 1800 WATT; 800 WATT BRIDGE
- · PIGHT FRONT 6"/1,200 WATT
- · PIGHT PEAR 9" 6"/2,500 WATT 1,000 WATT
- · FIVE YEAR LIMITED WARRANTY GURFACE ELEMENTS





YECU GEPIEG COOKTOPG

- · 4 FOOT FLEXIBLE CONDUIT INCLUDED WITH COOKTOP
- · 9 WIFE WITH APOUND
- · 240-208/120 V, 60 HZ
- · YEOU 1 05:
 - · MAXIMUM AMPS (240 VOLTS) 35.0
 - · MAXIMUM AMPG (208 VOLTG) 30.3
- · YEOU 105:
 - · MAXIMUM AMPO (240 VOLTO) 49.2
 - · MAXIMUM AMPS (208 YOLTS) 42.6



- · OTAINLEOG OTEEL/BLACK (OB) AND OTAINLEOG OTEEL/WHITE (OW) HAVE OTAINLEOG OTEEL TRIM/FRAME AND CONTROL PANEL.
- · GTAINLEGG GTEEL/BLACK UNITG HAVE BLACK GLAGG AND BLACK KNOBG
- · STAINLESS STEEL/WHITE UNITS HAVE WHITE GLASS AND WHITE KNOBS
- · BPAGG TPIM OPTION (BP) FOR ANY FINIGH; INCLUDEG KNOB BEZELG, CONTROL PANEL FRAME AND NAMEPLATE. ALL HAYE A PROTECTIVE COATING FOR MAINTENANCE-FREE NORMAL UGE.


PROFESSIONAL 30" & 36" WIDE -VCCU-


BUILT-IN ELECTRIC INDUCTION/RADIANT COOKTOPS (24" DEPTH)

BUILT-IN INDUCTION/PADIANT GLAGG CEPAMIC COOKTOPG

クロ"W. - YCCU 1 05-45 クロ"W. - YCCU 1 65-65 APPROX GHIPPING WT. LEG(FG) 52 (29.4) APPROX GHIPPING WT. LEG(FG) 69 (28.4)

- · MACNEQUICKT INDUCTION POWER GENERATORS UTILIZE MACNETIC ENER-CAY FOR SUPERIOR POWER, RESPONSIVENESS AND EFFICIENCY
- · QUICKCOOKTH ELECTRIC ELEMENTS UTILIZE PIBBON ELEMENT TECH-NOLOGY TO REACH FULL POWER IN ABOUT 9 SECONDS
- · GTRONG, WEAR REGIGTANT GLAGG CERAMIC TOP
- · COMMERCIAL-TYPE STYLING
- · 90"W. MODELG
 - · LEFT FRONT (PADIANT) 9" 6"/2,500 1,000 WATT
 - · LEFT PEAP (PADIANT) 7"/1,500 WATT
 - · PIGHT FRONT (INDUCTION) 7"/1,800 WATT
 - · PIGHT PEAP (INDUCTION) 9"/7,700 WATT
- · 96"W. MODELO
- · LEFT FRONT (PADIANT) 9" 6"/2,200 750 WATT
- · LEFT PEAP (PADIANT) 7"/1,500 WATT
- · CENTER FRONT (PADIANT) 7"/1,800 WATT
- · CENTER REAR (RADIANT) 7"/1,800 WATT; 800 WATT BRIDGE
- · PIGHT FRONT (INDUCTION) 7"/1,800 WATT
- · PIGHT PEAP (INDUCTION) 9"/9,700 WATT
- · FIVE YEAR LIMITED WARRANTY GURFACE ELEMENTS





YCCU SEPIES COOKTOPS

- · 4 FOOT FLEXIBLE CONDUIT INCLUDED WITH COOKTOP
- · 9 WIPE WITH GROUND
- · 240-208/120 V, 60 HZ
- · Y660105:
- · MAXIMUM AMP6 (240 VOLT6) 37.9
- · MAXIMUM AMPG (208 VOLTG) 35.4
- · Y660165:
- · MAXIMUM AMPO (240 VOLTO) 55
- · MAXIMUM AMPG (208 VOLTG) 50.2

- · OTAINLEOG OTEEL/BLACK (OB) AND OTAINLEOG OTEEL/WHITE (OW) HAVE OTAINLEOG OTEEL TRIM/FRAME AND CONTROL PANEL.
- \cdot 9TAINLE99 9TEEL/BLACK UNIT9 HAVE BLACK GLA99 AND KNOB9.
- · GTAINLEGG GTEEL/WHITE UNITG HAVE WHITE GLAGG AND WHITE KNOBG
- · BPAGG TPIM OPTION (BP) FOR ANY FINIGH; INCLUDEG KNOB BEZELG, CONTROL PANEL FRAME AND NAMEPLATE. ALL HAVE A PROTECTIVE COATING FOR MAINTENANCE-FREE NORMAL UGE.


PROFESSIONAL 30" & 36" WIDE -VICU-


BUILT-IN ELECTRIC ALL INDUCTION COOKTOPS (24" DEPTH)

BUILT-IN ALL INDUCTION COOKTOPS

クロ"W. - YICU 1 05-45 クロ"W. - YICU 1 65-65 APPROX OHIPPING WT. LEKG) 52 (29.4) APPROX OHIPPING WT. LEKG) 69 (28.4)

- · MACNEQUICKTM INDUCTION POWER GENERATORS UTILIZE MAC-NETIC ENERGY FOR SUPERIOR POWER, RESPONSIVENESS AND EFFICIENCY
- · OTPONG, WEAP PEOIOTANT GLAGO CEPAMIC TOP
- · COMMERCIAL-TYPE STYLING
- · 90"W. MODELO
 - · LEFT FRONT 9"/2,700 WATT
 - · LEFT PEAP 7"/1,800 WATT
- · PIGHT FRONT 7"/1,200 WATT
- · PIGHT PEAP 9"/9,900 WATT
- · 36"W. MODELS
- · LEFT FRONT (ELECTRIC) 7"/1,800 WATT
- · LEFT PEAP (ELECTPIC) 9"/2,700 WATT
- · CENTER FRONT (ELECTRIC) 9"/2,700 WATT
- · CENTER REAR (ELECTRIC) 7"/1,800 WATT
- · PIGHT FRONT (INDUCTION) 7"/1,200 WATT · PIGHT PEAR (INDUCTION) - 9"/9,900 WATT
- · FIVE YEAR LIMITED WARRANTY GURFACE ELEMENTO





YICU SEPIES COOKTOPS

- · 4 FOOT FLEXIBLE CONDUIT INCLUDED WITH COOKTOP
- · 9 WIFE WITH APOUND
- · 240-208/120 V. 60 HZ
- · VIGU 105:
- · MAXIMUM AMP6 (240 VOLT6) 37.5
- · MAXIMUM AMPG (208 VOLTG) 99
- · VICU 1 65:
- · MAXIMUM AMPS (2 40 VOLTS) 56.3
- · MAXIMUM AMPG (208 VOLTG) 49

- · OTAINLEOG OTEEL/BLACK (OB) AND OTAINLEOG OTEEL/WHITE (OW) HAVE OTAINLEOG OTEEL TRIM/FRAME AND CONTROL PANEL.
- · OTAINLEGO OTEEL/BLACK UNITO HAVE BLACK GLAGO AND KNOBO.
- · STAINLEGS STEEL/WHITE UNITS HAVE WHITE GLASS AND WHITE KNOBS
- · BRAGG TRIM OPTION (BP) FOR ANY FINIGH; INGLUDEG KNOB BEZELG, CONTROL PANEL
 FRAME AND NAMEPLATE. ALL HAVE A PROTECTIVE COATING FOR MAINTENANCE-FREE NORMAL UGE.

DESIGNER

30", 36" & 45" WIDE -DECU-

BUILT-IN ELECTRIC RADIANT GLASS CERAMIC COOKTOPS (24" DEPTH)

BUILT-IN ELECTRIC PADIANT GLAGO CERAMIC COOKTOPS

70"W. - DECU 1 05 - 4B

APPROX OHIPPING WT. LB(FG) 52 (27.4)


76"W. - DECU 1 65 - 5B

APPROX OHIPPING WT. LB(FG) 60 (27.0)


45"W. - DECU 1 55 - 6B

APPROX OHIPPING WT. LB(FG) 7 1 (92.0)

- · STRONG, WEAR REGISTANT GLASS CERAMIC TOP
- · QUICKCOOKTH GUPFACE ELEMENTS UTILIZE PIBBON ELEMENT TECHNOLOGY - PEACH FULL POWER IN ABOUT 9 SECONDS
- · HEAVY-DUTY GTAINLEGG GTEEL CONTROL FNODG WITH PUGH-TO TURN GAFE-TY FEATURE
- · 90"W. COOKTOP 4 ELEMENT
- · LEFT FRONT 7" 1,800 WATT ELEMENT; 800 WATT BRIDGE
- · LEFT PEAP 7" 1,800 WATT ELEMENT
- · PIGHT PEAP 9"- 6" 2,500 1,000 WATT ELEMENT
- · PIGHT FRONT 61/2" 1,500 WATT ELEMENT
- · 76"W. COOKTOP 5 ELEMENT
- · LEFT FRONT 7" 1,800 WATT ELEMENT; 800 WATT BRIDGE
- · LEFT PEAP 7" 1,800 WATT ELEMENT
- · CENTER 9"- 6" 2,500 1,000 WATT ELEMENT
- · PIGHT PEAP 84"- 49/4" 2,200 750 WATT ELEMENT
- · PIGHT FRONT 61/2" 1,500 WATT ELEMENT
- · 45"W. COOKTOP G ELEMENT
- · LEFT FRONT 7" 1,800 WATT ELEMENT; 800 WATT BRIDGE
- · LEFT PEAP 7" 1,800 WATT ELEMENT
- · LEFT CENTER 9"- 6" 2,500 1,000 WATT ELEMENT
- · PIGHT CENTER 6" 1,200 WATT ELEMENT
- · PIGHT PEAP 814"- 47/4" 2,200 750 WATT ELEMENT
- · PIGHT FRONT 61/2" 1,500 WATT ELEMENT
- · OVERALL/BURNER BOX DIMENGIONG DEGIGNED TO FIT THE MAJORITY OF GIMILARLY GIZED COOKTOP CUTOUTG
- · FIVE YEAR LIMITED WARRANTY SURFACE BURNERS



クロ"W. - DECUIO5-45



ク6"W. - DECU 1 65-55

DECU SEPIES COOKTOPS

- · 4 FOOT FLEXIBLE CONDUIT INCLUDED WITH COOKTOP
- · 9 WIFE WITH GROUND
- · 240-208 V, 60 HZ
- · MAX AMP USAGE
 - · YEOU (05 カ5/カロ.カ
 - · YEGU 1 65 44/34.2
 - · YECU 155 49/42.8



45"W. - DECUISS-65

- · STAINLESS STEEL/BLACK(SB) STAINLESS STEEL TRIM/CONTROL PANEL AND KNOBS; BLACK GLASS AND KNOB CRIP
- · GTAINLEGG GTEEL/WHITE(GW) GTAINLEGG GTEEL TRIM/CONTROL PANEL AND KNOBG; WHITE GLAGG; GRAY KNOB GRIP
- · BRAGG TRIM OPTION (BR) BRAGG FINIGH KNOBG

VGSU COOKTOP ACCESSORIES

WOK PING PWRG-6

APPROX GHIPPING WT. LEG(KG) 6(2.7)

- · STAINLESS STEEL
- · DEGIGNED TO GECUPELY FIT ON ALL Y46U GOOKTOPG (LEFT FRONT BURNER REGOMMENDED)
- · SIX PER CASE




PORTABLE APIDDLE

9UP-P4D

APPROX GHIPPING WT. LEG(KG) 8 (9.6)

- · CAST ALUMINUM NO-STICK FINISH ON COOKING SURFACE
- · GREAGE GROOVE GURROUNDS COOKING AREA
- · PACK, SECUPED BY SUPFACE GRATES, HOLDS GRIDDLE IN PLACE
- · CAN ALGO BE UGED TO QUICKLY DEFPOST FROZEN FOODS




HAPDWOOD GOVER

GUP-CCHG

APPROX GHIPPING WT. LEG(FG) 48 (21.6)

- · MAPLE HAPDWOOD "BUTCHER BLOCK" CONSTRUCTION
- · CAN ALGO BE UGED AG CUTTING BOAPD
- · FITS OVER SURFACE GRATES
- · 101/2"W. X 201/2"L. X 21/4"H.



LP/PROPANE CONVERGION FIT

LPK 9-VGOU APPROX GHIPPING WT. LIB(KG) 1 (0.5)

FOR Y46U 1 0 2 AND Y46U 1 62 MODELS

- · FOR FIELD CONVERSION FROM NATURAL TO LP/PROPANE GAS
- · INSLUDES ALL HARDWARE NECESSARY TO CONVERT 90" OF 96"W. VGSU COOKTOP

NATURAL CONVERSION FIT

NK 2 YGOU APPROX SHIPPING WT. LEG(KG) I (0.5)

FOR YAGU AND YAGU I G2 MODELG

- · FOR FIELD CONVERSION FROM LP/PROPANE GAS TO NATURAL
- · INCLUDEO ALL HARDWARE NECEOGARY TO CONVERT 90" OR 96"W. VGGU COOKTOP

DESIGNER SURFACE COOKING ACCESSORIES

WOK PING DGG-WRG

APPROX GHIPPING WT. LB(KG) (0.5)

- · STAINLESS STEEL
- · DEGIGNED TO GEGURELY FIT ON ANY DEGIGNER DAGU GAG COOKTOPG (FRONT LEFT BURNER RECOMMENDED)



PORTABLE APIDOLE

APPROX GHIPPING WT. LEG(KG) 8 (3.6)

- · CAST ALUMINUM WITH PUGGED COMMERCIAL GRADE NO-STICK FINISH ON COOKING SURFACE
- · AREAGE TROUGH
- · CAN ALGO BE UGED TO QUICKLY DEFROGT FROZEN FOODS
- · FOR USE WITH DESIGNER DAGU AND DAGU COOKTOPS



POPTABLE APIDDLE

DEC-PUD APPROX 6H

APPROX GHIPPING WT. LEG(KG) 8 (9.6)

- · CAST ALUMINUM WITH PUGGED COMMERCIAL GRADE NO-STICK FINISH ON COOKING SUPFACE
- · GREAGE TROUGH
- · PLACE OVER TWO LEFT ELEMENTS WITH BRIDGE ELEMENT
- · FOR USE WITH DESIGNER DECU ELECTRIC COOKTOPS



LP/PROPANE CONVERGION KIT

DLPK APPROX SHIPPING WT. LIB(KG) 2 (0.9)

- · FOR FIELD CONVERSION FROM NATURAL TO LP/PROPANE GAS
- · INCLUDES ALL HAPDWAPE NECESSARY TO CONVERT 90" OR 96"W. D49U COOKTOP


PROFESSIONAL ULTRA PREMIUM SELECT


BUILT-IN ELECTRIC 27" & 30" WIDE SINGLE/DOUBLE OVENS

ELECTPIC 27" AND 90" W. THEPMAL - CONVECTION OVENG

VEOO 1 27 - 27"W. ONGLE
VEOO 1 27 - 27"W. ONGLE
VEOO 1 27 - 27"W. DOUBLE
VEOO 1 20 - 20"W. ONGLE
VEOO 1 20 - 20"W. ONGLE
VEOO 1 20 - 20"W. DOUBLE
APPLOX OHIPPING WT. LB(FG) 278 (1 26.1)
VEOO 1 20 - 20"W. DOUBLE
APPLOX OHIPPING WT. LB(FG) 4 2 4 (1 9 2.2)

- · EXCLUDIVE VARI-OPEED DUAL FLOW+TH CONVECTION DYSTEM WITH S 1/2" DIAMETER FAN BLADE LARGEST IN THE INDUSTRY
- · EXOLUGIVE PAPID PEADY+TM PREHEAT GYGTEM PROVIDEG GUPER FAGT PREHEATING
- · CONCEALED I O-PAGG DUAL BAKE ELEMENT PROVIDEG FINER TEMPERATURE CONTROL AND MAKEG CLEANUP EAGY
- · 10-PAGG BEOILER WITH HEAT REFLECTOR
- · HALOGEN OVEN LIGHTING
- · THREE HEAVY DUTY RACKO / GIX PORCELAIN COATED RACK POGITIONG
- · COMMERCIAL TYPE STYLING
- · DIGITAL CLOCK/OYEN FUNCTIONS
- · 1 00 MINUTE TIMER
- · GET GOOKING TIME FOR UP TO 12 HOURS
- · TONE AND DIGITAL DIGPLAY INDICATE PRE-GET GOOKING TIME IG FINIGHED
- · GELF-GLEAN OVENS
- · OVEN FUNCTIONS (CONVECTION SYSTEM IN UPPER OVEN OF DOUBLE OVEN)
- · TWO-ELEMENT BAKE
- · CONVECTION BAKE
- · TRUCONVECTM CONVECTION COOK (ELEMENT AROUND FAN)
- · CONVECTION POAGT
- · CONVECTION EPOIL
- ·HIBROLL
- · MEDIUM BROIL
- · LOW BROIL
- · CONVECTION DEHYDRATE
- · CONVECTION DEFEOST
- · 27"W. OVENG: LAPGEGT GELF CLEAN, CONVECTION OVENG- EXCLUGIVE
- · OYEPALL 227/16" X 161/2"H. X 191/2"D. 4.2 CUBIC FEET
- · AHAM STANDARD 227/16" X 16/2"H. X 16/2/16"D. 3.6 CUBIC FEET
- · 90"W. OYENG: LAPGEST SELF CLEAN, CONVECTION OVENS- EXCLUSIVE
- · OVERALL 257/10" X 161/2"H. X 191/2"D. 4.8 CUBIC FEET
- · AHAM OTANDAPD 257/16" X 161/2"H. X 1617/16"D. 4.1 CUBIC FEET
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVENS
- · FIVE-YEAR LIMITED WARRANTY HEATING ELEMENTS





YEGO/YEDO GEPIEG OYENG

- · 5 FOOT FLEXIBLE STEEL CONDUIT WITH OVEN
- · 4 WIFE WITH APOUND
- · 240-208/120 V/60 HZ
- · MAXIMUM AMPS 2 40 VOLTS/208 VOLTS
- · ALL VEGO 90 AMP CONNECTION PEQUIPED
- · ALL VEDO 50 AMP CONNECTION PEQUIPED

- · OTAINLEGO OTEEL (GO), BLACK (BK), WHITE (WH)
- · FINIGH DEGICNATEG DOOR FRONTG. BLACK UNITG HAVE A BLACK CONTROL PANEL AND BLACK KNOBG/GWITCHEG. WHITE UNITG HAVE A WHITE CONTROL PANEL AND WHITE KNOBG/GWITCHEG. GTAINLEGG GTEEL AND ALL COLOR FINIGHEG HAVE A GTAINLEGG GTEEL CONTROL PANEL AND BLACK KNOBG/GWITCHEG. ALL FINIGHEG HAVE GILVER FINIGHED VERTICAL/HORIZONTAL TRIM, AND GTAINLEGG GTEEL DOOR HANDLEG WITH CHROME PLATED BRACKETG.
- · BRAGG TRIM OPTIONG (BR) FOR ANY FINIGH; INCLUDEG NAMEPLATE, WINDOW TRIM, DOOR HANDLEG/BRACKETG AND FNOB BEZELG. GUPER DURABLE, LONG LAGTING BRAGG FINIGH ON "HIGH TRAFFIC" PARTG (HANDLEG); ALL OTHER PARTG HAVE A DURABLE PROTECTIVE COATING. ALL PARTG DEGIGNED FOR MAINTENANCE-FREE UGE.

PROFESSIONAL ULTRA PREMIUM PREMIERE

BUILT-IN ELECTRIC 27" & 30" WIDE SINGLE/DOUBLE OVENS

ELECTPIC 27" AND 90" W. THEPMAL - CONVECTION OVENS


 YE00527-27"W. GINGLE
 APPROX GHIPPING WT. LE(KG)
 279(129.8)


 YED0527-27"W. DOUBLE
 APPROX GHIPPING WT. LE(KG)
 409(185.5)

 YE00590-90"W. GINGLE
 APPROX GHIPPING WT. LE(KG)
 299(192.9)

 YED0590-90"W. DOUBLE
 APPROX GHIPPING WT. LE(KG)
 449(209.7)

- · EXOLUGIVE VARI-SPEED DUAL FLOW+TM CONVECTION SYSTEM WITH S 1/2" DIAMETER FAN BLADE LARGEST IN THE INDUSTRY
- · EXOLUGIVE PAPID PEADY+TH PREHEAT GYGTEM PROVIDEG GUPER FAGT PREHEATING
- · CONCEALED I O-PAGG DUAL BAKE ELEMENT PROVIDEG FINER TEMPERATURE CONTROL AND MAKEG CLEANUP EAGY
- · GOUPMET GLOTH GLAGG ENGLOGED INFPAPED EPOILER
- · THREE STRATEGICALLY LOCATED HALOGEN OVEN LIGHTS
- · THREE HEAVY DUTY RACKS / SIX PORCELAIN COATED RACK POSITIONS INCLUDING ONE TRUCKIDEM FULL EXTENSION RACK (ONE IN EACH OVEN OF A DOUBLE OVEN)
- · COMMERCIAL TYPE STYLING
- · DIGITAL CLOCK/OYEN FUNCTIONS
- · 1 00 MINUTE TIMER
- · SET COOKING TIME FOR UP TO 12 HOURS
- · DELAY GOOKING FEATURE
- · TONE AND DIGITAL DIGPLAY INDICATE PRE-GET COOKING TIME IG FINIGHED
- · MEAT PROBE (UPPER OVEN IN DOUBLE OVENO)
- · TIMER GOUNDO AND OVEN GHUTG OFF WHEN DEGIRED TEMPERATURE IG REACHED
- · GELF-GLEAN OVENG
- · OVEN FUNCTIONS (CONVECTION SYSTEM IN BOTH UPPER AND LOWER OVEN OF DOUBLE OVENS)
- · TWO-ELEMENT BAKE
- · CONVECTION BAKE
- · TRUCONVECTM CONVECTION COOK (ELEMENT AROUND FAN)
- · CONVECTION POAGT
- · CONVECTION BROIL
- ·HIPPOIL
- · MEDIUM BROIL
- · LOW BROIL
- · CONVECTION DEHYDRATE
- · CONVECTION DEFPOST
- · 2 7"W. OYENG: LAP-GEGT SELF CLEAN, CONVECTION OYENG- EXCLUSIVE
- · OYEPALL 227/16" X 161/2"H. X 191/2"D. 4.2 CUBIC FEET
- · AHAM STANDARD 227/16" X 1612"H. X 1612/16"D. 2.6 CUBIC FEET
- · 90"W. OYENG: LAPGEGT GELF CLEAN, CONVECTION OYENG- EXCLUSIVE
- · OVERALL 257/16" X 16/2"H. X 19/2"D. 4.8 CUBIC FEET
- · AHAM STANDARD 257/16" X 16/2"H. X 16/2/16"D. 4.1 CUBIC FEET
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVENS
- · FIVE-YEAR LIMITED WARRANTY HEATING ELEMENTS





YEGO/YEDO GERIEG OYENG

- · 5 FOOT FLEXIBLE STEEL CONDUIT WITH OVEN · 4 WIRE WITH OROUND · 240-208/120 V/60 HZ
- · MAXIMUM AMP6 2 40 VOLT6/208 VOLT6 · ALL VEGO 90 AMP CONNECTION REQUIRED · ALL VEDO 90 AMP CONNECTION REQUIRED

- · STAINLEGG (GG), BLACK (BK), WHITE (WH), ALMOND (AL), BIGCUIT (BT), STONE GRAY (GG), GRAPHITE GRAY (GG), BURGUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREGT GREEN (FG), VIKING BLUE (VB), COBALT BLUE (CB) AND EGGPLANT (EP)
- · FINIGH DEGIGNATEG DOOR FRONTG. BLACK UNITG HAVE A BLACK CONTROL PANEL AND BLACK KNOBG/GWITCHEG.
 WHITE UNITG HAVE A WHITE CONTROL PANEL AND WHITE KNOBG/GWITCHEG. GTAINLEGG GTEEL AND ALL COLOR FINIGHEG
 HAVE A GTAINLEGG GTEEL CONTROL PANEL AND BLACK KNOBG/GWITCHEG. ALL FINIGHEG HAVE GILVER FINIGHED VERTICAL/HORIZONTAL TRIM, AND GTAINLEGG GTEEL DOOR HANDLEG WITH CHROME PLATED BRACKETG.
- · BRAGO TRIM OPTIONO (BR) FOR ANY FINIOH; INCLUDEO NAMEPLATE, WINDOW TRIM, DOOR HANDLEO/BRACKETO AND FNOB BEZELO. GUPER DURABLE, LONG LAGTING BRAGO FINIOH ON "HIGH TRAFFIC" PARTO (HANDLEO); ALL OTHER PARTO HAVE A DURABLE PROTECTIVE COATING. ALL PARTO DEGIGNED FOR MAINTENANCE-FREE UGE.

ELECTRIC 27" AND 30" W. THERMAL - CONVECTION OVENS

DEGO 1 27 - 27"W. GINGLE APPROX GHIPPING WT. LEG(KG) 258 (117.6) DEDO 1 27- 27"W. DOUBLE APPROX GHIPPING WT. LEG(KG) 284(147.2)


DEDO 190-90"W. DOUBLE APPROX 6HIPPING WT. LEG(FG) 424 (192.3)

DEGO 190-90"W. GINGLE APPROX SHIPPING WT. LEG(KG) 278(126.1)

DESIGNER ULTRA PREMIUM SELECT BUILT-IN ELECTRIC 27" & 30" WIDE SINGLE/DOUBLE OVENS

- · EXCLUSIVE VARI-SPEED DUAL FLOW+TH CONVECTION SYSTEM WITH 8 1/2" DIAMETER FAN BLADE - LARGEOT IN THE INDUSTRY
- · EXOLUGIVE PAPID PEADY+TH PREHEAT GYGTEM PROVIDEG GUPER FAGT PREHEATING
- · CONCEALED I O-PAGG DUAL BAKE ELEMENT PROVIDEG FINER TEMPERATURE CONTROL AND MAKES CLEANUP EASY
- · 10-PAGG BROILER WITH HEAT PEFLECTOR
- · HALOGEN OVEN LIGHTING
- · THPEE HEAVY DUTY PACKO / GIX POPCELAIN COATED PACK POGITIONG
- · COMMERCIAL TYPE OTYLING
- · DIGITAL CLOCK/OVEN FUNCTIONS
- · 1 00 MINUTE TIMER
- · SET COOKING TIME FOR UP TO 12 HOURS
- · TONE AND DIGITAL DIGPLAY INDICATE PRE-GET COOKING TIME IG FINIGHED
- · GELF-CLEAN OVENO
- · OVEN FUNCTIONS (CONVECTION SYSTEM IN UPPER OVEN OF DOUBLE OVEN)
- · TWO-ELEMENT BAKE
- · TRUCONVECTM CONVECTION COOK (ELEMENT AROUND FAN)
- · CONVECTION POAGT
- · CONVECTION BROIL
- · HI 150201L
- · MEDIUM BROIL
- · LOW BROIL
- · CONVECTION DEHYDRATE
- · CONVECTION DEFPOST
- · 2 7"W. OYENG: LAPGEGT GELF CLEAN, CONVECTION OYENG- EXCLUGIVE
- · OVERALL 227/16" X 16/2"H. X 19/2"D. 4.2 CUBIC FEET
- · AHAM OTANDARD 227/16" X 1012"H. X 1017/16"D. 9.6 CUBIC FEET
- · 90"W. OYENG: LAPGEGT GELF CLEAN, CONVECTION OYENG- EXCLUGIVE
- · OVERALL 257/16" X 161/2"H. X 191/2"D. 4.8 CUBIC FEET
- · AHAM STANDARD 257/16" X 16/2"H. X 16/17/16"D. 4.1 CUBIC FEET
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVENS
- · FIVE-YEAR LIMITED WARRANTY HEATING ELEMENTS

0. Sylvania Sylvania 0



DEGO/DEDO GERIEG OVENG

- · 5 FOOT FLEXIBLE STEEL CONDUIT WITH OVEN
- · 4 WIFE WITH OF OUND
- · 240-208/120 V/60 HZ
- · MAXIMUM AMPS 2 40 VOLTS/208 VOLTS
- · ALL DEGO 90 AMP CONNECTION PEQUIPED
- · ALL DEDO 50 AMP CONNECTION PEQUIPED

- · GTAINLEGG GTEEL (GG), BLACK (BK), AND WHITE (WH)
- · DOOR FRONTS AND CONTROL PANEL MATCH DESIGNATED FINISH; STAINLESS STEEL KNOBS, BUTTONS AND HANDLE(S); BLACK KNOB GRIPG FOR ALL FINIGHEG EXCEPT WHITE - WHITE FINIGH HAG GRAY KNOB GRIPG.
- · BRAGG TRIM OPTIONG (BR) GUPER DURABLE, LONG LAGTING BRAGG FINIGH KNOBG AND HANDLE(G)

ELECTRIC 27" AND 30" W. THERMAL - CONVECTION OVENS

APPROX GHIPPING WT. LEKY) 279 (129.8) APPROX GHIPPING WT. LEKY 409 (185.5) APPROX GHIPPING WT. LEKY 299 (192.9) DEG0527 - 27"W. GINGLE DED0527-27"W. DOUBLE DEG0570- 70"W. GINGLE DEDO570-70"W. DOUBLE APPROX GHIPPING WT. LEG(KG) 449 (209.7)

· EXCLUSIVE TIMEPIECE CLOCK/TIMEP


- · EXCLUDIVE YARI-OPEED DUAL FLOW+TH CONVECTION GYOTEM WITH 8 1/2" DIAMETER FAN BLADE - LARGEST IN THE INDUSTRY
- · EXOLUGIVE PAPID PEADY+TM PREHEAT GYSTEM PROVIDES SUPER FAST PREHEATING
- · CONCEALED I O-PAGG DUAL BAKE ELEMENT PROVIDEG FINER TEMPERATURE
- CONTROL AND MAKES CLEANUP EASY
- · GOUPMET GLOTH GLAGG ENGLOGED INFRAPED BROILER
- · THEEE OTEATEGICALLY LOCATED HALOGEN OVEN LIGHTS
- · THREE HEAVY DUTY RACKS / SIX PORCELAIN COATED RACK POSITIONS INCLUDING ONE TRUGLIDETM FULL EXTENSION RACK (ONE IN EACH OVEN OF A DOUBLE OVEN)
- COMMERCIAL TYPE STYLING
- · DIGITAL CLOCK/OYEN FUNCTIONS
- · 1 00 MINUTE TIMER
- · SET GOOKING TIME FOR UP TO 12 HOURS
- · DELAY GOOKING FEATURE
- · TONE AND DIGITAL DISPLAY INDICATE PRE-SET COOKING TIME IS FINISHED
- · MEAT PROBE (UPPER OVEN IN DOUBLE OVENS)
- · TIMER GOUNDO AND OVEN GHUTG OFF WHEN DEGIRED TEMPERATURE IG REACHED
- · GELF-CLEAN OVENG
- · OVEN FUNCTIONS (CONVECTION SYSTEM IN BOTH UPPER AND LOWER OVEN OF DOUBLE OVENO)
- · TWO-ELEMENT BAKE
- · CONVECTION BAKE
- · TRUCONVECTM CONVECTION COOK (ELEMENT AROUND FAN)
- · CONVECTION POAGT
- · CONVECTION BROIL
- ·HIBROL
- · MEDIUM BROIL
- · LOW BROIL
- · CONVECTION DEHYDRATE
- · CONVECTION DEFPOST
- · 2 7"W. OYENG: LAPGEGT GELF CLEAN, CONVECTION OYENG- EXCLUGIVE
- · OVERALL 227/16" X 161/2"H. X 191/2"D. 4.2 CUBIC FEET
- · AHAM STANDARD 227/16" X 161/2"H. X 1619/16"D. 9.6 CUBIC FEET
- · 90"W. OVENO: LAPCIEGT GELF CLEAN, CONVECTION OVENO- EXCLUGIVE
- · OYEPALL 257/16" X 161/2"H. X 191/2"D. 4.8 CUBIC FEET
- · AHAM STANDARD 257/16" X 161/2"H. X 1619/16"D. 4.1 CUBIC FEET
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OYENG
- · FIVE-YEAR LIMITED WARRANTY HEATING ELEMENTS


DEGO/DEDO GEPIEG OVENG

- · 5 FOOT FLEXIBLE STEEL CONDUIT WITH OVEN
- · 4 WIFE WITH APOUND
- · 240-208/120 Y/60 HZ
- · MAXIMUM AMPS 240 VOLTS/208 VOLTS
 - · ALL DEGO 90 AMP CONNECTION PEQUIPED
- · ALL DEDO 50 AMP CONNECTION PEQUIPED

- · OTAINLEGO OTEEL (GO), BLACK (BK), WHITE (WH), BIOCUIT (BT), STONE GRAY (SG), GRAPHITE GRAY (GG)
- · DOOR PANEL AND CONTROL PANEL MATCH DESIGNATED FINISH: STAINLESS STEEL KNOBS, BUTTONS AND HANDLE(S); BLACK KNOB GRIPS FOR ALL FINISHES EXCEPT WHITE - WHITE FINISH HAG GRAY KNOB GRIPG.
- · BRAGG TRIM OPTIONG (BR) GUPER DURABLE, LONG LAGTING BRAGG FINIGH - KNOBG AND HANDLEG







ELECTRIC 27" AND 30" W. THERMAL - CONVECTION OVENS

DEGO 1 2 TT - 2 T"W. ONALE APPROX OHIPPINA WT. LB(F4) 250 (117.6)
DEDO 1 2 TT - 2 T"W. DOUBLE APPROX OHIPPINA WT. LB(F4) 204 (174.2)
DEGO 1 2 OT - 20"W. ONALE APPROX OHIPPINA WT. LB(F4) 270 (126.1)

DEDO 190T-90"W. DOUBLE APPROX GHIPPING WT. LB(KG) 424(192.9)

DESIGNER

ULTRA PREMIUM


TOUCH CONTROL SELECT


BUILT-IN ELECTRIC

27" & 30" WIDE

SINGLE/DOUBLE OVENS

- · EXCLUGIVE CUGTOM DEGICNED ELECTRONIC TOUCH CONTROLG WHICH DIGAPPEAR WHEN NOT IN UGE
- · EXCLUGIVE YARI-GPEED DUAL FLOW+TM CONVECTION GYGTEM WITH 8 1 / 2 " DIAMETER FAN BLADE LARGEGT IN THE INDUGTRY
- · EXOLUGIVE PAPIO PEADY+TH PREHEAT GYGTEM PROVIDEG GUPER FAGT PREHEATING
- · CONCEALED I O-PAGG DUAL BAKE ELEMENT PROVIDEG FINER TEMPERATURE CONTROL AND MAKEG CLEANUP EAGY
- · 10 PAGG BROILER WITH HEAT REFLECTOR
- · HALOGEN OVEN LIGHTING
- · THPEE HEAVY-DUTY PACKO/OIX POPCELAIN COATED PACK POOITIONO
- · COMMERCIAL TYPE STYLING
- · DIGITAL CLOCK/OYEN FUNCTIONS
- · 100 MINUTE TIMER
- · SET COOKING TIME FOR UP TO 12 HOURS
- · DELAY GOOKING FEATURE
- · TONE AND DIGITAL DIGPLAY INDICATE PRE-GET COOKING TIME IG FINIGHED
- · GELF-CLEAN OVENG
- · OVEN FUNCTIONS (CONVECTION SYSTEM IN UPPER OVEN OF DOUBLE OVEN)
- · TWO-ELEMENT BAKE
- · CONVECTION BAKE
- · TRUCONVECT CONVECTION COOK (ELEMENT AROUND FAN)
- · CONVECTION POAGT
- · CONVECTION EPOIL
- ·HIBROLL
- · MEDIUM BROIL
- · LOW BROIL
- · CONVECTION DEHYDRATE
- · CONVECTION DEFPOST
- · GABBATH MODE
- · 27"W. OYENG: LAPGEGT GELF CLEAN, CONVECTION OVENG EXCLUGIVE
- · OVERALL 227/16"W. X 1612"H. X 1912"D. 4.2 CUBIC FEET
- · AHAM OTANDAPO 227/16"W. X 1612/16"D. 9.6 CUBIC FEET
- · 90"W. OVENO: LAPGEOT GELF CLEAN, CONVECTION OVENO EXCLUGIVE
- · OVERALL 257/16"W. X 161/2"H. X 191/2"D. 4.8 CUBIC FEET
- · AHAM STANDARD 257/16"W. X 1612"H. X 1617/16"D. 4.1 CUBIC FEET
- · TEN YEAR LIMITED WARRANTY PORCELAIN OVENS
- · FIVE-YEAR LIMITED WARRANTY HEATING ELEMENTS





DEGO/DEDO GEPIEG OVENG

- · 5 FOOT FLEXIBLE STEEL CONDUIT WITH OVEN
- · 4 WIPE WITH GROUND
- · 240-208/120 V/60 HZ
- · MAXIMUM AMPS 2 40 VOLTS/208 VOLTS
- · ALL DEGO 90 AMP CONNECTION PEQUIPED
- · ALL DEDO 50 AMP CONNECTION PEQUIPED

- · OTAINLEOO OTEEL (OO), BLACK (BK), WHITE (WH), BIOCUIT (BT), OTONE GRAY (OG), GRAPHITE GRAY (GG)
- · DOOR PANEL AND CONTROL PANEL MATCH DEGIGNATED FINIGH; GTAINLEGG GTEEL HANDLE(G)
- · BRAGG TRIM OPTIONG (BR) GUPER DURABLE, LONG LAGTING BRAGG FINIOH HANDLE(G)

ELECTPIC 27" AND 90" W. THEPMAL - CONVECTION OVENS DESCI 27T - 27"W. SINGLE APPROX SHIPPING WT. LE(KG) 279 (129.8) DEDCI 27T - 27"W. DOUBLE APPROX SHIPPING WT. LE(KG) 409 (185.5) DESCI 90T - 90"W. SINGLE APPROX SHIPPING WT. LE(KG) 299 (192.9)


DESIGNER
77 (127.6)
17 (127.6)
29 (185.5)
29 (185.5)
29 (185.5)
29 (185.5)
39 (192.9)
449 (209.7)
TOUCH CONTROL PREMIERE
BUILT-IN ELECTRIC
27" & 30" WIDE


SINGLE/DOUBLE OVENS

- · EXCLUSIVE CUSTOM DESIGNED ELECTRONIC TOUCH CONTROLS WHICH DISAPPEAR WHEN NOT IN USE
- · EXCLUGIVE VARI-OPEED DUAL FLOW+TM CONVECTION GYGTEM WITH 6 1/2" DIAMETER FAN BLADE LARGEGT IN THE INDUSTRY

DEDO 1 90T- 90"W. DOUBLE APPROX SHIPPING WT. LEG(KG)

- · EXOLUGIVE PAPID PEADY+TH PREHEAT GYGTEM PROVIDEG GUPER FAGT
 PREHEATING
- · CONCEALED I O-PAGG DUAL BAKE ELEMENT PROVIDEG FINER TEMPERATURE CONTROL AND MAKEG CLEANUP EAGY
- · GOUPMET GLOTH GLASS ENGLOSED INFRAPED BROILER
- · THREE STRATEGICALLY LOCATED HALOGEN OVEN LIGHTS
- THREE HEAVY DUTY PACKS / GIX POPCELAIN COATED PACK POGITIONS INCLUDING ONE TRUGLIDEM FULL EXTENSION PACK (ONE IN EACH OVEN OF A DOUBLE OVEN)
- · COMMERCIAL TYPE STYLING
- · DIGITAL CLOCK/OVEN FUNCTIONS
- · 1 00 MINUTE TIMER
- · SET GOOKING TIME FOR UP TO 12 HOURS
- · DELAY GOOKING FEATURE
- · TONE AND DIGITAL DISPLAY INDICATE PRE-SET COOKING TIME IS FINISHED
- · MEAT PROBE (UPPER OVEN IN DOUBLE OVENS)
- · TIMER GOUNDS AND OVEN SHUTS OFF WHEN DESIRED TEMPERATURE IS REACHED
- · GELF-CLEAN OVENG
- · OVEN FUNCTIONS (CONVECTION SYSTEM IN BOTH UPPER AND LOWER OVEN OF DOUBLE OVENS)
- · TWO-ELEMENT BAKE
- · CONVECTION BAKE
- · TRUCONVECT CONVECTION COOK (ELEMENT AROUND FAN)
- · CONVECTION POAGT
- · CONVECTION BROIL
- ·HIBROIL
- · MEDIUM BROIL
- · LOW BROIL
- · CONVECTION DEHYDRATE
- · CONVECTION DEFPOST
- · 27"W. OVENO: LAPGEOT GELF CLEAN, CONVECTION OVENO- EXCLUGIVE
- · OYEP-ALL 227/10" X 161/2"H. X 191/2"D. 4.2 CUBIC FEET
- · AHAM OTANDAPD 227/16" X 16/2"H. X 16/3/16"D. 3.6 CUBIC FEET
- · 90"W. OYENO: LARGEST SELF CLEAN, CONVECTION OVENS- EXCLUSIVE
- · OYEPALL 257/16" X 1612"H. X 1912"D. 4.8 CUBIC FEET
- · AHAM OTANDARD 257/16" X 1612"H. X 1612/16"D. 4.1 CUBIC FEET
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVENO
- · FIVE-YEAR LIMITED WARRANTY HEATING ELEMENTO





DEGO/DEDO GEPIEG OVENG

- · 5 FOOT FLEXIBLE STEEL CONDUIT WITH OVEN
- · 4 WIFE WITH APOUND
- · 240-208/120 V/60 HZ
- · MAXIMUM AMPS 2 40 VOLTS/208 VOLTS
- · ALL DEGO 90 AMP CONNECTION PEQUIPED
- · ALL DEDO 50 AMP CONNECTION PEQUIPED

- · OTAINLEGO OTEEL (GO), BLACK (BK), WHITE (WH), BIGCUIT (BT), OTONE GRAY (GG), GRAPHITE GRAY (GG)
- · DOOR PANEL AND CONTROL PANEL MATCH DEGIGNATED FINIGH; GTAINLEGG GTEEL HANDLE(G)
- · BRAGG TRIM OPTIONG (BR) GUPER DURABLE, LONG LAGTING BRAGG FINIGH HANDLE(G)

BUILT-IN ELECTRIC 36"W. GINGLE AND DOUBLE OVENS

APPROX 6HIPPING WT. LB(FG) 990 (148.5) APPROX 6HIPPING WT. LB(FG) 575 (258.7) VEGO 166-96"W. SINGLE PROFESSIONAL YEDO 266 - 76"W. DOUBLE 36" WIDE BUILT-IN ELECTRIC

- · COMMERCIAL-TYPE STYLING
- · ELECTRONIC CLOCK/TIMER
- · 100 MINUTE TIMER
- · SET GOOKING TIME FOR UP TO 12 HOURS
- · DELAY GOOKING FEATURE
- · TONE AND DIGITAL DIGPLAY INDICATE PRE-GET GOOKING TIME IG FIN-IGHED
- · ALGO FUNCTIONS AS AN ALARM
- · GELF-GLEAN OVENO
- · THERMAL-CONVECTION OVENS
- · TWO-ELEMENT BAKE
- · CONVECTION BAKE
- · MAXI-BROIL (EIGHT-PAGG ELEMENT)
- · MINI-BROIL (FOUR-PAGG ELEMENT)
- · CONVECTION BROIL (EIGHT-PAGG ELEMENT)
- · TRUCONVECTM CONVECTION COOKING (ELEMENT AROUND FAN)
- · CONVECTION DEHYDRATE
- · CONVECTION DEFPOST
- · 96"W. OVENO: LAPGE SELF CLEAN, CONVECTION OVENS
- · OYERALL 29"W. X 161/6" H. X 184" D. 5.1 CUBIC FEET
- · AHAM 29"W. X 161/0" H. X 157/0" D. 4.2 CUBIC FEET
- · THREE HEAVY-DUTY RACKO/OIX POOITIONO/TWO LIGHTO
- · TEN-YEAR LIMITED WARRANTY PORCELAIN OVENO; FIVE-YEAR LIMITED WAPPANTY - HEATING ELEMENTS

SINGLE/DOUBLE OVENS

VEGO/VEDO GEPIEG OVENG

- · 5 FOOT FLEXIBLE STEEL CONDUIT WITH OVEN
- · 4 WIFE WITH APOUND
- · 240-208/120 V/60 HZ
- · MAXIMUM AMPS 240 VOLTS/208 VOLTS
- · YEGO 166-27.4/27.9
- · YED0266-54.8/47.8

- · OTAINLEOO OTEEL (OO), BLACK (BK), AND WHITE (WH), DEOIGNER FINIOHEO: ALMOND (AL), BIOCUIT (BT), OTONE GRAY (GG), GRAPHITE GRAY (GG), BURGUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREGT GREEN (FG), YIKING BLUE (VB), GOBALT BLUE (GB) AND EGGPLANT (EP)
- · FINIGH DEGIGNATEG DOOR FRONTG. BLACK UNITG HAVE A BLACK CONTROL PANEL AND BLACK KNOBG/ SWITCHES. WHITE UNITS HAVE A WHITE CONTROL PANEL AND WHITE MOBS/SWITCHES. STAINLESS STEEL AND ALL DEGICNER FINIGHEG HAVE A GTAINLEGG GTEEL CONTROL PANEL AND BLACK KNOBG/GWITCHEG. ALL FIN-16HEG HAVE GILVER FINIGHED VERTICAL/HORIZONTAL TRIM, AND GTAINLEGG GTEEL DOOR HANDLEG WITH CHROME PLATED BRACKETS.
- · BRAGG TRIM OPTIONG (BR) FOR ANY FINIGH; INCLUDEG NAMEPLATE, WINDOW TRIM, DOOR HANDLEG/BRACKETG AND HIGH DEZELO. GUPER DURABLE, LONG LAGTING BRAGG FINIGH ON "HIGH TRAFFIC" PARTG (HANDLEG); ALL OTHER PARTO HAYE A DURABLE PROTECTIVE COATING. ALL PARTO DEGIGNED FOR MAINTENANCE-FREE UGE.

BUILT-IN ELECTRIC OVEN ACCESSORIES

TRUGLIDETH FULL EXTENSION OVEN PACKS

TEGO 2 7 FOR 2 7"W. PRO AND DEGIGNER BUILT IN ELECTRIC OVENG APPROX GHIPPING WT. LEKG) (5.9)

TEGOTO FOR TO "W. PRO AND DEGIGNER BUILT IN ELECTRIC OVENO APPROX GHIPPING WT. LB(FG) 15 (6.8)

- · PACK FITG GECUPELY ON PACK GUPPORTS AND FULLY EXTENDS MAKING IT EASIER TO LOAD AND UNLOAD FOOD ITEMS
- · CAN BE USED IN ANY OF THE SIX OVEN PACK POSITIONS
- · HEAVY-DUTY CHROME PLATED RACKS MATCH THE REGULAR RACKS SHIPPED WITH THE OVEN
- · WILL FIT IN SELECT OF PREMIER MODEL OVENS



Y-PACK AND DEIP PAN

CYD APPROX. SHIPPING WEIGHT LB(KG) 4 (1.8)

- · NO STICK Y-RACK CAN BE USED FOR COOKING ROASTS, HAMS, RIBS, ETC.
- · DP-IP PAN CATCHEO DP-IPPINAO FROM ITEMO COOKED IN Y-RACK TO GENERATE FLAVOR AND PREVENT FLARE-UPO



YIKING HEAPTH OTONE

04018

APPROX. GHIPPING WEIGHT LEG(KG)

19(5.9)


- · HAPD-FIRED CEPAMIC BAKING STONE
- · ABGORBO HEAT AND GENDO IT BACK INTO FOOD DURING COOKING
- · CAN BE USED IN ALL YIFING OVENS (EXCEPT LEFT OVEN IN 48"W. PANGE)
- ・ 175/0"W.×19"D.



BUILT-IN GAO 96"W. SINGLE OVEN/ACCESSOPIES VGOO 1 GG APPROX SHIPPING WT. LE(KG) 257 (1 15.7)

- · COMMERCIAL STYLING AND CONSTRUCTION
- · DIMENGIONED TO FIT UGA 96"W. OF EUROPEAN 90 CM CABINETS
- · ELECTRONIC CLOCK/TIMER
- · EXCLUSIVE COMBINATION OF DUAL BAKE BURNERS AND INFRARED BROIL BURNER, ALL WITH AUTOMATIC IGNITION
- · GIX FUNCTIONS:
 - · NATURAL AIRFLOW BAKE
- · CONVECTION BAKE
- · INFRARED BROIL
- · CONVECTION INFRAPED BROIL
- · CONVECTION DEHYDRATE
- · CONVECTION DEFPOST
- · LAPGEST BUILT-IN GAS CONVECTION OVEN CAVITY AVAILABLE
- · OVERALL 24 1/0"W. X 1 3%"H. X 1 8%"D. 3.6 CUBIC FEET
- · AHAM OTANDARD 24 1/e"W. X 1 9 2"H. X 1 7 1/e"D. 9.9 CUBIC FEET
- · THREE HEAVY-DUTY RACKG/FOUR POSITIONS; TWO LIGHTS
- · TEN YEAP LIMITED WAPPANTY POPCELAIN OYEN; FIVE YEAP LIMITED WAPPANTY -TUBE BUPNEPO





V490 166 SEPIES OVENS

- · SHIPPED STANDARD FOR NATURAL GAS; FIELD CONVERT TO LP/PROPANE WITH STANDARD REGULATOR
- · 4 FOOT COPD INCLUDED WITH OVEN
- · 2 WIFE WITH GROUND/9 PRONG PLUG
- · 120 V/60 HZ
- · MAXIMUM AMPG 8.0

FINIOH DETAILS

- · OTAINLEOO OTEEL (OO), BLACK (BK), WHITE (WH), ALMOND (AL), BIOCUIT (BT), OTONE GRAY (OG), GRAPHITE GRAY (GG), BURGUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREOT GREEN (FG), VIKING BLUE (VB), COBALT BLUE (CB), AND EGGPLANT (EP).
- · FINIGH DEGICNATEG DOOR FRONT, LOWER PANEL, AND CONTROL PANEL FRAME. ALL FINIGHEG EXCEPT WHITE HAVE BLACK FNOB, GWITCHEG, AND CONTROL PANEL. WHITE UNITG HAVE WHITE FNOB, GWITCHEG, AND CONTROL PANEL. ALL FINIGHEG HAVE GILVER FINIGHED VERTICAL/HORIZONTAL TRIM, AND A GTAINLEGG GTEEL DOOR HANDLE WITH CHROME PLATED BRACKETG.
- · BRAGG TRIM OPTIONG (BR) FOR ANY FINIGH; INCLUDEG NAMEPLATE, OVEN WINDOW TRIM, DOOR HANDLE/BRACKETG, DUAL BURNER THERMAL-CONVECTION PLATE, AND CONTROL PANEL TRIM. GUPER DURABLE, LONG LAGTING BRAGG FINIGH ON "HIGH TRAFFIC" PARTG (HANDLEG); ALL OTHER PARTG HAVE A DURABLE PROTECTIVE COATING. ALL PARTG DEGIGNED FOR MAINTENANCE-FREE UGE.

DOUBLE INSTALLATION CENTER TRIM

DCT-V460 APPROX 6HIPPING WT. LB(KG) 2 (0.9)

- · GTAINLEGG GTEEL (GG) ONLY; COOPDINATEG WITH ALL FINIGHEG
- · COVERS FINISH OF CABINET WHEN INSTALLED AS DOUBLE (TWO SINGLE CUTOUTS)
- · PROVIDES CONTINUOUS LOOK AND DOUBLE OVEN APPEARANCE
- · EAGILY ATTACHED AFTER OVENO ARE INGTALLED

DOUBLE INSTALLATION GAS CONNECTION FIT

1KD-V460 APPROX GHIPPING WT. LB(KG) 2 (0.9)

- · PROVIDEO ALL NECEOGARY COMPONENTO TO EAGILY MAKE DOUBLE INOTALLATION GAO CONNECTION (TWO GINGLE CUTOUTO)
- · INCLUDEO FLEXIBLE GAO TUBING WITH TWO FITTINGO, PIPE NIPPLE, AND INOTPUCTIONO

COMBI STEAM/CONVECTION OVEN AND ACCESSORIES

COMBI STEAM/CONVECTION OVEN

VCGO 2 4 4 (PROFEGGIONAL OVEN)

YOTK 2 7 4 (2 7 W. PROFEGGIONAL BUILT-IN TRIM KIT)

YOTK 904 (90"W. PROFESSIONAL BUILT-IN TRIM HIT)

YOTK 764 (76"W. PROFESSIONAL BUILT-IN TRIM FIT)


D660244 (DEGIGNER OVEN)


DOTK 2 7 4 (2 7"W. DEGIGNER BUILT-IN TRIM KIT)

DOTK 904 (90"W. DEGIGNER BUILT-IN TRIM KIT)

APPROX GHIPPING WT. LEG(KG)	フク (クラ)
APPROX GHIPPING WT. LEG(KG)	6.4 (2.9)
APPROX GHIPPING WT. LEG(KG)	7.5 (2.4)
APPROX GHIPPING WT. LEG(KG)	9.9 (4.2)
APPROX GHIPPING WT. LEG(KG)	フク(クラ)
APPROX GHIPPING WT. LEG(KG)	9.7 (4.4)
APPROX SHIPPING WT. LEG(KG)	10.5 (4.8)

- · ELECTPONIC STEAM SYSTEM PROVIDES EFFICIENT USE OF WATER AND ENERGY FOR STEAM PRODUCTION
- · EXTERNAL BOILER ENGURES NO ACCUMULATION OF LIMESCALE WITHIN THE OVEN
- · CLIMATE GENGOR MAINTAING THE IDEAL CLIMATE FOR GENTLE COOKING
- · AUTOMATIC DESCALING/CLEANING DISPLAY
- · MUST USE DESCALING CLEANSER PROVIDED WITH OVEN
- · 5 ¼ CUP (1.25 LITEP) WATER TANK
- · HOLDS FRESH WATER FOR STEAMING UP TO 2 HOURS AT 2 1 2 °F (100°C)
- · GIX COOKING FUNCTIONS WITH PECOMMENDED TEMPERATURES
 - · GTEAMING GENTLY GOOFG FOODS WHILE PETAINING NATURAL VITAMINS AND MINERALS
- · PEHEAT OF DEFPOST FOODS USING STEAM WITH THE PEHEAT PLUST
- · PROBAKE COOKING PROVIDES TWO COOKING PHASES OF STEAM AND HEAT TO SEAL IN THE MOISTURE WHILE BROWNING THE OUTSIDE OF FOODS
- TPUCONVECTMCOOKING WITH FAN-FORCED AIR PERFECT FOR MULTIPLE PACK BAKING
- · OTEAM HEATM AND TRUGTEAMM COOKING (UDED FOR ROAGTING AND BAKING) - WITH FAN-FORCED AIR TO BROWN THE OUTGIDE OF FOOD WHILE ENGURING THE INTERIOR IS COOKED
- · ELECTRONIC CLOCK/TEMPERATURE AND SPECIAL SETTINGS DISPLAY
- · 10 HOUR INDEPENDENT TIMER
- · DELAY COOKING FEATURE
- · TONE AND ELECTPONIC DIGPLAY INDICATE COOPING TIME IG COMPLETE
- TEXT DIGPLAY, PROVIDED IN GEVEN LANGUAGEG, EAGILY GUIDEG YOU
 THROUGH THE FUNCTIONG AND GETTINGG
- · FOR GAFETY, THE CONTROL PANEL CAN BE LOCKED TO PREVENT UNWANTED OPERATION
- · TWO WIRE PACKO/OIX PACK POOITIONS
- * 9TANDAPD ACCE990PIE9 INCLUDE 2 WIPE PACK9, MULTI-PUPPOSE COOKING TRAY, STEAMER TRAY, MEAT PROBE, WATER TANK, DESCALER AND 9 PEPLACEMENT WATER FILTERS
- · EAGY TO CLEAN STAINLESS STEEL INTERIOR OVEN CAVITY
- ・19¼"W.×10¼"H.×14"D.-1.16U.FT.(11L)
- · MUST INSTALL AS BUILT-IN USING A TRIM FIT (LISTED BELOW SOLD SEPARATELY)





PACK

YGGR (FOR PRO & DG COMBI GTEAM/CONVECTION OVENS)

APPROX SHIPPING WT. LEG(KG)

1.9 (0.6)

- · OTAINLEGG STEEL
- · PLACE CAKE AND BAKING PANO ON FOR STEAMING AND BAKING
- · CAN BE USED IN ANY OF THE SIX OVEN PACK POSITIONS
- · FRONT ROUNDED RACKS GIVE THE DISTINCTION OF A TRULY UNIQUE VIKING COMBI/CONVECTION STEAM OVEN



MULTI-PURPOSE GOOKING TRAY

YCGGM APPROX GHIPPING WT. LB(KG) 2 (0.9)

- · STAINLESS STEEL
- · CATCHEO DEIPPINGO WHEN USED WITH PACK OF STEAMER TRAY
- · COOKS A VAPIETY OF FOODS AND MEATS
- · 1 % QUART (1.7 LITER) CAPACITY
- · 12½"(カ1.8 CM)×¾"(1.9 CM)×1カ¾"(カ4.9 CM)
- · DIGHWAGHER GAFE



STEAMER TRAY

YCOT APPROX GHIPPING WT. LEG(FG) 2.2 (1.0)

- · OTAINLEGG OTEEL
- · OTEAMO FREOH OR FROZEN VEGETABLES AND MEATS
- · 9½ QUART (9.9 LITER) CAPACITY
- ・12½"(カ1.8 CM)×1½"(カ.8 CM)×1カ¾"(カ4.9 CM)
- · DIGHWAGHER GAFE



COMBI GTEAM DEGCALING CLEANGER

YCODCIO (IOPER CAGE)

APPROX SHIPPING WT. LEG(FG) 2.2 (1.0)

- · ONLY OPECIAL DEGCALER DEVELOPED FOR APPLIANCE
- · PROVIDEG GENTLE AND PROFEGGIONAL DEGCALING
- · AMOUNT OF USE DEPENDS ON WATER HARDNESS AND FREQUENT USE OF APPLIANCE
- · 1 6.9 02. (500 ML) ENTIPE BOTTLE USED FOR DESCALING



DEEP MULTI-PURPOSE GOOKING TRAY

YCODM APPROX OHIPPING WT. LEG(KG) 1.9 (0.6)

STAINLESS STEEL

- · CATCHEO DEIPPINGO WHEN UDED WITH PACK OF OTEAMER TRAY
- · USED TO COOK A VAPIETY OF FOODS AND MEATS
- · 3½ QUAPT (3.3 LITER) CAPACITY
- · 12½"(カ1.8 CM)×1½"(カ.8 CM)×13¾"(カ4.9 CM)
- · DIGHWAGHER GAFE



DEEP MULTI-PURPOSE GOOKING TRAY WITH POURING SLOT

VCGP APPROX 9HIPPING WT. LB(KG) 2.2 (1.0)

DEEP MULTI-PURPOSE COOKING TRAY WITH POURING SLOT

- · OTAINLEGG OTEEL
- · CATCHEO DEIPPINGO WHEN UDED WITH PACK OF OTEAMER TRAY
- · FOR POURING EXTRACTED JUICES AND DRIPPINGS FROM FRUITS AND BER-RIES
- · 3½ QUAPT (3.3 LITER) CAPACITY
- $\bullet \hspace{0.1cm} \mid \hspace{0.1cm} 2\hspace{0.1cm} \cancel{1}\hspace{0.1cm} "\hspace{0.1cm} (\hspace{0.1cm} \gamma \hspace{0.1cm} I.\hspace{0.1cm} \mathcal{S} \hspace{0.1cm} \hspace{0.1cm} \mathsf{CM}) \hspace{0.1cm} \hspace$
- · DIOHWAOHER OAFE



POPCELAIN MULTI-PUPPOSE GOOFING TRAY

VCOPM APPROX OHIPPING WT. LB(KG) 2.6(1.2

POPCELAIN MULTI-PURPOSE COOKING TRAY

- · CATCHEO DEIPPINGO WHEN UOED WITH PACK OF OTEAMER TRAY
- · COOKS A VAPIETY OF FOODS AND MEATS
- · 1% QUAPT (1.7 LITER) CAPACITY
- ・ 12½"(カ1.8 CM)×¾"(1.9 CM)× 1カ¾"(カ4.9 CM)
- · HAND WAGHING PECOMMENDED



PROFESSIONAL PROFESSIONAL OVEN HIGH SPEED CONVECTION AND ACCESSORIES

HIGH SPEED CONVECTION OVEN AND TRIM KITS

VHOO 205 PROFESSIONAL MODEL	APPROX GHIPPING WT. LEG(KG)	95 (49.1)
VHTK 2 75 (2 7"W. PROFEGGIONAL BUILT-IN TRIM KIT)	APPROX GHIPPING WT. LEG(KG)	14 (6.5)
VHTK905 (90"W. PROFESSIONAL BUILT-IN TRIM KIT)	APPROX GHIPPING WT. LEG(KG)	15 (6.9)
VHTK365 (36"W. PROFESSIONAL BUILT-IN TRIM KIT)	APPROX GHPPING WT. LEG(KG)	16(7.2)


- · COMMERCIAL TYPE-GTYLING AND DEGIGN
- · COOKS UP TO 80% FASTER THAN CONVENTIONAL OVENS
- · EAGY-TO-UGE INTERACTIVE DIGPLAY
- · MANUAL AND AUTOMATIC SPEED COOKING
- · AUTOMATIC GETTINGG INCLUDE:
- · 100 SPECIFIC PREPROGRAMMED RECIPES WITH COOKBOOK
- · 8 4 BAGIC COOK GETTINGG ALLOWG ADAPTATION OF PECIPEG NOT IN COOKBOOK
- · I 7 MICROWAYE OPTIONS INCLUDING POPCORN, REHEAT, DEFROST, AND COOK
- · MANUAL GETTINGG INCLUDE:
- · SPEED/APILL MAX HEAT (450°F) + MAX AIRFLOW WITH AUTO PREHEAT
- · SPEED/POAST SET AT 925°F, POASTING TIMES 99% TO 50% FASTER THAN CONVENTIONAL OVENS. NO PREHEAT NECESSARY.
- · SPEED/BAKE FROM I OO" TO 450°F THIS SETTING IS FOR MORE TRADITIONAL BAKING. REDUCES COOKING TIMES BY 25% TO 97%.
- · HELP FEATURES INCLUDE:
- · CHILD LOCK
- · GOUND ELIMINATION
- · AUTO START PROGRAM OVEN TO START AT SPECIFIC TIME
- · PEFPEGH CYCLE GMOKE AND ODOF PEMOVAL
- ·TIMER
- · DEMO MODE
- · INTERIOR OVEN CAVITY
- · 16 1/8" X 8 3/8" X 1 9 5/8"
- · 1.1 601516 FT
- · MUST BE INSTALLED WITH BUILT-IN TRIM FIT
- · FIVE-YEAR LIMITED WARRANTY MAGNETRON TUBE

VH90205

- · 9.5 FT. POWER CORD
- · 240 V/60 HZ
- · 2.2 KW
- · 15.0 AMPG

FINIOH DETAILS

· OTAINLEGO OTEEL (GG) ONLY




PROFESSIONAL & DESIGNER


MICROWAVE OVENS AND TRIM KITS

MICPOWAYE OYENG AND BUILT-IN TRIM FITG

VMOG200-PROFEGGIONAL MICROWAVE	APPROX GHIPPING WT. LEG(KG) 55 (24.7)
VMTK 27 1 - 27 "W. PROFEGGIONAL BUILT-IN TRIM KIT	APPROX GHIPPING WT. LEG(KG) 14 (6.5)
VMTK901-90"W. PROFEGGIONAL BUILT-IN TRIM KIT	APPROX GHIPPING WT. LEG(KG) 15 (6.9)
VMTK961 - 96"W. PROFEGGIONAL BUILT-IN TRIM KIT	APPROX GHIPPING WT. LEG(KG) 16(6.9)
DMOG200 - DEGIGNER MICROWAVE	APPROX GHIPPING WT. LEG(KG) 55 (24.7)
DMTK 2 7 1 - 2 7 "W. DEGIGNER BUILT-IN TRIM KIT	APPROX GHIPPING WT. LB(KG) 14 (6.5)
DMTK901 - 90"W. DEGIGNER BUILT-IN TRIM KIT	APPROX GHIPPING WT. LEG(KG) 15 (6.9)

- · COMMERCIAL TYPE-GTYLING AND DEGIGN
- · 19 SENSOR SETTINGS
- · BREAKFAGT AND LUNCH OPTIONS FOR COOKING AND REHEATING FOODS
- · I S MINUTE DINNERS AND PRESET RECIPES EACH OFFER S RECIPES WITH EASY TO FOLLOW STEPS
- · ADD-A-MINUTE ALLOWG YOU TO ADD A MINUTE TO COOPING TIME BY GIMPLY TOUCHING A BUTTON
- · WARM/HOLD FEATURE ALLOWG YOU TO KEEP FOOD WARM FOR UP TO 90 MINUTEG
- · CHILD LOCK GAFETY FEATURE LOCKS THE CONTROL PANEL TO PREVENT UNWANTED OPERATION
- · 2.0 6UBIG FT.
- · 1 6" DIAMETER TURNTABLE
- · INTERIOR OVEN CAVITY
- · 17 9/8"W. X 10"H. X 18 5/8"D.
- · PLACE ON COUNTERTOP, IN 90"W. OR 96"W. MULTI-UGE-CHAMBER, OR INGTALL AG A BUILT-IN UGING A TRIM FIT LIGTED ABOVE; GOLD GEPARATELY
- · FIVE-YEAR LIMITED WARRANTY MAGNETRON TUBE





PROFEGGIONAL

VM06200/DM06200

- · 9.5 FT POWER CORD
- · 120 4/60 HZ
- · 1.65 KW
- · 1 7.8 AMP6


FINIOH DETAILS


PROFESSIONAL MODELS

OTAINLEOO OTEEL (OO), BLACK (BK), AND WHITE (WH), DEOIGNER FINIOHEO: ALMOND (AL), BIOCUIT (BT), OTONE GRAY (OG), GRAPHITE GRAY (GG), BURGUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREOT GREEN (FG), YIKING BLUE (VB), COBALT BLUE (CB) AND EGGPLANT (EP)

DEGIGNER MODELG

STAINLESS STEEL (SS)






DEGIGNER


PROFESSIONAL & DESIGNER

CONVECTION MICROWAVE OVENS & TRIM KITS

CONVECTION MICEOWAVE OVENO AND BUILT-IN TRIM HITO

- · COMMERCIAL TYPE-GTYLING AND DEGIGN
- · INSTANT SENSOR SETTINGS FOR COOKING, REHEATING FOODS AND POPPING POPCORN
- · FOUR CONVECTION SETTINGS: CONVECTOPOIL, CONVECTOAST, CONVECTOAKE AND MANUAL CONVECTION
- · CONVECTION GETTINGS USE A HIGH SPEED FAN THAT CIRCULATES AIR PAST THE HEAT SOURCE AND AROUND THE FOOD; ALLOWS MULTIPLE RACK BAKING
- · LOW MIX BAKE AND HIGH MIX POAGT SETTINGS OFFER USE OF CONVECTION HEAT TO SEAL AND BROWN OUTSIDE OF FOODS WHILE USING MICROWAVE ENERGY TO ENSURE THE INTERIOR IS COOKED
- · ADD-A-MINUTE ALLOWG YOU TO ADD A MINUTE TO COOKING TIME BY GIMPLY TOUGHING A BUTTON
- · CHILD LOCK GAFETY FEATURE LOCKS THE CONTROL PANEL TO PREVENT UNWANTED OPERATION
- · CONVECTION MICROWAVE COOKBOOK COMES STANDARD WITH UNIT
- · 159/8" DIAMETER TURNTABLE
- · INTERIOR OVEN CAVITY
- · 161/8"W. X 95/8"H. X 161/8"D.
- ・1.5 CUEIC FT.
- · PLACE ON COUNTERTOP OR INSTALL AS A BUILT-IN USING A TRIM FIT (LISTED ABOVE SOLD SEPARATELY)
- · FIVE-YEAR LIMITED WARRANTY MAGNETRON TUBE





PROFESSIONAL

VM06205/DM06205


- · 9.5 FT POWER GORD
- · 120 V/60 HZ
- · 1.55 FW
- · 13.0 AMPG


FINIOH DETAILS

PROFESSIONAL MODELS

· OTAINLEOG OTEEL (OO), BLACK (BK), AND WHITE (WH), DEOIGNER FINIOHEO: ALMOND (AL), BIOCUIT (BT), OTONE GRAY (OG), GRAPHITE GRAY (GG), BURGUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREOT GREEN (FG), VIKING BLUE (VB), COBALT BLUE (CB) AND EGGPLANT (EP)

DEGIGNER MODELG GTAINLEGG GTEEL (GG)






DEGIGNER

PROFESSIONAL & DESIGNER CONVECTION MICROWAVE HOODS


CONVECTION MICEOWAVE HOODS

VMOR 205 - PROFESSIONAL MICROWAVE HOOD DMOR 205 - DESIGNER MICROWAVE HOOD APPROX SHIPPING WT. LE(KG) 85(98.6) APPROX SHIPPING WT. LE(KG) 85(98.6)

- · COMMERCIAL TYPE-GTYLING AND DEGIGN
- · INSTANT SENSOR SETTINGS FOR COOKING, REHEATING FOODS AND POPPING POPCORN
- · FOUR CONVECTION GETTINGS: CONVECTEOIL, CONVECTEOAGT, CONVECTION
- · CONVECTION SETTINGS USE A HIGH SPEED FAN THAT CIPCULATES AIR PAST THE HEAT SOURCE AND AROUND THE FOOD; ALLOWS MULTIPLE RACK BAKING
- · LOW MIX BAKE AND HIGH MIX POAGT GETTINGG OFFER UGE OF CON-VECTION HEAT TO GEAL AND BROWN OUTGIDE OF FOODS WHILE UGING MICROWAYE ENERGY TO ENGURE THE INTERIOR IS COOKED
- · ADD-A-MINUTE ALLOWG YOU TO ADD A MINUTE TO COOKING TIME BY GIMPLY TOUCHING A BUTTON
- · CHILD LOCK GAFETY FEATURE LOCKS THE CONTROL PANEL TO PREVENT UNWANTED OPERATION
- · CONVECTION MICROWAVE COOKBOOK COMES STANDARD WITH UNIT
- · BUILT-IN EXHAUGT GYGTEM
 - · 900 OFM BLOWER
- · MAY BE VENTED OUT THE TOP, BACK OF CONVERTED TO RE-CIR-CULATE
- · 1 9" DIAMETER TURNTABLE
- · EXTERIOR DIMENSIONS
- · 29 15/16"W. X 166/16"H X 15 5/16"D.
- · INTERIOR OVEN CAVITY
- · 1.1 60816 FT.
- · FOR USE OVER 24" AND 30"W. VIKING NON-GRILL PRODUCTS
- · FIVE-YEAR LIMITED WARRANTY MAGNETRON TUBE



PROFEGGIONAL



DEGIGNER

YMOP 205/DMOP 205

- · 9.5 FT POWER CORD
- · 120 V/60 HZ
- · 1.6 KW · 19.2 AMP6

FINIOH DETAILS

· GTAINLEGG GTEEL (GG)

PROFESSIONAL AND DESIGNER BUILT-IN ELECTRIC 27", 30", AND 36" W. WARMING DRAWERS

 VEWD 1 79 - 27"W. PROFESSIONAL
 APPROX SHIPPING WT. LB(KG)
 80 (96)

 VEWD 109 - 90"W. PROFESSIONAL
 APPROX SHIPPING WT. LB(KG)
 90 (40.5)

 VEWD 169 - 96"W. PROFESSIONAL
 APPROX SHIPPING WT. LB(KG)
 1 (0 (49.5)

 DEWD 171 - 27"W. DESIGNER
 APPROX SHIPPING WT. LB(KG)
 90 (40.5)

 DFWD 171 - 27"W. FULL OVERLAY
 APPROX SHIPPING WT. LB(KG)
 90 (40.5)

 DFWD 101 - 90"W. FULL OVERLAY
 APPROX SHIPPING WT. LB(KG)
 90 (40.5)

· PROFEGGIONAL WARMING DRAWER


- · 2 7"W. MODEL: 1719/16"W. X 6"H. X 2 23"D 1.4 CU. FT. 4 25 WATT ELEMENT
- · 90"W. MODEL: 2012"W. X 6"H. X 223"D. 1.6 CU. FT. 450 WATT ELEMENT
- · 10"W. MODEL: 25"W. X 6"H. X 2 23"D. 2.0 CU. FT. 550 WATT ELEMENT
- · COMMERCIAL-TYPE SIZE, CONSTRUCTION, DESIGN, AND STYLING
- · MOIGTUPE GELECTOR CONTROL
- · TEMPERATURE SETTINGS FROM 900F TO 2500F
- · DEGIGNER WARMING DRAWER
- \cdot 27"W. MODEL: 1719/16"W. \times 6"H. \times 22%"D. -1.4 CU. FT. 425 WATT ELEMENT
- · 10"W. MODEL: 2012"W. X 6"H. X 2234"D. 1.66 CU. FT. 475 WATT ELEMENT
- · MOIGTUPE GELECTOP CONTPOL
- · TEMPERATURE SETTINGS FROM 900F TO 2500F
- · FULL OVEPLAY WAPMING DPAWER
- · 27"W. MODEL: 171%/16"W. X 6"H. X 22%"D. 1.4 CU. FT. 425 WATT ELEMENT
- · 10"W. MODEL: 2012"W. X 6"H. X 2234"D. 1.6 CU.FT. 450 WATT ELEMENT
- · TEMPERATURE SETTINGS FROM 900F TO 2500F
- · INSTALL WITH LOCALLY SUPPLIED CUSTOM DOOP FRONT
- · EXOLUGIVE TWO HALF-GIZED LOW PACKG AND MOIGTUPE CUP GTANDAPD
- · STAINLESS STEEL LOW PACKS WITH SLOTS FOR HEAT DISTRIBUTION
- · PARTIALLY FILL MOISTURE CUP WITH WATER TO INCREASE MOISTURE IN PAN
- · ENTIPE DRAWER REMOVES FOR EASY CLEANING
- · OTAINLEGO OTEEL POLLEP BEAPING GLIDEG
- · FIVE-YEAR LIMITED WARRANTY HEATING ELEMENT

6

PPOFEGGIONAL



DEGIGNER



FULL OYEPLAY

VEWD SEPIES WAPMING DPAWERS

- · HAPD WIPE DIRECT WITH 2 WIPE WITH AROUND
- · 120 V/50-60 HZ
- · YEWD 1 7 9 MAXIMUM AMPG 9.6
- · YEWD 109 MAXIMUM AMPG 9.8
- · YEWD 1 69 MAXIMUM AMP6 4.6

FINIOH DETAILS

- · OTAINLEOO OTEEL (OO), BLACK (BK), WHITE (WH), ALMOND (AL), BIOCUIT (BT), OTONE GRAY (OG), GRAPHITE GRAY (GG), BURGUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREOT GREEN (FG), VIKING BLUE (VB), COBALT BLUE (OB) AND EGGPLANT (EP)
- · FINIGH DEGICNATEG DRAWER AND CONTROL PANEL FRONTG.
 ALL FINIGHEG EXCEPT WHITE HAVE A BLACK KNOB. WHITE UNITG
 HAVE A WHITE KNOB. ALL FINIGHEG HAVE GILVER FINIGHED VERTICAL/HORIZONTAL TRIM, AND GTAINLEGG GTEEL DOOR HANDLEG
 WITH CHROME PLATED BRACKETG.
- · BPAGG TPIM OPTIONG (BP) FOR ANY FINIGH; INCLUDED NAME-PLATE, DPAWER HANDLE/BRACKETG, AND KNOB BEZEL. GUPER DURABLE, LONG LAGTING BRAGG FINIGH ON "HIGH TRAF-FIC" PARTG (HANDLEG); ALL OTHER PARTG HAVE A DURABLE PROTECTIVE COATING. ALL PARTG DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.

DEWD/DFWD SEPIES WAPMING DPAWERS

- · HAPO WIPE DIPECT WITH 2 WIPE WITH GROUND
- · 120 1/50-60 HZ
- · DEWD/DFWD 17 | MAX AMPG 9.6
- · DEWD/DFWD 10 1 MAX AMP6 4.0

FINIOH DETAILS FOR DEWD ONLY

- · OTAINLEOG OTEEL (GG), BLACK (BK), WHITE (WH), BIOCUIT (BT), OTONE GRAY (GG) AND GRAPHITE GRAY (GG)
- · DOOR PANEL MATCHEO DEOLCHATED FINIOH; OTAIN-LEOO OTEEL KNOD AND HANDLE; DLACK KNOD CRIPO FOR ALL FINIOHEO EXCEPT WHITE - WHITE FINIOH HAD CRAY KNOD CRIPO.
- · BRAGG TRIM OPTION BRAGG FINIGH KNOBG AND HANDLE

WARMING DRAWER ACCESSORIES

HANDLE KITS

PHY 2 9-66 FOR DEWD 1 70 & DEWD 1 00 - PROFEGGIONAL GTAINLEGG STEEL HANDLE KIT

PHY 2 9-10P FOR DFWD 1 70 & DFWD 1 00 - PROFESSIONAL BRASS HANDLE FIT


DHY 18-66 FOR DEWD 170 - DEGIGNER STAINLEGG STEEL HANDLE FIT

DHK 18-BR FOR DFWD 170 - DEGIGNER BRAGG HANDLE KIT

DHY 20-66 FOR DFWD 100 - DEGIGNER GTAINLEGG GTEEL HANDLE KIT

DHY 20-BP FOR DFWD 100 - DEGIGNER BRAGG HANDLE FIT

- · FOR USE WITH DEWD WARMING DRAWERS
- · FOR USE ON LOCALLY SUPPLIED FULL OVERLAY PANELS
- · INCLUDES HANDLES AND INSTALLATION HAPDWAPE
- · ALLOWO DEWD WITH FULL OVERLAY PANEL TO COORDINATE WITH OTHER PROFESSIONAL & DESIGNER PRODUCTS





APPROXIMATE SHIPPING WEIGHTS 5 (.29)

PAN/LID GET

- · FIVE COMMERCIAL PANG WITH LIDG
- · TWO 21/2"D. X 1 2"L. X 7"W.
- · TWO 4"D. X 12"L. X 7"W.
- · ONE 4"D. X | 2"L. X | 0½"W. · HEAVY GAUGE STAINLESS STEEL



APPROXIMATE SHIPPING WEIGHTS (0(4.5)

27", 90", AND 96" MULTI-UGE CHAMBERG

YMW617227"W. APPROX SHIPPING WT. LB(KG) 100 (45.0) VMW6102 20"W. APPROX SHIPPING WT. LEG(KG) 105 (47.3) VMW6162 36"W. APPROX GHIPPING WT. LEG(FG) 115 (51.8)


PROFESSIONAL & DESIGNER

CHAMBERS

- · NUMEROUS STORAGE OPTIONS HELP MAINTAIN COMMERCIAL-TYPE STYLING 27", 30", AND 36"W. THEOUGHOUT FITCHEN MULTI-USE
- · CONCEAL MICROWAYE
- · CONCEAL TELEVISION
- · STORE "COUNTERTOP" APPLIANCES OR COOKWARE
- · STORE COOKBOOKS, COOKING UTENSILS, ETC.
- · "UP-GWING" DOOP FOR EAGY ACCEGG
- · INTEPIOR CAVITY LARGEST POSSIBLE USEABLE SPACE (TWO OPTIONS GIVEN DUE TO THE LOCATION OF THE HINGES FOR THE UPSWING DOOR)
- · 27"W. MODEL: 21"W. X 15"H. X 22½"D. OP 2カラ/e"W. X 12"H. X 22½"D.
- · 10"W. MODEL: 25"W. X 15"H. X 22½"D. OF 265/6"W. X 12"H. X 22½"D.
- · クロ"W. MODEL: クロ"W. X 15"H. X 2 2½"D. OP ク25/6"W. X 1 2"H. X 2 2½"D.
- · COMMERCIAL STYLING AND CONSTRUCTION




DMW6171 27"W. APPROX GHIPPING WT. LEG(KG) 100 (45.0) DMW6101 30"W. APPROX SHIPPING WT. LEG(FG) 105 (47.9)



PROFEGGIONAL

- · NUMEROUS STORAGE OPTIONS HELP MAINTAIN KITCHEN DESIGN AND STYLING
- · CONCEAL MICPOWAYE
- · CONCEAL TELEVISION
- · STORE "COUNTERTOP" APPLIANCES OR COOKWARE
- · STORE GOOKBOOKS, GOOKING UTENSILS, ETC.
- · "UP-GWING" DOOR FOR EAGY ACCESS
- · INTEPIOR CAVITY USABLE SPACE (TWO OPTIONS GIVEN DUE TO THE LOCATION OF THE HINGES FOR THE UP-SWING DOOR)
- · 2 7"W. MODEL: 2 ク 5/6"W. X | 2 ¾"H. X 2 2 ½"D. OP 2 2 ¾"W. X | 5"H. X 2 2 ½"D.
- $\cdot \ \, 70\text{"W. MODEL:} \ \, 26\text{-}/6\text{"W.} \times 12\text{\%"H.} \times 22\text{\%"D.} \ \, \text{OP } 2\text{-}5\text{\%"W.} \times 1\text{-}5\text{"H.} \times 22\text{\%"D.}$



DEGIGNER

YMWO/DMWO GERIEG MULTI-UGE CHAMBERG

MULTI-UGE CHAMBERG ARE NOT CONNECTED TO GAG OR ELECTRICITY. A LARGE ACCEGG HOLE IN REAR WALL OF INTERI-OR PROVIDES VENTILATION AND ELECTRICAL CORD OUTLET FOR "LOCALLY SUPPLIED" MICROWAYE OVEN.


FINIOH DETAILS FOR YMWO

- · OTAINLEOO OTEEL (OO), BLACK (BK), WHITE (WH), ALMOND (AL), BIOCUIT (BT), OTONE CRAY (OC), CRAPHITE CRAY (C), BUPAUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREST AREEN (FA), VIKINA BLUE (VB), COBALT BLUE (CB), AND EAAPLANT
- · FINIGH DEGIGNATEG DOOP FRONT AND SIDE DOOP FRAME. ALL FINIGHEG HAVE GTAINLEGG GTEEL HANDLEG WITH CHROME
- · BRAGG TRIM OPTION (BR) FOR ANY FINIGH; INCLUDEG NAMEPLATE AND DOOR HANDLE/BRACKETG. GUPER DURABLE, LONG LAGTING BRAGG FINIGH ON "HIGH TRAFFIC" PART (HANDLE); ALL OTHER PARTG HAVE A DURABLE PROTECTIVE COATING. ALL PARTO DEGIGNED FOR MAINTENANCE-FREE USE.

FINIOH DETAILS FOR DMWG

- · OTAINLEGG OTEEL (GG), BLACK (BK), WHITE (WH), BIGCUIT (BT), OTONE CRAY (GG), AND CRAPHITE CRAY (GG)
- · DOOR PANEL MATCHEO DEGIGNATED FINIOH; OTAINLEGO OTEEL HANDLE
- · BRAGG TRIM OPTION BRAGG FINIGH HANDLE

WOSOONG



PROFEGGIONAL AND DEGIGNER YENTILATION PRODUCTO

PROFESSIONAL INTERIOR POWER WALL HOOD 24", 30" & 36"W. / 10"H.


- · HEAVY-DUTY CONGTPUCTION; PROFEGGIONAL-TYPE GIZE, CONGTPUCTION, DEGIGN, AND GTYLING
- · VIRTUALLY SEAMLESS DESIGN WITH NO VISIBLE SCREWS
- · HALOGEN LIGHTS WITH DIMMER CONTROL; ON/OFF AND DIMMER CONTROL ARE SEPARATE
- · DIMMER ON LIGHTS ALLOWS CUSTOM LIGHTING SEPARATE ON/OFF SWITCH ALLOWS CONSUMER TO LEAVE DIMMER AT FAVORITE POSITION
- · ALL HOODS HAVE A HEAT SENSOR THAT TURNS THE VENTILATOR ON FULL POWER WHEN COOKING TEMPERATURES REACH UNCOMFORTABLE LEVELS

PROFEGGIONAL BUILT-IN 10"H. INTERIOR POWER WALL



YWH2410 24"W./21"D. APPROX. 6HPPING WEIGHT LB(KG) 46(21.7) YWH9010 90"W./21"D. APPROX. 6HPPING WEIGHT LB(KG) 56(25.2) YWH9610 96"W./21"D. APPROX. 6HPPING WEIGHT LB(KG) 60(27.0)

- · 460 OFM BLOWER
- · VAPIABLE OPEED VENTILATOR CONTROLO; SEPARATE CONTROLO FOR ON/OFF AND OPEED CONTROL
- · 2 HALOGEN LIGHTS WITH DIMMER CONTROL
- · SEPARATE CONTROLS FOR ON/OFF AND DIMMER
- · DIOHWAOHER-GAFE COMMERCIAL-TYPE GO BAFFLE FILTERG
- · HEAT GENGOR AUTOMATICALLY TURNO YENTILATOR ON FULL POWER WHEN TEMPERATURES REACH UNCOMFORTABLE LEVELS
- · VIRTUALLY GEAMLEGG GTAINLEGG GTEEL CANOPY INTERIOR FOR EAGY CLEANING
- · PECOMMENDED FOR USE WITH 90"W. PANGES, 96"W. NON-GRIDDLE/GRILL PANGES AND PANGETOPS, AND 90"/96"W. COOKTOPS; FOR LARGER EQUIPMENT USE 18"H. HOOD
- · FIVE-YEAP LIMITED ALL VENTILATOR MOTORS



PROFEGGIONAL RECIPCULATING HOOD CONVERGION FIT

- YRK 2 4 FOR 2 4 "W. HOOD APPROX. GHIPPING WEIGHT LEKKG) IO(4.5) YRK 90 FOR 90 "W. HOOD APPROX. GHIPPING WEIGHT LEKKG) IO(5.9) YRK 96 FOR 96 "W. HOOD APPROX. GHIPPING WEIGHT LEKKG) IO(7.9)
- · FOR USE WITH YWH2410, YWH9010 AND YWH9610 HOODS ONLY
- · INCLUDES CHAPCOAL FILTERS, TOP VENT/GRILLE, AND INSTALLATION HAPDWAPE
- · TOP YENT/APILLE: 4"H. X I 2"D.
- . 99 FINISH ONLY

ACCEGGORY PAIL OPTION FOR WALL HOODG (10"H. MODELG)

- · AVAILABLE IN 66/CHROME (CR) OR BRAGG (BR); 66/CHROME INCLUDEG A GTAINLEGG GTEEL RAIL WITH CHROME GUPPORTG/BRACKETG AND HOOKG; BRAGG INCLUDEG BRAGG RAIL, GUPPORTG/BRACKETG, HOOKG, AND NAMEPLATE; ALL BRAGG COMPONENTG HAVE A PROTECTIVE COATING FOR MAINTENANCE-FREE NORMAL UGE
- · FRONT OF HOOD
- · HOOKS FOR PACK INCLUDED
- · MUST BE OPDEPED FACTORY INSTALLED
- · ADD OPTION CODE (CF OF 154) TO END OF HOOD MODEL NUMBER (AFTER COLOR CODE)
- · ADD OPTION GOST TO WALL HOOD GOST

FINIOH DETAILS

· OTAINLEOG OTEEL (GO), BLACK (BK), WHITE (WH), ALMOND (AL), BIOCUIT (BT), OTONE GRAY (GG), GRAPHITE GRAY (GG), BURGUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREOT GREEN (FG), VIKING BLUE (VB), COBALT BLUE (CB), AND EGGPLANT (EP). GO/CHROME OR BRAGG ACCEGGORY PAIL OPTION AVAILABLE FOR ANY FINIGH.

DESIGNER BUILT-IN 6"H. INTERIOR POWER WALL HOODS


- · ALLOWO TPUE PEPLACEMENT OF MOST OLDEP, LOW-PEPFORMANCE HOODS WITH MINIMAL CABINET ALTERATION
- · VAPIABLE SPEED VENTILATOR CONTROLS; ON/OFF AND SPEED CONTROL ARE SEPARATE
- · HALOGEN LIGHTS WITH DIMMER CONTROL; ON/OFF AND DIMMER CONTROL ARE SEPARATE
- · MAY BE VENTED OUT THE TOP, BACK, OF CONVERTED TO PECIFICULATE
- · DIGHWAGHER-GAFE GTAINLEGG GTEEL MEGH FILTERG (FRAME AND MEGH ARE GTAINLEGG GTEEL)
- · CANOPY INTERIOR 19 COMPLETELY LINED IN STAINLESS STEEL FOR EASY CLEANING

DEGIGNER BUILT-IN 6"H. INTERIOR-POWER WALL HOODS

DWH 2 4 0 G FOR 2 4 "W. / 2 0"D. APPROX. GHIPPING WEIGHT LEG(FG) 40 (18.1)
DWH 9 0 0 G FOR 9 0 "W. / 2 0 "D. APPROX. GHIPPING WEIGHT LEG(FG) 48 (21.7)
DWH 9 6 0 G FOR 9 6 "W. / 2 0 "D. APPROX. GHIPPING WEIGHT LEG(FG) 54 (24.9)



- · VAPIABLE OPEED VENTILATOR CONTROLO; GEPARATE CONTROLO FOR ON/OFF AND OPEED CONTROL
- · 2 HALOGEN LIGHTS WITH DIMMER CONTROL
 - · GEPARATE CONTROLG FOR ON/OFF AND DIMMER
- · DIGHWAGHER-GAFE GTAINLEGG GTEEL MEGH FILTERG (FRAME AND MEGH ARE GTAINLEGG GTEEL)
- · YIRTUALLY SEAMLESS STAINLESS STEEL CANOPY INTERIOR FOR EASY CLEANING
- · PECOMMENDED FOR USE WITH 2 4"W. NON-GRIDDLE/GRILL RANGE. 90"W.
 RANGES, 96"W. NON-GRIDDLE/GRILL RANGES
 AND RANGETOPS, AND 90"/96"W. COOKTOPS
- · FIVE-YEAP LIMITED ALL VENTILATOR MOTORS



PROFEGGIONAL BUILT-IN 18"H. / 24" AND 27"D. WALL HOODS

PROFESSIONAL BUILT-IN 18"H. WALL HOODS

2 4" D. HOODS		
VWH2448 24"W.	APPROX. GHIPPING WEIGHT LEG(FG)	52 (27.6)
VWH7048 70"W.	APPROX. GHIPPING WEIGHT LEG(KG)	60 (27.0)
VWH7648 76"W.	APPROX. GHIPPING WEIGHT LEG(KG)	68 (70.6)
VWH4248 42"W.	APPROX. GHIPPING WEIGHT LEG(KG)	76 (94.2)
VWH4848 48"W.	APPROX. GHIPPING WEIGHT LEG(KG)	88 (99.6)
VWH5448 54"W.	APPROX. GHIPPING WEIGHT LEG(KG)	96 (43.2)
VWH6048 60"W.	APPROX. GHIPPING WEIGHT LEG(KG)	108 (48.6)
VWH6648 66"W.	APPROX. GHIPPING WEIGHT LEG(KG)	121(54.5)
27" D. HOODS		
VWH9078 90"W.	APPROX. GHIPPING WEIGHT LEG(KG)	66 (29.7)
VWH9678 96"W.	APPROX. GHIPPING WEIGHT LEG(KG)	74(カカ.カ)
VWH4878 48"W.	APPROX. GHIPPING WEIGHT LEG(KG)	94 (42.7)
VWH6078 60"W.	APPROX. GHIPPING WEIGHT LEG(KG)	114(51.3)



TEGTG GHOW 24"D. HOODG PERFORM PROPERLY OVER 27"D. RANGEG.

- · CANOPY ONLY; MUST ALSO PURCHASE INTERIOR OR EXTERIOR VENTILATOR FIT, SOLD SEPARATELY
- · YARIABLE SPEED YENTILATOR CONTROLS; SEPARATE CONTROLS FOR ON/OFF AND SPEED CONTROL
- · HALOGEN LIGHTO WITH DIMMER CONTROL; GEPARATE CONTROLO FOR ON/OFF AND DIMMER
- · HEAT LAMPS STANDARD (250 WATT HEAT LAMP BULB NOT INCLUDED)
- · HIGH-GHELF (WITH COOKING PRODUCT) OR WARMING GHELF PANEL GHOULD BE INGTALLED FOR USE WITH HEAT LAMP
- · DIGHWAGHER-GAFE COMMERCIAL-TYPE GG BAFFLE FILTERG
- · GEPAPATE PEMOVABLE GREAGE TROUGH FOR EAGY CLEANING
- · HEAT GENGOP AUTOMATICALLY TUPNG VENTILATOR ON FULL POWER WHEN TEMPERATURES REACH UNCOMFORTABLE LEVELS
- · VIRTUALLY GEAMLEGG GTAINLEGG GTEEL CANOPY INTERIOR FOR EAGY CLEANING

ACCESSORY PAIL OPTION FOR WALL HOODS (10"H. AND 18"H. MODELS)

- · AVAILABLE IN 99/CHROME (CR) OF BRAGG (BR); 99/CHROME INCLUDES A STAINLEGE STEEL RAIL WITH CHROME SUPPORTS/BRACKETS AND HOOKS; BRAGG INCLUDES BRAGG RAIL, SUPPORTS/BRACKETS, HOOKS, AND NAMEPLATE; ALL BRAGG COMPONENTS HAVE A PROTECTIVE COATING FOR MAINTENANCE-FREE NORMAL USE
- · FRONT OF HOOD
- · HOOKG FOR PACK INCLUDED
- · MUST BE OPDEPED FACTORY INSTALLED
- · ADD OPTION CODE (CP OR BP) TO END OF HOOD MODEL NUMBER (AFTER COLOR CODE)
- · ADD OPTION GOST TO WALL HOOD GOST


SEE PAGE 106 FOR VENTILATOR HITS

PROFESSIONAL PROFESSIONAL BUILT-IN 18"H. / 24" CHIMNEY WALL HOODS

BUILT-IN CHIMNEY WALL HOODS 18"H. / 24"D.


2 4" D. HOODS

YOWH3048	クO"W.	APPROX. GHIPPING WEIGHT LEG(KG)	120(54.5)
YOWH7648	96"W.	APPROX. GHIPPING WEIGHT LEG(KG)	127(57.7)
YOWH4248	4 2 "W.	APPROX. GHIPPING WEIGHT LEG(KG)	198 (62.7)
Y6WH4848	48"W.	APPROX. GHIPPING WEIGHT LEG(KG)	145 (65.8)
YOWH5448	54"W.	APPROX. GHIPPING WEIGHT LEG(KG)	159 (69.5)
Y6WH6048	60"W.	APPROX. GHIPPING WEIGHT LEG(KG)	160 (72.6)
YCWH6648	66"W.	APPROX. GHIPPING WEIGHT LEG(KG)	167 (75.8)



- · MUST ALSO PUPCHASE INTERIOR OF EXTERIOR VENTILATOR HIT SOLD SEPARATELY
- · ADJUSTABLE DUCT COVER STANDARD FOR 8' TO 9' CEILINGS
- · VAPIABLE SPEED VENTILATOR CONTROLS; SEPARATE CONTROLS FOR ON/OFF AND SPEED GONTROL
- · HALOGEN LIGHTS WITH DIMMER CONTROL; SEPARATE CONTROLS FOR ON/OFF AND
- · HEAT LAMPS STANDARD (250 WATT HEAT LAMP BULB NOT INCLUDED)
- · HIGH-SHELF (WITH COOKING PRODUCT) OF WARMING SHELF PANEL SHOULD BE NOTALLED FOR USE WITH HEAT LAMP
- · DIGHWAGHER-GAFE COMMERCIAL-TYPE GG BAFFLE FILTERG
- · SEPARATE REMOVABLE CREASE TROUGH FOR EASY CLEANING
- · HEAT GENGOP AUTOMATICALLY TUPNG VENTILATOR ON FULL POWER WHEN TEMPERATURES REACH UNCOMFORTABLE LEVELS
- · VIRTUALLY GEAMLEGG GTAINLEGG GTEEL CANOPY INTERIOR FOR EAGY CLEANING

TEGTO SHOW 2 4"D. HOODS PERFORM PROPERLY OVER 2 7"D. RANGES.



DUCT COYER EXTENDIONO

DCCE1210 FOR 30", 36", 42"W. HOODS APPROX. GHIPPING WEIGHT LEG(KG) 6(2.7) DUCE 1810 FOR 48", 54"W. HOODS APPROX. GHIPPING WEIGHT LEG(KG) 8 (9.6) DUCE 2410 FOR 60", 66"W. HOODS APPROX. GHIPPING WEIGHT LEG(KG) 11(4.9)

- · FOR USE WITH PROFESSIONAL CHIMNEY WALL HOODS
- · EXTEND HEIGHT OF DUCT COVER UP TO 12 (FOR 10 CEILINGS)
- · PEPLAGEO ADJUOTABLE DUCT GOVER INOERT; GUPPLIED OTANDARD WITH HOOD
- · OPECIFY FINIOH

ACCEGGOPY PAIL OPTION FOR WALL HOODG (10"H. AND 18"H. MODELG)

- · AVAILABLE IN 99/CHPOME (CP) OP BPAGG (BP); 99/CHPOME INCLUDEG A GTAINLEGG GTEEL PAIL WITH CHPOME SUPPORTS/BRACKETS AND HOOKS; BRASS INCLUDES BRASS RAIL, SUPPORTS/BRACKETS, HOOKS, AND NAMEPLATE; ALL BRAGG COMPONENTG HAVE A PROTECTIVE COATING FOR MAINTENANCE-FREE NORMAL UGE
- · FRONT OF HOOD
- · HOOKS FOR PACK INCLUDED
- · MUST BE OPDEPED FACTORY INSTALLED
- · ADD OPTION CODE (CP OF 15P) TO END OF HOOD MODEL NUMBER (AFTER COLOR CODE)
- · ADD OPTION COST TO WALL HOOD COST

SEE PAGE 106 FOR VENTILATOR FITS

DESIGNER CLASSIC CHIMNEY WALL HOODS

DEGIGNER CLAGGIC CHIMNEY WALL HOOD 24"D.

DCWH3042	クロ"W./12"H.	APPROX. GHIPPING WEIGHT LEG(KG)	51(23.0)
D6WH9644	96"W./14"H.	APPROX. GHIPPING WEIGHT LEG(KG)	61 (27.5)
D6WH4244	42"W./14"H.	APPROX. GHIPPING WEIGHT LEG(KG)	71 (92.0)
D6WH4844	42"W./14"H.	APPROX. GHIPPING WEIGHT LEG(KG)	82 (76.9)


- · COMES STANDARD W/ADJUSTABLE DUCT COVER FOR 8' TO 9' CEILINGS
- · FACTORY-INSTALLED CHROME OR BRASS ACCESSORY RAIL OPTION AVAILABLE RAIL ON FRONT ONLY
- · DCCE DUCT COVER EXTENSION ACCESSORY FOR CEILINGS UP TO 10. SOLD SEPARATELY (SEE HOOD ACCESSORIES PAGE)



DEGIGNER GLAGGIC CHIMNEY WITH LEDGE WALL HOOD 2 4"D.

D6WL9942	99"W./12"H.	APPROX. GHIPPING WEIGHT LEG(KG)	54(24.9)
D6WL9944	99"W./14"H.	APPROX. GHIPPING WEIGHT LEG(KG)	64 (28.8
D6WL4544	45"W./14"H.	APPROX. GHIPPING WEIGHT LEG(KG)	74 (カカ.カ)
D6WL5144	51"W/14"H	APPROX GHIPPING WEIGHT LEGIFG)	85 (28.2)


- · COMES STANDARD WITH ADJUSTABLE DUCT COVER FOR 8. TO 9. CEILINGS
- · DCCE DUCT COVER EXTENSION ACCESSORY FOR CEILINGS UP TO 10. SOLD SEPARATELY (SEE HOOD ACCESSORIES PAGE)



DEGIGNER GLAGGIO CHIMNEY LEDGELEGG WALL HOOD 2 4"D.

DCWN3042 3	0"₩./12"H.	APPROX. SHIPPING WEIGHT LEG(KG)	与 1 (23.0)
DCWN3644 3	6"W./14"H.	APPROX. GHIPPING WEIGHT LEG(KG)	61 (27.5)
D6WN4244 4	2"W./14"H.	APPROX. SHIPPING WEIGHT LEG(KG)	71 (92.0)
D6WN4844 48	3"W./14"H.	APPROX. SHIPPING WEIGHT LEG(KG)	82 (96.9)

- · COMES STANDARD WITH ADJUSTABLE DUCT COVER FOR 8 TO 9 CEILINGS
- · DCCE DUCT COVER EXTENSION FOR CEILINGS UP TO I O FEET SOLD SEPARATELY (SEE HOOD ACCESSORIES PAGE)



PROFEGGIONAL IGLAND HOODG 18"H. / 24"D.

VH9608 96"W.	APPROX. GHIPPING WEIGHT LEG(KG)	81 (96.5)
VIH4208 42"W.	APPROX. GHIPPING WEIGHT LEG(KG)	92 (41.4)
VIH5408 54"W.	APPROX. GHIPPING WEIGHT LEG(KG)	127(57.2)
VIH6608 66"W.	APPROX. SHIPPING WEIGHT LEG(KG)	142 (69.9)

PROFESSIONAL ISLAND HOODS VENTILATOR HIT, GOLD GEPARATELY VARIABLE GPEED VENTILATOR CONTROLG; GEPARATE CONTROLG FOR CUSTOM VENTILATOR CUSTOM VENTILA

- ON/OFF AND DIMMER
- · DIGHWAGHER-GAFE COMMERCIAL-TYPE GG BAFFLE FILTERG
- · GEPAPATE PEMOVABLE APEAGE TROUGH FOR EAGY CLEANING
- · HEAT GENGOR AUTOMATICALLY TURNG VENTILATOR ON FULL POWER WHEN TEMPERATURES REACH UNCOMFORTABLE LEVELS
- · YIRTUALLY GEAMLEGG GTAINLEGG GTEEL CANOPY INTERIOR FOR EAGY CLEANING

OPTION CODES

CR 2 STAINLESS STEEL/CHROME, FRONT/BACK

CR4 STAINLESS STEEL/CHROME, FRONT/BACK/BOTH SIDES

BP2 BPAGG FRONT/BACK

BR 4 BRAGG FRONT/BACK/BOTH GIDEG




ACCESSORY PAIL OPTION FOR ISLAND HOODS

- · AVAILABLE IN CHROME OR BRAGG; GG/CHROME INCLUDEG A GTAINLEGG GTEEL RAIL WITH CHROME SUPPORTS/BRACKETS AND HOOKS; BRASS INCLUDES BRASS RAIL, SUPPORTS/BRACKETS, HOOKS, AND NAMEPLATE; ALL BEAGG COMPONENTG HAVE A PROTECTIVE COATING FOR MAINTENANCE-FREE NORMAL
- · CAN BE OPDEPED ON FRONT AND BACK, OP ON FRONT, BACK, AND BOTH GIDEG
- · HOOKS FOR PACK INCLUDED
- · MUST BE OPDEPED FACTORY INSTALLED
 - · ADD OPTION CODE TO END OF MODEL NUMBER (AFTER COLOR CODE)
 - · ADD OPTION COST TO ISLAND HOOD COST

FINIOH DETAILS - WALL AND ISLAND HOODS

· OTAINLEGO OTEEL (GO), BLACK (BK), WHITE (WH), ALMOND (AL), BIGGUIT (BT), STONE GRAY (SG), GRAPHITE GRAY (GG), BURGUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREST AREEN (FA), VIKINA BLUE (VB), COBALT BLUE (CB), AND EGAPLANT (EP). 99/CHROME OF BRAGG ACCEGGORY RAIL OPTION AVAILABLE FOR ANY FINIGH.

IMPORTANT: VIKING VENTILATOR KITO ARE DEGIGNED SPECIFICALLY FOR USE WITH VIKING HOODS. USE OF NON-VIKING VENTILATOR KITS VOIDS THE HOOD WARRANTY.



BUILT-IN CUSTOM YENTILATOR SYSTEMS

FOR USE WITH GUSTOM WALL HOODS

YBCY7078 70"W/18"H/22"D.	APPROX. GHIPPING WEIGHT LEG(KG)	60 (27.0)
YBCY9698 96"W./18"H./22"D.	APPROX. GHIPPING WEIGHT LEG(KG)	68 (70.6)
YBCV4298 42"W/18"H/22"D.	APPROX. GHIPPING WEIGHT LEG(KG)	76(94.2)
YBCY4878 48"W./18"H./22"D.	APPROX. GHIPPING WEIGHT LEG(KG)	88 (79.6)
YBCY5498 54"W./18"H./22"D.	APPROX. GHIPPING WEIGHT LEG(KG)	96 (47.2)
YBCY6078 60"W./18"H./22"D.	APPROX. GHIPPING WEIGHT LEG(KG)	108 (48.6)
YBCY6678 66"W./18"H./22"D.	APPROX. GHIPPING WEIGHT LEG(KG)	121(54.5)

SEE PAGE 106 FOR VENTILATOR KITS

BUILT-IN CUSTOM VENTILATOR SYSTEMS

FOR USE WITH CUSTOM ISLAND HOODS


 VICY9698 96"W./[8"H./29"D.
 APPROX. OHIPPING WEIGHT LE(KG)
 79(99.1)

 VICY4298 42"W./[8"H./29"D.
 APPROX. OHIPPING WEIGHT LE(KG)
 89(97.7)

 VICY5498 54"W./[8"H./29"D.
 APPROX. OHIPPING WEIGHT LE(KG)
 [552.2)

 VICY6698 66"W./[8"H./29"D.
 APPROX. OHIPPING WEIGHT LE(KG)
 [28(58.1)

SEE PAGE 106 FOR VENTILATOR KITS



PROFEGGIONAL CHIMNEY IGLAND HOODS 18"H. / 90"D.

YOH7608 76"W.	APPROX. GHIPPING WEIGHT LEG(KG)	92 (41.4)
YOH4208 42"W.	APPROX. GHIPPING WEIGHT LEG(KG)	127(57.4)
YOH5408 54"W.	APPROX. GHIPPING WEIGHT LEG(KG)	142(69.9)
VOH6608 66"W.	APPROX. GHIPPING WEIGHT LEG(KG)	158 (71.6)

OPTION CODES


CP 2 STAINLESS STEEL/CHPOME, FRONT/BACK

CR4 STAINLESS STEEL/CHROME, FRONT/BACK/BOTH SIDES

BP2 BPAGG FRONT/BACK

BR 4 BRAGG FRONT/BACK/BOTH GIDEG

PROFESSIONAL CHIMNEY ISLAND HOODS



(DUCT COYER GOLD GEPARATELY)

- · CANOPY ONLY; MUST ALSO PURCHASE INTERIOR OR EXTERIOR VENTILATOR FIT, SOLD SEPARATELY
- · YAPIABLE OPEED VENTILATOR CONTROLO; GEPARATE CONTROLO FOR ON/OFF AND GPEED CONTROL
- · HALOGEN LIGHTS WITH DIMMER CONTROL; SEPARATE CONTROLS FOR ON/OFF AND DIMMER
- · DIGHWAGHER-GAFE COMMERCIAL-TYPE GG BAFFLE FILTERG
- · SEPAPATE PEMOVABLE CREASE TROUCH FOR EASY CLEANING
- · HEAT GENGOR AUTOMATICALLY TURNG VENTILATOR ON FULL POWER WHEN TEMPERATURES REACH UNCOMFORTABLE LEVELS
- · YIRTUALLY SEAMLESS STAINLESS STEEL CANOPY INTERIOR FOR EASY CLEANING

ACCESSORY PAIL OPTION FOR ISLAND HOODS

- · AVAILABLE IN CHROME OR BRAGO; GG/CHROME INCLUDEG A GTAINLEGG GTEEL RAIL WITH CHROME GUPPORTG/BRACKETG AND HOOKG; BRAGO INCLUDEG BRAGO RAIL, GUPPORTG/BRACKETG, HOOKG, AND NAMEPLATE; ALL BRAGO COMPONENTG HAVE A PROTECTIVE COATING FOR MAINTENANCE-FREE NORMAL UGE
- · CAN BE OPDEPED ON FRONT AND BACK, OP ON FRONT, BACK, AND BOTH SIDES
- · HOOKS FOR PACK INCLUDED
- · MUST BE OPDEPED FACTORY INSTALLED
- · ADD OPTION CODE TO END OF MODEL NUMBER (AFTER COLOR CODE)
- · ADD OPTION COST TO ISLAND HOOD COST

FINIGH DETAILS - WALL AND ISLAND HOODS

· OTAINLEGO OTEEL (GO), BLACK (BK), WHITE (WH), ALMOND (AL), BIOCUIT (BT), OTONE GRAY (GG), GRAPHITE GRAY (GG), BURGUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREOT GREEN (FG), VIKING BLUE (VB), COBALT BLUE (CB), AND EGGPLANT (EP). GG/CHROME OR BRAGG ACCEGGORY RAIL OPTION AVAILABLE FOR ANY FINIGH.

IMPORTANT: VIKING VENTILATOR KITS ARE DESIGNED SPECIFICALLY FOR USE WITH VIKING HOODS. USE OF NON-VIKING VENTILATOR KITS VOIDS THE HOOD WARRANTY.

SEE PAGE 106 FOR VENTILATOR FITS

DESIGNER WALL HOODS


DEGIGNER CLAGGIC CHIMNEY IGLAND HOOD - 90"D.

 DOH 9 60 4 9 6" W./ 1 4" H.
 APPROX. SHIPPING WEIGHT LIS(KG)
 92 (41.4)

 DOH 4 2 0 4 4 2" W./ 1 4" H.
 APPROX. SHIPPING WEIGHT LIS(KG)
 1 0 5 (47.9)

 DOH 5 4 0 4 5 4" W./ 1 4" H.
 APPROX. SHIPPING WEIGHT LIS(KG)
 1 48 (66.6)


- · DUCT COYER MUST BE ORDERED SEPARATELY (SEE HOOD ACCESSORIES PAGE) DUCT COYERS AVAILABLE FOR INSTALLATIONS WITH S', 9', OR I O' CEILINGS
- · CHROME (CR4) OR BRAGG (BR4) ACCEGGORY RAIL OPTION AVAILABLE RAIL AROUND COMPLETE UNIT



DEGIGNER GLIM TRADITIONAL WALL HOOD - 24"D.

DTW69049	90"W./9"H.	APPROX. GHIPPING WEIGHT LEG(KG)	50(22.5)
DTW09649	96"W./9"H.	APPROX. GHIPPING WEIGHT LEG(KG)	60 (27.0)
DTW94249	42"W./9"H.	APPROX. SHIPPING WEIGHT LEG(KG)	70(カ1.5)
DTW94849	48"W./9"H.	APPROX. SHIPPING WEIGHT LEG(KG)	81 (96.5)

- · COMEG GTANDAPD W/ADJUGTABLE DUCT COVER FOR 8 TO 9 CEILINGG
- · FACTORY-INSTALLED CHROME OF BRASS ACCESSORY PAIL OPTION AVAILABLE - PAIL ON FRONT ONLY
- · DOGE DUCT COVER EXTENSION ACCESSORY FOR CEILINGS UP TO 10'; SOLD SEPARATELY (SEE HOOD ACCESSORIES PAGE)



DEGIGNER TALL TRADITIONAL LEDGELEGG WALL HOOD - 2 4"D.

DTWN9048	90"W./18"H.	APPROX. GHIPPING WEIGHT LEG(FG)	59 (26.6)
DTWN9648	96"W./18"H.	APPROX. GHIPPING WEIGHT LEG(KG)	69 (71.1)
DTWN4248	42"W./18"H.	APPROX. GHIPPING WEIGHT LEG(KG)	79 (35.6)
DTWN4848	48"W./18"H.	APPROX. GHIPPING WEIGHT LEG(KG)	90 (40.5)

· DUCT COVERS MUST BE ORDERED SEPARATELY (SEE HOOD ACCESSORIES PAGE)



- · BLACK (BK), WHITE (WH), STAINLESS STEEL (SS), BISCUIT (BT), STONE GRAY (SG), AND GRAPHITE GRAY (GG)
- · ACCEGGORY PAIL (FOR CLAGGIC CHIMNEY ONLY) GG/CHROME OR BRAGG
- · FRONT OF HOOD WALL HOOD; FRONT, BACK AND BOTH GIDEG IGLAND HOOD
- · HOOKS FOR PACK INCLUDED
- · OUTGIDE OF CANOPY MATCHEG DEGIGNATED FINIGH; CANOPY INTERIOR 1G ALWAYG GTAINLEGG GTEEL
- · CUSTOM VENTILATOR SYSTEMS ARE DESIGNED TO BE COVERED BY CUSTOM MATERIALS AND DO NOT HAVE A STANDARD EXTERIOR FINISH. THE INTERIOR IS STAINLESS STEEL.

BUILT-IN GUSTOM VENTILATOR SYSTEMS

FOR USE WITH GUSTOM WALL HOODS

DBCV9082 90"W./[2"H./[8"D. APPROX. 6HIPPING WEIGHT LB(FG) 69 (28.4)
DBCV9682 96"W./[2"H./[8"D. APPROX. 6HIPPING WEIGHT LB(FG) 70 (9 [.5)
DBCV4282 42"W./[2"H./[8"D. APPROX. 6HIPPING WEIGHT LB(FG) 77 (94.7)
DBCV4882 48"W./[2"H./[8"D. APPROX. 6HIPPING WEIGHT LB(FG) 85 (98.9)

DESIGNER CUSTOM 70 (2 8.4) VENTILATOR 77 (2 4.7) SYSTEMS

IOLAND CUSTOM VENTILATOR SYSTEMS

FOR USE WITH GUSTOM ISLAND HOODS

 DIGV9692 96"W./12"H./29"D.
 APPROX. GHIPPING WEIGHT LEG(KG)
 88 (40.0)

 DIGV4292 42"W./12"H./29"D.
 APPROX. GHIPPING WEIGHT LEG(KG)
 96 (49.6)

 DIGV5492 54"W./12"H./29"D.
 APPROX. GHIPPING WEIGHT LEG(KG)
 106 (48.1)



INTERIOR POWER YENTILATOR KITS

SEE PAGE 105 FOR CFM RECOMMENDATIONS

DIV900 900 CFM VENTILATOR FIT. VIV900 900 CFM VENTILATOR FIT. DIV440 440 CFM VENTILATOR FIT. DIV600 600 CFM VENTILATOR FIT.	APPROX. GHIPPING WEIGHT LEG(KG) APPROX. GHIPPING WEIGHT LEG(KG) APPROX. GHIPPING WEIGHT LEG(KG) APPROX. GHIPPING WEIGHT LEG(KG)	(5 (6.8) 27 (12.2) 25 (11.2) 27 (12.2)
VIVGOO GOO OFM VENTILATOR HIT.	APPROX. GHIPPING WEIGHT LEG(KG)	27 (12.2)
DIVBBO BBO OFM VENTILATOR HIT.	APPROX. GHIPPING WEIGHT LEG(KG)	76 (16.2)
DIV 200 200 CFM VENTILATOR HIT.	APPROX. GHIPPING WEIGHT LEG(FG)	49 (19.4)
VIV 200 200 CFM VENTILATOR HIT.	APPROX. GHIPPING WEIGHT LEG(FG)	49 (19.4)

EXTERIOR POWER YENTILATOR FITS

SEE PAGE 105 FOR CFM RECOMMENDATIONS

DEV900 900 OFM VENTILATOR HIT.	APPROX. GHIPPING WEIGHT LEG(KG)	99(17.6)
VEV900 900 OFM VENTILATOR FIT.	APPROX. GHIPPING WEIGHT LEG(KG)	99(17.6)
DEV 1200 1200 CFM VENTILATOR KIT.	APPROX. GHIPPING WEIGHT LEG(KG)	与カ(2カ.9)
VEV 1200 1200 OFM VENTILATOR FIT.	APPROX. GHIPPING WEIGHT LEG(KG)	与カ(2カ.9)
DEV 1500 1500 OFM VENTILATOR HIT.	APPROX. GHIPPING WEIGHT LEG(KG)	47 (21.9)
VEV 1500 1500 CFM VENTILATOR FIT.	APPROX. GHIPPING WEIGHT LEG(KG)	47 (21.9)

DUCT COVERS FOR WALL HOODS

DCW24 24"W.	APPROX. GHIPPING WEIGHT LEG(KG)	9 (4.0)
D6W90 30"W.	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)
DUW96 76"W.	APPROX. GHIPPING WEIGHT LEG(KG)	11(5.0)
DCW42 42"W.	APPROX. GHIPPING WEIGHT LEG(KG)	1 カ (ち.9)
DCW48 48"W.	APPROX. GHIPPING WEIGHT LEG(KG)	14 (6.7)
DOW54 54"W.	APPROX. GHIPPING WEIGHT LEG(KG)	29(10.4)
D6W60 60"W.	APPROX. GHIPPING WEIGHT LEG(KG)	24(10.8)
DCW66 66"W.	APPROX. GHIPPING WEIGHT LEG(KG)	26(11.7)

HOOD ACCESSORIES

- · EXTENDS HEIGHT OF HOOD BY 12; CONCEALS DUCT
- · 12"D.
- · SPECIFY FINISH

DUCT COVERS FOR ISLAND HOODS

DO196 96"W. APPROX. 9HIPPING WEIGHT LEG(FG) [5 (6.8)]
DO142 42"W. APPROX. 9HIPPING WEIGHT LEG(FG) [8 (8.1)]
DO154 54"W. APPROX. 9HIPPING WEIGHT LEG(FG) 24 (10.8)]
DO166 66"W. APPROX. 9HIPPING WEIGHT LEG(FG) 94 (15.9)

- · EXTENDO HEIGHT OF HOOD BY 12"; CONCEALS DUCT
- · 12"D.
- · SPECIFY FINISH

HOOD ACCESSORIES


DUCT COVERS FOR CLASSIC CHIMNEY ISLAND HOODS (YCH) ONLY

FOR 96"W. H	0006		
16617608	12"H./FOR 8' CEILING	APPROX. GHIPPING WEIGHT LEG(FG)	20 (9.0)
16617609	2 4"H./FOR 9" CEILING	APPROX. GHIPPING WEIGHT LEG(FG)	ク 与 (15.8)
46613610	36"H./FOR 10" CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	50(22.5)
FOR 42"W. H	0006		
	12"H./FOR 8' CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	24(10.8)
16614209	2 4"H./FOR 9' CEILING	APPROX. GHIPPING WEIGHT LEG(FG)	42(18.9)
16614210	36"H./FOR 10" CEILING	APPROX. GHIPPING WEIGHT LEG(FG)	60 (27.0)
FOR 54"W. H	0006		
	12"H./FOR 8' CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	92(14.4)
16615409	2 4"H./FOR 9" CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	50(25.2)
16615410	36"H./FOR 10" CEILING	APPROX. GHIPPING WEIGHT LEG(FG)	80 (76.0)
FOR 66"W. HOODS			
16616608	12"H./FOR 8' CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	42(18.9)
	24"H./FOR 9' CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	69 (71.1)
16616610	36"H./FOR 10" CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	90 (40.5)

[·] ALL COVERS ARE 12"D.

BACKOPLAGHEG (WALL HOODG)

BK624 12"W. BK690 90"W. BK696 96"W. BK642 42"W.	APPEOX. GHIPPING WEIGHT LEG(FG) APPEOX. GHIPPING WEIGHT LEG(FG) APPEOX. GHIPPING WEIGHT LEG(FG) APPEOX. GHIPPING WEIGHT LEG(FG)	5 (2.7) 7 (7.2) 9 (4.1) 1 2 (5.4)
BK648 48"W. BK654 54"W. BK660 60"W. BK660 66"W.	APPROX. GHIPPING WEIGHT LEY(FG) APPROX. GHIPPING WEIGHT LEY(FG) APPROX. GHIPPING WEIGHT LEY(FG) APPROX. GHIPPING WEIGHT LEY(FG)	1 4 (6.9) 1 7 (7.7) 2 0 (9.0) 2 9 (1 0.4)



- · HEMMED EDGEG WITH GOPEW HOLEG
- · FAGTENING GOPEWG INCLUDED
- ・クO"H.
- · STAINLESS STEEL ONLY

WARMING SHELF PANELS (WALL HOODS)

WGP24	12"W. ONE SHELF	APPROX. GHIPPING WEIGHT LEG(KG)	6(2.7)
Wapgo	90"W. ONE SHELF	APPROX. GHIPPING WEIGHT LEG(KG)	9 (4.1)
Wap 36	36"W. TWO SHELVES	APPROX. GHIPPING WEIGHT LEG(KG)	12(5.4)
WGP 42	42"W. TWO GHELVEG	APPROX. GHIPPING WEIGHT LEG(KG)	14 (6.9)
WUP48	48"W. TWO SHELVES	APPROX. GHIPPING WEIGHT LEG(KG)	16(7.2)
Wap54	54"W. TWO GHELVEG	APPROX. GHIPPING WEIGHT LEG(KG)	20(9.0)
W4P60	60"W. THREE GHELVEG	APPROX. GHIPPING WEIGHT LEG(FG)	29(10.4)
W4P66	66"W. THREE OHELVEO	APPROX. GHIPPING WEIGHT LEG(FG)	26(11.7)



- · FOLD UP/DOWN HEAVY-DUTY GHELVEG (NOT REMOVABLE) FACTORY INGTALLED ON GG BACKGPLAGH
- · FAGTENING GOPEWG INCLUDED

[·] OPECIFY FINIOH

DUCT COVERS FOR CLASSIC CHIMNEY ISLAND HOODS (DCIH) ONLY

FOR 36"W. HOODS

D6617608	12"H./FOR 8 CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	20 (9.0)
06617609	2 4"H./FOR 9" CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	クラ (15.8)
06617610	96"H./FOR 10" CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	50(22.5)
FOR 42"W. H	0006		
D6614208	12"H./FOR 8 CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	24(10.8)
DUU 14209	2 4"H./FOR 9" CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	42(18.9)

FOR 54"W. HOODS

D6615408 12"H	/FOR 8 CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	92(14.4)
D6615409 24"H	/FOR 9 CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	56(25.2)
DCC15410 36"H	/FOR 10 CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	80 (96.0)

[·] ALL COVERS ARE 12"D.

PEPLACEMENT CHAPCOAL FILTERS

CFYII FOR 24"W. PROFEGGIONAL HOODG	APPROX. SHIPPING WEIGHT LES(KG)	1 (0.5)
CFY 19 FOR 90" \$ 96"W. PROFEGGIONAL HOODG	APPROX. GHIPPING WEIGHT LEG(KG)	2 (0.9)
CF-DI2 FOR 90"W. DEGIGNER HOODG	APPROX. GHIPPING WEIGHT LEG(KG)	2 (0.9)
CF-DI4 FOR 96"W. DEGIGNER HOODG	APPROX. GHIPPING WEIGHT LEO(KG)	2 (0.9)

[·] FOUR USE WITH YRK & DRK CONVERSION KITS

[·] OPECIFY FINIOH

[·] PECOMMEND PEPLACEMENT EVERY 6-12 MONTHG

DUCT COVERS FOR BOX WALL HOODS (DOWB) ONLY

FOR 90"W. HO	0006		
D6937008	12"H./FOP & CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	17(7.7)
D6653009	2 4"H./FOR 9" CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	27(12.2)
D66B3010	96"H./FOP 10" CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	97 (16.7)
FOR 96"W. HO	0006		
D6687608	12"H./FOR 8" CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	19 (8.6)
D66B9609	2 4"H./FOR 9" CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	29(17.1)
0663610	96"H./FOR 10" CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	99(17.6)
FOR 42"W. HO	0006		
D6684208	12"H./FOR & CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	24(10.8)
D6684209	2 4"H./FOR 9" CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	カカ (14.9)
D6684210	96"H./FOR 10" CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	50(22.5)
FOR 48"W. HO	0006		
	12"H./FOR 8 CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	26(11.7)
	24"H./FOR 9" CEILING	APPROX. GHIPPING WEIGHT LEG(KG)	40 (18.0)
	96"H./FOP 10 CEILING	APPROX. SHIPPING WEIGHT LEG(KG)	54(24.3)

[·] ALL COVERS ARE 12"D.

DUCT COVERS FOR TALL TRADITIONAL WALL HOODS

DCW90 90"W.	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)
DCW96 96"W.	APPROX. GHIPPING WEIGHT LEG(KG)	11(5.0)
DCW42 42"W.	APPROX. GHIPPING WEIGHT LEG(KG)	1カ(ち.9)
DCW48 48"W.	APPROX. GHIPPING WEIGHT LEG(KG)	14(6.7)

[·] EXTENDS HEIGHT OF HOOD BY 12"; CONCEALS DUCT

DUCT COVER EXTENDIONO

DCCE1010 FOR 90" AND 99"W.HOODS	APPROX. GHIPPING WEIGHT LEG(KG)	4 (1.8)
DCCE 2 0 FOR 36", 39", 42" AND 45"W. HOODS	APPROX. GHIPPING WEIGHT LEG(KG)	6(2.7)
DCCE 1610 FOR 30" AND 36"W. DCH HOODS ONLY	APPROX. GHIPPING WEIGHT LEG(FG)	7 (15.4)
DCCE1810 FOR 48" AND 51"W.		
CLAGGIC CHIMNEY-GTYLE HOODG ONLY	APPROX. GHIPPING WEIGHT LEG(KG)	8 (7.6)
DCCE 2010 FOR 48"W. GLIM TRADITIONAL HOODS ONLY	APPROX. GHIPPING WEIGHT LEG(KG)	9 (4.1)

- · EXTENDS HEIGHT OF ADJUSTABLE DUCT COVER BY UP TO 12" (FOR 10' CEILINGS)
- · PEPLACEO ADJUOTABLE DUCT COVER INSERT SUPPLIED STANDARD WITH HOOD
- · FOR CLAGGIC CHIMNEY (DCWH), CLAGGIC CHIMNEY W/LEDGE (DCWL), CLAGGIC CHIMNEY LEDGELEGG (DCWN) & GLIM TRADITIONAL (DTWG) WALL HOODG ONLY
- · SPECIFY FINISH

MODEL # DUCT DIMENGIONG WITH EXTENGIONG

DCCE | 0 | 0 | W. X | 2 | D. X 90 | - 42 | H.

DCCE | 2 | 0 | 2 | W. X | 2 | D. X 28 | - 40 | H.


DCCE | 6 | 0 | 6 | W. X | 2 | D. X 28 | - 40 | H.

DCCE | 8 | 0 | 8 | W. X | 2 | D. X 28 | - 40 | H.


DCCE | 0 | 0 | 20 | W. X | 2 | D. X 28 | - 40 | H.

ADJUSTABLE DUCT COVER

DOG 1 G FOR 5 TO 9 CEILINGS. APPROX. SHIPPING WEIGHT LIB(KG) 20 (9.0)



- · FOR 30" AND 36"W. HOODS
- · SPECIFY FINISH



[·] SPECIFY FINISH

[·] FOR DTWN AND DTWL ONLY


PROFESSIONAL AND DESIGNER BUILT-IN REAR DOWNDRAFT

BUILT-IN VERGAVENTTH REAR DOWNDRAFT

VERGAVENT INTAKE/PLENUM WITH CONTROLG ON INTAKE TOP

ALLE 101	90"W.PROFEGGIONAL	APPROX. GHIPPING WEIGHT LEG(KG)	49(19.4)
VIPP 161	96"W. PROFEGGIONAL	APPROX. GHIPPING WEIGHT LEG(KG)	50(22.5)
VIPP 181	48"W. PROFEGGIONAL	APPROX. GHIPPING WEIGHT LEG(KG)	66 (29.7)


- · FOR PROFESSIONAL COOKTOPS ONLY
- · PAIGEG AND LOWERS AT TOUCH OF BUTTON
- · DELAY FUNCTION TURNS UNIT OFF AFTER 10 MINUTES
- · FOUR FAN SPEEDS
- · TWO PEMOVABLE, EAGY-TO-CLEAN MEGH FILTERS
- · FLAGHING LIGHT PEMINDG UGEP TO CLEAN FILTERS AFTER APPROXIMATELY 90 HOURS OF UGE
- · CHOOGE INTERIOR OF EXTERIOR VENTILATOR FIT (GEE NEXT PAGE)



VERGAVENT INTAKE/PLENUM WITH CONTROLG ON INTAKE TOP

NIDE 1015	90"W. PROFESSIONAL	APPROX. SHIPPING WEIGHT LES(KG)	49 (19.4)
VIPP 101P	36"W. PROFEGGIONAL	APPROX. GHIPPING WEIGHT LEG(FG)	50(22.5)
VIPP 181P	48"W. PROFEGGIONAL	APPROX. GHIPPING WEIGHT LEG(FG)	66 (29.7)
DIPP 100P	90"W. DEGIGNER	APPROX. GHIPPING WEIGHT LEG(KG)	49 (19.4)
DIPP 160P	96"W. DEGIGNER	APPROX. GHIPPING WEIGHT LEG(KG)	50(22.5)
DPP 150P	45"W. DEGIGNER	APPROX. GHIPPING WEIGHT LEG(KG)	66 (29.7)

- · FOR PANGETOPS/COOKTOPS ONLY (PANGETOP MUST BE INSTALLED WITH ISLAND TRIM)
- · DO NOT INSTALL WITH GRILL MODEL PANGETOPS
- PAIGES AND LOWERS AT THE TOUCH OF A BUTTON
- · DELAY FUNCTION TURNS UNIT OFF AFTER 10 MINUTES
- · FOUR FAN SPEEDS
- · 4"W. X 21/2"D. CONTROL PANEL MOUNTO SEPARATELY ON COUNTERTOP FOR EASE OF USE; STAINLESS STEEL TRIM WITH BLACK MEMBRANE/CONTROL PANEL
- · TWO PEMOVABLE, EAGY-TO-CLEAN MEGH FILTERS
- · FLAGHING LIGHT PEMINDS USER TO CLEAN FILTERS AFTER APPROXIMATELY 90 HOURS OF USE
- · CHOOGE INTERIOR OR EXTERIOR VENTILATOR FIT





DOWNDRAFT ACCESSORIES

PEAR DOWNDRAFT ACCESSORIES

INTERIOR-POWER YENTILATOR

YIDY500 APPROX. GHIPPING WEIGHT LEG(FG) 92(14.4)

- . 500 OFM
- · MOUNTS ON ANY SIZE PLENUM
- \cdot 9 | /4" X | 0" DUCT TAKEOFF; CONTINUE WITH THIS SIZE OF TRANSITION TO 6" ROUND
- · CAN PUN DUCT TO LEFT, PIGHT, OF DOWN
- · FIVE-YEAR LIMITED WARRANTY MOTOR

EXTEPIOP-POWER VENTILATOR


YEDY 9 00 APPROX. 6HIPPING WEIGHT LB(KG) 4 2 (18.9) YEDY 1 2 00 APPROX. 6HIPPING WEIGHT LB(KG) 4 4 (19.8)


- . 900 CFM OF 1200 CFM
- · MOUNTO ON WALL OF POOF (NO POOF CAP PEQUIPED)
- · YENT OPENING ON VENTILATOR MUST BE INSTALLED IN THE DOWN POSITION (ALL INSTALLATIONS)
- · COMES WITH IO" POUND DUCT TAKEOFF PLATE WHICH MOUNTS TO ANY SIZE PLENUM
- · 1200 OFM PECOMMENDED FOR VIPP 181 48"W. DOWNDRAFT ONLY
- · FIVE-YEAR LIMITED WARRANTY MOTOR

PEMOTE MOUNTED CONTROL

DOPLOGY APPROX. OHIPPING WEIGHT LEG(FG) 1.5 (0.7)

- · PEPLAGES STANDARD DESIGNER CONTROL
- · EAGY TO INSTALL
- · GAME FEATUREG AG NOTED ABOVE
- · STAINLESS STEEL TRIM WITH ARAY MEMBRANE/CONTROL PANEL COORDINATES WITH WHITE DESIGNER COORTOPS







DEGGRIPTION	FILTERS	HALOGEN LIGHTG	HEAT LAMP	PECOMMENDED OFM I	2 <i>0</i> VA <i>C/G0</i> H2 MA	
10" HIGH VWH WALL HOODS						
2 4"W.			11/1	460 LEMINTEDIOD OTANDADIO MAY		
29 W.	2	2	N/A	460 CFM INTERIOR STANDARD MAX. DUCT RUN 50'(15.2 CM) (7" ROUND DUCT)	5.6	
10 vv. 26"₩.	2	2	N/A	(7" EOUND DUZT)	5.6	
7 0 yy.	2	2	N/A		5.6	
18" HIGH YWH WALL	H0006					
2 4 "W.	2	2	1	VIV900/VIV600/VEV900/VEV 200	5.0/6.2/8.7/8.7/6.1	
クロ" AND クロ"W.	2	2	1	YIY 900/YIY 600/YIY 1 200/YEY 900/YEY 1 200	5.0/6.2/8.7/8.7/6.1	
4 2 "W.	2	2	1	VIV600/VIV 200/VEY900/VEY 200	6.2/8.7/8.7/6.1	
48" AND 54"W.	9	2	2	VIV 200/VEV 200/VEV 500	11.1/8.4/9.1	
60" AND 66"W.	4	4	2	VIV 1 200/VEV 1 200/VEV 1 500	11.5/8.8/9.5	
18" HIGH 16LAND VIH	H0006					
26"₩.	4	4	N/A		4.9/7.4/4.7	
4 2 " * .	4	4	N/A	VIV600/VEV900/VEV1 200	4.9/7.4/7.4/4.8/5.5	
54"W.	6	6	N/A	YIY600/YIY 200/YEY 900/YEY 200/	8.2/5.5/6.2	
66"W.	8	8	N/A	VEV 1500	9.0/6.3/7.1	
	U			VIV 1 200/VEV 1 200/VEV 1 500	9.070.777.1	
18" HIGH YOWH CHIM	NEY WALL	H0000		yiy 200/yey 200/yey 500		
90" AND 96"W.	2	2	1		7.9/4.0/8.7/4.0	
4 2 " * .	2	2			4.0/8.7/4.0	
48" AND 54"W.	2	2	2	DIY900/DIY600/DEY900/DEY 1 200	11.5/8.5/9.2	
60" AND 66"W.	4	4	2	DIV600/DEV900/DEV1200	11.9/8.9/9.2	
			-	DIV 1 200/DEV 1 200/DEV 1 500	11.9/2.9/9.2	
18" HIGH YOH CHIMNE	EY IOLAND	H0006		DIY 200/DEY 200/DEY 500		
96"₩.	4	4	N/A		7.9/6.6/7.9	
4 2 "W.	4	4	N/A	DIY600/DEY900/DEY1200	4.7/7.4/4.8/5.5	
54"W.	6	6	N/A	DIV600/DEV900/DEV1200/DEV1500	8.6/5.6/6.4	
66"W.	8	8	N/A	DIV 200/DEV 200/DEV 500	9.5/6.5/7.9	
				DIV 200/DEV 200/DEV 500		
YECY CUSTOM VENT	TLATOR 6	yotemo	- FOR			
H0006	2	2	1		5.0/6.2/8.7/8.7/6.1	
90" AND 96"W.	2	2	1	VIV 300/VIV 600/VIV 200/VEV 900/VEV 200		
4 2 " 😾 .	2	2	2	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	11.1/8.4/9.1	
48" AND 54"W.	4	4	2	VIV 200/VEV 200/VEV 500	11.5/8.8/9.5	
60" AND 66"W.				YIY 200/YEY 200/YEY 500	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
18" HIGH CHIMNEY 16L	AND YICY	H0000				
26"W.	4	4	N/A		4.9/7.4/4.7	
4 2 "\.	4	4	N/A	YIY600/YEY900/YEY 200	4.9/7.4/7.4/4.8/5.5	
54"W.	6	6	N/A	YIY600/YIY 200/YEY900/YEY 200/	8.2/5.5/6.2	
66" ₩.	8	8	N/A	VEV 1500	9.0/6.9/7.1	
				YIY 200/YEY 200/YEY 500		
				VIV 200/VEV 200/VEV 500		

PROPER INSTALLATION/DUCTING 16 EXTREMELY IMPORTANT TO ENSURE MAXIMUM PERFORMANCE FROM ANY VENTILATION PRODUCT

- · ALL CFMO OTATED BAOED ON TEOTO WITH . I OTATIC PREODURE: WITHOUT APPLYING OTATIC PREODURE (GOME BRANDO CONOCIOUOLY DO NOT), CFM COULD BE GREATLY OVEROTATED.
- · DUCT PUN LENATH 16 FOR GENERAL REFERENCE ONLY; FOR LONGER DUCT PUNG, INCREAGE DUCT GIZE AND CONTACT A QUALIFIED AND TRAINED INSTALLER.
- · OTPAIGHT PUNG AND GRADUAL TURNG ARE BEGT; FOR EXAMPLE, EACH 900 ELBOW 16 EQUIVALENT TO 5-10 FEET (1.52-9.05CM) OF OTPAIGHT PUN.
- ·NEVER USE FLEXIBLE DUCT; IT CREATES BACK PRESSURE/AIR TURBULENCE AND CREATLY REDUCES PERFORMANCE.
- · PROPER PERFORMANCE 10 DEPENDENT UPON PROPER DUCTING; MAKE OURE THAT A QUALIFIED AND TRAINED INSTALLER 16 UPED.
- · CHECK WITH A QUALIFIED AND TRAINED INSTALLER OR LOCAL CODES FOR MAKEUP AIR REQUIREMENTS, IF ANY.
- · MAX. AMP RATING FOR HOODS INCLUDES RECOMMENDED VENTILATOR FIT RATING; ALL PRODUCTS MUST BE HARD WIRED DIRECT WITH 2-WIRE WITH GROUND.
- · A | 200 OF | 500 CFM (IF APPLICABLE) VENTILATOR FIT SHOULD BE USED WHEN INSTALLED OVER PANGE/PANGETOPS WITH GAS CHAP-GPILL.

DEGIGNER HOOD DATA

DEGGRIPTION	FILTERS	HALOGEN LIGHTG	PECOMMENDED OFM	1 20 VAC/60 HZ MAX AMP6
1 2 "H. DCH WALL HOODG 30" AND 36"W.	2	2	460 CFM INTERIOR STANDARD MAX. DUCT RUN 50'(15.2 CM) (7" ROUND DUCT)	5.6
CLAGGIC CHIMNEY, CLAGG	OL CHIMNE	EY LEDGI	ELEGG, CLAGGIC CHIMNEY WITH LEDGE - WAL	L H0006
クロ" AND クラ"W.	2	2	DIY900/DIY440/DEY900/DEY1200	1.7/9.2/6.6/9.9
96" AND 99"W.	2	2	DIY900/DIY600/DEY900/DEY1200	1.7/9.9/6.6/9.9
42" AND 45"W.	9	2	DIY600/DEY900/DEY1200	7.9/6.6/7.9
48" AND 51"W.	7	9	DIY 200/DEY 200/DEY 500	7.9/4.9/5.1
CLAGGIC CHIMNEY - IGLAN	D H00D6	,		
9 6 "₩.	2	4	DIV600/DEV900/DEV1200	7.9/6.6/7.9
4 2 "W.	9	4	DIV600/DEV900/DEV 200/DEV 500	4.7/7.4/4.7/5.5
54"W.	7	6	DIY 200/DEY 200/DEY 500	8.6/5.6/6.4
GLIM TRADITIONAL - WALI	- HOODS			
90"₩.	2	2	DIY900/DIY440/DEY900	1.7/2.2/6.6
9 6 "₩.	2	2	DIV900/DIV440/DEV900/DEV1200	1.7/2.2/6.6/2.9
4 2 "W.	9	2	DIY440/DEY900/DEY1200	7.2/6.6/7.9
48"W.	7	9	DIY880/DEY 200/DEY 500	5.6/4.7/5.1
TALL TRADITIONAL WITH I	-ED4E \$ T	ALL TRA	ADITIONAL LEDGELEGG - WALL HOODG	
クロ" AND クロ"W.	2	2	YIY900/YIY600/YIY 200/YEY900/	2.4/4.6/6.6/6.6/9.9
4 2 "W.	9	2	YEY 1 200	4.6/6.6/6.6/7.9
48"W.	9	2	YIY600/YIY 200/YEY900/YEY 200	7/4.9/5.1
			YIY 200/YEY 200/YEY 500	
BOX - WALL HOODS				
90"₩.	2	2		1.7/9.2/6.6
96"₩.	2	2	DIY900/DIY440/DEY900	1.7/9.2/6.6/9.9
4 2 "W.	9	2	DIY900/DIY440/DEY900/DEY1200	7.2/6.6/7.9
48"W.	9	2	DIV440/DEV900/DEV1200	5.6/4.9/5.1
DBOY OUSTOM YENTILAT	OR 649T	EMG - Fa	DIV880/DEY 200/DEY 500 OF WALL H <i>00</i> D6	
20" AND 26"W.	2	2		1.7/9.2/6.6/9.9
4 2 "W.	2	2	DIV900/DIV440/DEV900/DEV1200	7.2/6.6/7.9
48"W.	2	2	DIV440/DEV900/DEV1200	5.6/4.9/5.1
	7	•	DIV880/DEV 200/DEV 500	J. 4. 7/ J. (
DICY CUSTOM YENTILATO	P GYGTE	M6 - F01		
26"₩.	2	4		4.0/7.5/5.2
4 2 "W.	2	4	DIV440/DEV900/DEV1200	4.0/7.5/5.2/6.0
54"₩.	2	4	DIV440/DEV900/DEV1200/DEV1500	6.4/5.2/6.0
	•	•	DIV880/DEV 200/DEV 500	

PROPER INSTALLATION/DUCTING IS EXTREMELY IMPORTANT TO ENSURE MAXIMUM PERFORMANCE FROM ANY VENTILATION PRODUCT

NOTE: I 200 OF I 500 CFM (IF APPLICABLE) VENTILATOR FITO GHOULD BE USED WITH COOFING PRODUCTS THAT CONTAIN THE CHAR-CRILL FEATURE. CLASSIC CHIMNEY ISLAND HOODS, BOX WALL HOODS, SLIM
TRADITIONAL WALL HOODS, AND DICY CUSTOM ISLAND VENTILATOR SYSTEMS SHOULD NOT BE INSTALLED OVER
PROFESSIONAL COOKING PRODUCTS THAT CONTAIN THE CHAR-CRILL FEATURE.


PROFEGGIONAL & DEGIGNER HOOD DATA

MODEL NUM	BER	OFM	PECOMMENDED DUCT	MAX DUCT PUN	1 20 V/60 HZ MAX AMP6
FOR USE WITH	H H0006		6 12 E		
D14700	(INTERIOR)	200	7" POUND	50 FEET (15.2M)	
Y14900	(INTERIOR)	200	7" POUND	50 FEET (15.2M)	
DIV440	(INTERIOR)	440	7" POUND	50 FEET (15.2M)	
DIV600	(INTERIOR)	600	7" POUND	50 FEET (15.2M)	
Y1Y600	(INTERIOR)	600	7" POUND	50 FEET (15.2M)	
DIV880	(INTERIOR)	880	10" POUND	50 FEET (15.2M)	
DEV900	(EXTEPIOP)	900	10" POUND	50 FEET (15.2M)	
YEY900	(EXTEPIOP)	900	10" POUND	50 FEET (15.2M)	
DIY 1 200	(INTERIOR)	1200	10" POUND	50 FEET (15.2M)	
YIY 1 200	(INTERIOR)	1200	10" POUND	50 FEET (15.2M)	
DEY 1200	(EXTEPIOP)	1200	10" POUND	50 FEET (15.2M)	
YEY 1200	(EXTEPIOP)	1200	10" POUND	50 FEET (15.2M)	
DEV 1500	(EXTEPIOP)	1500	10" POUND	75 FEET (22.9M)	
YEY 1500	(EXTEPIOP)	1500	10" POUND	75 FEET (22.9M)	
FOR USE WITH	H DOWNDRAFTS				
YIDY500	(INTERIOR)	500	3/4 X10" CAN	40 FEET (12.2M)	
			TRANGITION TO 6" ROUND		
YEDY900	(EXTEPIOP)	900	10" POUND	50 FEET (15.2M)	
YEDY 1 200	(EXTEPIOP	1200	10" POUND	50 FEET (15.2M)	
VIL900(IN-LINE	≡)	900	10" POUND	50 FEET (15.2M)	
DIL900	(IN-LINE)	900	10" POUND	50 FEET (15.2M)	
VIL 1 200	(IN-LINE)	1200	10" POUND	50 FEET (15.2M)	
DIL 1 200	(IN-LINE)	1200	10" POUND	50 FEET (15.2M)	

PROPER INSTALLATION/DUCTING IS EXTREMELY IMPORTANT TO ENSURE MAXIMUM PERFORMANCE FROM ANY VENTILATION PRODUCT

- · ALL CFMO OTATED BAOED ON TEOTO WITH . I STATIC PREOQURE: WITHOUT APPLYING OTATIC PREOQURE (GOME BRANDO CONOCIOUOLY DO NOT), CFM COULD BE CREATLY OVEROTATED.
- · DUCT PUN LENATH 10 FOR GENERAL REFERENCE ONLY; FOR LONGER DUCT PUNG, INCREAGE DUCT GIZE AND CONTACT A QUALIFIED AND TRAINED INGTALLER.
- · STRAIGHT RUNG AND GRADUAL TURNG ARE BEGT; FOR EXAMPLE, EACH 900 ELBOW IG EQUIVALENT TO 5-10 FEET (1.52-9.05CM) OF GTRAIGHT RUN.
- · NEVER USE FLEXIBLE DUCT: IT CREATES BACK PRESSURE/AIR TURBULENCE AND GREATLY REDUCES PERFORMANCE.
- · PROPER PERFORMANCE 16 DEPENDENT UPON PROPER DUCTING; MAKE GURE THAT A QUALIFIED AND TRAINED INGTALLER 16 UGED.
- · CHECK WITH A QUALIFIED AND TRAINED INSTALLER OR LOCAL CODES FOR MAKEUP AIR REQUIREMENTS, IF ANY.
- · MAX. AMP RATING FOR HOODS INCLUDES RECOMMENDED VENTILATOR FIT RATING; ALL PRODUCTS MUST BE HARD WIRED DIRECT WITH 2-WIRE WITH GROUND (REFER TO HOOD DATA CHART FOR MORE INFORMATION).
- · A | 200 OF | 500 CFM (IF APPLICABLE) YENTILATOR FIT GHOULD BE UGED WHEN INGTALLED OVER PANGE/PANGETOPG WITH GAG CHAP-GPILL.

V10:00016



PROFEGGIONAL AND DEGIGNER PEFRICERATION PRODUCTS

BUILT-IN 36"W.BOTTOM MOUNT REFRIGERATOR/FREEZERS

PEFPIGERATOR CAPACITY: 15.2 CU. FT. TOTAL CAPACITY: 20.7 CU. FT. FREEZER CAPACITY: 5.1 CU. FT.

470(2115)

YCBB369 (P/L*) - PROFESSIONAL DOOR YIBBOOO (P/L*) - PROFESSIONAL INTEGRATED DOOR

DDBB969 (P/L*) - DEGIGNER DOOR DFBBOGO (P/L*) - FULL OVEPLAY

- · 84"4/24"D
- · PROCHILL™ TEMPERATURE MANAGEMENT GYGTEM
- · VAPIABLE SPEED SINGLE COMPRESSOR SYSTEM INCLUDES THE QUIETEST, MOST TECHNOLOGICALLY ADVANCED COMPRESSOR AVAILABLE
- · ELECTPONIC CONTROLO MAINTAIN THE TEMPERATURE GELECTION WITHIN 1 OF
- · MULTI-CHANNEL AIRFLOW GYGTEM REMOVEG ODORG AND EXCEGG HUMIDITY
- · FROST-FREE REFRIGERATOR
- · FIVE ADJUSTABLE TEMPERED GLASS SPILLPROOF SHELVES
- · CONVERTIBLE TEMPERATURE CONTROLLED MEAT SAYORTM/PRODUCE DRAWER WITH POLLER BEARING GLIDES
- · TWO MOIGTURE ADJUGTABLE, GEE-THROUGH PRODUCE DRAWERS
- · TWO IN-THE-DOOP DAILY COMPARMENTS WITH COVERS
- · FIVE ADJUSTABLE ALUMINUM DOOR BINS WITH TEMPERED GLASS FRONTS
- · TOP SHELF PROVIDES QUICK CHILL DOWN AREA
- · STANDARD ACCESSORIES INCLUDE EGG BIN AND BUTTER TRAY
- · FROGT-FREE FREEZER
- · ADAPTIVE DEFPOST
- · FACTORY-INGTALLED AUTOMATIC ICE MAKER
- · TWO SLIDE OUT WIFE BASKETS
- · OPEN DOOR ALARM GOUNDG AND GLOWG TO WARN THAT DOOR HAG BEEN AJAR FOR THREE MINUTES
- · ADJUSTABLE DOOR STOPS STANDARD 900, 1100 OR 1200 SWING
- · TWO YEAR FULL WARRANTY COMPLETE UNIT: GIX-YEAR FULL WARRANTY -SEALED SYSTEM AND ICE MAKER; TWELVE-YEAR LIMITED - SEALED SYSTEM

*P=PIGHT HINGE; L=LEFT HINGE

YCEB/DDBB/DFBB REFRIGERATOR/FREEZERG

ELECTPICAL

- · 5 FT. CORD INCLUDED WITH UNIT
- · 2 WIPE WITH GROUND/9 PRONG PLUG
- · 1 154/60H2; MAXIMUM AMPG 9.9

WATER


· INLET WATER REQUIREMENTS - 1/4" COPPER TUBING

FINIOH DETAILS FOR VOBB MODELS ONLY


- · OTAINLEOO OTEEL (OO), ELACK (EK), WHITE (WH), ALMOND (AL), EIOCUIT (ET), OTONE GRAY (OG), GRAPHITE GRAY (QQ), BUP-QUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREST AREEN (FQ), VIRING BLUE (VB), COBALT BLUE (OB), AND EGAPLANT (EP)
- · FINIGH CODEG DEGIGNATE DOOR FRONTS, ALL FINIGHEG HAVE STAINLEGG STEEL UPPER CRILLE, STAINLEGG STEEL SIDE TRIM, STAINLESS STEEL DOOR HANDLES WITH CHROME PLATED BRACKETS, AND BLACK LOWER KICKPLATE.
- · BRAGG TRIM OPTION (BR) FOR ANY FINIGH; INCLUDEG NAMEPLATE, DOOR HANDLE/BRACKETG, AND GIDE TRIM. SUPER DURABLE, LONG LASTING BRASS FINISH FOR "HIGH TRAFFIC" PARTS (HANDLE); ALL OTHER PARTS HAVE A DUPABLE PROTECTIVE COATING. ALL PARTO DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.

FINIOH DETAILS FOR DOBB MODELS ONLY

- · OTAINLEOO OTEEL (OO), BLACK (BK), WHITE (WH), BIOCUIT (BT), OTONE GRAY (OG), AND GRAPHITE GRAY (GG)
- · DOOR PANELS MATCH DESIGNATED FINISH, STAINLESS STEEL HANDLE
- · FINIGH CODES DESIGNATE DOOR FRONTS. ALL FINISHES HAVE STAINLESS STEEL FINISHED UPPER GRILLE, STAINLESS STEEL FINISHED SIDE TRIM, STAINLESS STEEL HANDLES AND BLACK LOWER KICKPLATE.
- · BRAGG TRIM OPTION (BR) HANDLE. GUPER DURABLE, LONG LAGTING BRAGG FINIGH. DEGIGNED FOR MAINTENANCE-FREE NORMAL USE.








BUILT-IN 42"W. SIDE-BY-SIDE REFRIGERATOR/FREEZERS

TOTAL CAPACITY: 2 4.0 CU. FT. PEFPIGEPATOR CAPACITY: 15.0 CU. FT. FREEZER CAPACITY: 9.0 CU. FT.

APPROX. GHIPPING WEIGHT LEG(KG) 515(1961)

VCOB429 PROFEGGIONAL DOOP VIODA 29 PROFEGGIONAL INTEGRATED DOOR DDOB429 DEGIGNER DOOR DFOB429 FULL OVERLAY

- · 84"H./24"D.
- · PROCHILL™ TEMPERATURE MANAGEMENT GYGTEM
- · VARIABLE OPEED GINGLE COMPREGGOR GYGTEM INCLUDED THE QUIETEGT. MOGT TECHNOLOGICALLY ADVANCED COMPREGGOR AVAILABLE
- · ELECTPONIC CONTPOLO MAINTAIN THE TEMPERATURE GELECTION WITHIN I OF
- · MULTI-CHANNEL AIRFLOW GYGTEM REMOVEG ODORG AND EXCEGG HUMIDITY
- · FROST-FREE REFRIGERATOR
- · FIVE ADJUSTABLE TEMPERED GLASS SPILLPROOF SHELVES
- · CONVERTIBLE TEMPERATURE CONTROLLED MEAT SAYORTM/PRODUCE DRAWER WITH PRECISION BALL-BEARING GLIDES
- · GEPARATE TEMPERATURE CONTROL CAN BE GET FOR PRODUCE OR FREGH MEAT GTOR-AUE
 - · QUICK CHILL OPTION CHILLY FOODS AND BEVERAGES IN MINUTES
- · MOIGTURE ADJUGTABLE, GEE-THROUGH PRODUCE DRAWER WITH PRECIGION BALL-BEARING GLIDES
- · TWO IN-THE-DOOP DAIRY COMPARTMENTS WITH COVERS
- · FOUR ADJUSTABLE ALUMINUM DOOR BINS WITH TEMPERED GLASS FRONTS
- · TOP SHELF PROVIDES QUICK CHILL DOWN AREA
- · STANDARD ACCESSOPIES INCLUDE EGG BIN AND BUTTER TRAY
- · FROST-FREE FREEZER
- · ADAPTIVE DEFEOST
- · FACTORY-INGTALLED AUTOMATIC ICE MAKER
- · THREE WIRE OHELVES AND TWO SLIDE-OUT BASKETS
- · THREE ADJUGTABLE ALUMINUM DOOR BING WITH TEMPERED GLAGG FRONTG
- · OPEN DOOR ALARM GOUNDS AND GLOWS TO WARN THAT DOOR HAS BEEN AJAR FOR THREE MINUTES
- · ADJUSTABLE DOOR STOPS STANDARD 900, I 100 AND I 200 SWING
- · TWO YEAR FULL WARRANTY GOMPLETE UNIT; GIX-YEAR FULL WARRANTY GEALED GYOTEM AND ICE MAKER; TWELVE-YEAR LIMITED - GEALED GYGTEM



YCOB/DDOB/DFOB PEFPICEPATOP/FPEEZEPO

ELECTPICAL

- · 5 FT. COPD INCLUDED WITH UNIT
- · 2 WIPE WITH APOUND/ 9 PRONG PLUG
- · 1 15Y/GOHZ; MAXIMUM AMPG 9.9

WATER

· INLET WATER REQUIREMENTS - 14" COPPER TUBING

FINIOH DETAILS FOR YOUR MODELS ONLY

· STAINLEGG STEEL (GG), BLACK (BK), WHITE (WH), ALMOND (AL), BIGCUIT (BT), STONE CRAY (64), APAPHITE APAY (44), BUPAUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREST APEEN (FA),

(YB), COBALT BLUE (CB), AND EGGPLANT (EP)

- · FINIGH CODES DESIGNATE DOOR FRONTS. ALL FINISHES HAVE STAINLESS STEEL UPPER CRILLE, STAINLESS STEEL SIDE TRIM, STAINLESS STEEL DOOR HANDLES WITH CHROME PLATED BRACKETS, AND BLACK LOWER
- · BRAGG TRIM OPTION (BR) FOR ANY FINIGH; INCLUDEG NAMEPLATE, DOOR HANDLE/BRACKETG, AND GIDE TRIM. SUPER DURABLE, LONG LASTING BRASS FINISH FOR "HIGH TRAFFIC" PARTS (HANDLE); ALL OTHER PARTS HAVE A PUPABLE PROTECTIVE COATING. ALL PARTS DESIGNED FOR MAINTENANCE-FREE NORMAL USE.


FINISH DETAILS FOR DOOPS MODELS ONLY

- · OTAINLEOO OTEEL (OO), BLACK (BK), WHITE (WH), BIOCUIT (BT), OTONE GRAY (OG), AND GRAPHITE GRAY (GG)
- · DOOR PANELO MATCH DEGIGNATED FINIOH, GTAINLEGG GTEEL HANDLE
- · FINIGH CODEG DEGICNATE DOOR FRONTG. ALL FINIGHEG HAVE GTAINLEGG GTEEL FINIGHED UPPER GRILLE, STAINLESS STEEL FINISHED SIDE TRIM, STAINLESS STEEL HANDLES AND BLACK LOWER KICKPLATE.
- · BRAGG TRIM OPTION (BR) HANDLE. GUPER DURABLE, LONG LAGTING BRAGG FINIGH. DEGIGNED FOR MAINTENANCE-FREE NORMAL USE.









FULL OVEPLAX

BUILT-IN 42"W. SIDE-BY-SIDE REFRIGERATOR/FREEZERS WITH ICE & WATER DISPENSER

TOTAL CAPACITY: 29.1 CU. FT. PEFPICEPATOP CAPACITY: 14.5 CU. FT. FPEEZEP CAPACITY: 8.6 CU. FT.


APPROX. GHIPPING WEIGHT LEG(KG)


525 (236.2)

VCOB429D PROFESSIONAL DOOR VISB429D PREOFESSIONAL INTEGRATED DOOR DDSB429D DESIGNER DOOR DFSB429D FULL OVERLAY




- · PROCHILL™ TEMPERATURE MANAGEMENT GYGTEM
- · VARIABLE OPEED GINGLE COMPREGGOR GYGTEM INCLUDEG THE QUIETEGT, MOGT TECHNOLOGICALLY ADVANCED COMPREGGOR AVAILABLE
- · ELECTRONIC CONTROLO MAINTAIN THE TEMPERATURE SELECTION WITHIN I OF
- · MULTI-CHANNEL AIRFLOW GYGTEM REMOYEG ODORG AND EXCEGG HUMIDITY
- · FROST-FREE REFRIGERATOR
- · FIVE ADJUSTABLE TEMPERED GLASS SPILLPROOF SHELVES
- · CONVERTIBLE TEMPERATURE CONTROLLED MEAT GAYORTM/PRODUCE DRAWER WITH PRECIGION BALL-BEARING CLIDEG
- · SEPARATE TEMPERATURE CONTROL CAN BE SET FOR PRODUCE OR FRESH MEAT STORAGE
- · QUICK CHILL OPTION CHILLS FOODS AND BEYERAGES IN MINUTES
- · MOISTURE ADJUSTABLE, SEE-THROUGH PRODUCE DRAWER WITH PRECISION BALL-BEARING GLIDES
- · TWO IN-THE-DOOP DAIRY COMPARMENTS WITH COVERS
- · FOUR ADJUSTABLE ALUMINUM DOOR BINS WITH TEMPERED GLASS FRONTS
- · TOP GHELF PROVIDEG QUICK CHILL DOWN AREA
- · OTANDARD ACCESSOPIES INCLUDE EGG BIN AND BUTTER TRAY
- · FP-06T-FPEE FPEE2EP
- · ADAPTIVE DEFEOST
- · FACTORY-INSTALLED AUTOMATIC ICE MAKER
- · THREE WIRE SHELVES AND TWO SLIDE-OUT BASKETS
- · THREE LARGE ADJUSTABLE ALUMINUM DOOR BINS WITH TEMPERED GLASS FRONTS
- · ICE/WATER DISPENSER
- · THROUGH-THE-DOOR DIGPENGER PROYIDEG CUBED ICE, CRUGHED ICE AND WATER IN EAGY ONE-HAND OPERATION
- PREMIUM WATER FILTER PROVIDEO CLEANER WATER AND ICE OUPPLY BY FILTERING BAD TAOTEO, ODORO, OEDIMENT AND HARMFUL CONTAMINANTO
- · OPEN DOOR ALARM GOUNDG AND GLOWG TO WARN THAT DOOR HAG BEEN AJAR FOR THREE MINUTEG
- · ADJUGTABLE DOOR STOPS STANDARD 900, 1100 AND 1200 SWING
- · TWO YEAR FULL WARRANTY COMPLETE UNIT; GIX-YEAR FULL WARRANTY GEALED GYGTEM AND ICE MAKER; TWELVE-YEAR LIMITED GEALED GYGTEM





DEGIGNER





FULL OVERLAY

BUILT-IN 48"W. SIDE-BY-SIDE REFRIGERATOR/FREEZERS

TOTAL CAPACITY: 27.4 CU. FT. PEFPIGEPATOP CAPACITY: 18.5 CU. FT.

FREEZER CAPACITY: 8.9 CU. FT.

APPROX. 9HIPPING WEIGHT LEG(KG)
650 (292.5)


YCOB 489 PROFESSIONAL DOOR

VIODABO PROFEGGIOANL INTEGRATED DOOR


DD95489 DE9IGNER D00R

DFOB489 FULL OVERLAY

- · 84"H./24"D.
- · PROCHILLIM TEMPERATURE MANAGEMENT GYGTEM
- · VARIABLE OPEED OINGLE COMPREGGOR GYGTEM INCLUDED THE QUIETEGT,
 MOST TECHNOLOGICALLY ADVANCED COMPREGGOR AVAILABLE
- · ELECTPONIC CONTROLO MAINTAIN THE TEMPERATURE SELECTION WITHIN I OF
- · MULTI-CHANNEL AIRFLOW GYGTEM REMOYEG ODORG AND EXCEGG HUMIDITY
- · FROST-FREE REFRIGERATOR
- · FIVE ADJUGTABLE TEMPERED GLAGG GPILLPROOF GHELVEG
- · CONVERTIBLE TEMPERATURE CONTROLLED MEAT GAVORM/PRODUCE DRAWER WITH ROLLER BEARING GLIDEG
- · TWO MOIGTURE ADJUGTABLE, GEE-THROUGH PRODUCE DRAWERG WITH ROLLER BEARING GLIDEG
- · TWO IN-THE-DOOP DAIRY COMPARMENTS WITH COVERS
- · THREE ADJUGTABLE ALUMINUM DOOR BING WITH TEMPERED GLAGG FRONTG
- · TOP SHELF PROVIDES QUICK CHILL DOWN AREA
- · GTANDARD ACCEGGORIEG INCLUDE EGG BIN AND BUTTER TRAY
- · FPOOT-FPEE FPEEZER
- · ADAPTIVE DEFEOST
- · FACTORY-INGTALLED AUTOMATIC ICE MAKER
- · THREE WIRE OHELVES AND TWO SLIDE-OUT BASKETS
- · FOUR ADJUSTABLE ALUMINUM DOOR BINS WITH TEMPERED GLASS FRONTS
- · OPEN DOOR ALARM GOUNDG AND GLOWG TO WARN THAT DOOR HAG BEEN AJAR FOR THREE MINUTEG
- · ADJUSTABLE DOOR STOPS STANDARD 900, 1100 AND 1200 SWING
- · TWO YEAR FULL WARRANTY COMPLETE UNIT; OIX-YEAR FULL WARRANTY -OEALED OYOTEM AND ICE MAKER; TWELVE-YEAR LIMITED - OEALED OYOTEM




PROFESSIONAL



DEGIGNER

Wood/custom Moterials



FULL OVEPLAY

YOOB/DDOB/DFOB PEFPIGEPATOP/FPEEZEPO

ELECTRICAL

- · 5 FT. COPD INCLUDED WITH UNIT
- · 2 WIPE WITH GROUND/3 PRONG PLUG
- · 1 154/60H2; MAXIMUM AMPG 9.9 (NON-DIGPENGER); 1 1.5 (DIGPENGER)

WATER

· INLET WATER REQUIREMENTS - 4" COPPER TUBING

FINIOH DETAILS FOR YOBB MODELS ONLY

- · OTAINLEOO OTEEL (OO), BLACK (BK), WHITE (WH), ALMOND (AL), BIOCUIT (BT), OTONE ARAY (OA), ARAPHITE ARAY (AA), BURAUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREOT AREEN (FA), VIKINA BLUE (VB), COBALT BLUE (CB), AND EACHLANT (EP)
- · FINIGH CODEG DEGICINATE DOOR FRONTG. ALL FINIGHEG HAVE STAINLEGG STEEL UPPER CIPILLE, STAINLEGG STEEL SIDE TRIM, STAINLEGG STEEL DOOR HANDLEG WITH CHROME PLATED BRACKETG, AND BLACK LOWER FICKPLATE.
- · BRAGG TRIM OPTION (BR) FOR ANY FINIGH; INCLUDED NAMEPLATE, DOOR HANDLE/BRACKETO, AND SIDE TRIM. SUPER DURABLE, LONG LAGTING BRAGG FINIGH FOR "HIGH TRAFFIC" PARTS (HANDLE); ALL OTHER PARTS HAVE A DURABLE PROTECTIVE COATING. ALL PARTS DESIGNED FOR MAINTENANCE-FREE NORMAL USE. FINIGH DETAILS FOR DOBB MODELS ONLY
- · STAINLEGG GTEEL (GG), BLACK (BK), WHITE (WH), BIGCUIT (BT), STONE CRAY (GG), AND CRAPHITE CRAY (GG)
- · DOOR PANELS MATCH DESIGNATED FINISH, STAINLESS STEEL HANDLE
- · FINIGH CODEG DEGICNATE DOOR FRONTG. ALL FINIGHEG HAYE GTAINLEGG GTEEL FINIGHED UPPER CRILLE,
- OTAINLEOO OTEEL FINIOHEO OIDE TRIM, OTAINLEOO OTEEL HANDLEO AND BLACK LOWER KICKPLATE.
- · BRAGG TRIM OPTION (BR) HANDLE. GUPER DURABLE, LONG LAGTING BRAGG FINIGH. DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.

BUILT-IN 48"W. SIDE-BY-SIDE REFRIGERATOR/FREEZERS WITH ICE & WATER DISPENSER

TOTAL CAPACITY: 26.4 CU. FT. PEFPIGEPATOR CAPACITY: 17.9 CU. FT. FREEZER CAPACITY: 8.5 CU. FT.


APPROX. GHIPPING WEIGHT LEG(KG)


VCOB489D PROFEGGIONAL DOOR


650 (292.5)


VIOD 4890 PROFEGGIONAL INTEGRATED DOOR DDOB489D DEGIGNER DOOR DFOB489D FULL OVERLAY

- · 84"H./24"D.
- · PROCHILL™ TEMPERATURE MANAGEMENT GYGTEM
- · YAPIABLE OPEED GINGLE COMPREGGOR GYGTEM INCLUDES THE QUIETEST, MOST TECHNOLOGICALLY ADVANCED COMPRESSOR AVAILABLE
- · ELECTRONIC CONTROLS MAINTAIN THE TEMPERATURE SELECTION
- · MULTI-CHANNEL AIRFLOW GYGTEM REMOVEG ODORG AND EXCEGG HUMIDITY
- · FROOT-FREE REFRIGERATOR
- · FIVE ADJUSTABLE TEMPERED GLASS SPILLPROOF SHELVES
- · CONVERTIBLE TEMPERATURE CONTROLLED MEAT GAYOR TH/PRODUCE DRAWER WITH POLLER BEARING GLIDES
- · TWO MOISTURE ADJUSTABLE, SEE-THROUGH PRODUCE DRAWERS WITH POLLER BEARING GLIDES
- · TWO IN-THE-DOOP DAIRY COMPARMENTS WITH COVERS
- · FOUR ADJUSTABLE ALUMINUM DOOR BINS WITH TEMPERED GLASS FRONTS
- · TOP SHELF PROVIDES QUICK CHILL DOWN AREA
- · STANDARD ACCESSORIES INCLUDE EGG BIN AND BUTTER TRAY
- · FROGT-FREE FREEZER
- · ADAPTIVE DEFEOST
- · FACTORY INSTALLED AUTOMATIC ICE MAKER
- · THREE WIRE SHELVES AND SLIDE-OUT BASKET
- · THREE LARGE ALUMINUM DOOR BING WITH TEMPERED GLAGG FRONTG
- · ICE/WATER DISPENSER
- · THEOUGH-THE-DOOR DISPENSER PROVIDES CUBED ICE, CRUSHED ICE AND WATER IN EAGY ONE-HAND OPERATION
- · PREMIUM WATER FILTER PROVIDES CLEANER WATER AND ICE SUPPLY BY FILTERING BAD TAGTEG, ODORG, GEDIMENT AND HARMFUL CONTAMINANTS
- · OPEN DOOR ALARM GOUNDS AND GLOWS TO WARN THAT DOOR HAS BEEN AJAP FOR THREE MINUTES
- · ADJUSTABLE DOOR STOPS STANDARD 90°, 110° AND 120° SWING
- · TWO YEAR FULL WARRANTY COMPLETE UNIT; SIX-YEAR FULL WARRANTY -GEALED GYGTEM AND ICE MAKER; TWELVE-YEAR LIMITED - GEALED GYGTEM









FULL OYEPLAY

BUILT-IN 30"W. ALL REFRIGERATOR

VCPB904 PROFESSIONAL DOOR VIPEOO 4 PROFEGGIONAL INTEGRATED APPROX. GHIPPING WEIGHT LEI(KG) DDPB904 DEGIGNER DOOR DFPB904 FULL OVEPLAY

APPROX. GHIPPING WEIGHT LEG(KG) 425(191.9) APPROX. GHIPPING WEIGHT LEG(KG) 425(1913) APPROX. GHIPPING WEIGHT LEG(FG) 425 (191.2)

TOTAL CAPACITY: 18.2 CU. FT.

- · 84"4/24"D
- · PROCHILLIM TEMPERATURE MANAZIEMENT GYGTEM
- · VAPIABLE OPEED SINGLE COMPRESSOR SYSTEM INCLUDES THE QUIETEST,
- MOST TECHNOLOGICALLY ADVANCED COMPRESSOR AVAILABLE
- · ELECTPONIC CONTROLO MAINTAIN THE TEMPERATURE DELECTION WITHIN I OF
- · MULTI-GHANNEL AIRFLOW GYGTEM REMOVEG ODORG AND EXCEGG HUMIDITY
- · CONVERTIBLE TEMPERATURE CONTROLLED MEAT GAVORTM/PRODUCE DRAWER WITH PRECISION BALL-BEARING GLIDES
- · SEPAPATE TEMPERATURE CONTROL CAN BE SET FOR PRODUCE OR FRESH MEAT GTOPAGE
- · QUICH CHILL OPTION CHILLS FOODS AND BEYERAGES IN MINUTES
- · TWO MOISTURE ADJUSTABLE, SEE-THROUGH PRODUCE DRAWERS WITH FULL- EXTENSION PRECIGION BALL-BEARING GLIDES
- · FOUR ADJUSTABLE FULL-WIDTH TEMPERED GLASS SPILLPROOF SHELVES
- · TWO CONVENIENTLY LOCATED DELI DRAWERS WITH FULL-EXTENSION PRECISION BALL-BEARING GLIDEG
- · TWO IN-THE-DOOR GEALED DAIRY COMPARTMENTS WITH MACNETIC COVERS
- · FOUR ADJUSTABLE ALUMINUM DOOR BINS WITH TEMPERED GLASS FRONTS
- · TOP SHELF PROVIDES QUICK CHILL DOWN AREA
- · OTANDARD ACCEOGORIEG INCLUDE EGG BIN AND BUTTER TRAY WITH COVER
- · TOP MOUNTED AND FRONT YENTING GEALED PEFRIGERATION GYGTEM
- · DUAL MAGNET AND OPPING-AGGIGTED DOOP CLOGER MECHANIGM
- · POBUGT HEAVY-DUTY DOOP HINGEG
- · POWER INTERPUPTION OWITCH TO TURN OFF ALL POWER
- · AUTOMATIC ENERGY GAYING EXTERIOR MOIGTURE CONTROL GYGTEM
- · OPEN DOOR ALARM GOUNDS AND GLOWS TO WARN THAT DOOR HAS BEEN AJAR FOR THEEE MINUTES
- · ADJUGTABLE DOOR GTOPG GTANDARD 900, 1100 AND 1200 GWING
- · GABBATH MODE
- · TWO YEAR FULL WARRANTY COMPLETE UNIT: SIX YEAR FULL WARRANTY -SEALED SYSTEM; TWELVE YEAR LIMITED WARRANTY - SEALED SYSTEM; NINETY- DAY LIMITED - COGMETIC PARTO OUCH AO GLAGO, PAINTED ITEMO AND DECORATIVE ITEMO

*P=PIGHT HINGE; L=LEFT HINGE

YORB/DORB/DFRB ALL PEFPIGERATOR ELECTRICAL


- · 5 FT. CORD INCLUDED WITH UNIT
- · 2 WIPE WITH GROUND/3 PRONG PLUG
- · 1 15V/GOHZ: MAXIMUM AMPG 9.9

FINIOH DETAILS FOR YORB MODELS ONLY

- · OTAINLEOO OTEEL (OO), BLACK (BK), WHITE (WH), ALMOND (AL), BIOCUIT (BT), OTONE ARAY (OA), ARAPHITE ARAY (44), BUPAUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREST AREEN (F4), YIKINA BLUE (YB), COBALT BLUE (CB) AND EGAPLANT (EP)
- · FINIGH CODEG DEGICNATE DOOR FRONTS. ALL FINIGHEG HAVE STAINLEGG STEEL UPPER CRILLE, STAINLEGG STEEL SIDE TRIM, STAINLESS STEEL DOOR HANDLES WITH CHROME PLATED BRACKETS, AND BLACK LOWER HICKPLATE.
- · BEAGG TRIM OPTION (BR) FOR ANY FINIGH: INCLUDEG NAMEPLATE, DOOR HANDLE/BRACKETG, AND GIDE TRIM, SUPER DURABLE, LONG LASTING BRASS FINISH FOR "HIGH TRAFFIC" PARTS (HANDLE); ALL OTHER PARTS HAVE A DUPABLE PROTECTIVE COATING. ALL PARTO DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.

FINIOH DETAILS FOR DORES MODELS ONLY


- · OTAINLEGG OTEEL (GG), BLACK (BK), WHITE (WH), BIGCUIT (BT), OTONE GRAY (GG) AND GRAPHITE GRAY (GG)
- · DOOR PANELO MATCH DEGIGNATED FINIOH, STAINLEGG STEEL HANDLE
- · FINIGH CODEG DEGICNATE DOOR FRONTG. ALL FINIGHEG HAVE GTAINLEGG GTEEL FINIGHED UPPER GRILLE STAINLEGG STEEL FINIGHED SIDE TRIM, STAINLEGG STEEL HANDLEG AND BLACK LOWER KICKPLATE.
- · BRAGG TRIM OPTION (BR) HANDLE. GUPER DURABLE, LONG LAGTING BRAGG FINIGH. DEGIGNED FOR MAINTENANCE-FREE NORMAL USE.




PROFESSIONAL



DEGIGNER





FULL OVERLAY


BUILT-IN 36"W. ALL REFRIGERATOR


YORBIGA PROFESSIONAL DOOR VIPED 9 6 4 PROFESSIONAL INTEGRATED DOOR APPROX. SHIPPING WEIGHT LEGIFG) DDPB964 DEGIGNER DOOR DFPB964 FULL OVERLAY

APPROX. GHIPPING WEIGHT LEGIKG) 500 (225) 500 (225) APPROX. GHIPPING WEIGHT LEG(KG) 500 (225) APPROX. GHIPPING WEIGHT LEG(KG) 500 (225)

TOTAL CAPACITY: 22.8 CU. FT.


- · 84"H/24"D
- · PROCHILL™ TEMPERATURE MANAGEMENT GYGTEM
- · VARIABLE OPEED GINGLE COMPREGGOR GYGTEM INCLUDEG THE QUIETEGT, MOGT TECHNOLOGICALLY ADVANCED COMPRESSOR AVAILABLE
- · ELECTPONIC CONTPOLO MAINTAIN THE TEMPERATURE DELECTION WITHIN I OF
- · MULTI-CHANNEL AIRFLOW SYSTEM REMOVES ODORS AND EXCESS HUMIDITY
- · CONVERTIBLE TEMPERATURE CONTROLLED MEAT GAVORM/PRODUCE DRAWER WITH PRECIGION BALL-BEARING GLIDEG
- · GEPARATE TEMPERATURE CONTROL CAN BE GET FOR PRODUCE OR FREGH MEAT GTOPAGE
- · QUICK CHILL OPTION CHILLS FOODS AND BEVERAGES IN MINUTES
- · TWO MOISTURE ADJUSTABLE, SEE-THROUGH PRODUCE DRAWERS WITH FULL- EXTENSION PRECIGION BALL-BEARING GLIDEG
- · 91X ADJU9TABLE TEMPEPED GLAGG SPILLPROOF SHELVEG (4 HALF-WIDTH, 2 FULL-WIDTH)
- · TWO CONVENIENTLY LOCATED DELI DRAWERS WITH FULL-EXTENSION PRECISION BALL-BEARING GLIDEG
- · TWO IN-THE-DOOP GEALED DAIRY COMPARTMENTS WITH MAGNETIC COVERS
- · FIVE ADJUSTABLE ALUMINUM DOOR BINS WITH TEMPERED GLASS FRONTS (2 HALF-WIDTH; 7 FULL-WIDTH)
- · TOP SHELF PROVIDES QUICK CHILL DOWN AREA
- · STANDARD ACCESSORIES INCLUDE EAG BIN AND BUTTER TRAY WITH COVER
- · TOP MOUNTED AND FRONT VENTING SEALED REFRIGERATION SYSTEM
- · DUAL MAGNET AND SPRING-ASSISTED DOOR CLOSER MECHANISM
- · POBUST HEAVY-DUTY DOOP HINGES
- · POWER INTERPUPTION OWITCH TO TURN OFF ALL POWER
- · AUTOMATIC ENERGY GAVING EXTERIOR MOIGTURE CONTROL GYGTEM
- · OPEN DOOR ALARM GOUNDS AND GLOWS TO WARN THAT DOOR HAS BEEN AJAR FOR THREE MINUTES
- · ADJUSTABLE DOOR STOPS STANDARD 900, 1100 AND 1200 SWING
- · GABBATH MODE
- · TWO YEAR FULL WARRANTY GOMPLETE UNIT; GIX YEAR FULL WARRANTY GEALED SYSTEM; TWELVE YEAR LIMITED WARRANTY - SEALED SYSTEM; NINETY-DAY LIMITED -COGMETIC PARTS SUCH AS GLASS, PAINTED ITEMS AND DECORATIVE ITEMS





DEGIGNER

*P=PIGHT HINGE; L=LEFT HINGE



BUILT-IN 30"W. ALL FREEZER

 VOFB904 PROFESSIONAL DOOR
 APPROX. SHIPPING WEIGHT LB(KG)
 425(191.9)

 VIFB904 PROFESSIONAL INTEGRATED DOOR APPROX. SHIPPING WEIGHT LB(KG)
 425(191.9)

 DDFB904 DESIGNER DOOR
 APPROX. SHIPPING WEIGHT LB(KG)
 425(191.9)

APPROX. GHIPPING WEIGHT LEG(KG)

425(191.9)

TOTAL CAPACITY: 15.9 CU. FT.

DFFB304 FULL OVERLAY

- · 84"H./24"D.
- · PROCHILL™ TEMPERATURE MANAGEMENT GYGTEM
- · VARIABLE OPEED ONGLE COMPREGGOR GYGTEM INCLUDED THE QUIETEGT,
 MOGT TECHNOLOGICALLY ADVANCED COMPREGGOR AVAILABLE
- · ELECTPONIC CONTROLO MAINTAIN THE TEMPERATURE DELECTION WITHIN I OF
- · MULTI-CHANNEL AIRFLOW GYGTEM REMOVEG ODORG AND EXCEGG HUMIDITY
- · GIX ADJUGTABLE HALF-WIDTH WIPE GHELVEG
- · ONE FULL-WIDTH METAL GHELF
- · TWO FULL-WIDTH GLIDE-OUT WIRE BAGKETO WITH TEMPERED GLAGG FRONTS
- · FACTORY-INGTALLED AUTOMATIC ICE MAKER
- · ONE FULL-WIDTH ICE STOPAGE DRAWER WITH TWO SEPARATE METAL ICE BINS
- · FULL-EXTENGION PRECIGION BALL-BEARING GLIDEG ON ALL BAGKETG AND DRAWERG
- · THREE ADJUGTABLE ALUMINUM DOOR BING WITH TEMPERED GLAGG FRONTG
- · ADAPTIVE DEFPOST
- · ALL METAL FREEZER INTERIOR
- · TOP MOUNTED AND FRONT YENTING GEALED REFRIGERATION GYGTEM
- · DUAL MAGNET AND SPRING-ASSISTED DOOR GLOSER MECHANISM
- · POBUGT HEAVY-DUTY DOOP HINGEG
- · POWER INTERPUPTION OWITCH TO TURN OFF ALL POWER
- · AUTOMATIC ENERGY GAVING EXTERIOR MOIGTURE CONTROL GYGTEM
- · OPEN DOOR ALARM GOUNDS AND GLOWS TO WARN THAT DOOR HAS BEEN AJAR FOR THREE MINUTES
- · ADJUSTABLE DOOR STOPS STANDARD 900, 1100 AND 1200 SWING
- · GABBATH MODE
- · TWO YEAR FULL WARRANTY COMPLETE UNIT; GIX YEAR FULL WARRANTY GEALED GYGTEM; TWELVE YEAR LIMITED WARRANTY GEALED GYGTEM; NINETY-DAY LIMITED COGMETIC PARTO GUCH AG GLAGO, PAINTED ITEMO AND DECORATIVE ITEMO

*P=PIGHT HINGE; L=LEFT HINGE

YOFB/DDFB/DFFB ALL FREEZER

ELECTRICAL

- · 5 FT. COPD INCLUDED WITH UNIT
- · 2 WIPE WITH APOUND/9 PRONG PLUG
- · 1 154/60H2; MAXIMUM AMPG 9.9

WATER

· INLET WATER REQUIREMENTS - 4" COPPER TUBING

FINISH DETAILS FOR YORB MODELS ONLY

 \cdot OTAINLEOG OTEEL (GG), BLACK (BK), WHITE (WH), ALMOND (AL), BIGCUIT (BT), OTONE ARAY (GG), ARAPHITE

CRAY (GG), BURGUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREST GREEN (FG), VIKING BLUE (VB), COBALT

BLUE (CB) AND ECAPLANT (EP)


- · FINIOH CODEO DEOICNATE DOOR FRONTO. ALL FINIOHEO HAVE OTAINLEOO OTEEL UPPER APILLE, OTAINLEOO OTEEL OIDE TRIM, OTAINLEOO OTEEL DOOR HANDLEO WITH CHROME PLATED BRACKETO, AND BLACK LOWER FICKPLATE.
- · BRAGO TRIM OPTION (BP) FOR ANY FINIOH; INCLUDED NAMEPLATE, DOOR HANDLE/BRACKETO, AND GIDE TRIM.

 OUPER DURABLE, LONG LAGTING BRAGO FINIOH FOR "HIGH TRAFFIC" PARTO (HANDLE); ALL OTHER PARTO HAVE


 A DURABLE PROTECTIVE COATING. ALL PARTO DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.


FINIGH DETAILS FOR DORPS MODELS ONLY

- · OTAINLEOG OTEEL (GG), BLACK (BK), WHITE (WH), BIGCUIT (BT), OTONE CRAY (GC) AND CRAPHITE CRAY (GC)
- · DOOR PANELO MATCH DEGIGNATED FINIOH, GTAINLEGG GTEEL HANDLE
- · FINIGH CODEG DEGICNATE DOOR FRONTG. ALL FINIGHEG HAVE GTAINLEGG GTEEL FINIGHED UPPER CRILLE, GTAINLEGG GTEEL FINIGHED GIDE TRIM, GTAINLEGG GTEEL HANDLEG AND BLACK LOWER KICKPLATE.
- · BRAGG TRIM OPTION (BR) HANDLE. GUPER DURABLE, LONG LAGTING BRAGG FINIGH. DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.



PPOFEGGIONAL






FULL OVEPLAY

BUILT-IN 36"W. ALL FREEZER


YOFB 764 PROFESSIONAL DOOR VIFE 964 PROFESSIONAL NTECRATED DOOR APPROX. SHIPPING WEIGHT LEGIFG) DDFB964 DEGIGNER DOOR DFFB964 FULL OVERLAY

APPROX. GHIPPING WEIGHT LEG(KG) APPROX. SHIPPING WEIGHT LES(KG) APPROX. GHIPPING WEIGHT LEGIFG)


500 (225) 500 (225) 500 (225) 500 (225)



PROFESSIONAL



Wood/custom Materials



TOTAL CAPACITY: 19.1 CU. FT.

- · 84"H./24"D.
- · PROCHILL™ TEMPERATURE MANAGEMENT GYGTEM
- · VAPIABLE OPEED SINGLE COMPRESSOR SYSTEM INCLUDES THE QUIETEST, MOST TECHNOLOGICALLY ADVANCED COMPRESSOR AVAILABLE
- · ELECTRONIC CONTROLO MAINTAIN THE TEMPERATURE DELECTION WITHIN I OF
- · MULTI-CHANNEL AIRFLOW GYGTEM REMOVEG ODORG AND EXCEGG HUMIDITY
- · GIX ADJUGTABLE HALF-WIDTH WIPE GHELVEG
- · ONE FULL-WIDTH METAL SHELF
- · TWO FULL-WIDTH OLIDE-OUT WIRE BASKETS WITH TEMPERED GLASS FRONTS
- · FACTORY-INSTALLED AUTOMATIC ICE MAKER
- · ONE FULL-WIDTH ICE STORAGE DRAWER WITH TWO SEPARATE METAL ICE BINS
- · FULL-EXTENGION PRECIGION BALL-BEARING GLIDEG ON ALL BAGKETG AND DRAWERG
- · FIVE ADJUGTABLE ALUMINUM DOOR BING WITH TEMPERED GLAGG FRONTS
- · ADAPTIVE DEFPOST
- · ALL METAL FREEZER INTERIOR
- · TOP MOUNTED AND FRONT YENTING SEALED REFRIGERATION SYSTEM
- · DUAL MAGNET AND OPPING-AGGIOTED DOOP CLOGER MECHANIGM
- · POBUST HEAVY-DUTY DOOP HINGES
- · POWER INTERPUPTION SWITCH TO TURN OFF ALL POWER
- · AUTOMATIC ENERGY GAVING EXTERIOR MOIGTURE CONTROL GYGTEM
- · OPEN DOOR ALARM GOUNDS AND GLOWS TO WARN THAT DOOR HAS BEEN AJAR FOR THREE MINUTES
- · ADJUGTABLE DOOR STOPS STANDARD 900, 1100 AND 1200 SWING
- · GABBATH MODE
- · TWO YEAR FULL WARRANTY COMPLETE UNIT; OIX YEAR FULL WARRANTY -SEALED SYSTEM; TWELVE YEAR LIMITED WARRANTY - SEALED SYSTEM; NINETY- DAY LIMITED - COOMETIC PARTO GUCH AG GLAGO, PAINTED ITEMO AND DECORATIVE ITEMS

*P=PIGHT HINGE; L=LEFT HINGE

BUILT-IN REFRIGERATOR ACCESSORIES

GIDE PANEL AND TOP KITG

76" W.	BOTTOM-MOUNT
--------	--------------

POOPL9 PROFEGGIONAL SIDE PANEL LEFT	APPROX. GHIPPING WEIGHT LEG(KG)	45 (20.2)
POOPES PROFESSIONAL SIDE PANEL PIGHT	APPROX. GHIPPING WEIGHT LEG(KG)	45 (20.2)
DGGPL9 DEIGGNER GIDE PANEL LEFT	APPROX. GHIPPING WEIGHT LEG(KG)	45 (20.2)
DOOPED DEOIGNER OIDE PANEL RIGHT	APPROX. GHIPPING WEIGHT LEG(KG)	45 (20.2)

42" W. GIDE-BY-GIDE/48"W. GIDE-BY-GIDE/90" W \$ 96" W.

ALLPEFRIGERATORS/FREEZERS

ALLELI FIGURA I OPEN PLUZUPE		
PGGPL 2 PROFEGGIONAL GIDE PANEL LEFT	APPROX. GHIPPING WEIGHT LEG(KG)	45 (20.2)
POOPE 2 PROFEGGIONAL GIDE PANEL PIGHT	APPROX. GHIPPING WEIGHT LEG(FG)	45 (20.2)
DOOPL 2 DEIGGNER OIDE PANEL LEFT APPRO	PX. GHIPPING WEIGHT LEO(FG) 45 (2)	0.2)
DGGPR 2 DEGIGNER GIDE PANEL RIGHT	APPROX. GHIPPING WEIGHT LEG(KG)	45 (20.2)

TOP PANEL HITS

TOP-90 90"W.	APPROX. SHIPPING WEIGHT LEG(FG)	21 (9.5)
TOP-96 96"W.	APPROX. SHIPPING WEIGHT LEG(KG)	22(10.0)
TOP-42 42"W.	APPROX. GHIPPING WEIGHT LED(KG)	29 (10.4)
TOP-48 48"W.	APPROX. GHIPPING WEIGHT LEG(KG)	24 (10.8)


· STAINLESS STEEL

- · PROVIDEG FINIGHED "FREEGTANDING" LOOK
- · UNIT MUST STILL BE SECUPED TO WALL

HANDLE FITS

PHR-DFBB-66 PROFESSIONAL STAINLESS STEEL HANDLE FIT	APPROX. GHIPPING WEIGHT LB(RG)	10(4.5)
PHK-DFBB-BR PROFEGGIONAL BRAGG HANDLE KIT	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)
PHK-DFGB-GG PROFEGGIONAL GTAINLEGG GTEEL HANDLE KIT	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)
PHK-DFGB-BR PROFEGGIONAL BRAGG HANDLE KIT	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)
HKFD6-66 PROFE66IONAL STAINLEGG STEEL HANDLE KIT	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)
HKFDG-BR PROFEGGIONAL BRAGG HANDLE KIT	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)
PHK 2 6-66 PROFEGGIONAL STAINLEGG STEEL HANDLE KIT	APPROX. GHIPPING WEIGHT LEG(KG)	7 (9.2)
PHK 26-BP PROFEGGIONAL BRAGG HANDLE KIT	APPROX. GHIPPING WEIGHT LEG(KG)	7 (9.2)
DHY 26-66 DEGIGNER GTAINLEGG GTEEL HANDLE KI	APPROX. GHIPPING WEIGHT LEG(KG)	7 (9.2)
DHK 26-BP DEGIGNER BRAGG HANDLE KIT	APPROX. GHIPPING WEIGHT LEG(KG)	フ (カ.2)


- · FOR USE WITH FULL OVERLAY REFRIGERATORS/FREEZERS
- · FOR USE ON LOCALLY SUPPLIED FULL OVERLAY PANELS
- · ALLOWS PEFPIGEPATOR/FPEEZERS WITH FULL OVERLAY PANEL TO COOPDINATE WITH OTHER PROFESSIONAL AND DESIGNER PRODUCTS
- · PHYDFBB/HYFDG FOR DFBB (TWO HANDLEG)
- · PHYDFOB/HYFDO FOR DFOB (TWO HANDLEG)
- · BOTTOM-MOUNT PEFPIGEPATOP/FPEEZEPS ACCEPT PHYOFBB AND HYFDS HANDLE KITS
- · OIDE-BY-OIDE PEFPIGEPATOR/FREEZERO ACCEPT PHYDFOB AND HYFDO HANDLE YITO
- $\cdot \text{ALL PEFPIGEPATOP6/ALL FPEEZEP6 ACCEPT PHF 2 G/DHF 2 5 (ONE HANDLE) OPPHFDF6/B/HFFD6 (TWO HANDLE) FIT6 }$



TOP GRILLE FITS / CENTER TRIM FITS

APPROX. GHIPPING WEIGHT LEO(KG)	25(11.7)
APPROX. GHIPPING WEIGHT LEG(KG)	25(11.7)
APPROX. GHIPPING WEIGHT LEO(KG)	21 (9.5)
APPROX. GHIPPING WEIGHT LEG(KG)	29 (10.4)
APPROX. GHIPPING WEIGHT LEG(KG)	25(11.7)
APPROX. GHIPPING WEIGHT LEO(KG)	21 (9.5)
APPROX. GHIPPING WEIGHT LEG(KG)	29 (10.4)
APPROX. GHIPPING WEIGHT LEG(KG)	25(11.9)
APPROX. GHIPPING WEIGHT LEO(KG)	21 (9.5)
APPROX. GHIPPING WEIGHT LEG(KG)	29 (10.4)
APPROX. GHIPPING WEIGHT LEO(KG)	25(11.7)
APPROX. GHIPPING WEIGHT LES(KG)	与(2. ク)
	APPEOX. GHIPPING WEIGHT LE(FG)

- · FOR USE WITH INSTALLATION OF TWO REFRIGERATORS AND/OR FREEZERS
- · CREATES A "SINGLE UNIT" LOOK
- $\cdot \text{ CRILLE FITG INGLUDE FULL-LENGTH UPPER GRILLE, CENTER CABINET TRIM CONNECTOR, AND ALL INSTALLATION HARDWARE$
- · CENTER TRIM HIT INCLUDES CENTER CABINET TRIM CONNECTOR TO INSTALL TWO FULL OVERLAY WITH WOOD TOP CRILLE
- · PERTAK FOR TWO YOBE UNITS
- · DEPTAK FOR TWO DOBES OF DEBES UNITS
- · PGK FOR TWO VCPB/VCFB UNITS
- · DAK FOR TWO DDRB/DDFB/DFRB/DFFB UNITS
- · FTCK FOR TWO DFBB/DFRB/DFFB UNITS



PEPLACEMENT WATER FILTER

PWF-DIGP APPROX. GHIPPING WEIGHT LEG(KG) 5 (2.9)

- · PEPLACEO WATER FILTER CARTRIDAEO OUPPLIED WITH OIDE-BY-OIDE REFRIAERATORO WITH ICE AND WATER DIOPENOERO
- · PEDUCES SEDIMENT, TASTE, AND ODOP
- · PEDUCEO CYOTO, PARTICULATEO, TURBIDITY, LEAD, CHLORINE, ATRAZINE AND LINDANE
- · NOF CEPTIFIED
- PEADY TO INSTALL NO ASSEMBLY PEQUIPED

SIDE PANEL HAPDWAPE FIT

OPHKOO APPROX. OHIPPING WEIGHT LEG(KG) 9 (1.4)

- · FOR USE WITH DESIGNER BUILT-IN PEFFIGERATOR/FREEZERS
- · ALLOWS INSTALLATION OF CUSTOM SIDE PANELS
- · FIT CONTAINS BEACKETS, SCREWS AND INSTALLATION INSTRUCTIONS TO MOUNT PANELS ON LEFT AND PIGHT SIDE

FREESTANDING 36"W. BOTTOM-MOUNT REFRIGERATOR/FREEZERS

TOTAL CAPACITY: 19.9 CU. FT PEFPIGEPATOP CAPACITY: 14.4 CU. FT FPEEZEP CAPACITY: 5.5 CU. FT.

VOBFO 96 (P/L) PROFESSIONAL DOORAPPROX. SHIPPING WEIGHT LES(FG)DDBFO 96 (P/L) DESIGNER DOORAPPROX. SHIPPING WEIGHT LES(FG)

- · CABINET DEPTH DEGIGN (2 4 IN. DEEP GIDE PANELG) INTEGRATEG WITH GUPPOUNDING CABINETPY
- · ELECTPONIC TEMPERATURE CONTROL WITH TEMPERATURE READOUT

 MAINTAINS THE SELECTED TEMPERATURE IN BOTH THE REPRISERATOR AND FREEZ
 ER COMPARMENTS
- · FROOT-FREE REFRIGERATOR
- · FOUR SLIDE-OUT ADJUSTABLE TEMPERED GLASS SPILLPROOF SHELVES; ONE STATIONARY GLASS SHELF
- TEMPERATURE ADJUSTABLE MEAT SAVORTM/PRODUCE DRAWER CAN BE SET FOR EITHER PRODUCE OR LONG-TERM FRESH MEAT STORAGE WITH ITS SEPARATE TEMPERATURE CONTROL
- · TWO MOISTURE-ADJUSTABLE, SEE-THROUGH PRODUCE DRAWERS
- · IN-THE-DOOR DAIRY COMPARTMENT WITH COVER
- · FOUR DOOR BING (THREE HALF-WIDTH, ONE FULL-WIDTH)
- · INTERNAL FILTERED WATER DISPENSING
- · PREMIUM WATER FILTER PROVIDES CLEANER WATER SUPPLY BY FILTERING BAD TASTES, ODORS, SEDIMENT AND HARMFUL CONTAMINANTS
- · STANDARD ACCESSORIES INCLUDE EGG BIN AND BUTTER TRAY WITH LID
- · FROST-FREE FREEZER
- · ADAPTIVE DEFPOST
- · FACTORY INSTALLED AUTOMATIC ICE MAKER
- · MAX ICE FEATURE
- · TWO SLIDE-OUT BASKETS
- · DOOR OPEN ALARM GOUNDS TO WARN THAT DOOR HAS BEEN AJAR FOR FIVE MINUTES
- · ENERGY STAR QUALIFIED
- · TWO-YEAR FULL WARRANTY- COMPLETE UNIT; GIX-YEAR FULL WARRANTY GEALED GYGTEM AND ICEMAKERG; TWELVE-YEAR LIMITED - GEALED GYGTEM

YCBF/DDBF PEFPIGEPATOP/FPEEZEPS


- · 5 1/2 FOOT CORD INCLUDED WITH UNIT
- · 9 WIFE WITH APOUND/9 PRONG PLUG
- · 1 154/60H2; MAXIMUM 7.9 AMPS

WATER

· INLET WATER REQUIREMENTS - 1/4 IN. COPPER TUBING


FINIOH DETAILS

· STAINLESS STEEL (SS) DOOR FRONT WITH BLACK CABINET



327 (148.7)

927 (148.7)



FREESTANDING 36"W. FRENCH DOOR BOTTOM-MOUNT REFRIGERATOR/FREEZERS

TOTAL CAPACITY: 19.6 CU. FT PEFFICEPATOP CAPACITY: 14.1 CU. FT FPEEZEP CAPACITY: 5.5 CU. FT.

YCFF096 PROFESSIONAL DOOR DDFF096 DESIGNER DOOR APPROX. GHIPPING WEIGHT LEG(FG)
APPROX. GHIPPING WEIGHT LEG(FG)

927 (148.7) 927 (148.7)

- · CABINET DEPTH" DEGIGN (2 4" DEEP GIDE PANELG) INTEGRATEG WITH GURROUNDING CABINETRY
- · ELECTPONIC TEMPERATURE CONTROL WITH TEMPERATURE READOUT MAINTAINS THE SELECTED TEMPERATURE IN BOTH THE REPRICERATOR AND FREEZER COMPARMENTS
- · FROST-FREE PEFRIGERATOR
- · FOUR GLIDE-OUT ADJUGTABLE TEMPERED GLAGG GPILLPROOF GHELVEG; ONE GTATIONARY GLAGG GHELF
- · TEMPERATURE ADJUGTABLE MEAT GAYORM/PRODUCE DRAWER CAN BE GET FOR EITHER PRODUCE OR LONG-TERM FREGH MEAT GTORAGE WITH ITG GEPA-RATE
- · TEMPERATURE CONTROL
- · TWO MOIGTURE-ADJUGTABLE, GEE-THROUGH PRODUCE DRAWERS
- · IN-THE-DOOP DAIRY COMPARMENT WITH COVER
- · FIVE DOOP BING; TWO FOR GALLON STORAGE
- · INTERNAL FILTERED WATER DIOPENOING
- · PREMIUM WATER FILTER PROVIDES CLEANER WATER SUPPLY BY FILTERING BAD TASTES, ODORS, SEDIMENT AND HARMFUL CONTAMINANTS
- · GTANDARD ACCEGGORIEG INCLUDE EGG BIN AND BUTTER TRAY WITH LID
- · FROGT-FREE FREEZER
- · ADAPTIVE DEFPOST
- · FACTORY INSTALLED AUTOMATIC ICE MAKER
- · MAX ICE FEATURE
- · TWO GLIDE-OUT BAGKETS
- · DOOR OPEN ALARM GOUNDS TO WARN THAT DOOR HAS BEEN AJAR FOR FIVE MINUTES
- · ENERGY STAR QUALIFIED
- · TWO-YEAR FULL WARRANTY COMPLETE UNIT; GIX-YEAR FULL WARRANTY GEALED GYGTEM AND ICEMAKERG; TWELVE-YEAR LIMITED GEALED GYGTEM



ELECTPICAL


- · 5½ FOOT COPD INCLUDED WITH UNIT
- · 9 WIRE WITH AROUND/9 PRONG PLUG
- · 1 154/60H2; MAXIMUM 7.9 AMPS

WATER


· INLET WATER REQUIREMENTS - 1/4 IN. COPPER TUBING

FINIOH DETAILS

· STAINLESS STEEL (SS) DOOP FRONT WITH BLACK CABINET



PP-OFEGGIONAL



DEGIGNER

FREESTANDING 36"W. SIDE-BY-SIDE REFRIGERATOR/FREEZERS


TOTAL CAPACITY: 21.5 CU. FT PEFPIGERATOR CAPACITY: 19.5 CU. FT FREEZER CAPACITY: 6.0 CU. FT.

VCOFO 9 G PROFESSIONAL DOOR APPROX. SHIPPING WEIGHT LB(FG) 9 (4 (141.9) DDOFO 9 G DESIGNER DOOR APPROX. SHIPPING WEIGHT LB(FG) 9 (4 (141.9)

- · CABINET DEPTH DEGIGN (2 4" DEEP GIDE PANELG) INTEGRATEG WITH GURROUNDING CABINETRY
- · ELECTPONIC TEMPERATURE CONTROL WITH TEMPERATURE READOUT MAINTAINS
 THE SELECTED TEMPERATURE IN BOTH THE REFRIGERATOR AND FREEZER
 COMPARMENTS
- · FROST-FREE REFRIZERATOR
- · FOUR TEMPERED GLAGG GPILLPROOF GHELVEG
- · TEMPERATURE ADJUGTABLE MEAT GAYORTM/PRODUCE DRAWER CAN BE GET FOR EITHER PRODUCE OR LONG-TERM FREGH MEAT GTORAGE WITH ITG GEPARATE TEMPERATURE CONTROL
- · TWO MOISTURE-ADJUSTABLE, SEE-THROUGH PRODUCE DRAWERS
- · IN-THE-DOOR DAIRY COMPARTMENT WITH COVER
- · FIVE DOOR BING; THREE FOR GALLON STORAGE
- · GEPARATE ADJUGTABLE TEMPERATURE CONTROL FOR DOOR BIN AREA
- · STANDARD ACCESSORIES INCLUDE EGG BIN AND BUTTER TRAY WITH LID
- · FROGT-FREE FREEZER
 - · ADAPTIVE DEFPOST
 - · FACTORY INSTALLED AUTOMATIC ICE MAKER
 - · MAX ICE FEATURE
 - TWO WIPE SHELVES AND TWO SLIDE-OUT BASKETS
 - · FIVE DOORS BING; THREE TILT OUTWARD FOR EASY ACCESS
- · DOOR OPEN ALARM GOUNDS TO WARN THAT DOOR HAS BEEN AJAR FOR FIVE MINUTES
- · ENERGY STAR QUALIFIED
- · TWO-YEAR FULL WARRANTY COMPLETE UNIT; GIX-YEAR FULL WARRANTY GEALED GYGTEM AND ICEMAKERG; TWELVE-YEAR LIMITED GEALED GYGTEM



PROFEGGIONAL



DEGIGNER

YCGF/DDGF PEFPIGEPATOP/FPEEZEPG

ELECTPICAL

- · 5 1/2 FOOT CORD INCLUDED WITH UNIT
- · 9 WIFE WITH GROUND/9 PRONG PLUG
- · 1 154/60HZ; MAXIMUM 7.8 AMPG

WATER

· INLET WATER REQUIREMENTS - 14 IN. COPPER TUBING

FINIGH DETAILS

· STAINLESS STEEL (SS) DOOR FRONT WITH BLACK CABINET

FREESTANDING 36"W. SIDE-BY-SIDE

REFRIGERATOR/FREEZERS WITH ICE AND WATER DISPENSERS

TOTAL CAPACITY: 21.00 CU. FT PEFPIGEPATOR CAPACITY: 19.5 CU. FT FPEEZEP CAPACITY: 8.1 CU. FT.

 VC6F0 96D PEOFEGGIONAL DOOP
 APPROX. GHIPPING WEIGHT LB(FG)
 9 1 4 (1 4 1.9)

 DD6F0 96D DEGIGNER DOOP
 APPROX. GHIPPING WEIGHT LB(FG)
 9 1 4 (1 4 1.9)

- · CABINET DEPTH DEGICN (2 4 IN. DEEP GIDE PANELG) INTECRATEG WITH GUPPOUNDING CABINETRY
- · ELECTPONIC TEMPERATURE CONTROL WITH TEMPERATURE READOUT
 MAINTAINO THE SELECTED TEMPERATURE IN BOTH THE REFRIGERATOR AND
 FREEZER COMPARMENTO
- · FROGT-FREE REFRIGERATOR
 - · FOUR TEMPERED GLAGG SPILLPROOF SHELVES
 - TEMPERATURE ADJUGTABLE MEAT GAYORM/PRODUCE DRAWER CAN BE GET FOR EITHER PRODUCE OR LONG-TERM FREGH MEAT GTORAGE WITH ITG GEPARATE TEMPERATURE CONTROL
 - · TWO MOISTURE-ADJUSTABLE, SEE-THROUGH PRODUCE DRAWERS
 - · IN-THE-DOOR DAIRY COMPARMENT WITH COVER
 - · FOUR DOOR BING; THREE FOR GALLON STORAGE
 - · GEPARATE ADJUGTABLE TEMPERATURE CONTROL FOR DOOR BIN AREA
 - · GTANDAPD ACCEGGOPIEG INCLUDE EGG BIN AND BUTTER TRAY WITH LID
- · FROST-FREE FREEZER
 - · ADAPTIVE DEFPOST
 - · FACTORY INSTALLED AUTOMATIC ICE MAKER
 - · MAX ICE FEATURE
 - · TWO WIPE GHELVEG AND TWO GLIDE-OUT BAGKETS
 - · FOUR DOORS BINS; TWO TILT OUTWARD FOR EASY ACCESS ICE/WATER DISPENSER
 - · THROUGH-THE-DOOR DIGPENGER PROVIDEG CUBED ICE, CRUGHED ICE AND WATER IN EAGY ONE-HAND OPERATION
 - · PREMIUM WATER FILTER PROVIDES CLEANER WATER AND ICE SUPPLY BY FILTERING BAD TASTES, ODORS, SEDIMENT AND HARMFUL CONTAMINANTS
- · DOOP OPEN ALARM GOUNDS TO WARN THAT DOOP HAS BEEN AJAR FOR FIVE MINUTES
- · ENERAY STAR QUALIFIED
- · TWO-YEAR FULL WARRANTY COMPLETE UNIT; GIX-YEAR FULL WARRANTY GEALED GYGTEM AND ICEMAKERG; TWELVE-YEAR LIMITED GEALED GYGTEM



ELECTPICAL


- · 5 1/2 FOOT CORD INCLUDED WITH UNIT
- · 9 WIPE WITH GROUND/9 PRONG PLUG
- · 1 154/60H2; MAXIMUM 9.4 AMPG

WATER


· INLET WATER REQUIREMENTS - 1/4 IN. COPPER TUBING

FINIOH DETAILS

· STAINLESS STEEL (SS) DOOP FRONT WITH BLACK CABINET;



PROFEGGIONAL



DEGIGNER

FREESTANDING REFRIGERATOR ACCESSORIES

PEPLACEMENT WATER FILTER

PWF-FP APPROX. SHIPPING WEIGHT LB(KG) 5 (2.3)



- · PEDUCES SEDIMENT, BAD TASTE, AND ODOR
- · PEDUCEO CYOTO, PARTICULATEO, TURBIDITY, LEAD, CHLORINE, ATRAZINE AND LINDANE
- · NOF CERTIFIED
- · PEADY TO INSTALL NO ASSEMBLY PEQUIPED

BRAGO HANDLE KITG

PFRHKBBR (PROFEGGIONAL BOTTOM-MOUNT)	APPROX. GHIPPING WEIGHT LEG(FG)	10(4.5)
PFRHKFBR (PROFEGGIONAL FRENCH DOOR)	APPROX. GHIPPING WEIGHT LEG(KG)	15 (6.8)
PFRHKGBR (PROFEGGIONAL GIDE-BY-GIDE)	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)
DFPHKBP (DEGIGNER BOTTOM-MOUNT/GIDE-BY-GIDE	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)
DFPHKFBP (DEGIGNER FRENCH DOOR)	APPROX. GHIPPING WEIGHT LEG(KG)	15 (6.8)

- · PEPLACES HANDLES SUPPLIED WITH UNIT FOR BRASS TRIM
- · BOTTOM-MOUNT AND GIDE-BY-GIDE KITG INCLUDE TWO HANDLEG; FRENCH DOOR KITG INCLUDE THREE HANDLEG

SIDE TRIM AND TOP GRILLE FITS FOR BUILT-IN LOOK

- · STAINLESS STEEL FINISH
- · USE OF BOTH SIDE TRIM AND TOP GRILLE HIT PROVIDES BUILT-IN LOOK

KITS TO ORDER FOR PROFESSIONAL PIGHT HINGED BOTTOM-MOUNT

FROTKRE (OIDE TRIM KIT)	APPROX. GHIPPING WEIGHT LEO(KG)	1 カ (ち.9)
PFRAKRED (ARILLE KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)

KITO TO OPDER FOR PROFESSIONAL LEFT HINGED BOTTOM-MOUNT

FROTKLES (OIDE TRIM KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	1 カ (ち.9)
PFRAKLED (ARILLE KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)

KITS TO OPDER FOR PROFESSIONAL FRENCH DOOR BOTTOM-MOUNT

FROTKF (OIDE TRIM KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	19 (5.9)
PFRAKFO (ARILLE KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)

KITO TO OPDER FOR PROFESSIONAL SIDE-BY-SIDE

FROTKO (OIDE TRIM KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	1 カ (ち.9)
PFRAKFO (ARILLE KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)

KITS TO OPDER FOR DESIGNER PIGHT HINGED BOTTOM-MOUNT

FROTKRE (OIDE TRIM KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	1 ク (ち.9)
DFRAKRES (ARILLE KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)

KITG TO OPDER FOR DEGIGNER LEFT HINGED BOTTOM-MOUNT

FROTELB (OIDE TRIM KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	19(5.9)
DFRAKLES (ARILLE KIT)	APPROX. GHIPPING WEIGHT LEG(FG)	10(4.5)

KITS TO OPDER FOR DESIGNER FRENCH DOOR BOTTOM-MOUNT

FROTKF (OIDE TRIM KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	19(5.9)
DFRAKFG (ARILLE KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)

KITS TO OPDER FOR DESIGNER SIDE-BY-SIDE

FEB (FB (BIDE FIM FIL)	APPROX. GHIPPING WEIGHT LIBITED	(ク(ラ.9)
DFRAKFG (ARILLE KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)



- · OTAINLEGO OTEEL FINIOH
- · USE OF ALL THREE KITS PROVIDES WRAPPED LOOK
- · GIDE PANEL FITG INCLUDE PANELS FOR BOTH SIDES

HITS TO OPDER FOR PROFESSIONAL RIGHT HINGED BOTTOM-MOUNT

PFRAKRED (ARILLE KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)
FROPKRE (OIDE PANEL KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	60 (27.0)
FRTOP (TOP KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	19 (8.6)

HITO TO OPDER FOR PROFESSIONAL LEFT HINGED BOTTOM-MOUNT

PFRAKLES (ARILLE KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)
FROPKLIS (SIDE PANEL KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	60 (27.0)
FRTOP (TOP KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	19(8.6)

HITS TO OPDER FOR PROFESSIONAL FRENCH DOOR BOTTOM-MOUNT

PFRAKFG (ARILLE KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)
FROPKF (OIDE PANEL KIT)	APPROX. GHIPPING WEIGHT LES(KG)	60 (27.0)
FRTOP (TOP KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	19(8.6)

KITS TO OPDER FOR PROFESSIONAL SIDE-BY-SIDE

PFRAKFG (ARILLE KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)
FROPKO (OIDE PANEL KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	60 (27.0)
FRTOP (TOP KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	19 (8.6)

KITO TO OPDER FOR DEGIGNER PIGHT HINGED BOTTOM-MOUNT

DFRAKRB (ARILLE KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)
FROPKRB (OIDE PANEL KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	60 (27.0)
FRTOP (TOP KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	19 (8.6)

KITS TO OPDER FOR DESIGNER LEFT HINGED BOTTOM-MOUNT

DFP-GKLPS (GP-ILLE KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)
FROPKLES (OIDE PANEL KIT)	APPROX. GHIPPING WEIGHT LEG(FG)	60 (27.0)
FRTOP (TOP KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	19 (8.6)

KITS TO OPDER FOR DESIGNER FRENCH DOOR BOTTOM-MOUNT

DFRAKFG (ARILLE KIT)	APPROX. SHIPPING WEIGHT LEG(KG)	10(4.5)
FROPKF (OIDE PANEL KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	60 (27.0)
FRTOP (TOP KIT)	APPROX. SHIPPING WEIGHT LEG(FG)	19(8.6)

KITS TO OPDER FOR DESIGNER SIDE-BY-SIDE

DFP-GKFG (GPILLE KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)
FROPKO (OIDE PANEL KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	60 (27.0)
FRTOP (TOP KIT)	APPROX. GHIPPING WEIGHT LEG(KG)	19 (8.6)

BUILT-IN 30"W. FULL HEIGHT WINE CELLARS


VCWB900 (P/L*) - PROFEGGIONAL CLEAR CLAGG DOOR
VCWB900F (P/L*) - PROFEGGIONAL FLUTED CLAGG DOOR
DDWB900 (P/L*) - DEGICNER CLEAR CLAGG DOOR
DDWB900F (P/L*) - DEGICNER FLUTED CLAGG DOOR
DFWB900 (P/L*) - FULL OVERLAY CLEAR CLAGG DOOR
DFWB900F (P/L*) - FULL OVERLAY FLUTED CLAGG DOOR


APPEOX. GHIPPING WEIGHT LEG(FG)

4) 575 (261.0) 4) 575 (261.0) 4) 575 (261.0) 4) 575 (261.0) 4) 575 (261.0) 4) 575 (261.0)

- · クロ"W. X 84"H. X 24"D.
- · EXCLUSIVE TRITEMPTM STORAGE SYSTEM
- · THREE INDEPENDENT TEMPERATURE 20NEO
- · GETTINGO ARE ADJUGTABLE IN EACH 20NE FROM 490F (6.106) TO GOOF (18.906)
- · ELECTPONIC CONTROL CENTER MAINTAINS SET TEMPERATURE WITHIN 1.50F
- · EXCLUSIVE GLASS CONTROL PAD
- · ACCOMMODATES UP TO 150 FULL-SIZE BOTTLES
- · YERGATILE GHELYING GYGTEM GTOREG GTANDARD, MAGNUM, AND HALF-GIZE BOTTLEG
- · TWO CONVERTIBLE WINE OHELVES ADJUST TO ALLOW FOR BOTTLE DISPLAY
- · GOLID MAPLE WOOD FACINGS MAY BE FINISHED TO COOPDINATE WITH SUPPOUNDING CABINETRY
- · COATED WINE SHELVES PEDUCE VIBRATION AND HOLD BOTTLES IN PLACE
- · SHELVES ARE FULLY REMOVABLE FOR EASY CLEANING
- · ULTPAVIOLET PEGIGTANT TEMPEPED GLAGG
- · POLACK INTERIOR
- · LOW INTENDITY LIGHTING
- · LOWER ZONE WITH PAISED WOOD FACINGS
- · HIGH TEMPERATURE ALARM
- · DOOR OPEN ALARM
- · HOME SECURITY SYSTEM CONNECTION
- · DUAL MAGNET AND OPPING AGGIGT DOOP CLOGUPE MECHANIGM
- · KEYED DOOP LOCK
- · DOOR STOP POSITIONS OF 900, 1100 AND 1200
- · POWER INTERPUPTION OWITCH
- · TOP MOUNTED AND FRONT VENTING GEALED REFRIGERATION GYGTEM
- · PEMOVABLE LOWER FICKPLATE
- · TWO YEAR FULL WARRANTY COMPLETE UNIT; GIX YEAR FULL WARRANTY GEALED GYGTEM; TWELVE YEAR LIMITED WARRANTY GEALED GYGTEM

*P=PIGHT HINGE; L=LEFT HINGE






PROFESSIONAL

DEGIGNER

Wood/custom Materials



FULL OVERLAY

YOWB/DDWB/DFWB WINE CELLARG

ELECTPICAL

- · 5 FT. CORD INCLUDED WITH UNIT
- · 2 WIFE WITH GROUND/ OPPONG PLUG
- · 1 15 Y/60 HZ; MAXIMUM AMPG 2.0

FINIOH DETAILS YOWB

- · CLEAP AND FLUTED CLAGG DOOPG AVAILABLE IN GTAINLEGG STEEL (GG) - GTAINLEGG GTEEL FRAME AROUND LARGE WINDOW DOOP,
- STAINLESS STEEL DOOF HANDLE WITH CHROME PLATED BRACKETS.
- · BPAGG TPIM OPTION (BP) INCLUDEG NAMEPLATE AND DOOP HANDLE/BPACKETG. GUPEP DUPABLE, LONG LAGTING BPAGG FINIGH FOR "HIGH TPAFFIC" PAPTG (HANDLE); ALL OTHER PAPTG HAVE A DUPABLE PROTECTIVE COATING. ALL PAPTG DEGICNED FOR MAINTENANCE-FREE NORMAL UGE.

FINIOH DETAILS DOWS

- · CLEAR AND FLUTED GLAGO DOORG AVAILABLE IN STAINLEGG STEEL (GG)-GTAINLEGG STEEL FRAME AROUND LARGE WIN-DOW DOOR, STAINLEGG STEEL DOOR HANDLE.
- · BPAGG TRIM OPTION (BP) INCLUDEG DOOP HANDLEG. SUPER DUPABLE, LONG LAGTING BPAGG FINIGH. ALL PARTG DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.

FINISH DETAILS DEWE

· DFWB ACCEPTS 3" THICK CUSTOM PANEL - NO VISIBLE TRIM

FULL HEIGHT WINE CELLAR ACCESSORIES

GIDE PANEL AND TOP HITG

POOPL 2 PROFEOGIONAL GIDE PANEL LEFT APPROX. GHIPPING WEIGHT LB(KG) 45 (20.2)
POOPL 2 PROFEOGIONAL GIDE PANEL PIGHT APPROX. GHIPPING WEIGHT LB(KG) 45 (20.2)
DOOPL 2 DEGIGNER GIDE PANEL LEFT APPROX. GHIPPING WEIGHT LB(KG) 45 (20.2)
DOOPR 2 DEGIGNER GIDE PANEL PIGHT APPROX. GHIPPING WEIGHT LB(KG) 45 (20.2)

TOP PANEL KITS

TOP-90 TOP PANEL - 90"W.


APPROX. GHIPPING WEIGHT LEG(FG) 21 (9.5)

- · STAINLESS STEEL
- · PROVIDEG FINIGHED "FREEGTANDING" LOOK
- · UNIT MUST STILL BE SECUPED TO WALL

HANDLE KITS

PHF 2 σ - σ 0 PPOFE σ 0 ONAL σ T AINLE σ 0 OTEEL HANDLE FIT APPROX. σ 1 HIPPING WEIGHT LE(FG) 7 (9.2) PHF 2 σ - σ 0 DE σ 1 DE σ 1 DE σ 2 OTEEL HANDLE FIT APPROX. σ 1 HIPPING WEIGHT LE(FG) 7 (9.2) DHF 2 σ - σ 0 DE σ 1 DE σ 2 OTEEL HANDLE FIT APPROX. σ 1 HIPPING WEIGHT LE(FG) 7 (9.2) DHF 2 σ - σ 1 DE σ 2 DE σ 3 DE σ 4 DE σ 4 DE σ 4 ANDLE FIT APPROX. σ 4 DE σ 5 DE σ 6 DE σ 6 DE σ 6 DE σ 6 DE σ 7 (9.2) APPROX. σ 6 HIPPING WEIGHT LE(FG) 7 (9.2)

- · FOR USE WITH FULL OVERLAY DEWIS WINE SELLARS
- · FOR USE ON LOCALLY SUPPLIED FULL OVERLAY PANELS
- · INCLUDES HANDLE AND OTHER INSTALLATION HARDWARE
- · ALLOWO DEWE WITH FULL OVERLAY PANEL TO COOPDINATE WITH OTHER PROFESSIONAL & DESIGNER PRODUCTS



UNDERCOUNTER/FREESTANDING 15"W. REFRIGERATED BEVERAGE CENTERS

YUAR I 500 (P/L*) - PROFEGGIONAL GOLID DOOR
DUAR I 500 (P/L*) - DEGIGNER GOLID DOOR
YUAR I 50 (REVERGIBLE) - PROFEGGIONAL CLEAR GLAGG DOOR
YUAR I 50 (REVERGIBLE) - PROFEGGIONAL FLUTED GLAGG DOOR
YUAR I 5 (REVERGIBLE) - PROFEGGIONAL FLUTED GLAGG DOOR
YUAR I 5 (REVERGIBLE) - PROFEGGIONAL FLUTED GLAGG DOOR
DUAR I 50 (REVERGIBLE) - DEGIGNER CLEAR GLAGG DOOR
DUAR I 50 (REVERGIBLE) - DEGIGNER CLEAR GLAGG DOOR
DUAR I 50 (REVERGIBLE) - DEGIGNER CLEAR GLAGG DOOR
DUAR I 5 (REVERGIBLE) - DEGIGNER CLEAR GLAGG DOOR
DUAR I 5 (REVERGIBLE) - DEGIGNER CLEAR GLAGG DOOR
DUAR I 5 (REVERGIBLE) - DEGIGNER CLEAR GLAGG DOOR
DUAR I 5 (REVERGIBLE) - DEGIGNER FLUTED GLAGG DOOR
DFUR I 50 (P/L*) - FULL OYERLAY CLEAR GLAGG
DFUR I 5 (P/L*) - FULL OYERLAY CLEAR GLAGG
DFUR I 5 (P/L*) - FULL OYERLAY CLEAR GLAGG

APPROX. GHIPPING WEIGHT LEG(KG) 110(49.5) 110(49.5) APPROX. GHIPPING WEIGHT LEG(KG) 110(49.5) APPROX. GHIPPING WEIGHT LEG(KG) APPROX. GHIPPING WEIGHT LEG(KG) 110(49.5) APPROX. GHIPPING WEIGHT LEGIFG) APPROX. GHIPPING WEIGHT LEGIKG) 110(49.5) APPROX. GHIPPING WEIGHT LEGIFG) 110(49.5) APPROX. GHIPPING WEIGHT LEG(KG) 110(49.5) APPROX. GHIPPING WEIGHT LEGIKG) 110(49.5) APPROX. GHIPPING WEIGHT LEG(KG) 110(49.5) 110(49.5) APPROX. GHIPPING WEIGHT LEGIFG) APPROX. GHIPPING WEIGHT LEG(KG) 110(49.5) APPROX. GHIPPING WEIGHT LEG(KG) 110(49.5) APPROX. GHIPPING WEIGHT LEG(KG) 110(49.5)

- · 9.0 CUBIC FEET OF STOPAGE
- · TWO FULL-DEPTH REMOVABLE WIRE GHELVEG
- · ONE FULL-DEPTH TEMPERED GLAGG GHELF OREATEG DIGTINGT TEMPERATURE 20NE FOR WINE STORAGE
- · WINE SHELF HOLDS FIVE BOTTLES OF WINE AND PULLS OUT FOR EASY ACCESS
- · TEMPERATURE ADJUGTO FROM 99-420F TO 54-560F
- · AUTOMATIC CYCLE DEFPOST
- · INTERIOR LIGHT TURNS ON BY SWITCH OR WHEN DOOR IS OPENED
- · INSTALL AS UNDERCOUNTER OF FREESTANDING UNIT
- · BLACK EXTERIOR CABINET
- · TWO YEAR FULL WARRANTY COMPLETE UNIT; GIX YEAR FULL WARRANTY GEALED GYGTEM; TWELVE YEAR LIMITED WARRANTY GEALED GYGTEM
- · 150 MODELG HAVE WHITE INTERIOR / 15 | MODELG HAVE BLACK INTERIOR
- · WHITE INTERIOR GLAGG DOOR MODELG AVAILABLE AG GPECIAL ORDER *P=PIGHT HINGE; L=LEFT HINGE





- · 7 FT. CORD INCLUDED WITH UNIT
- · 2 WIPE WITH GROUND/9 PRONG PLUG
- . 1 15 V/60 HZ; MAXIMUM AMP6 15"W. MODEL - 3 0. 24"W MODEL - 3 3

FINIOH DETAILS - YUAP

- · CLEAP AND FLUTED DOOPS
- · AVAILABLE IN OTAINLEGG OTEEL (GG) -OTAINLEGG OTEEL FRAME AROUND LARGE WINDOW DOOR, OTAINLEGG OTEEL DOOR HANDLE WITH CHROME PLATED BRACKETG AND BLACK EXTERIOR CABINET
- · 60LID DOOR
- · BLACK (BK), WHITE (WH), OTAINLEGO OTEEL (GO), ALMOND (AL), BIOCUIT (BT), OTONE GRAY (GG), GRAPHITE GRAY (GG), BURGUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREOT GREEN (FG), VIKING BLUE (VB), COBALT BLUE (CB), AND EGGPLANT (EP)
- · FINIOH CODEO DEOIGNATE DOOR FRONTO.
 ALL FINIOHEO HAVE OTAINLEOO OTEEL
 HANDLE WITH CHROME PLATED BRACKETO
 AND BLACK EXTERIOR CABINET
- · BRAGG TRIM OPTION (BR) INCLUDEG NAME PLATE AND DOOR


HANDLE/BRACKETO. ALL BRAGO COMPONENTO HAVE A DURABLE, PROTECTIVE COATING FOR MAINTENANCE-FREE NORMAL USE

FINIOH DETAILO - DUAP

- · CLEAP AND FLUTED DOOPS
 - · AVAILABLE IN STAINLESS STEEL (SG) STAINLESS STEEL FRAME AROUND
 LARGE WINDOW DOOR, STAINLESS STEEL
 DOOR HANDLE WITH CHROME PLATED
 BRACKETS AND BLACK EXTERIOR
 CABINET
- . 60LID DOOR
- · BLACK (BK), WHITE (WH), OTAINLEOO OTEEL (OO), BIOCUIT (BT), OTONE GRAY (OG), GRAPHITE GRAY (GG)
- · FINIOH CODEO DEOIGNATE DOOR FRONTO. ALL FINIOHEO HAVE CAOT OTAINLEOO OTEEL HANDLE AND BLACK EXTERIOR CABINET
- · BPAGG TPIM OPTION (BP) FOR DOOR HANDLE. ALL BPAGG COMPONENTG HAVE A DURABLE, PROTECTIVE COATING FOR MAINTENANCE - FREE NORMAL UGE



- · CLEAP AND FLUTED DOOPS
- · ACCEPT 1/2" CUSTOM WOOD FRAME



PP-OFEGGIONAL



DEGIGNER



FULL OVEPLAY

UNDERCOUNTER/FREESTANDING 24"W. REFRIGERATED BEVERAGE CENTERS

YUAP 1 400 (P/L*) - PROFESSIONAL SOLID DOOP DUAP 1 400 (P/L*) - DEGIGNEP GOLID DOOP YUAR 1 40 (REVERSIBLE) - PROFESSIONAL CLEAR GLASS DOOR YUAP I 40F (REVERSIBLE) - PROFESSIONAL FLUTED GLASS DOOR YUAR 141 (REVERSIBLE) - PROFESSIONAL CLEAR GLASS DOOR YUAR 141F (REYERGIBLE) - PROFEGGIONAL FLUTED GLAGG DOOR DUAP 1 40 (P/L*) - DEGIGNER CLEAR GLAGG DOOR DUAP 1 4 OF (P/L*) - DESIGNER FLUTED GLASS DOOR DUAP 1 4 1 (P/L*) - DEGIGNER CLEAR GLAGG DOOR DUAP 1 4 IF (P/L*) - DEGIGNER FLUTED GLAGG DOOR DFUP 1 40 (P/L*) - FULL OVEPLAY CLEAP GLAGG DFUP 1 4 OF (P/L*) - FULL OVEPLAY FLUTED GLAGG DFUP 141 (P/L*) - FULL OVEPLAY CLEAP GLAGG DFUP (4) F (P/L*) - FULL OVERLAY FLUTED GLASS

APPROX. GHIPPING WEIGHT LEGIFG) 140 (69.0) APPROX. GHIPPING WEIGHT LEG(KG) 140 (62.0) APPROX. GHIPPING WEIGHT LEG(KG) 140 (62.0) APPROX. SHIPPING WEIGHT LES(KG) 140 (69.0) APPROX. GHIPPING WEIGHT LEG(KG) 140 (62.0) APPROX. GHIPPING WEIGHT LEG(KG) 140 (69.0) APPROX. GHIPPING WEIGHT LEG(KG) 140 (62.0) APPROX. GHIPPING WEIGHT LEGING 140(620) APPROX. GHIPPING WEIGHT LEG(KG) 140 (620) APPROX. GHIPPING WEIGHT LEG(KG) 140 (62.0) APPROX. GHIPPING WEIGHT LEG(KG) 140 (62.0) APPROX. GHIPPING WEIGHT LEG(KG) 140(620) 140(69.0) APPROX. GHIPPING WEIGHT LEG(KG) APPROX. GHIPPING WEIGHT LEG(KG) 140 (69.0)

· G. I CUBIC FEET OF STOPAGE

- · TOP WIRE SHELF HAS 6 1/2" FLIP -UP SECTION TO CHILL OF STORE OPEN WINE BOTTLES OF LARGE CONTAINERS
- · TWO FULL-DEPTH TEMPERED GLAGO GHELVEG WITH TOP WIRE GHELF HOLD | 48 | 2 02. CANO AND OPEATE DISTINCT TEMPERATURE 20NES FOR WINE STORAGE
- · TWO WINE SHELVES CRAPLE I 4 BOTTLES AND PULL OUT FOR EASY ACCESS
- · TEMPERATURE ADJUGTO FROM 99-420F TO 54-560F
- · AUTOMATIC CYCLE DEFPOST
- · INTEPLOP LIGHT TUPNG ON BY GWITCH OF WHEN DOOP IG OPENED
- · INSTALL AS UNDERCOUNTER OF FREESTANDING UNIT
- · BLACK EXTERIOR CABINET
- · TWO YEAR FULL WARRANTY COMPLETE UNIT; SIX YEAR FULL WARRANTY -SEALED SYSTEM; TWELVE YEAR LIMITED WARRANTY - SEALED SYSTEM
- · 140 MODELO HAVE WHITE INTERIOR / 141 MODELO HAVE BLACK INTERIOR
- · WHITE INTERIOR GLAGG DOOR MODELG AVAILABLE AG GPECIAL ORDER

*P=PIGHT HINGE; L=LEFT HINGE

ELECTRICAL

- · 7 FT. COPD INCLUDED WITH UNIT
- · 2 WIPE WITH GROUND/3 PRONG PLUG
- · 1 15 V/60 HZ: MAXIMUM AMPG 15"W. MODEL - 9.0; 24"W. MODEL - 9.9

FINIOH DETAILS - YUAR

- · CLEAR AND FLUTED DOORS
 - · AVAILABLE IN GTAINLEGG GTEEL (GG) -STAINLESS STEEL FRAME AROUND LAPGE WINDOW DOOP, STAINLESS STEEL DOOR HANDLE WITH CHROME PLATED BRACKETS AND BLACK EXTERIOR CABINET
- · GOLID DOOR
- · BLACK (BK), WHITE (WH), STAINLESS STEEL (SS), ALMOND (AL), BISCUIT (BT), STONE GRAY (SG), GRAPHITE GRAY (GG), BUPGUNDY (BU), LEMONADE (LE), MINT JULEP(MJ), FOREST GREEN (FG), VIKING BLUE (YB), COBALT BLUE (CB), AND EGAPLANT (EP)
- · FINIGH CODES DESIGNATE DOOP FRONTS. ALL FINIOHEO HAVE OTAINLEGO OTEEL HANDLE WITH CHPOME PLATED BRACKETO AND BLACK EXTERIOR CABINET
- · BRAGG TRIM OPTION (BR) INCLUDEG NAME PLATE AND DOOP HANDLE/BRACKETS. ALL BRAGS


COMPONENTS HAVE A DUPABLE, PROTECTIVE GOATING FOR MAINTENANCE FREE NORMAL USE

FINIOH DETAILS - DUAP


- · CLEAP AND FLUTED DOOPS
 - · AYAILABLE IN GTAINLEGG GTEEL (GG) -STAINLESS STEEL FRAME AROUND LAPGE WINDOW DOOP, STAINLESS STEEL DOOR HANDLE WITH CHROME PLATED BRACKETO AND BLACK EXTERIOR CABINET
- · 90LID DOOR
- · BLACK (BK), WHITE (WH), OTAINLEGO STEEL (SS), BISCUIT (BT), STONE GRAY (64), GRAPHITE GRAY (44)
- · FINIGH CODES DESIGNATE DOOR FRONTS
- . ALL FINIOHEO HAVE CAST STAINLESS STEEL HANDLE AND BLACK EXTERIOR CABINET
- · BRAGG TRIM OPTION (BR) FOR DOOR HANDLE. ALL BRAGG COMPONENTS HAVE A DUPABLE, PROTECTIVE COATING FOR MAINTENANCE - FREE NORMAL USE

FINIOH DETAILS - DEUP


- · CLEAR AND FLUTED DOORS
- · ACCEPT 1/2" CUSTOM WOOD FRAME




PROFEGGIONAL





DEGIGNER



UNDERCOUNTER/FREESTANDING 24"W. REFRIGERATED BEVERAGE CENTER/ICEMAKERS







PROFEGGIONAL

DEGIGNER

FULL OVERLAY

 YURI I 40D (R/L*) - PROFESSIONAL DOOR
 APPROX. SHIPPING WEIGHT LES(KG)
 I 40 (69.0)

 DURI I 40D (R/L*) - DESIGNER DOOR
 APPROX. SHIPPING WEIGHT LES(KG)
 I 40 (69.0)

 DFRI I 40D (R/L*) - FULL OVERLAY
 APPROX. SHIPPING WEIGHT LES(KG)
 I 40 (69.0)

2 4"W. PEFPIGERATED BEYERAGE CENTER/ICEMAKERS

- · G. I GU. FT. CAPACITY
- · ONE FULL DEPTH REMOVABLE WIRE GHELF AND 9 DOOR GHELVEG
- · TEMPERATURE ADJUGTO FROM 99-45 FIN BEVERAGE GEOTION
- · ICE MAKER PRODUCES UP TO 2 LESS OF ICE PER DAY
- · ICE BIN STOPES UP TO 5 LBS OF ICE
- · TEMPERATURE ADJUGTO FROM 5-15° IN ICE MAKER SECTION
- · AUTOMATIC CYCLE DEFROST
- · INTERIOR LIGHT TURNS ON WHEN DOOR IS OPENED
- · INSTALL AS UNDEPCOUNTER OF FREESTANDING UNIT
- · BLACK EXTERIOR CABINET
- · TWO YEAR FULL WARRANTY COMPLETE UNIT; OIX YEAR FULL WARRANTY GEALED GYGTEM; TWELVE YEAR LIMITED WARRANTY - GEALED GYGTEM

*P=PIAHT HINAE; L=LEFT HINAE

YUPI/DUPI/DFPI COMBINATION BEVERAGE CENTERS/ICEMAKERS ELECTRICAL

- · 7 FT. CORD INCLUDED WITH UNIT
- · 2 WIPE WITH APOUND/9 PRONG PLUG
- · 1 154/60H2; MAXIMUM AMPG 2.2

WATER

· INLET WATER REQUIREMENTS - 14 IN. COPPER TUBING

FINIOH DETAILO - YURI

· GOLID DOOR - AVAILABLE IN GTAINLEGG GTEEL (GG), BLACK (BK), WHITE (WH), ALMOND (AL), BIGCUIT (BT), GTONE GRAY (GG),
GRAPHITE GRAY (GG), BURGUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREGT GREEN (FG), VIKING BLUE (VB), COBALT BLUE (CB)
AND EGGPLANT (EP) FINIGH CODE DEGIGNATEG DOOR FRONTG. ALL FINIGHEG HAVE GTAINLEGG GTEEL HANDLE WITH CHROME
PLATED BRACKETG AND BLACK EXTERIOR CABINET BRAGG TRIM OPTION (BR) - INCLUDEG NAMEPLATE, DOOR HANDLE AND
BRACKETG. ALL BRAGG COMPONENTG HAVE A DURABLE, PROTECTIVE COATING FOR MAINTENANCE-FREE NORMAL UGE.


FINIOH DETAILO - DUPI


· 90LID DOOR - AVAILABLE IN STAINLESS STEEL (SS), BLACK (BK), WHITE (WH), BISCUIT (BT), STONE ARAY (SQ),
ARAPHITE ARAY (AG) FINISH CODE DESIGNATES DOOR FRONTS. ALL FINISHES HAVE STAINLESS STEEL HANDLES AND
BLACK EXTERIOR CABINET BRASS TRIM OPTION (BR) - INCLUDES DOOR HANDLE. ALL BRASS COMPONENTS HAVE A
DURABLE, PROTECTIVE COATING FOR MAINTENANCE-FREE NORMAL USE.


FINIOH DETAILS - DEPL

· ACCEPTO ¾ IN. CUOTOM WOOD PANEL

UNDERCOUNTER/FREESTANDING 24"W. REFRIGERATED DRAWERS AND ACCESSORIES







PROFEGGIONAL

DEGIGNER

FULL OVEPLAY

2 4"W. PEFPIGEPATED DPAWERS

YURD 1 400 (PROFEGGIONAL) APPROX. GHIPPING WEIGHT LB(KG) 1 40 (69.0) DUPD 1 4 0D (DEGIGNER) APPROX. SHIPPING WEIGHT LEG(FG) 140 (69.0) DFRD 1 400 (FULL OYERLAY) APPROX. GHIPPING WEIGHT LEG(KG) 140 (69.0)

- · G. I CU. FT. CAPACITY
- · TEMPERATURE ADJUSTS FROM 39-45°F
- · STAINLESS STEEL INTERIOR
- · FULL EXTENSION DRAWER GLIDES
- · YERTICAL STORAGE OF WINE BOTTLES OR TWO-LITER DRINK BOTTLES IN BOTTOM DRAWER
- · HIDDEN TOUCHPAD CONTROL WITH LED DIGITAL TEMPERATURE READOUT
- · AUTOMATIC CYCLE DEFPOST
- · INTERIOR LED LIGHTING
- · INSTALL AS UNDERCOUNTER OR FREESTANDING UNIT
- · BLACK EXTERIOR CABINET
- · TWO YEAR FULL WARRANTY COMPLETE UNIT; OIX YEAR FULL WARRANTY GEALED OYOTEM; TWELVE YEAR LIMITED WAPPANTY - SEALED SYSTEM

YURD/DURD/DFRD REFRIGERATED DRAWERS ELECTPICAL

- · 7 FT. COPD INCLUDED WITH UNIT
- · 2 WIRE WITH AROUND/3 PRONG PLUG
- · 1 15Y/GOHZ; MAXIMUM XX AMPG

FINIOH DETAILS - YURD/DURD

- · GOLID DOOR AVAILABLE IN STAINLESS STEEL (SS)
- · FINIGH CODE DEGIGNATES DOOR FRONTS. ALL FINISHES HAVE STAINLESS STEEL HANDLE WITH OHE PLATED BEACKETS AND BLACK EXTERIOR CABINET

FINIOH DETAILS - DEPLO

· ACCEPTO ¾ IN. CUSTOM WOOD PANEL

PAN GET

PDP6 APPROX. SHIPPING WEIGHT LEG(KG)

- · FOUR COMMERCIAL REGTAURANT STYLE STAINLESS STEEL PANS WITH CLEAR COVERS
- ·TWO 6 IN. D X 6 15/16 IN.L. X 6 3/0 IN.W. 2.9 AT. CAPACITY (2.2 LITERS)
- · ONE O IN. D X (2 19/16 IN.L. X O 15/16 IN.W. 5.8 QT. CAPACITY (5.5 LITERS)
- · ONE O IN. D X 1 2 19/10 IN.L. X 1 07/10 IN.W. 1 1.0 9T. CAPACITY (1 1 LITEPO)
- · STAINLE: SS STEEL PAN SUPPORT PAIL

· ADJUGTABLE DIVIDERG ALLOW CUGTOMIZED PLACEMENT OF ITEMG WITHIN DRAWER







UNDERCOUNTER/FREESTANDING 15"W. WINE CELLARS

YUWC 152D (P/L*) - PROFESSIONAL SOLID DOOP	APPROX. GHIPPING WEIGHT LED(KG)	110(49.5)
DUWC 152D (P/L*) - DEGIGNER GOLID DOOR	APPROX. GHIPPING WEIGHT LED(KG)	110(49.5)
VUWC 152 (P/L*)-PROFEGGIONAL CLEAR GLAGG DOOR	APPROX. GHIPPING WEIGHT LED(KG)	110(49.5)
YUWC 152F (P/L*) - PROFEGGIONAL FLUTED GLAGG DOOP	APPROX. GHIPPING WEIGHT LEG(KG)	110(49.5)
DUWC152 (R/L*) - DEGIGNER CLEAR GLAGG DOOR	APPROX. GHIPPING WEIGHT LEG(KG)	110(49.5)
DUWC 152F (P/L*) - DEGIGNER FLUTED GLAGG DOOR	APPROX. GHIPPING WEIGHT LEG(KG)	110(49.5)
DFUW 152 (P/L*)-FULL OVEPLAY CLEAP GLAGO	APPROX. GHIPPING WEIGHT LEG(KG)	110(49.5)
DFUW 152F (P/L*) - FULL OVEPLAY FLUTED GLAGO	APPROX. GHIPPING WEIGHT LEG(KG)	110(49.5)

- · TEMPERATURE ADJUGTO FROM 40-490F TO 64-660F
- · GIX WIPE GHELVEG CRADLE 2 4 BOTTLEG OF WINE HOPIZONTALLY TO KEEP CORKG MOIGT
- · GHELYEG ARE COATED TO REDUCE YIBRATION AND HOLD BOTTLEG GNUGLY IN PLACE
- · GHELYEG ALIDE IN AND OUT FOR EAGY ACCEGG TO GTORED BOTTLEG
- · LOCKS ON SHELF ALIDES PREVENT SHELVES FROM BEING REMOVED INADVERTENTLY
- · GHELVEG CAN BE PEMOVED TO GTORE MAGNUM OR LARGER BOTTLEG
- · ULTPAVIOLET-PEGIGTANT TEMPERED GLAGG AND BLACK INTERIOR PROTECTS WINE FROM HARMFUL LIGHT
- · MAPLE WOOD FACINGS PROVIDE ADDITIONAL ULTRAVIOLET PROTECTION
- · LOW INTENDITY LIGHTING DIOPLAYO WINE WITH MINIMAL HEAT AND LIGHT OUTPUT
- · LIGHT TUPNO ON WHEN DOOP 10 OPENED OF BY OWITCH TO ILLUMINATE CONTENTO
- · KEYED DOOR LOCK PROVIDES PROTECTION FOR STORED WINES (GLASS DOOR MODELS)
- · MUST BE OPDEPED PIGHT OF LEFT HINGE
- · BLACK EXTERIOR CABINET
- · INSTALL AS UNDERCOUNTER OF FREESTANDING UNIT
- · TWO YEAR FULL WARRANTY COMPLETE UNIT; GIX YEAR FULL WARRANTY GEALED GYGTEM: TWELVE YEAR LIMITED WARRANTY GEALED GYGTEM
- · 1520 GOLID DOOR MODELG ARE AVAILABLE GPECIAL ORDER



PROFEGGIONAL

*P=PIGHT HINGE; L=LEFT HINGE

YUWC/DUWC/DFUW WINE CELLARG

ELECTPICAL

- · 7 FT. CORD INCLUDED WITH UNIT
- · 2 WIFE WITH AFOUND/9 PFONA PLUA
- · 1 | 5 V/60 HZ; MAXIMUM AMP6 -| 15"W. MODEL - 9.0; 2 4"W. MODEL -9.9

FINIOH DETAILS - YUWG

- · CLEAP AND FLUTED DOOPS
- · AVAILABLE IN GTAINLEGG GTEEL
 (GG) GTAINLEGG GTEEL FRAME
 AROUND LARGE WINDOW DOOR,
 GTAINLEGG GTEEL DOOR HANDLE
 WITH CHROME PLATED BRACKETG
 AND BLACK EXTERIOR CABINET
- · 60LID DOOP
- · BLACK (BK), WHITE (WH), OTAINLEGO OTEEL (OG), ALMOND (AL), BIOCUIT (BT), OTONE ARAY (OG), ARAPHITE ARAY (AG), BURAUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREOT AREEN (FG), VIKING BLUE (VB), COBALT BLUE
- FINIOH CODEO DEOICNATE DOOR FRONTO. ALL FINIOHEO HAVE OTAINLEOO OTEEL HANDLE WITH CHROME PLATED BRACKETO AND BLACK EXTERIOR CABINET

(OB), AND EGGPLANT (EP)

· BPAGG TRIM OPTION (BP) - INCLUDEG NAME PLATE AND DOOP HANDLE/BPACKETG. ALL BPAGG COMPONENTG HAVE A DUPABLE, PROTECTIVE COATING FOR MAINTENANCE-FREE NORMAL USE

FINIOH DETAILS - DUWG

- · CLEAP AND FLUTED DOOPS
 - · AVAILABLE IN OTAINLEOO OTEEL (OO)

 OTAINLEOO OTEEL PRAME AROUND

 LARGE WINDOW DOOR, OTAINLEOO

 OTEEL DOOR HANDLE WITH CHROME

 PLATED BRACKETO AND

 BLACK EXTERIOR CABINET
- · 60LID DOOP
- · BLACK (BK), WHITE (WH), OTAINLEOO OTEEL (OO), BIOCUIT (BT), OTONE CRAY (OO), CRAPHITE CRAY (OO)
- FINIOH CODEO DEGIGNATE DOOR FRONTO. ALL FINIOHEO HAVE CAST STAINLEGO STEEL HANDLE AND BLACK EXTERIOR CABINET
- BRAGE TRIM OPTION (BP) FOR DONO (CUSTOM)
 HANDLE. ALL BRAGE COMPONENTS
 MATERIALS


 COATING FOR MAINTENANCE-FREE
 NORMAL USE

FINIOH DETAILS - DFUW

- · CLEAP AND FLUTED DOOPS
- · ACCEPT 1/2" CUSTOM WOOD FRAME



DEGIGNER




FULL OVEPLAY

UNDERCOUNTER/FREESTANDING 24"W. WINE CELLARS

YUWC 1 42D (P/L*) - PROFESSIONAL SOLID DOOP APPROX. GHIPPING WEIGHT LEG(KG) 140(620) DUWC 1 4 2D (P/L*) - DEGIGNER GOLID DOOR APPROX. GHIPPING WEIGHT LEG(KG) 140 (62.0) YUWC 1 42 (P/L*) - PROFESSIONAL CLEAR GLASS DOOR APPROX. GHIPPING WEIGHT LEG(KG) 140 (69.0) YUWC 1 4 2F (P/L*) - PROFESSIONAL FLUTED GLASS DOOR APPROX. GHIPPING WEIGHT LEG(KG) 140 (62.0) DUWC 1 4 2 (P/L*) - DEGIGNER CLEAR GLAGG DOOR APPROX. GHIPPING WEIGHT LEG(KG) 140 (69.0) DUWG 1 4 2 F (P/L*) - DEGIGNER FLUTED GLAGG DOOR 140 (62.0) APPROX. GHIPPING WEIGHT LEG(KG) DFUW 1 42 (P/L*) - FULL OVEPLAY CLEAP GLAGO APPROX. SHIPPING WEIGHT LES(KG) 140(620) DFUW 1 4 2F (P/L*) - FULL OVERLAY FLUTED GLAGO APPROX. GHIPPING WEIGHT LEG(KG) 140 (62.0)

- · TEMPERATURE ADJUSTS FROM 40-490F TO 64-660F
- · GIX WIPE GHELVEG PLUG BOTTOM WOOD CRADLE HOLD 54 BOTTLEG OF WINE HORIZONTALLY TO KEEP CORKS MOIGT
- · GHELYEG ARE COATED TO REDUCE VIBRATION AND HOLD BOTTLEG GNUGLY IN PLACE
- · GHELVEG GLIDE IN AND OUT FOR EAGY ACCEGG TO GTORED BOTTLEG
- · SHELVES CAN BE PEMOVED TO STOPE MAGNUM OF LAPGER BOTTLES
- · ULTPAYIOLET-PEGIGTANT TEMPERED GLAGG AND BLACK INTERIOR PROTECTS WINE FROM HARMFUL LIGHT
- · MAPLE WOOD FACINGS PROVIDE ADDITIONAL ULTRAVIOLET PROTECTION
- · LOW INTENDITY LIGHTING DIOPLAYO WINE WITH MINIMAL HEAT AND LIGHT OUTPUT
- · LIGHT TUPNO ON WHEN DOOP 10 OPENED OF BY OWITCH TO ILLUMINATE CONTENTO
- · YEYED DOOR LOCK PROVIDEG PROTECTION FOR GTORED WINEG (GLAGG DOOR MODELG)
- · MUST BE OPDEPED PIGHT OF LEFT HINGE
- · BLACK EXTERIOR CABINET
- · INSTALL AS UNDERCOUNTER OF FREESTANDING UNIT
- · TWO YEAR FULL WARRANTY COMPLETE UNIT; SIX YEAR FULL WARRANTY SEALED SYSTEM; TWELVE YEAR LIMITED WARRANTY SEALED SYSTEM
- · 1 4 1 D GOLID DOOR MODELG ARE AVAILABLE GPECIAL ORDER



PROFEGGIONAL

*P=PIGHT HINGE; L=LEFT HINGE

YUWC/DUWC/DFUW WINE CELLARG

ELECTPICAL

- · 7 FT. COPD INCLUDED WITH UNIT
- · 2 WIPE WITH APOUND/3 PRONG PLUG
- · 1 15 Y/60 HZ; MAXIMUM AMP6 15"W. MODEL - 9.0; 24"W. MODEL - 9.9

FINIOH DETAILS - YUWG

- · CLEAP AND FLUTED DOOPS
 - · AVAILABLE IN OTAINLEOG OTEEL (OG)

 OTAINLEOG OTEEL FRAME AROUND

 LARGE WINDOW DOOR, OTAINLEOG

 OTEEL DOOR HANDLE WITH CHROME

 PLATED BRACKETO AND BLACK

 EXTERIOR CABINET
- . 60LID DOOR
- · BLACK (BK), WHITE (WH), OTAINLEOO OTEEL (OO), ALMOND (AL), BIOCUIT (BT), OTONE GRAY (OG), GRAPHITE GRAY (GG), BURGUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREOT GREEN (FG), VIKING BLUE (VB), COBALT BLUE (CB), AND EGGPLANT (EP)
- FINIOH CODES DESIGNATE DOOR
 FRONTS. ALL FINISHES HAVE STAINLESS
 STEEL HANDLE WITH CHROME PLATED
 BRACKETS AND BLACK EXTERIOR
 CABINET
- · BPAGG TPIM OPTION (BP) INCLUDEG NAME PLATE AND DOOP HANDLE/BPACKETG. ALL BPAGG

COMPONENTO HAVE A DUPABLE, PROTECTIVE COATING FOR MAINTENANCE-FREE NORMAL USE

FINIOH DETAILS - DUWG

- · CLEAP AND FLUTED DOOPS
 - · AVAILABLE IN OTAINLEOO OTEEL (OO)

 OTAINLEOO OTEEL PRAME AROUND

 LARGE WINDOW DOOP, OTAINLEOO


 OTEEL DOOP HANDLE WITH CHROME

 PLATED BRACKETO AND BLACK


 EXTERIOR LABINET
- · 60LID DOOR
- · BLACK (BK), WHITE (WH), OTAINLEOO OTEEL (OO), BIOCUIT (BT), OTONE CRAY (OC), CRAPHITE CRAY (CC)
- · FINIOH CODEO DEOICNATE DOOR FRONTO. ALL FINIOHEO HAVE CAOT OTAINLEOO OTEEL HANDLE AND BLACK EXTERIOR CABINET
- · BRAGG TRIM OPTION (BP) FOR DOOR HANDLE. ALL BRAGG COMPONENTS HAVE A DURABLE, PROTECTIVE COATING FOR MAINTENANCE-FREE NORMAL USE

FINIOH DETAILS - DEUX

- · CLEAR AND FLUTED DOORS
- · ACCEPT 1/2" CUSTOM WOOD FRAME



DEGIGNER



FULL OYEPLAY



UNDERCOUNTER/FREESTANDING 15"W. ICE MACHINE

YUIM 1 500 (P/L*) - PROFESSIONAL SOLID DOOR

DUIM 1500 (P/L*) - DEGIGNER GOLID DOOR

DFIM 1 500 (P/L*) - FULL OVEPLAY GOLID DOOP

· 9/4" GOUAPE CLEAP ICE


- · PRODUCES UP TO 35 LBS. OF ICE PER DAY
- · HEAVY-DUTY ICE GLOOP INCLUDED
- · 95 LB. CAPACITY ICE BIN
- · DRAINING PROCESS AUTOMATICALLY REMOVES OLD ICE TO ENOUPE A CONSTANT SUPPLY OF FRESHICE
- · EQUIPPED WITH CLEANING MODE
- · INSTALL AS UNDERGOUNTER OF FREESTANDING UNIT
- · BLACK EXTERIOR CABINET
- · TWO YEAR FULL WARRANTY COMPLETE UNIT; SIX YEAR FULL WAPPANTY - SEALED SYSTEM; TWELVE YEAR LIMITED WAPPANTY - GEALED GYGTEM

*P=PIGHT HINGE; L=LEFT HINGE

110(49.5) APPROX. GHIPPING WEIGHT LEG(KG)

APPROX. GHIPPING WEIGHT LEG(KG) 110(49.5)

APPROX. GHIPPING WEIGHT LEG(KG) 110(49.5)







PROFESSIONAL

DEGIGNER

FULL OYEPLAY

GEALED PEGERVOIR DRAIN PUMP

DP-YUIM APPROX. GHIPPING WEIGHT LEG(KG) 2 (0.91)

- · EXCLUDIVELY FOR ICE MACHINES
- · FOR USE WHEN FLOOP DRAIN IS NOT AVAILABLE
- · COMPLETELY SEALED PESERYOIP
- · UNIT SHUTS OFF POWER TO ICE MACHINE IN THE EVENT OF A PUMP FAILURE
- · SPECIAL DESIGN MAKES THE POSSIBILITY OF FOREIGN MATERIAL CLOGGING PUMP VERY REMOTE
- · CHECK VALVE IN DIOCHARAE TUBE PREVENTO DIOCHARAE WATER FROM FLOWING BACK INTO THE PUMP
- · SUPPLIED WITH 2 WIRE WITH GROUND/9 PRONG PLUG FOR CONNECTION TO 1 154/60H2 AND INCORPORATES A POWER RECEPTAGLE INTO WHICH THE ICE MACHINE IS PLUGGED
- · INCLUDES PUMP AND OTHER PARTS/HARDWARE

YUIM/DUIM GEPIEG ICE MACHINEG

ELECTRIC

- · 7 FT. COPD INCLUDED WITH UNIT
- · 2 WIFE WITH GROUND/3 PRONG PLUG
- · 1 154/60HZ; MAXIMUM AMPG 9.0

YUIM FINIOH DETAILS

- . 60 LID DOOR
- · OTAINLEOO OTEEL (OO), BLACK (BK), WHITE (WH), ALMOND (AL), BIGGUIT (BT), STONE GRAY (GG), GRAPHITE GRAY (GG), BURGUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREST GREEN (FG), VIKING BLUE (YB), COBALT BLUE (CB), AND EGGPLANT (EP)
- · FINIOH CODES DESIGNATE DOOR FRONTS. ALL FINIGHEG HAVE GTAINLEGG GTEEL HANDLE WITH CHROME PLATED BRACKETS AND BLACK EXTERIOR CAPINET.
- · BRAGG TRIM OPTION (BP) INCLUDEG NAMEPLATE AND DOOP HANDLE/BRACKETS. SUPER DURABLE, LONG LASTING BRAGG FINIGH FOR "HIGH TRAFFIC" PARTS (HANDLE); ALL OTHER PARTO HAVE A DURABLE PROTECTIVE COATING. ALL PARTO DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.

DUIM FINIOH DETAILS

- . 60LID DOOR
- · STAINLESS STEEL (SS), BLACK (BK), WHITE (WH), BISCUIT (BT), STONE GRAY (SG), GRAPHITE GRAY (GG)
- · FINIGH CODES DESIGNATE DOOP FRONTS. ALL FINIOHEO HAVE OTAINLEGO OTEEL HANDLE AND BLACK EXTERIOR CABINET.
- · BRAGG TRIM OPTION (BR) FOR DOOR HANDLE. ALL BRAGG COMPONENTS HAVE A DURABLE, PROTECTIVE COATING FOR MAINTENANCE-FREE NORMAL USE

DFIM FINIOH DETAILS


· ACCEPTO ¾" CUSTOM WOOD PANEL

UNDERCOUNTER/FREESTANDING REFRIGERATED BEVERAGE CENTER AND WINE CELLAR ACCESSORIES


HANDLE KITG

PHK90-66 PROFE6610NAL GTAINLE66 STEEL HANDLE FIT APPROX. GHIPPING WEIGHT LE(KG) 6(2.7) PHE 9 O-BR PROFESSIONAL BRASS HANDLE FIT APPROX. GHIPPING WEIGHT LEG(KG) 6(2.7) PHY 2 9-66 PROFEGGIONAL STAINLESS STEEL HANDLE FIT APPROX. SHIPPING WEIGHT LIB(FG) 6(2.7) PHY 2 9-BP PROFESSIONAL BRASS HANDLE KIT APPROX. GHIPPING WEIGHT LEG(KG) 6(2.7) DHK 1 8-66 DEGIGNER OTAINLEGG OTEEL HANDLE KIT APPROX. GHIPPING WEIGHT LEG(KG) **与(2.9)** DHY 18-BR DEGIGNER BRAGG HANDLE KIT APPROX. GHIPPING WEIGHT LEG(KG) 5 (2.2) TRIM-18 TRIMFIT APPROX. GHIPPING WEIGHT LEG(KG) 5(2.2)

- · PHF 90 FOR USE WITH DFUR OR DFUW
- · PHY 2 9 FOR USE WITH DEPLO OF DEIM
- · DHK I & FOR USE WITH DEUR, DEUW, DERI, DERD, OR DEIM
- · FOR USE ON LOCALLY SUPPLIED FULL OYERLAY PANELS
- · INCLUDES ONE HANDLE AND INSTALLATION HAPDWAPE
- · ALLOWS FULL OVERLAY PRODUCTS TO COORDINATE WITH OTHER PROFESSIONAL & DESIGNER PRODUCTS



WOSTONG




PROFEGGIONAL AND DEGIGNER FITCHEN CLEANUP PRODUCTS

UNDERCOUNTER DISHWASHERS


DFUDO 42 "NO FRONT" DFUDI 42 "NO FRONT"

APPROX. GHIPPING WEIGHT LEG(FG) [19(51.0) APPROX. GHIPPING WEIGHT LEG(FG) [19(51.0)

- · SHIPPED WITH STAINLESS STEEL DOOP INSTALLED OF "NO FRONT" TO ACCEPT CUSTOM FULL OVERLAY PANEL OF OPTIONAL DOOP PANEL
- · CONTROLS LOCATED ON TOP OF INNER DOOR; CONTROLS ARE HIDDEN WHEN DOOR IS
- · STAINLESS STEEL TANK/INNER DOOR
- · QUIET CLEAN SYSTEMM WITH ASPHALT, FELT, AND FOAM INSULATION
- · GEPAPATE MOTOPG/PUMPG FOR CIPCULATION AND DPAIN
- · "GUPER-EXTENDABLE" GRAPHITE NYLON RACKS
- · AUTOMATIC WATER HEATING (850F-1700F)
- · MULTI-LEVEL WAGH GYGTEM
- · TRIPLE FILTRATION AND WASTE REMOVAL SYSTEM
- · CONVECT-AIRTH FAN DRYING
- · ACCOMMODATES I G INTERNATIONAL PLACE SETTINGS
- · EXTPA-TALL TANK ALLOWS TALLER DISHES TO BE PLACED IN UPPER PACK
- · ELIMINATES NEED FOR TOP FILL STRIP
- · ALLOWS FULL SIZE PLATES TO BE LOADED IN UPPER PACK
- · POTO/PANO, HEAVY WAOH, NOPMAL WAOH, LIGHT/OHINA, QUICK WAOH AND PINOE/HOLD
- · OPTIONS INCLUDE: TEMP SELECTION, EXTRA DRY AND FIVE HOUR DELAY
- · END OF CYCLE SIGNAL
- · DFUD 1 4 2 EXTRA FEATURES:
- · LAPGE CUTLEPY/UTENOIL OPADLE
- · INTEPIOP LIGHT
- · OPTIONO INCLUDE: TEMP GELECTION, EXTRA DRY, FIVE HOUR DELAY, EXPRESS AND TOP OR BOTTOM BASKET ONLY
- · CONTROL LOCK GAFETY FEATURE
- · TWENTY-FIVE-YEAR LIMITED WARRANTY 60 TANK \$ INNER DOOR; FIVE-YEAR LIMITED WARRANTY - RACKO, MOTORG/PUMPO AGGEMBLY AND WATER DIGTRIBUTION GYOTEM



PROFEGGIONAL







UNDERCOUNTER DISHWASHER ACCESSORIES

DOOF PANELS


PTD 2 4 PROFEGGIONAL DOOR PANEL APPROX. GHIPPING WEIGHT LEG(FG) [4 (6.9) DTD 2 4 DEGIGNER DOOR PANEL APPROX. GHIPPING WEIGHT LEG(FG) [4 (6.9)

- · FOR USE WITH DEUD DISHWASHER
- · ALLOWO DFUD TO COORDINATE WITH OTHER PROFEGGIONAL AND DEGIGNER PRODUCTS
- · SPELIFY FINISH

HANDLE HITO

PHY 2 9-66 PROFESSIONAL STAINLESS STEEL HANDLE KIT	APPROX. GHIPPING WEIGHT LEG(KG)	ら (2.7)
PHK 2 9-BP PROFEGGIONAL BRAGG HANDLE KIT	APPROX. GHIPPING WEIGHT LEG(KG)	ら (2.3)
DHY 20-66 PROFEGGIONAL GTAINLEGG GTEEL HANDLE HIT	APPROX. GHIPPING WEIGHT LEG(KG)	ら (2.7)
DHK 20-BR PROFEGGIONAL BRAGG HANDLE KIT	APPROX. GHIPPING WEIGHT LEG(KG)	ら (2.7)

- · FOR USE WITH DFUD DISHWASHER
- · FOR USE ON LOCALLY SUPPLIED FULL-OVERLAY PANELS
- · INCLUDES HANDLE AND INSTALLATION HAPDWAPE
- · ALLOWO DFUD WITH FULL OVEPLAY PANEL TO COOPDINATE WITH OTHER PROFESSIONAL & DESIGNER PRODUCTS



DFUD SEPIES DISHWASHERS

DIGHWAGHER GHIPPED WITH TWO GG GIDE TRIM GTRIPG (4"W.)

FOR 24"W. CUTOUT, 61/2 FOOT, 34"110

"CRIMP-PROOF" PUBBER DRAIN HOSE, GFT WATER TUBING WITH 1/6" COMPRESSION FITTING AND G FOOT ELECTRICAL CORD.

ELECTRIC

- · 9-PRONG ELECTRICAL CORD GUPPLIED WITH UNIT
- · 1201/60H2; MAXIMUM AMP6 15.0

WATER/DRAIN

- · I 200F MINIMUM HOT WATER AT THE DIGHWAGHER RECOMMENDED; DIGHWAGHER WILL, HOWEVER, PERFORM PROPERLY WITH COLD WATER
- · FOR DRAIN, USE FACTORY PACKED DRAIN HOSE WITH MINIMUM 20" HIGH LOOP
- · CHECK LOCAL CODES FOR DRAIN AIR GAP REQUIREMENT

FINISH DETAILS FOR PROFESSIONAL DOOR PANELS

- · STAINLESS STEEL (SS), BLACK (BK), WHITE (WH), ALMOND (AL), BISCUIT (BT), STONE GRAY (SG), GRAPHITE GRAY (GG), BURGUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREST GREEN (FG), VIKING BLUE (VB), COBALT BLUE (CB) AND EGGPLANT (EP)
- · ALL FINIOHEO HAVE OTAINLEGO OTEEL HANDLE WITH CHROME PLATED BRACKETO

FINIOH DETAILS FOR DESIGNER DOOR PANELS

- · OTAINLEOG OTEEL (GG), BLACK (BK), WHITE (WH), BIGCUIT (BT), OTONE CRAY (GG) AND CRAPHITE CRAY (GG)
- · BRAGG TRIM OPTION (BR) AVAILABLE FOR ALL FINIGHEG

UNDERCOUNTER 18"W. TRASH COMPACTORS


YUC 181 PROFESSIONAL DOOR

DUC 180 DEGIGNER DOOR

APPROX. GHIPPING WEIGHT LEG(KG)

210(94.5) DFG 180 FULL OVERLAY DOOR

- · COMMERCIAL-TYPE STYLING AND CONSTRUCTION
- · BUILT-IN SMALL LITTER AREA
- · BUILT-IN STORAGE COMPARTMENT
- · LAPGE 1.7 CU. FT. TPAGH DPAWER
- · BREAK-AWAY TRAGH BAGKET WITH PREGGURE RELEAGE PLATE
- · ACTIVATED CHAPCOAL AIR FILTER/FAN/LIGHT
- · 1/2 HP MOTOR WITH 2000 POUNDS OF FORCE (DELIVERED AT ALL POSITIONS AND AT ALL POINTS OF THE PAM HEAD)
- · HEAVY GAUGE STEEL FRAME AND DOUBLE REINFORGED BAGE
- · KEY LOCK AND POSITIVE DRAWER CLOSING
- · FIVE YEAR LTD. WARRANTY DRIVE GYGTEM MOTOR



YUC/DUC/DFC GEPIEG COMPACTORG


ELECTRIC

- · 6 FT. CORD INCLUDED WITH COMPACTOR
- · 2 WIFE WITH GROUND/3 PRONG PLUG
- · 1 154/60H2; MAXIMUM AMPG 9.0

FINIOH DETAILS FOR YUC COMPACTORS

- · STAINLEGG STEEL (GG), BLACK (BK), WHITE (WH), ALMOND (AL), BIGCUIT (BT), STONE GRAY (GG), GRAPHITE GRAY (GG), BURGUNDY (BU), LEMONADE (LE), MINT JULEP (MJ), FOREST AREEN (FA), VIKINA BLUE (VB), COBALT BLUE (OB), AND EAAPLANT (EP)
- · FINIOH DEGIGNATES DOOR AND DRAWER PANEL. ALL FINIOHES HAVE STAINLESS STEEL CONTROL PANEL WITH BLACK GRAPHICS, STAINLESS STEEL LITTER DOOR PULL, AND GTAINLEGG GTEEL DRAWER HANDLE WITH CHROME PLATED BRACKETS. THE CONTRO PANEL GWITCHEG FOR ALL FINIGHEG ARE BLACK. BRAGG TRIM OPTION (BR) - FOR ANY FINICH; INCLUDED NAMEPLATE, DRAWER HANDLE/BRACKETD, AND LITTER DOOR PULL. GUPER DURABLE, LONG LAGTING BRAGO FINIOH ON "HIGH TRAFFIC" PARTO (HANDLEG); ALL OTHER PARTS HAVE A DURABLE PROTECTIVE COATING. ALL PARTS DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.





FULL OYERLAY

FINIOH DETAILS - FOR DUG MODELS

- · STAINLESS STEEL (SS), BLACK (BY), WHITE (WH), BISCUIT (BT), STONE GRAY (SG) AND GRAPHITE GRAY (GG)
- · FINIGH DEGIGNATEG DOOP AND CONTROL PANEL.
- · BRAGG TRIM OPTION (BR) FOR ANY FINIGH; INCLUDEG DRAWER HANDLE AND RELEAGE LEVER. GUPER DUPABLE, LONG LAGTING BPAGG FINIGH ON "HIGH TPAFFIC" PAPTG (HANDLEG); ALL OTHER PARTG HAVE A DUPABLE PROTECTIVE COATING. ALL PARTS DESIGNED FOR MAINTENANCE-FREE NORMAL USE.

FINIOH DETAILS - FOR DFG MODELS

· DEGIGNED TO HAVE A CUGTOM FRONT PANEL AND DO NOT HAVE AN EXTERIOR FINIGH. CONTROL PANEL ON DFC MODELS IS STAINLESS STEEL

UNDERCOUNTER TRASH COMPACTOR ACCESSORIES

HANDLE KITG

PHY I 7-66 PROFESSIONAL STAINLESS STEEL HANDLE FIT


PHY 17-BP PROFESSIONAL BRASS HANDLE KIT

DHK I 7-66 DEGIGNER STAINLESS STEEL HANDLE FIT

DHY 17-BY DEGIGNEY BRAGG HANDLE FIT

APPROX. GHIPPING WEIGHT LEG(FG) 2 (0.9)
APPROX. GHIPPING WEIGHT LEG(FG) 2 (0.9)
APPROX. GHIPPING WEIGHT LEG(FG) 4 (1.8)
APPROX. GHIPPING WEIGHT LEG(FG) 4 (1.8)

- . FOR USE WITH DFG TRASH COMPACTOR
- · FOR USE ON LOCALLY SUPPLIED GUSTOM PANELS
- · INCLUDES HANDLE AND INSTALLATION HAPDWAPE
- · ALLOWO DFC WITH CUSTOM PANEL TO COOPDINATE
 WITH OTHER PROFESSIONAL AND DESIGNER PRODUCTS



DEGIGNER

PROFESSIONAL

BAGG AND TIEG (15 PER PACK)

TOBO (12 BOXES OF 15 BAGS) APPR

APPROX. SHIPPING WEIGHT LEG(KG) 38 (17.1)

- · 5 BAGG GHIPPED WITH PRODUCT
- · SPECIFICALLY DESIGNED FOR 18"W. UNIT
- · PREPUNCHED HOLES MATCH RETAINER BUTTONS
- · 3½ MIL THICK




CHAPCOAL FILTER

AUF-YUU

APPROX. SHIPPING WEIGHT LEG(FG) 1 (.05)

- · ONE GHIPPED WITH PRODUCT
- · PEPLACE EVERY 6-9 MONTHS
- · CAPTURES AND REMOVES ODORS RATHER THAN "PERFUME" APPROACH



HEAVY-DUTY FOOD WASTE DISPOSERS



3/4 HP CONTINUOUS FEED FOOD WASTE DISPOSED

YOFW750

APPROX. GHIPPING WEIGHT LEG(KG)

29(10.4)

- · 9/4 HP INSTANT START MOTOR
- · ANTI-JAM AUTO PEVERGING
- · GUPER QUIET OPERATION
- · CAST GRIND ELEMENTS EXCLUSIVE
- · 1.4 MILLION UPPERCUTTINGS MOST AND EXCLUSIVE
- · 1.9 MILLION UNDERCUTTINGS MOST AND EXCLUSIVE
- · QUIET, EFFICIENT FIXED IMPELLERS EXCLUSIVE
- · 66 AND CAST HOUSINGS
- · 7 YEAR FULL WARRANTY



I HP CONTINUOUS FEED FOOD WASTE DISPOSED

YCFW1000

APPROX. GHIPPING WEIGHT LEG(KG)

29 (10.4)

- · I HP INSTANT START MOTOR
- · POWER PLUG JAM-INATOR BUTTON GTEP-UP EXCLUGIVE
- · ANTI-JAM AUTO PEVERGING
- · SUPER QUIET OPERATION
- · CAGT CIPIND ELEMENTS EXCLUSIVE
- · 1.4 MILLION UPPERCUTTINGS MOST AND EXCLUSIVE
- · 1.9 MILLION UNDERCUTTINGS MOST AND EXCLUSIVE
- · QUIET, EFFICIENT FIXED IMPELLEPS EXCLUSIVE
- · 66 AND CAST HOUSINGS
- · 10 YEAR FULL WARRANTY

DISPOSER SHIPPED WITH 11/2" OD WASTE LINE SPOUT WITH GASKET AND HAS 7/8" OD DISHWASHER CONNECT TUBE

ELECTPIC

- · HAPD WIPE DIRECT WITH 2-WIPE WITH APOUND
- · 120 Y/60H2; MAXIMUM AMP6 10.0 (1000 MODEL); 8.0 (750 MODEL)

HEAVY-DUTY FOOD WASTE DISPOSER ACCESSORIES

BATCH FEED ACCESSORY FIT

BFAK APPROX. GHIPPING WEIGHT LB(KG) 9 (1.4)

· CONVERTO CONTINUOUO FEED DIOPOGER INTO MAGNETICALLY ACTIVATED BATCH FEED UNIT



COUNTER/GINK GWITCH KIT

STOK APPROX. SHIPPING WEIGHT LB(KG) 2 (0.9)

- · EAGILY MOUNTS TO SINK OF COUNTERTOP
- · PERFECT FOR IGLAND INSTALLATIONS
- · AIP ACTIVATED
- · PROVIDES EXTRA OUTLET
- · FIT INCLUDES CHROME AND WHITE BUTTONS



GINK FLANGES

OFLAS SINK FLANGE APPROX. SHIPPING WEIGHT LEG(KG) (0.5)


- · STANDARD SINK FLANGES AVAILABLE IN BRASS, WHITE AND BISCUIT
- · MAGTER PACK OF FIVE



GINK GTOPPERG

66TP5 APPROX. 6HIPPING WEIGHT LEG(KG) (0.5)

- · STANDARD SINK STOPPERS AVAILABLE IN BRASS WITH AND BISCUIT TO COORDINATE WITH
 SINK FLANCES
- · MAGTER PACK OF 5




DEEP SINK FLANGE

OFLADS DEEP SINK FLANGE APPROX. SHIPPING WEIGHT LIB(KG) 9 (1.4)

- · DEEP GINK FLANGE AVAILABLE IN IN GTAINLEGG GTEEL ACCOMMODATEG UP TO I %" THICK GINKG (FARMHOUGE GTYLE)
- · MAGTER PACK OF 5



WOSOONG




PROFEGGIONAL OUTDOOR PRODUCTS

T-SERIES OUTDOOR ULTRA-PREMIUM GAS GRILLS WITH GOURMET-GLO[™] ROTISSERIE


YGBG900-2PI-N NATURAL	APPROX. SHIPPING WEIGHT LEG(KG)	ク25(147.5)
VABA900-2PI-L LP/PROPANE	APPROX. GHIPPING WEIGHT LEG(KG)	925(147.5)
VABA412-2PI-N NATURAL	APPROX. GHIPPING WEIGHT LEG(KG)	かちの(158.9)
VABOAI2-2PI-L LP/PROPANE	APPROX. GHIPPING WEIGHT LEG(KG)	かちの(158.9)
VABA410-9PI-N NATURAL	APPROX. GHIPPING WEIGHT LES(KG)	カラの(1725)
VABA410-9PI-LLP/PROPANE	APPROX. GHIPPING WEIGHT LES(KG)	カラの(172.5)
VABA592-9PI-N NATURAL	APPROX. GHIPPING WEIGHT LES(KG)	460 (208.8)
VABA592-9PI-L LP/PROPANE	APPROX. GHIPPING WEIGHT LES(KG)	460 (208.8)
VABA590-4PI-N NATURAL	APPROX. GHIPPING WEIGHT LEG(KG)	490 (222.5)
VABA590-4PI-L LP/PROPANE	APPROX. GHIPPING WEIGHT LEG(KG)	490 (222.5)

- · YGBQ900-2PT 2-25,000 BTU STAINLESS STEEL GRILL BURNERS (ONE IS DUAL PURPOSE GRILL/SMOKER BURNER) WITH STAINLESS STEEL DRIP GUARDS · 9.9 1 SQ. FT (5G9 SQ. IN./9G92 SQ. CM.) GRILLING AREA
- · VABQ4 | 2-2PT 2-25,000 BTU OTAINLEOO OTEEL APILL BUPNERO (ONE 10 DUAL PURPOOE APILL/OMOKER BURNER) WITH OTAINLEOO OTEEL DRIP AUARDO
- · DOUBLE I 5,000 BTU STAINLESS STEEL SIDE BURNERS WITH PORCELAINIZED "Y" GRATES AND STAINLESS STEEL COVER
- · 3.9 1 69. FT (563 69. IN./3632 69. CM.) APILLING APEA
- · YABQ4 1 0-9PT 9-25,000 BTU STAINLESS STEEL APILL BUPNEPS (ONE IS DUAL PUPPOSE APILL/SMOKEP BUPNEP) WITH STAINLESS STEEL DRIP AUAPDS · 5.8 1 59. FT. (896 59. IN./5998 59. CM.) APILLING APEA
- · YABAS 9 2-9PT 9-25,000 BTU STAINLESS STEEL APILL BUPNERS (ONE IS DUAL PURPOSE APILL/SMOKER BURNER) WITH STAINLESS STEEL DRIP AUARDS
- · DOUBLE 15,000 BTU STAINLESS STEEL SIDE BURNERS WITH PORCELAINIZED "V" CRATES AND STAINLESS STEEL COVER
- · 5.8 1 69. FT. (876 69. IN./5798 69. CM.) APILLING APEA
- · YGB9590-4PT 4-25,000 BTU STAINLESS STEEL GPILL BUPNERS (ONE IS DUAL PURPOSE GRILL/SMOKER BURNER) WITH STAINLESS STEEL DRIP GUARDS
- \cdot 2 1 5,000 BTU GOURMET-GLO INFRARED REAR BURNER WITH ROTIGGERIE MOTOR, 1/2" ROTIGGERIE ROD AND HEAVY-DUTY FORKG
- · 7.8 69. FT. (1,120 69. IN./722669. CM.) GPILLING APEA
- · 15,000 BTU GOURMET-GLO INFRARED REAR BURNER WITH ROTIGGERIE MOTOR,
 1/2" ROTIGGERIE ROD AND HEAVY-DUTY FORKG
- · ELECTRONIC IGNITION POWERED BY 9Y BATTERY
- · POPCELAINIZED COOKING GRIDG
- · STAINLESS STEEL FLAVOR GENERATOR PLATES
- · PEMOVABLE SMOKER BOX
- · ADJUSTABLE THREE POSITION CHROME-PLATED WARMING RACK
- · OTAINLEOO OTEEL DEIP TRAY WITH AN INDIVIDUAL GREAOE MANAGEMENT TRAY AND OTAINLEOO OTEEL BALL BEARING ROLLER GLIDEO
- · THEPMOMETER ON CANOPY INDICATES TEMPERATURE RANGE FOR ARILLING, SMOKING, AND WARMING
- \cdot CAN BE BUILT-IN OF POPTABLE WITH CAPT ACCESSORY SOLD SEPARATELY (SEE ACCESSORIES PAGE
- · SIDE BURNERS MAY BE INSTALLED AS AN ACCESSORY SOLD SEPARATELY (SEE ACCESSORIES PACE
- · FIVE-YEAR LIMITED GRILL BURNER AGGEMBLIEG AND INFRARED BURNERG
- · LIFETIME LIMITED ALL STAINLESS STEEL COMPONENTS INCLUDING BURNERS AND PORCELAIN GRILL GRATES


MUST SPECIFY NATURAL GAS (N) OF LP/PROPANE (L)




90" APILL - YABA900-2PT




4 | " GPILL WITH SIDE BUPNERS YGBQ4 | 2-2PT



41" APILL - YABQ410-3PT



59" APILL WITH SIDE BUPNERS VARAS92-9RT



59" APILL - YABA590-4PT


T-SERIES OUTDOOR ULTRA-PREMIUM GAS GRILLS

WITH TRUSEAR INFRARED BURNER AND GOURMET-GLOTM ROTISSERIE


VGIQ900-2PT-N NATURAL	APPROX. GHIPPING WEIGHT LEG(KG)	925(147.5)
VGIQ900-2PT-L LP/PPOPANE	APPROX. GHIPPING WEIGHT LEG(KG)	925(147.5)
Vala410-3PI-N NATURAL	APPROX. GHIPPING WEIGHT LEG(KG)	780(172.5)
VGIQ410-9PI-LLP/PROPANE	APPROX. GHIPPING WEIGHT LEG(KG)	980(177.5)
Y419592-9PI-N NATURAL	APPROX. GHIPPING WEIGHT LEG(KG)	460 (208.8)
Valasge-gri-L LP/PROPANE	APPROX. GHIPPING WEIGHT LEG(KG)	460 (208.8)
VGIQ590-4PI-N NATURAL	APPROX. GHIPPING WEIGHT LEG(KG)	490 (222.5)
VGIQ590-4PI-L LP/PROPANE	APPROX. GHIPPING WEIGHT LEG(KG)	490 (222.5)

- · YAIQ? OO-2PT I-25,000 BTU GTAINLEGG GTEEL APILL BUPNER WITH GTAINLEGG GTEEL DRIP QUARDG
- · 1 5,000 BTU GOUPMET-GLO INFRAPED PEAR BUPNER WITH POTIGGEPIE MOTOR, ½" POTIGGEPIE ROD, AND HEAVY-DUTY FORKG
- · 9.9 1 69. FT. (569 69. IN./9692 69. CM) APILLING APEA
- · YGIG 4 10-9PT 2-25,000 BTU STAINLESS STEEL GPILL BUPNERS (ONE IS DUAL PURPOSE GRILL/SMOKER BURNER) WITH STAINLESS STEEL DRIP
- · 1 5,000 BTU GOUPMET-GLO INFRAPED PEAR BUPNER WITH POTIGGERIE MOTOR, 1/2" POTIGGERIE POD AND HEAVY-DUTY FORKG
- · 5.8 | 69. FT. (896 69. IN./5998 69. CM) APILLING APEA
- · VGIQ5 9 2-9PT 2-25,000 BTU GTAINLEGG GTEEL GPILL BUPNERG (ONE IG DUAL PURPOGE GPILL/GMOKER BURNER) WITH GTAINLEGG GTEEL DRIP GUARDG
- · 1 5,000 BTU GOUPMET-GLO INFRAPED REAR BURNER WITH POTIGGERIE MOTOR, ½" ROTIGGERIE ROD AND HEAVY-DUTY FORKG
- · DOUBLE 15,000 BTU STAINLESS STEEL SIDE BUPNERS WITH POPCELAINIZED "V" OPATES AND STAINLESS STEEL COVER
- · 5.8 1 69. FT. (896 69. IN./5998 69. CM) GPILLING APEA
- · VG19590-4PT 9-25,000 BTU GTAINLEGG GTEEL GRILL BURNERG (ONE 16 DUAL PURPOGE GRILL/GMOKER BURNER) WITH GTAINLEGG GTEEL DRIP GUARDG
- \cdot 2 1 5,000 BTU GOUPMET-GLO INFRAPED REAR BURNER WITH POTIGOEPIE MOTOR, 1/2" POTIGOEPIE POD AND HEAVY-DUTY FORKG
- · 7.8 69. FT. (1,12069. IN./722669. CM) GRILLING AREA
- · TRUGEAR INCONEL GTAINLEGG GTEEL INFRARED GRILL BURNER
- · 90,000 BTUG HIGH
- · 17,500 BTUG-LOW
- · ELECTRONIC IGNITION POWERED BY A 9Y BATTERY
- · POPCELAINIZED COOKING GPIDG
- · OTAINLEGO OTEEL FLAVOR GENERATOR PLATES
- · PEMOVABLE SMOKER BOX
- · ADJUGTABLE THREE POGITION CHROME PLATED WARMING PACK
- · GTAINLEGG GTEEL DRIP TRAY WITH TWO INDIVIDUAL GREAGE
- MANAGEMENT TRAYO AND OTAINLEGO OTEEL BALL BEARING ROLLER GLIDEO
- · THERMOMETER ON CANOPY INDICATES TEMPERATURE RANGE FOR ARILLING, SMOKING AND WARMING
- · CAN BE BUILT-IN OR PORTABLE WITH CART ACCESSORY SOLD SEPARATELY (SEE ACCESSORIES PAGE
- · FIVE-YEAR LIMITED ARILL BURNER AGGEMBLIEG AND INFRARED BURNERG
- · LIFETIME LIMITED ALL GTAINLEGG GTEEL COMPONENTG INCLUDING BURNERG AND PORCELAIN GRILL GRATEG


MUST SPECIFY NATURAL GAS (N) OF LP/PROPANE (L)



41" GPILL - YGIQ410-9PT



59" GRILL WITH SIDE BURNERS YGIQ592-9RT



59" APILL - YAIQ590-4PT

E-SERIES OUTDOOR ULTRA-PREMIUM GAS GRILLS WITH GOURMET-GLOTM ROTISSERIE

VGBQ900-2PE-N NATURAL	APPROX. GHIPPING WEIGHT LEG(KG)	925(147.5)
VUBQ900-2PE-L LP/PPOPANE	APPROX. GHIPPING WEIGHT LEG(KG)	ク25(147.5)
VGBQ412-2PE-NNATURAL	APPROX. GHIPPING WEIGHT LEG(FG)	クラの(158.9)
VABOA12-2PE-L LP/PROPANE	APPROX. GHIPPING WEIGHT LEG(KG)	950 (158.9)
VUB9410-9PE-N NATURAL	APPROX. GHIPPING WEIGHT LEG(KG)	クラの(1725)
VUBG410-9PE-LLP/PPOPANE	APPROX. GHIPPING WEIGHT LEG(FG)	クラ の (172.5)
VGBQ592-9PE-NNATURAL	APPROX. GHIPPING WEIGHT LEG(KG)	460 (208.8)
VUBO592-9PE-L LP/PROPANE	APPROX. GHIPPING WEIGHT LEG(KG)	460 (208.8)
VGBQ590-4PE-NNATURAL	APPROX. GHIPPING WEIGHT LEG(FG)	490 (222.5)
VOBOSSO-4RE-L LP/PROPANE	APPROX. GHIPPING WEIGHT LEG(KG)	490 (222.5)

- $\cdot \text{ YABA ? 00-2PE} \quad 2-25,000 \text{ BTU STAINLESS STEEL APILL BUPNEPS (ONE IS DUAL PUPPOSE APILL/SMOKEP BUPNEP) WITH STAINLESS STEEL DPIP AUAPDS$
- · 9.91 69. FT (569 69. IN./9692 69. CM.) GPILLING APEA
- · YABQ4 | 2-2FE 2-25,000 BTU STAINLESS STEEL APILL BUPNERS (ONE IS DUAL PURPOSE APILL/SMOKER BUPNER) WITH STAINLESS STEEL DRIP AUARDS
- · DOUBLE I 5,000 BTU GTAINLEGG GTEEL GIDE BURNERG WITH PORCELAINIZED "V" GRATEG AND GTAINLEGG GTEEL COVER
- · 9.9 1 69. FT (569 69. IN./9692 69. CM.) GPILLING APEA
- · YABQ4 1 0-9PE 9-25,000 BTU GTAINLEGG GTEEL APILL BUPNERG (ONE 16


PURPOSE ARILL/SMOKER BURNER) WITH STAINLESS STEEL DRIP GUARDS

- · 5.8 1 69. FT. (896 69. IN./5998 69. CM.) GPILLING APEA
- · YABAS 9 2-9PE 9-25,000 BTU STAINLESS STEEL APILL BURNERS (ONE IS


PURPOSE URILL/SMOKER BURNER) WITH STAINLESS STEEL DRIP GUARDS

- · DOUBLE I 5,000 BTU STAINLESS STEEL SIDE BURNERS WITH PORCELAINIZED "V" GRATES AND STAINLESS STEEL COVER
- · 5.8 1 69. FT. (896 69. IN./5998 69. CM.) UPILLING APEA
- · YABAS 90-4PE 4-25,000 BTU STAINLESS STEEL APILL BUPNERS (ONE IS DUAL PURPOSE APILL/SMOKER BURNER) WITH STAINLESS STEEL DRIP AUARDS
- · 2 1 5,000 BTU GOURMET-GLO INFRARED REAR BURNER WITH ROTIGGERIE MOTOR, 1/2" ROTIGGERIE ROD AND HEAVY-DUTY FORKG
- · 7.8 69. FT. (1,120 69. IN./722669. CM.) APILLING APEA
- · 1 5,000 BTU GOURMET-GLO INFRARED REAR BURNER WITH ROTIGGERIE MOTOR, ½" ROTIGGERIE ROD AND HEAVY-DUTY FORKG
- · ELECTRONIC IGNITION POWERED BY I 20V POWER
- · TWO HEAVY DUTY HALOGEN LIGHTS MOUNTED ON THE INSIDE OF GPILL CANOPY (STANDARD)
- · AUTOMATICALLY TUPN ON WHEN CANOPY IS LIFTED
- · BUPNERS ARE CONVENIENTLY IGNITED BY SIMPLY TUPNING KNOB TO THE LIGHT POSITION
- · AUTOMATIC PEIGNITION GYGTEM
- · POPCELAINIZED COOKING GRIDS
- · STAINLESS STEEL FLAVOR GENERATOR PLATES
- PEMOVABLE OMORER BOX
- · ADJUGTABLE THREE POGITION CHROME-PLATED WARMING RACK
- · STAINLESS STEEL DRIP TRAY WITH AN INDIVIDUAL GREASE
- MANAGEMENT TRAY AND STAINLESS STEEL BALL BEARING ROLLER GLIDES
- · THEPMOMETER ON CANOPY GIVES APPROXIMATE TEMPERATURE READOUT
- · CAN BE BUILT-IN OR PORTABLE WITH CART ACCESSORY SOLD SEPARATELY (SEE ACCESSORIES PAGE)
- · GIDE BURNERG MAY BE INGTALLED AG AN ACCEGGORY GOLD GEPARATELY (GEE ACCEGGORIEG PAGE)
- · FIVE-YEAR LIMITED ARILL BURNER AGGEMBLIEG AND INFRARED BURNERG
- · LIFETIME LIMITED ALL STAINLESS STEEL COMPONENTS INCLUDING BURNERS AND PORCELAIN GRILL GRATES


MUST SPECIFY NATURAL GAS (N) OF LP/PROPANE (L)




30" UPILL - YUBQ300-2PE




4 I " APILL WITH SIDE BUPNERS VABQ4 I 2-2PE



41" APILL - YABQ410-3PE



59" APILL WITH SIDE BUPNERS VARAS92-9RE



59" APILL - YABA590-4PE


T-SERIES OUTDOOR 30"W. PREMIUM GAS GRILL

T-GEPIEG OUTDOOP 90"W. PREMIUM GAG GPILL

 VABQO90-2I-N NATURAL
 APPROX. SHIPPING WEIGHT LB(KG)
 295 (106.6)

 VABQO90-2I-L LP/PROPANE
 APPROX. SHIPPING WEIGHT LB(KG)
 295 (106.6)

- · 2-25,000 BTU STAINLESS STEEL CRILL BURNERS WITH STAINLESS STEEL DRIP GUARDS
- · ELECTRONIC IGNITION POWERED BY A 9 VOLT BATTERY
- · POPCELAINIZED COOKING GPIDS
- · 9.91 69. FT (569 69. IN./1,490 69. CM.) GPILLING APEA
- · STAINLESS STEEL FLAVOR GENERATOR PLATES
- · ADJUGTABLE THREE POGITION CHROME-PLATED WARMING RACK
- · STAINLESS STEEL DRIP TRAY
- · THERMOMETER ON CANOPY INDICATES TEMPERATURE RANGE FOR WARMING, SMOKING, AND GRILLING
- · CAN BE BUILT-IN OF POPTABLE WITH CAPT ACCESSORY SOLD SEPARATELY (SEE ACCESSORIES PAGE)
- · SIDE BUPNERS MAY BE INSTALLED AS AN ACCESSORY SOLD SEPARATELY (SEE ACCESSORIES PACE)
- · FIVE-YEAR LIMITED ARILL BURNER AGGEMBLIEG
- · LIFETIME LIMITED ALL GTAINLEGG GTEEL COMPONENTG INCLUDING BURNERG AND PORCELAIN CRILL CRATEG



VABA T-SEPIES 90" PREMIUM OUTDOOR GAS APILLS

- · APILLO OHOULD BE OPDEPED FOR USE WITH LP/PROPANE (L) OR NATURAL GAG (N)
- · GRILLO ORDERED FOR USE WITH LP/PROPANE GAS ARE EQUIPPED WITH A HIGH CAPACITY HOSE/REGULATOR ASSEMBLY FOR CONNECTION TO A STANDARD 2 OLB. LP/PROPANE GAS CYLINDER EQUIPPED WITH A TYPE I, GCC-I CONNECTOR; LP TANK MUST BE FITTED WITH A CERTIFIED OPD (OVERFILLING PREVENTION DEVICE)
- · CIPILLO OPDEPED FOR USE WITH NATURAL GAS:
 CHECK WITH LOCAL GAS UTILITY COMPANY OF WITH
 LOCAL CODES FOR INSTRUCTIONS ON INSTALLING GAS SUPPLY LINES. YIFING CIPILLO OPERATE AT A PRESSURE OF 4"
 W.C. (WATER COLUMN) AND REQUIRE A SUPPLY PRES SURE
 OF G" TO 14" W.C., IF INCOMING PRESSURE
 EXCEEDS 14" W.C., A STEP-DOWN REGULATOR WILL BE
 PEQUIRED. AN INSTALLER-SUPPLIED GAS SHUT-OFF
 VALVE MUST BE INSTALLED IN AN EASILY
 ACCESSIBLE LOCATION.

FINIOH DETAILS (ALL GPILLS)

- · STAINLESS STEEL (SS)
- · ALL UNITO HAVE OTAINLEOS OTEEL HOOD OIDE
 PANELO, HOOD HANDLE/CHROME PLATE BRACKETO,
 OTAINLEOSO OTEEL DRIP TRAY PULL, CONTROL PANEL,
 AND LANDING LEDGE. ALL UNITO HAVE
 PORCELAINIZED COOKING GRIDO AND BLACK
 KNOBO.
- · BRAGO TRIM OPTION (BR) INCLUDED NAMEPLATE, HOOD HANDLE/BRACKETO, AND KNOB BEZELD. OUPER DURABLE, LONG LAGTING BRAGO FINIOH ON ALL "HIGH TRAFFIC" PARTO (HANDLE/BRACKETO); ALL OTHER PARTO HAVE A DURABLE PROTECTIVE

COATING. ALL PARTS DESIGNED FOR MAINTENANCE-FREE NORMAL USE.

GRILL CARTS

ULTRA-PREMIUM ARILL CART - 20"W. ARILLO

· HEAVY-DUTY OTAINLEGO OTEEL CONOTPUCTION

- · TWO STAINLESS STEEL I 6"W. X 2 4"D. FOLD DOWN SIDE SHELVES
- · TOWEL/UTENOIL POD

10000T7-00


- · FRONT ACCESS FOR LP TANK
- · FOUR LOCKING CASTERS PROVIDE MANEUVERABILITY AS WELL AS STABILITY
- · BRAGG TRIM OPTION AVAILABLE

ULTRA-PREMIUM APILL CART - 4 1 "W. APILLO

15-4-10T1-69 APPROX. 9HIPPING WEIGHT LEO(KG) 255 (115.8))

APPROX. GHIPPING WEIGHT LEG(FG)

- · HEAVY-DUTY STAINLESS STEEL CONSTRUCTION
- · TWO OTAINLEGO OTEEL I 6"W. X 2 4"D. FOLD-DOWN OIDE GHELYEG
- · FRONT ACCESS FOR LP TANK
- · TWO STOPAGE DPAWERS
- · LARGE IN-BOARD GOLID RUBBER REAR WHEELG AND LOCKING CAGTER FRONT WHEELG PROVIDE MANEUVERABILITY AG WELL AG GTABILITY
- · BRAGG TRIM OPTION AVAILABLE



ULTRA-PREMIUM ARILL CART - 50"W. ARILLO

100 100 1-66 APPROX. 6HIPPING WEIGHT LEG(FG) 290(191.7)


- · HEAVY-DUTY STAINLESS STEEL CONSTRUCTION
- · TWO OTAINLEGO OTEEL I G"W. X 2 4"D. FOLD-DOWN OIDE OHELVEG
- · FRONT ACCESS FOR LP TANK
- · TWO STOPAGE DPAWERS
- · FRONT STORAGE ACCESS DOOR
- · LARGE IN-BOARD GOLID RUBBER PEAR WHEELG AND LOCKING CAGTER FRONT WHEELG PROVIDE MANEUVERABILITY AG WELL AG GTABILITY
- · BRAGG TRIM OPTION AVAILABLE



PREMIUM GRILL CART - 30"W. GRILLS

B96090T9-66 APPROX. 6HIPPING WEIGHT LB(4G) (74.8)

- · HEAVY-DUTY STAINLESS STEEL CONSTRUCTION
- · ONE STAINLESS STEEL I G"W. X 2 4"D. FOLD-DOWN SIDE SHELF
- · PEAR ACCESS FOR LP TANK
- · FOUR LOCKING CASTERS PROVIDE MANEUVERABILITY AS WELL AS STABILITY





165 (74.9)

53"W. GRILL CART WITH GAS OVEN

BOGO 5 7 TI-N NATURAL APPROX. SHIPPING WEIGHT LEKG) 9 1 9 (1 4 9.5)
BOGO 5 9 TI-L LP/PROPANE APPROX. SHIPPING WEIGHT LEKG) 9 1 9 (1 4 9.5)

- · HEAVY-DUTY STAINLESS STEEL CONSTRUCTION
- · TWO GTAINLEGG GTEEL I G"W. X 2 4"D. FOLD DOWN GIDE GHELYEG
- · FRONT PULLOUT ACCESS FOR LP TANK WITH STORAGE AREA
- · TWO STORAGE DRAWERS LOCATED IN CENTER OF CART
- · LARGE IN-BOARD GOLID RUBBER REAR WHEELG AND LOCKING CAGTER FRONT WHEELG PROVIDE MANEUVERABILITY AG WELL AG GTABILITY
- · CART SHOULD BE ORDERED FOR USE WITH LP/PROPANE (L) OR NATURAL GAS (N)
- · CARTO OPDERED FOR USE WITH LP/PROPANE GAS ARE EQUIPPED WITH A HIGH CAPACITY HOSE/REGULATOR ASSEMBLY FOR CONNECTION TO A STANDARD 5 GALLON, 20 LB. LP/PROPANE GAS CYLINDER WITH TYPE 1, QCC-1 CONNECTION OR STANDARD 1/2"

 (1.9 CM) ID GAS SERVICE LINE
- · GRILLO OPDEPED FOR USE WITH NATURAL GAS PEQUIPE STANDARD PESIDENTIAL ½" (1.96M) ID GAS SERVICE LINE
- · OUTDOOR APPROVED GAG OVEN
- · ELECTRONIC IGNITION POWERED BY A 9 YOLT BATTERY
- · 181/6"W. X 127/16"H. X 184"D. OVEN CAVITY
- · 2.5 CUBIC FEET
- · NATURAL AIRFLOW BAKE
- · THREE HEAVY-DUTY RACKG/FOUR POGITIONS
- · FIVE-YEAR LIMITED TUBE BURNERS
- · TEN-YEAR LIMITED PORCELAIN OVEN



FINIOH DETAILS

- · OTAINLEGO OTEEL (GO)
- · BRAGO TRIM OPTION (BP) INCLUDEO NAMEPLATE, DRAWER HANDLE/BRACKETO, AND KNOB BEZEL. GUPER DURABLE, LONG LAGTING BRAGO FINIOH ON "HIGH TRAFFIC" PARTO (HANDLEO/BRACKETO); ALL OTHER PARTO HAVE A DURABLE PROTECTIVE COATING. ALL PARTO DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.


OUTDOOR GAS GRILL ACCESSORIES FOR VGBQ/VGIQ

YUBA/YUA YINYL GOVERS

CV90T-B1(90" B1)	APPROX. SHIPPING WEIGHT LEG(KG)	ら (2.7)
6490T-6 (90" CAPT)	APPROX. GHIPPING WEIGHT LEG(KG)	8 (7.6)
644 (T-151 (4 1" 151 - ALL APILL)	APPROX. GHIPPING WEIGHT LEG(KG)	8 (7.6)
644 (T-151615 (4 1" 151 - APILL W/615)	APPROX. GHIPPING WEIGHT LEG(KG)	8 (7.6)
CV4 IT-C (4 I" CAPT - ALL CPILL)	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)
CV4 1T-600 (4 1" CAPT - APILL W/610)	APPROX. GHIPPING WEIGHT LEG(KG)	10(4.5)
CV57T-101(50" 101 - ALL GPILL)	APPROX. GHIPPING WEIGHT LEG(KG)	1 カ (ち.ち)
6459T-151615 (59" 151 - APILL W/615)	APPROX. GHIPPING WEIGHT LEG(KG)	19 (5.9)
CY59T-C (59" CAPT - ALL CIPILL)	APPROX. GHIPPING WEIGHT LEG(KG)	15 (6.8)
6459T-668 (59" CART - GRILL W/68)	APPROX. GHIPPING WEIGHT LEG(KG)	15 (6.8)

- · STUPDY PEINFORCED VINYL ON THE OUTSIDE; FELT LINED TO PROTECT UNIT ON THE INSIDE
- · AVAILABLE IN 612E6 TO FIT BUILT-IN OF POPTABLE UNITS

6 = APILL WITH CAPT BI = BUILT-IN APILL BB = GIDE-BUPNEP



PORTABLE UPIDDLE

PAD APPROX. SHIPPING WEIGHT LEG(KG) 40 (18)


- . CAST ALUMINUM WITH PUGGED COMMERCIAL GRADE NO-STICK FINISH ON COOKING SUPFACE
- · APEAGE TROUGH IN FRONT
- · FITO OVER SIDE BURNER "Y" GRATES ONLY



WOY GRATE

WAT-BY APPROX. GHIPPING WEIGHT LB(KG) 6(2.7)

- · BLACK POPCELAIN/CAST IPON
- · USE IN PLACE OF SIDE BURNER "Y" GRATE (FRONT BURNER RECOMMENDED)



21 (9.5)

20(12.5

STAINLESS STEEL GRATES

662T4 FOR 90" CRILL AND 41" CRILL WITH SIDE BURNERS 669T4 FOR 41" ALL CRILL AND 59" CRILL WITH SIDE BURNERS 664T4 FOR 59" ALL CRILL

- · HEAVY-DUTY 9/0" THICK GTAINLEGG GTEEL
- · PROVIDES ANOTHER GRILL SURFACE OPTION FOR CUSTOMERS
- OPDER BY GIZE OF GRILL AREA



APPROX. GHIPPING WEIGHT LEG(KG)

APPROX. GHIPPING WEIGHT LEG(KG)




WARMING RACK

WP2TGG FOR 90" APILL AND 41" APILL WITH GIDE BUPNERG WR9TOO FOR 4 1" ALL APILL AND 59" APILL WITH OIDE BURNERO APPROX. GHIPPING WEIGHT LEGKG) WP4TGG FOR 50" ALL OPILL

APPROX. GHIPPING WEIGHT LEG(KG) **与(2.9)** 7 (2.2) APPROX. GHIPPING WEIGHT LEG(KG) 8 (7.6)

- · ONE STANDARD WITH ALL UNITS; CAN USE UP TO THREE RACKS
- · PROVIDEO ADDITIONAL PACK OPACE AREA FOR COOKING AND WARMING
- · OPDER BY GIZE OF GRILL AREA



POTIGGEPIE FORKG

RFK APPROX. SHIPPING WEIGHT LEG(KG) **与(2.9)**

· 2 POTIGGERIE FORKG FOR UGE WITH GOURMET-GLOTH ROTIGGERIE UNITG




POTIOGEPIE BAGKET

BORB906T (6"W.) FOR 90" GRILL AND 41" GRILL W/61DEBURNERS BORBTOST (8"W.) FOR 90" APILL AND 41" APILL W/GIDEBURNERG BORB410T (6"W.) FOR 41" ALL ARILL AND 59" ARILL W/GIDEBURNERG APPROX. GHIPPINA WEIGHT LIB(KG) BORED4 (8T (8"W.) FOR 4 1" ALL GRILL AND 5 9" GRILL W/GIDEBURNERG APPROX. GHIPPING WEIGHT LIB(KG) BORBSOBT (8"W.) FOR 59" ALL CIPILL

APPROX. GHIPPING WEIGHT LEG(KG) 6(2.7) APPROX. GHIPPING WEIGHT LEG(KG) 7 (2.2) 7 (2.2) 8 (2.6) 10(4.5) APPROX. GHIPPING WEIGHT LEG(KG)


- · HEAVY-DUTY OTAINLEGO OTEEL CONSTRUCTION
- · ADJUGTABLE CLAMPG
- · COOK DIFFERENT GIZE AND GHAPE ITEMS WITHOUT WIRING, TYING OF OPEAPING
- · LIMITED LIFETIME WAPPANTY
- · FOR USE WITH GOURMET-GLO ROTISSERIE UNITS



apill Liaht

Val APPROX. GHIPPING WEIGHT LEG(KG) 20(12.5)


- · HEAVY-DUTY CONSTRUCTION
- · ANODIZED BRUGHED ALUMINUM HANDLE AND VIGOR
- · 12 YOLT; 20 WATT LAMP WITH 8 FOOT ELECTPICAL COPD
- · 2 2" FLEXIBLE GOOGENECK WITH HEAT GEALED VINYL PROTECTIVE COVER
- · UNIQUE VIKING DEGIGN ALLOWG LIGHT TO MOUNT GEOUPELY TO POTIGOEPIE MOTOP AND QUICKLY BE PEMOVED FOR GTOPAGE
- · FITO BOTH BUILT-IN MODEL GRILLO AND GRILLO ON CARTO



PROFEGGIONAL 5 PIECE STAINLEGG STEEL BARBEQUE TOOL GET

BOTO APPROX. GHIPPING WEIGHT LB(KG) 90 (19.5)

- · COMMERCIAL-GTYLE APPEARANCE/DEGICN
- · SET INCLUDES: TURNER, FORK, KNIFE, TONG AND BRUSH
- · HANDLES PROVIDE SAFE, ERGONOMIC COOKING POSITION
- · BLADEG FABRICATED FROM HI-CARBON GTAINLEGG CUTLERY GTEEL
- · LIFETIME LIMITED WAPPANTY



PROFEGGIONAL COOKING MITT

POM APPROX. GHIPPING WEIGHT LB(KG) 12 (5.4)

- · CAN BE USED FOR COOKING INDOORS OF OUTDOORS
- · HAND AREA 16 EQUIPPED WITH VAPORGUARDTH LIQUID/VAPOR BARRIER WHICH PROTECTS AGAINST BURNS
- · HAND AREA MATERIAL IO NOMEX™ AND REGIGTO OCORCHING FROM OPEN FLAMEO
- · MITT HAG BLACK HAND AREA WITH GRAY UPPER GLEEVE AND EMBROIDERED VIKING LOGO
- · MACHINE WAGHABLE/DRYABLE



BROILER PAN AND TRAY

BPT APPROX. GHIPPING WEIGHT LB(KG) 5.5 (2.5)

- . FOR USE WITH ALL VIKING OUTDOOP GRILLS AND OVENS
- · HEAVY-DUTY POPCELAINIZED CONSTPUCTION
- · TRAY ALLOWS DRIPPINGS TO FALL THROUGH TO BROILER PAN
- · TRAY 10 REMOVABLE FOR EAGY CLEANING



BROILER PAN RACK

BPP APPROX. SHIPPING WEIGHT LEG(KG) 1 (.45)

- · FOR USE WITH VIKING BROILER PAN
- · PROVIDES BETTER BROILING AND ROASTING OPTIONS



GAG CONVERGION FITS

TNK-VUBA CONVERT FROM LP/PROPANE TO NATURAL

TNF-YGIQ CONVERT FROM LP/PROPANE TO NATURAL (FOR TRUGEAR INFRARED GRILLO AND GRILLER) TLPK-YGIDQ CONVERT FROM NATURAL TO LP/PROPANE

TLPK-YGIQ CONVERT FROM NATURAL TO LP/PROPANE (FOR TRUGEAR INFRARED GRILLG AND GRILLER) TNK-15960 CONVERT FROM LP/PROPANE TO NATURAL (FOR OUTDOOR GAG OVEN)

TNPK-BACO CONVERT FROM NATURAL TO LP/PROPANE (FOR OUTDOOR GAG OVEN)

· FOR FIELD CONVERSIONS - TWO SEPARATE KITS

APPROX. GHIPPING WEIGHT


LE(KG) 9(1.2)

- · CONVERT NATURAL TO LP/PROPANE
- · CONVERT LP/PROPANE TO NATURAL
 · INCLUDED ALL HARDWARE NECEDDARY FOR GAD CONVERDION

I 2 FT. NATURAL GAS SUPPLY HOSE & QUICK DISCONNECT ASSEMBLY

GOH 1 2 APPROX. GHIPPING WEIGHT LEG(KG) 9 (1.4)

- · COMPLETE QUICK DISCONNECT KIT FOR USE WITH NATURAL GAS FUEL SUPPLY
- · HOSE AND CONNECTOR ASSEMBLY IS INTENDED ONLY FOR OUTDOOR USE WITH PORTABLE APPLIANCES THAT MAY BE MOVED FOR CONVENIENCE OF OPERATION
- · VALVE IN THE GOCKET AUTOMATICALLY ALLOWG FULL GAG FLOW WHEN THE PLUG IG CONNECTED, AND PREVENTS GAG FLOW WHEN THE PLUG IG DIGCONNECTED
- · INCLUDES QUICK DISCONNECT SOCKET WITH FEMALE PIPE THREADS, PLUG AND HOSE ASSEMBLY AND AN ADAPTER TO MATE WITH A FEMALE FITTING ON THE GRILL (REMOVE FOR MATING HOSE TO MALE FITTINGS)





C^{4°} OUTDOOR COOKER AND CARTS

YCQ600 | APPROX. 9HIPPING WEIGHT LE(KG) (90 (65.5)

- · COMMERCIAL-TYPE CONSTRUCTION, DESIGN, AND STYLING
- · POPGELAIN GOATED APILL APATES
- · 9 1 5 69. IN. OF COOKING SUPFACE
- · CEPAMIC INTERIOR WITH I 8 GAUGE SPUN STAINLESS STEEL EXTERIOR
- · BUILT-IN THERMOMETER ON CANOPY GIVES PRECISE READINGS FROM 1500 TO 7500F
- \cdot CANOPY EQUIPPED WITH TWO HYDRAULIC CYLINDERS FOR EASIER OPENING AND CLOSING
- · CAN BE PORTABLE WITH CART ACCESSORY SOLD SEPARATELY
- · AGH TOOL COMES STANDARD FOR EASY AGH REMOVAL
- · PECOMMEND USING NATURAL LUMP CHARCOAL FOR FUEL
- · LIFETIME LIMITED WARPANTY ON CEPAMIC AND STAINLESS STEEL PARTS




996200-99

20" AND 90"W. 64 OUTDOOP COOKER CART

966200-66 APPROX. GHIPPING WEIGHT LEG(FG) 50(22.5)
966700-66 APPROX. GHIPPING WEIGHT LEG(FG) 170(76.5)

- . 00620000
- · COMPACT DEGICA TAKEG UP MINIMAL AMOUNT OF GPACE
- 0000000
- · HEAVY-DUTY OTAINLEGG OTEEL CONSTRUCTION
- · TWO 16"W. X 24"D. FOLD-DOWN GIDE GHELVEG
- · TOWEL/UTENOIL POD
- · LAPAE CAPACITY STOPAGE DRAWER FOR PROTECTING ITEMS AGAINST THE ELEMENTS
- · FOUR LARGE BLACK LOCKING CASTERS PROVIDE MANEUVERABILITY
 AS WELL AS STABILITY




99

4 I "W. 64 OUTDOOR COOKER CART W/DOUBLE SIDE BURNERS

9964 | 2-N APPROX. 9HPPING WEIGHT LB(KG) 275 (129.8)
9964 | 2-L APPROX. 9HPPING WEIGHT LB(KG) 275 (129.8)

- · HEAVY-DUTY STAINLESS STEEL CONSTRUCTION
- · TWO STAINLESS STEEL I G"W. X 2 4"D. FOLD-DOWN SIDE SHELVES
- · TOWEL/UTENOIL POD
- · LAPACE CAPACITY OTORAGE DRAWER FOR PROTECTING ITEMO AGAINOT THE ELEMENTO
- · FOUR LARGE BLACK LOCKING CAGTERG PROVIDE MANEUVERABILITY AG WELL AG STABILITY
- · TWO 15,000 BTU SIDE BURNERS
- · ELECTRONIC IGNITION POWERED BY A 9 YOLT BATTERY
- · EQUIPPED WITH POPCELAINIZED "Y" GRATEG
- · PROTECTIVE STAINLESS STEEL COVER




OUTDOOR CHARCOAL CERAMIC COOKING CAPSULE ACCESSORIES

64 YINXL GOVERS


 CV 2 O C 4 - C 2 O "W. CAPT
 APPPOX. OHIPPING WEIGHT LE(FG)
 5 (2.9)

 CV 9 O C 4 - C 9 O "W. CAPT
 APPPOX. OHIPPING WEIGHT LE(FG)
 8 (9.6)

 CV 4 | C 4 - C O E 4 | "W. CAPT W/O E
 APPPOX. OHIPPING WEIGHT LE(FG)
 1 O (4.5)



[·] AVAILABLE IN 612E6 TO FIT ALL MODELS



Y-PACK AND DPIP PAN

CYD APPROX. GHIPPING WEIGHT LB(KG) 4 (1.8)

- · NO STICK V-PACK CAN BE USED FOR COOKING POASTS, HAMS, PIBS, ETC.
- · DPIP PAN CATCHEG DPIPPINGG FROM ITEMG COOKED IN V-PACK TO GENERATE FLAVOR AND PREVENT FLARE-UPG



WATER PAN AND RACK

CWP APPROX. GHIPPING WEIGHT LEG(KG) 9 (1.4)


- · WATER PAN AND RACK ARE CONSTRUCTED OF STAINLESS STEEL TO RESIST RUSTING
- · LARGE CAPACITY WATER PAN HOLDS ONE GALLON OF WATER, WHICH IS ENOUGH FOR APPROXIMATELY SIX HOURS OF COOKING
- · PIGID OTAINLEGO OTEEL PACK HOLDO WATER PAN GEOURELY



PIZZA STONE

GPS APPROX. SHIPPING WEIGHT LB(KG) 10(4.5)

- · CONSTRUCTED OF HEAVY-DUTY CERAMIC MATERIAL
- · 151/2" DIAMETER ACCOMMODATES LARGE SIZE PIZZAS
- · ENGRAYED YIKING LOGO LOCATED IN CENTER OF STONE




30"W. ELECTRIC SMOKER OVEN

VE09100T

APPROX. GHIPPING WEIGHT LEG(KG)

260 (117.0)



- · AGENCY CERTIFIED FOR OUTDOOR USE
- · EXCLUGIVE PLENUM GYGTEM MIXEG HEAT, WATER VAPOR AND GMOKE FOR PERFECT COOKING ENVIRONMENT
- · CAN BE UGED FOR HOT OR COLD GMOKING AG WELL AG GTANDARD BAKING
- · 120 YOLT, THERMAL CONVECTION OVEN
- · 1.5 GALLON WATER PAN
- · 1.5 GALLON DPIP PAN
- · LARGE CAPACITY GMOKER BOX CAN ACCOMMODATE LARGE QUANTITIES OF WOOD CHIPS OR CHUNKS OF WOOD FOR SMOKING
- · LAPGE OVEN CAVITY
- · 20"W. X 15"H. X 16"D.
- · 9.2 CUPIC FEET
- · CAN ACCOMMODATE UP TO 40 LIBG. OF MEAT
- · THREE HEAVY-DUTY RACKG/GIX POGITIONG
- · COMMERCIAL TYPE CONSTRUCTION, DESIGN AND STYLING
- · FIVE-YEAR LIMITED HEATING ELEMENT
- · LIFETIME LIMITED STAINLESS COMPONENTS


VEOG GERIEG GMOKER OVEN

- · 4 FOOT FLEXIBLE STEEL CONDUIT WITH OVEN
- · 9 WIFE WITH APOUND
- · 120 Y/60H2 30 AMP
- · MAXIMUM AMPO 17.1

FINIOH DETAILS

OUTDOOR GAS AND ELECTRIC OVENS

- · STAINLESS STEEL (SS)
- · BRAGO TRIM OPTION (BP) INCLUDEO NAMEPLATE, DRAWER HANDLE/BRACKETO, AND KNOB BEZEL. OUPER DURABLE, LONG LAGTING BRAGO FINIOH ON "HIGH TRAFFIC" PARTO (HANDLEO/BRACKETO); ALL OTHER PARTO HAYE A DURABLE PROTECTIVE COATING. ALL PARTO DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.



26"W. OUTDOOR GAG OVEN

VGOO 2 GOTN NATURAL VGOO 2 GOTL LP/PROPANE

APPROX. SHIPPING WEIGHT LEG(FG)

196(88.2)

APPROX. GHIPPING WEIGHT LEG(KG)

196(88.2)

- · HEAVY-DUTY STAINLESS STEEL CONSTRUCTION
- · OUTDOOR APPROVED GAG OVEN
- · ELECTRONIC IGNITION POWERED BY A 9 YOLT BATTERY
- · 181/0"W. X 121/2"H. X 181/4"D. OVEN CAVITY
- · 2.5 CUBIC FEET
- · THREE HEAVY-DUTY PACKG/FOUR POGITIONS
- · FIVE-YEAR LIMITED TUBE BURNERS
- · TEN-YEAR LIMITED PORCELAIN OVEN

V460 OUTDOOR OVEN

- · OVEN GHOULD BE OPDEPED FOR UGE WITH LP/PROPANE (L) OP NATURAL GAG (N)
- · OVENG OPDERED FOR UGE WITH LP/PROPANE GAG EQUIPPED WITH A HIGH CAPACITY HOGE/REGULATOR AGGEMBLY FOR CONNECTION TO A STANDARD 5 GALLON, 20 LB. LP/PROPANE GAG CYLINDER WITH TYPE 1, GCC-1 CONNECTION OR STAND 1/2" (1.9 CM) ID GAG GERVICE LINE
- · OVENS OPDEPED FOR USE WITH NATURAL GAS PEQUIPE STANDARD RESIDENTIAL 1/2" (1.9 CM) ID GAS SERVICE LINE

FINIOH DETAIL

- · OTAINLEGG OTEEL (GG)
- · BRAGG TRIM OPTION (BP) INCLUDEG NAMEPLATE, HANDLE/BRACKETG AND KNOB BEZEL. GUPER DURABLE, LONG LAGTING BRAGG FINIGH ON "HIGH TRAFFIC" PARTG (HANDLEG/BRACKETG); ALL OTHER PARTG HAVE DURABLE PROTECTIVE COATING. ALL PARTG DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.

BUILT-IN GAS SIDE BURNERS & INFRARED GRILLERS


DOUBLE GIDE BURNER

 VAGO I 5 2 T-N NATURAL
 APPROX. GHIPPING WEIGHT LO(KG)
 80 (96.9)

 VAGO I 5 2 T-L LP/PROPANE
 APPROX. GHIPPING WEIGHT LO(KG)
 80 (96.9)

- · TWO 15,000 BTU BURNERS
- · HEAVY-DUTY STAINLESS STEEL CONSTRUCTION
- · ELECTRONIC IGNITION POWERED BY A 9 YOLT BATTERY
- · EQUIPPED WITH POPCELAINIZED "Y" GRATES
- · PROTECTIVE STAINLESS STEEL COVER PROVIDED
- · FOR BUILT-IN INSTALLATION ONLY


MUST SPECIFY NATURAL GAS (N) OF LP/PROPANE (L)



OUTDOOF WOK

YAWT 2 4 | T-N NATURAL APPROX. SHIPPING WEIGHT LEG(FG) | 45 (66.0) YAWT 2 4 | T-L LP/PROPANE APPROX. SHIPPING WEIGHT LEG(FG) | 45 (66.0)

- · AGENCY CEPTIFIED FOR OUTDOOP USE
- · 1-27,500 BTU POPCELAIN/CAGT IPON BUPNEP
- · ELECTRONIC IGNITION POWERED BY A 9 YOLT BATTERY
- · 20" STAINLESS STEEL WOK/TOP STANDARD
- · TWO-PIECE POPCELAIN/CAST IPON GRATE
- · EXCLUDIVE AGENCY CERTIFIED CENTER TRIVET ALLOWO USE OF LARGE STOCK POTS
- · OTAINLEOO OTEEL DRIP TRAY ON OTAINLEOO OTEEL BALL BEARING ROLLER GLIDEO
- · HEAVY-DUTY STAINLESS STEEL COVER
- · FIVE YEAR LIMITED WARRANTY BURNER
- · LIFETIME LIMITED WARPANTY ALL STAINLESS STEEL COMPONENTS



TRUGEAR INFRARED CRILLER

 YAIB I 5 I T-N NATURAL
 APPROX. GHIPPINA WEIGHT LB(KG)
 55 (24.8)

 YAIB I 5 I T-L LP/PROPANE
 APPROX. GHIPPINA WEIGHT LB(KG)
 55 (24.8)

 YAIB 2 4 2 T-N NATURAL
 APPROX. GHIPPINA WEIGHT LB(KG)
 55 (24.8)

 YAIB 2 4 2 T-L LP/PROPANE
 APPROX. GHIPPINA WEIGHT LB(KG)
 55 (24.8)

- · CONSTRUCTED OF HEAVY-DUTY INCONEL STAINLESS STEEL
- · 2 1,500 BTUG HIGH
- · 14,500 BTUG-LOW
- · ELECTPONIC IGNITION POWERED BY A 9 YOLT BATTERY
- · POPCELAINIZED COOKING GPIDG
- · PROTECTIVE STAINLESS STEEL COVER PROVIDED
- · FOR BUILT-IN INSTALLATION ONLY

OUTDOOR SIDE BURNERS AND WOR/GOOKER

- · ELECTRONIC IGNITION
- · UNIT MUST BE ORDERED NATURAL OR LP/PROPANE UNIT 16 NOT FIELD CONVERTIBLE (WOR/COOKER ONLY)

FINIOH DETAILS

- · OTAINLEOO OTEEL (OO) BLACK PORCELAIN CRATEO; OTAINLEOO OTEEL CONTROL PANEL, CRATE OUPPORT, LANDING LEDGE AND DRIP TRAY PULL; BLACK KNOBO
- · BRAGO TRIM OPTION (BR) INCLUDED DRIP TRAY
 PULL, NAMEPLATE, AND FNOB BEZEL(G). ALL HAVE A
 PROTECTIVE COATING FOR MAINTENANCE-FREE
 NORMAL USE.

YAIB OUTDOOR BUILT-IN AAG TRUGEARM INFRARED ARILLER

- · YAIB SHOULD BE OPDEPED FOR USE WITH LP/PROPANE (L) OP NATURAL (AS (N)
- · YAIB ORDERED FOR USE WITH LP/PROPANE GAS EQUIPPED WITH A HIGH CAPACITY HOSE/REGULATOR

AGGEMBLY FOR CONNECTION TO A GTANDARD 5 CALLON, 20 LB. LP/PROPANE GAG CYLINDER WITH TYPE 1, 906-1 CONNECTION OR STAND 1/2"

(1.9 CM) ID GAG GERVICE LINE

· YAID ORDERED FOR USE WITH NATURAL AAS PEQUIRE STANDARD RESIDENTIAL 1/2" (1.9 CM) ID AAS SERVICE LINE

FINISH DETAILS

- · GTAINLEGG GTEEL (GG)
- · BPAGG TPIM OPTION (BP) INCLUDEG NAMEPLATE AND FNOB BEZEL. GUPEP DUPABLE, LONG LAGTING BPAGG FINIGH ON "HIGH TPAFFIC" PARTG (HANDLEG/BPACKETG); ALL OTHER PARTG HAVE DUPABLE PROTECTIVE COATING. ALL PARTG DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.

OUTDOOR WARMING DRAWERS

YEWD 1 7 9 T 2 7 "W. APPROX. OHIPPING WEIGHT LE(KG) 95 (4 2.8)
YEWD 1 0 9 T 90 "W. APPROX. OHIPPING WEIGHT LE(KG) 1 08 (4 8.6)
YEWD 1 6 9 T 96 "W. APPROX. OHIPPING WEIGHT LE(KG) 1 2 4 (5 5.8)

- · AGENCY CERTIFIED FOR OUTDOOR USE
- · LAPGEST DPAWER PAN AVAILABLE
- · 27"W. MODEL: 1719/16"W. X 6"H. X 22%"D. 1.4 CU. FT.
- · 90"W. MODEL: 2012"W. X 6"H. X 2234"D. 1.6 CU. FT.
- · 76"W. MODEL: 25"W. X 6"H. X 2 23"D. 2.0 CU. FT.
- · EXCLUGIVE ONLY 96"W. WAPMING DPAWER AVAILABLE
- · EXCLUSIVE TWO HALF-SIZED LOW PACKS AND MOISTURE CUP STANDARD
- · STAINLESS STEEL LOW PACKS WITH SLOTS FOR HEAT DISTRIBUTION
- · PARTIALLY FILL MOISTURE CUP WITH WATER TO INCREASE MOISTURE IN PAN
- · ENTIPE DRAWER PEMOVES FOR EASY CLEANING
- · 2 7"W. MODEL 4 25 WATT ELEMENT
 - 90"W. MODEL 450 WATT ELEMENT
 - 96"W. MODEL 550 WATT ELEMENT
- · TEMPERATURE GETTINGG FROM 900F TO 2500F
- · MOIGTUPE GELECTOP CONTPOL
- · STAINLESS STEEL POLLER BEARING GLIDES
- · COMMERCIAL-TYPE GIZE, CONGTRUCTION, DEGICN, AND GTYLING
- · FIVE-YEAR LIMITED HEATING ELEMENT
- · LIFETIME LIMITED ALL STAINLESS STEEL COMPONENTS

YEWD GEPIEG WAPMING DPAWERG

- · HAPD WIPE DIRECT WITH 2 WIPE WITH GROUND
- · 1204/50-60 HZ
- · YEWD 1 7 2T MAXIMUM AMPS 9.6
- · YEWD I O2T MAXIMUM AMPG 3.8
- · YEWD I G2T MAXIMUM AMPG 4.6

FINIOH DETAILS


- · GTAINLEGG GTEEL (GG)
- · ALL MODELO HAVE A BLACK KNOB, BRUGHED OTAINLEGO OTEEL FINIOH VERTICAL/HORIZONTAL TRIM, AND OTAINLEGO OTEEL DOOR HANDLEG WITH CHROME PLATED BRACKETS.
- · BPAGG TPIM OPTIONG (BP.) INGLUDEG NAMEPLATE, DPAWEP HANDLE/BPACKETG, AND KNOB BEZEL. GUPEP DUPABLE, LONG LAGTING BPAGG FINIGH ON "HIGH TPAFFIC" PAPTG (HANDLEG/BPACKETG); ALL OTHEP PAPTG HAYE A DUPABLE PROTECTIVE COATING. ALL PARTG DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.

PAN/LID GET

PAN-YEWD APPROX. GHIPPING WEIGHT LE(KG) 10(4.5)

- · FIVE COMMERCIAL PANG WITH LIDG
 - · TWO 21/2"D. X 1 2"L. X 7"W.
 - · TWO 4"D. X 1 2"L. X 7"W.
- · ONE 4"D. X | 2"L. X | 01/2"W.
- · HEAVY GAUGE STAINLESS STEEL





OUTDOOR STORAGE DRAWERS

 6D 1 70 T 2 7"W.
 APPROX. OHIPPING WEIGHT LB(FG)
 86 (98.7)

 6D 1 00 T 90"W.
 APPROX. OHIPPING WEIGHT LB(FG)
 97 (49.5)

 6D 1 60 T 96"W.
 APPROX. OHIPPING WEIGHT LB(FG)
 [12 (50.4)

- · COMMERCIAL-TYPE GIZE, CONGTRUCTION, DEGICH AND GTYLING
- · SEALED FOR PROTECTION AGAINST THE ELEMENTS
- · OTAINLEGG OTEEL POLLEP BEAPING GLIDEG
- · EXTRA LARGE CAPACITY FOR STORING 19199 TOOLS, ACCESSORIES AND SEASONINGS
- · 27"W. MODEL: 219/0"W. X 29"D. X 57/0"H. 1.7 CU. FT.
- · 90"W. MODEL: 241/2"W. X 29"D. X 57/8"H. 1.9 CU. FT.
- · 96"W. MODEL: 901/0"W. X 29"D. X 57/0"H. 2.4 CU. FT.
- · CAN BE BUILT-IN INDOOPS AS WELL AS OUTDOOPS




OUTDOOR ACCESS DOORS

ALLEGO DOOPS

AD 1 62 OT SINGLE ACCESS DOOP. APPROX. SHIPPING WEIGHT LE(FG) 50 (22.5)
AD 282 OT DOUBLE ACCESS DOOP. APPROX. SHIPPING WEIGHT LE(FG) 75 (92.8)

- · PUGGED STAINLESS STEEL CONSTRUCTION
- · OTAINLEGG OTEEL TUBULAR HANDLEG
- · HIDDEN PIVOT POINT HINGES
- · EACH DOOP IS APPROXIMATELY I G"W. \times 20"H.; OVER ALL DIMENSIONS ARE APPROXIMATELY 92"W. \times 29"H. ON DOUBLE ACCESS DOOPS AND APPROX. 20"W. \times 29"H. ON SINGLE ACCESS DOOPS



OUTDOOR STAINLESS STEEL CABINETS

90"D. GPILL BAGE AND 90"D. GPILL BAGE WITH WAPMING DPAWER ACCEGG*

49809021 FOR 90"W. GPILL APPROX. GHIPPING WEIGHT LEG(KG) 162 (72.9) YABO4121 FOR 42"W. APILL APPROX. GHIPPING WEIGHT LEGIKG) 210(94.5) 49005922 FOR 59"W. GPILL APPROX. SHIPPING WEIGHT LEG(KG) 254(114.3) VAWO9010 FOR 90"W. APILL \$ 90" WIDE WARMING DRAWER APPROX. GHIPPING WEIGHT LEG(KG) 158(71.1) VAWO4 120 FOR 42 "W. CIPILL \$ 96" WIDE WARMING DRAWER APPROX. GHIPPING WEIGHT LEXIFG) 201 (90.5) YAWOSOII FOR SOMW. APILL & OG" WIDE WARMING DRAWER APPROX. GHIPPING WEIGHT LEGKG) 290(109.5)

90"D. OUTDOOR STAINLESS STEEL CABINETS

YEBO 160 1 90"D. GIDE BURNER/INFRARED GRILLER BAGE YEBO 2 60 2 90"D. WOK, PEFPEGHMENT CENTER, IP GRILLER BAGE YBO 1811 18"W/90"D. BAGE CABINET-ONE DRAWER, ONE DOOR YBO 1890 18"W./90"D. BAGE CABINET-THREE DRAWERG YOBO 2402 24"W/70"D. ONE BAGE VOB01602 16"W/10"D. OINK BAGE VTP0181018"W./90"D. TPAGHPULLOUT

- APPROX. GHIPPING WEIGHT LEG(KG) 82 (26.9) APPROX. GHIPPING WEIGHT LEG(KG) 112(50.4) APPROX. GHIPPING WEIGHT LEG(KG) 85 (78.7) APPROX. GHIPPING WEIGHT LEG(KG) 120(54) APPROX. GHIPPING WEIGHT LEGIKG) 84 (97.8) APPROX. GHIPPING WEIGHT LEG(KG) 119(50.9) 110(495) APPROX. GHIPPING WEIGHT LEG(KG)
- · COMMERCIAL-TYPE CONSTRUCTION, DESIGN AND STYLING
- · HEAVY-DUTY ALL STAINLESS STEEL CONSTRUCTION
- · FULLY CONCEALED DOOP HINGES
- · DRAWERS EQUIPPED WITH STAINLESS, FULL EXTENSION SLIDES
- · TWO-YEAR LIMITED DOOR HINGES AND DRAWER SLIDES
- · LIFETIME LIMITED WARPANTY PUST THROUGH ON ALL STAINLESS STEEL COMPONENTS

*NOTE - NEITHER GRILL NOR WARMING DRAWER 16 INCLUDED CABINETO AND MUOT BE PURCHAGED GEPARATELY. ALL CABINETS MUST BE INSTALLED WITH LOCALLY SUPPLIED COUNTERTOP.



FOR 30"W. GPILL



VaB04121 FOR 41"W. GPILL



Vabo5922 FOR 50"W. APILL



19W07010 FOR 90"W. GPILL \$ 90"W. WARMING DEAWER




V9W04120 FOR 41"W. GPILL \$ 26"W. WARMING DRAWER



19W05911 FOR 50"W. GRILL \$ OG"W. WARMING DEAWER



VBB01601 90"D. 61DE BUPNEP/INFPAPED CIPILLER BAGE



VKB02602 20"D.



VB01811 18"W./90"D. BAGE CABINET



VB01890 18"W./90"D. BAGE CABI-NET




VOB02402 24"W./70"D. GINK BAGE




VTP01810 18"W./70"D. TEAGH PULLOUT

WOK, PEFPEGHMENT CENTER, IF GEILLER BAOE


161




YEU09202



VER-09200



V4U07202





YEU09202 FOR 90"W. ELECTRIC SMOKER OVEN APPROX. GHIPPING WEIGHT LEG(KG) 275(124.7)

YERO9200 FOR 90"W. ELECTRIC SMOKER OVEN W/24"W. PEFPIGEPATOR

APPROX. GHIPPING WEIGHT LEG(KG) 255(115.7)

YGU09202 FOR 26"W. GAG OVEN

APPROX. SHIPPING WEIGHT LES(KG) 275(124.7)

YORO 9 200 FOR 26"W. GAG OYEN W/24"W. PEFRIGERATOR APPROX. GHIPPING WEIGHT LEG(KG) 255(115.7)

- · COMMERCIAL-TYPE CONSTRUCTION, DESIGN AND STYLING
- · HEAVY-DUTY ALL STAINLESS STEEL CONSTRUCTION
- · FULLY CONCEALED DOOR HINGES
- · TWO-YEAR LIMITED DOOR HINGES
- · LIFETIME LIMITED WARPANTY ALL STAINLESS STEEL COMPONENTS

*NOTE - NEITHER THE ELECTRIC OMORER OVEN NOR ANY REFRIGERA TION PRODUCT IS INCLUDED WITH THE CABINET AND MUST BE CHAGED GEPARATELY.


OUTDOOR STAINLESS STEEL CABINETS FOR UNDERCOUN-TER REFRIGERATION*

90"D. OUTDOOR GTAINLEGG GTEEL CABINETS FOR UNDERGOUTNER REFRIGERATION

YUPO 2 400 2 4"W. FOR 15"W PEFPIGEPATION APPROX. GHIPPING WEIGHT LEG(KG) 84 (97.8)

YURO9200 92"W. FOR 24"W REFRIGERATION APPROX. GHIPPING WEIGHT LEGIFG) 105 (46.7)

- · COMMERCIAL-TYPE CONSTRUCTION, DESIGN AND STYLING
- · HEAVY-DUTY ALL STAINLESS STEEL CONSTRUCTION
- · FULLY CONCEALED DOOP HINGES
- · TWO-YEAR LIMITED DOOR HINGES
- · LIFETIME LIMITED WAPPANTY ALL STAINLESS STEEL 60MPONENTO



*NOTE- PEFPIGEPATION PRODUCTO ARE NOT INCLUDED WITH THE CABINET AND MUOT BE PURCHAGED GEPARATELY.

OUTDOOR STAINLESS STEEL CABINETS INSTALLATION ACCESSORIES

BAGE GIDE PANEL, FILLER GTRIP, INGIDE & OUTGIDE CORNER FILLER GTRIPG

VFLP 4 4"W. FILLER STRIP	APPROX. GHIPPING WEIGHT LEG(KG)	8 (7.6)
YOP 90 SIDE PANEL FOR 90"D. CABINETS	APPROX. GHIPPING WEIGHT LEG(KG)	26(11.7)
YCF90 90 DEGPEE6	APPROX. GHIPPING WEIGHT LEG(KG)	ら (2.3)
YOUF 90 90 DEGREE OUTER CORNER FILLER	APPROX. GHIPPING WEIGHT LEG(KG)	ら (2.3)
YOF 195 DEGREEG	APPROX. GHIPPING WEIGHT LEG(KG)	ら (2.3)
YOCF 195 195 DECREE OUTER CORNER FILLER	APPROX. GHIPPING WEIGHT LEG(KG)	ら (2.3)
VTOP90 90"W./68"W. OVEN TOWER OIDE PANEL	APPROX. GHIPPING WEIGHT LEG(KG)	52 (23.6)
YHOP 90 26"W./26"W. OYEN TOWER "HALF" OIDE PANEL	APPROX. SHIPPING WEIGHT LEG(KG)	29(12.2)

BACK PANELO

YIP 1 6 FOR YBO 1 60 1	APPROX. SHIPPING WEIGHT LEG(KG)	26(11.7)
YIP 18 FOR YBO 1811 AND YBO 1890	APPROX. GHIPPING WEIGHT LEG(KG)	26(11.7)
VIP 2 4 FOR YOBO 2 4 0 2 AND YURO 2 4 0 0	APPROX. GHIPPING WEIGHT LEG(KG)	26(11.7)
VIP 26 FOR VKBO 260 2	APPROX. GHIPPING WEIGHT LEG(KG)	26(11.7)
VIPTO FOR VAROTO21 AND VAWOTO10	APPROX. GHIPPING WEIGHT LEG(KG)	26(11.7)
YIP 9 2 FOR YURO 9 200	APPROX. GHIPPING WEIGHT LEG(KG)	26(11.7)
VIP 96 FOR 46150 960 2	APPROX. GHIPPING WEIGHT LEG(KG)	26(11.7)
VIP4 FOP V91504 2 AND V9W04 20	APPROX. GHIPPING WEIGHT LEG(KG)	26(11.7)
VIP57 FOR VABO5922 AND VAWO5911	APPROX. GHIPPING WEIGHT LEG(KG)	26(11.7)
VEPFLE 4 FOR VFLE 4 FILLER STRIP	APPROX. GHIPPING WEIGHT LEG(KG)	8 (7.6)
YTBP92 FOR YEUO/YERO/YGUO/YGRO	APPROX. GHIPPING WEIGHT LEG(KG)	52(27.6)

OUTDOOR WALL HOODS - 18"H./27"D.

 YWH9078T 90"W.
 APPEOX. OHIPPING WEIGHT LEX(FG)
 74 (99.9)

 YWH4878T 40"W.
 APPEOX. OHIPPING WEIGHT LEX(FG)
 94 (42.9)

 YWH6078T 60"W.
 APPEOX. OHIPPING WEIGHT LEX(FG)
 [14 (51.9)

- · AGENCY CEPTIFIED FOR OUTDOOP USE
- · CANOPY ONLY; MUST ALSO PUPCHASE INTERIOR OF EXTERIOR VENTILATOR HIT, SOLD SEPARATELY
- · VAPIABLE SPEED VENTILATOR CONTROLS; SEPARATE CONTROLS FOR ON/OFF AND SPEED CONTROL
- · HALOGEN LIGHTS WITH DIMMER CONTROL; SEPARATE CONTROLS FOR ON/OFF AND DIMMER
- · DIGHWAGHER-GAFE COMMERCIAL-TYPE GG BAFFLE FILTERG
- · SEPAPATE PEMOVABLE APEASE TROUGH FOR EASY CLEANING
- · HEAT GENGOP AUTOMATICALLY TUPNG VENTILATOR ON FULL POWER WHEN EMPERATURES PEACH UNCOMFORTABLE LEVELS
- · VIRTUALLY SEAMLESS STAINLESS STEEL CANOPY INTERIOR FOR EASY CLEANING
- · YIKING OUTDOOR HOODS SHOULD BE INSTALLED IN A COYERED, NON-ENCLOSED AREA AND SHOULD BE PROTECTED FROM THE ELEMENTS AS MUCH AS POSSIBLE



ACCESSORY PAIL OPTION FOR OUTDOOP WALL HOODS

- · AVAILABLE IN 60/CHROME (CR) OR BRAGG (BR); 60/CHROME INCLUDEG A GTAINLEGG GTEEL RAIL WITH CHROME GUPPORTG/BRACKETG AND HOOKG; BRAGG INCLUDEG BRAGG RAIL, GUPPORTG/BRACKETG, HOOKG AND NAMEPLATEG; ALL BRAGG COMPONENTG HAVE A PROTECTIVE COATING FOR MAINTENANCE-FREE NORMAL UGE.
- · FRONT OF HOOD
- · HOOKS FOR PACKS INCLUDED
- · ADD OPTION CODE (CF OF BF) TO END OF MODEL NUMBER (AFTER COLOR CODE)
- · ADD OPTION COST TO WALL HOOD COST

FINIOH DETAILS

· GTAINLEGG GTEEL (GG)

IMPORTANT: VIKING VENTILATOR KITS ARE DESIGNED SPECIFICALLY FOR USE WITH VIKING HOODS.
USE OF NON-VIKING VENTILATOR KIT MAY VOID THE HOOD WARRANTY.

OUTDOOR WALL HOOD ACCESSORIES

VIVI 200 1200 CFM INTERIOR-POWER VENTILATOR FIT YEY | 200 | 200 OFM EXTERIOR-POWER YENTILATOR KIT YEV 1500 1500 CFM EXTERIOR-POWER VENTILATOR FIT APPROX. GHIPPING WEIGHT LIB.(FG) 47 (21.9)

APPROX. SHIPPING WEIGHT LB.(KG) 49 (19.4) APPROX. SHIPPING WEIGHT LES. (FG) 50 (20.9)

· FIVE YEAR LIMITED WARRANTY - MOTOR

DUCT GOVERS

DOW96T 96"W. APPROX. GHIPPING WEIGHT LES. (FG) 11 (5.0) DOW48T 48"W. APPROX. SHIPPING WEIGHT LED. (KG) 14 (6.9) DOWGOT GO"W. APPROX. SHIPPING WEIGHT LED. (FG) 24 (10.8)


- · EXTENDS HEIGHT OF HOOD BY 12"; CONCEALS DUCT
- . 12"0
- · SPECIFY FINISH

BACKOPLAGHEG

BK03636"W. APPROX. SHIPPING WEIGHT LED.(FG) 9 (4.1) BK948 48"W. APPROX. SHIPPING WEIGHT LES.(KG) 14 (6.3) BK960 60"W. APPROX. GHIPPING WEIGHT LES.(KG) 20 (9.0)

- · HEMMED EDGES WITH SOPEW HOLES
- · FAGTENING GOPEWG INCLUDED
- · カロ"H.
- · STAINLESS STEEL ONLY

BUILT-IN/PORTABLE REFRESHMENT CENTERS



BUILT-IN 2 4"W. PEFPEGHMENT CENTER

YBPC241 APPROX. GHIPPING WEIGHT LB.(KG) 82 (96.9)

- · COMMERCIAL-GTYLE APPEARANCE/DEGIGN
- · COLD WATER GINK WITH PROFEGGIONAL STYLE FAUCET
- · FOUR DEEP STAINLESS STEEL CONDIMENT BINS
- · BOTTLE BATH KEEPS DRINKS AND OTHER ITEMS COLD
- CUTTING BOARD WHICH GLIDES TO FIT OVER SINK
- · HIGH-GHELF WITH PAIL CONVENIENTLY HOLDG DPINK GLAGGEG AND OTHER ITEMG
- · SPEED PAIL HOLDS FIVE STANDARD WIN OF LIQUOR BOTTLES
- · BOTTLE OPENER WITH BOTTLE CAP CATCH

BUILT-IN 4 1 "W. PEFPEGHMENT CENTER


YERO410 APPROX. SHIPPING WEIGHT LEX.(KG) 905(197.9)



- · COMMERCIAL-GTYLE APPEARANCE/DEGIGN
- · COLD WATER SINK WITH PROFESSIONAL STYLE FAUCET
- · BIN BEHIND GINK IG LAPGE ENOUGH TO HOLD DPINK/JUICE CONTAINERG AND 2-LITER BOTTLEG
- · FOUR 6"W. X 4"D. STAINLESS STEEL CONDIMENT BINS
- · CUTTING BOARD WHICH GLIDEG TO FIT OVER GINK
- · HIGH-GHELF WITH PAIL CONVENIENTLY HOLDS DRINK GLASSES AND OTHER ITEMS
- · INGULATED BOTTLE BATH HOLDS TWO CASES OF DRINKS
- · SPEED PAIL HOLDS FIVE STANDARD WINE OF LIQUOR BOTTLES
- · BOTTLE OPENER WITH BOTTLE CAP CATCH
- · STOPAGE DRAWER PROTECTS ITEMS AGAINST THE ELEMENTS
- · PULLOUT TRAGH CONTAINER IS REMOVABLE FOR EASY USE



YPEC410 APPEOX. SHIPPING WEIGHT LES.(FG) 917(142)



- · COMMERCIAL-STYLE APPEARANCE/DESIGN
- · COLD WATER GINK WITH PROFESSIONAL STYLE FAUCET
- · BIN BEHIND GINF LARGE ENOUGH TO HOLD GALLON DRINF CONTAINERG AND 2 LITER BOTTLEG
- · FOUR 6"W. X 4"D. STAINLESS STEEL CONDIMENT BINS
- · CUTTING BOARD WHICH GLIDES TO FIT OVER SINK
- · ONE 16"W. X 24"D. FOLD-DOWN LEFT GIDE GHELF
- · FOLD-DOWN SHELF IN BACK PROVIDES ADDITIONAL SUPFACE AREA
- · HIGH-GHELF WITH PAIL CONVENIENTLY HOLDG DPINK GLAGGEG AND OTHER ITEMS
- · INGULATED BOTTLE BATH LOCATED UNDER COUNTERTOR GURFACE HOLDG LARGE AMOUNTS OF ICE REEPING DRINKS COLD
- · SPEED PAIL HOLDS FIVE STANDARD WINE OF LIQUOR BOTTLES
- · BOTTLE OPENER WITH BOTTLE CAP CATCH
- · LAPAE CAPACITY OTOPACE DPAWEP PPOTECTO ITEMO AGAINOT THE ELEMENTO
- · PULLOUT TRAGH CONTAINER 16 REMOVABLE FOR EAGY UGE
- · FOUR HEAVY-DUTY CAGTERS PROVIDE MANEUVERABILITY AS WELL AS STABILITY

YBPC/YPPC PEFPEGHMENT CENTERG FINIGH DETAILG


- · OTAINLEOO OTEEL (OO)
- · BRAGG TRIM OPTION (BR) INCLUDEG NAMEPLATE AND DOOR HANDLE/BRACKETG. GUPER DURABLE, LONG LAGTING BRAGG FINIGH FOR "HIGH TRAFFIC" PARTG (HANDLE); ALL OTHER PARTG HAVE A DURABLE PROTECTIVE COATING. ALL PARTG DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.

OUTDOOR UNDERCOUNTER/FREESTANDING REFRIGERATED BEVERAGE CENTERS

YUAP I SOTE GOLID (PIGHT HINGE)
YUAP I SOTL GOLID (LEFT HINGE)

APPROX. GHIPPING WEIGHT LEX.(FG) 110(49.5)
APPROX. GHIPPING WEIGHT LEX.(FG) 110(49.5)

- · AGENCY CERTIFIED FOR OUTDOOR USE
- · COMMERCIAL-GTYLE APPEARANCE/DEGICN
- · 9.0 CUBIC FEET OF STOPAGE
- · TWO FULL-DEPTH WIFE GHELVEG
- · ONE FULL-DEPTH TEMPERED GLAGO SHELF CREATED DIGTINGT TEMPERATURE 20NE FOR WINE STORAGE
- · WINE PACK SHELF HOLDS FIVE BOTTLES OF WINE AND PULLS OUT FOR EASY ACCESS
- · TEMPERATURE ADJUGTO FROM 99 950F TO 54 560F
- · AUTOMATIC CYCLE DEFPOST
- · INTERIOR LIGHT TURNS ON WHEN DOOR IS OPENED
- · MUST BE OPDEPED PIGHT OF LEFT HINGE
- · INSTALL AS UNDERCOUNTER OR FREESTANDING UNIT
- · GTAINLEGG GTEEL EXTEPIOR CABINET GURPOUNDG UNIT AND FORMG A WATER REGIGTANT GEAL
- · INOULATED ELECTRICAL TERMINALO, SEALED ELECTRICAL CONTACTO AND WATER REGISTANT THERMOSTAT
- · FIVE-YEAR LIMITED WARRANTY GEALED GYGTEM



2 4"W. OUTDOOP UNDERCOUNTER/FREESTANDING PEFRIGERATED BEVERAGE CENTER


YUAP (40TP GOLID (PIGHT HINGE)

APPROX. GHIPPING WEIGHT LB.(FG) (69.0)

YUAP (40TL GOLID (LEFT HINGE)

APPROX. GHIPPING WEIGHT LB.(FG) (409.0)

- · AGENCY CERTIFIED FOR OUTDOOR USE
- · COMMERCIAL-GTYLE APPEARANCE/DEGICN
- · 6. I CUBIC FEET OF STOPAGE
- · TOP WIRE SHELF HAS GIV!" FLIP UP SECTION TO CHILL OR STORE OPEN WINE BOTTLES OR LARGE CONTAINERS
- · TWO FULL-DEPTH CLAGO OHELVEO WITH TOP WIRE OHELF HOLD 148 12-OUNCE CANO
- · TWO WIFE GHELVEG CRADLE I 4 BOTTLEG IN HORIZONTAL POGITION TO KEEP CORKG MOIGT · GHELVEG CAN BE REMOVED TO GTORE LARGER BOTTLEG
- · FULL-DEPTH GHELYEG OPEATE DIGTINOT TEMPERATURE 20NEG FOR WINE GTORAGE
- · TEMPERATURE ADJUSTS FROM 99 950F TO 54 560F
- · INTERIOR LIGHT TURNS ON WHEN DOOR IS OPENED
- · MUST BE OPDEPED PIGHT OF LEFT HINGE
- · INGTALL AG UNDERCOUNTER OF FREEGTANDING UNIT
- · OTAINLEOG OTEEL EXTERIOR CABINET OURROUNDS UNIT AND FORMS A WATER REGIOTANT SEAL
- · INGULATED ELECTPICAL TEPMINALO, GEALED ELECTPICAL CONTACTO, AND WATER PEGIGTANT THERMOGTAT
- · FIVE-YEAR LIMITED WARRANTY GEALED GYGTEM



YUAP SEPIES PEFPIGEPATION PRODUCTS

ELECTPIC

- · 61/2 FT. COPD INCLUDED WITH UNIT
- · 2 WIPE WITH APOUND/9 PRONG PLUG
- · 1 154/60HZ; MAXIMUM AMPG -

15" = 9.0, 24" = 9.9


FINIOH DETAILS

- . 60LID DOOR
- · AVAILABLE IN OTAINLEGG STEEL (GG)
- · OTAINLEOO OTEEL HANDLE WITH CHROME PLATED BRACKETO AND OTAINLEOO OTEEL EXTERIOR CABINET
- BPAGG TPIM OPTION (BP) INCLUDEG NAMEPLATE AND DOOP HANDLE/BPACKETG. GUPER DURABLE, LONG LAGTING BRAGG FINIGH FOR "HIGH TRAFFIC" PARTG (HANDLE); ALL OTHER PARTG HAVE A DURABLE PROTECTIVE COATING. ALL PARTG DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.

OUTDOOR UNDERCOUNTER/FREESTANDING 15"W. ICE MACHINE AND ACCESSORY

1 5"W. OUTDOOP UNDEPLOUNTEP/FPEEDTANDING ICE MACHINE

YUIM 150T (P/L*) GOLID DOOR APPROX. GHIPPING WEIGHT LEG. (FG) 110 (49.5)



- · COMMERCIAL-GTYLE APPEARANCE/DEGIGN
- · AGENCY CEPTIFIED FOR OUTDOOP USE
- · OTAINLEGG OTEEL EXTERIOR CABINET SURROUNDS UNIT AND FORMS A WATER REGISTANT SEAL
- · OTAINLEOO OTEEL KICKPLATE
- · STAINLESS STEEL COVERED ICE BIN FRONT
- · OPEPATING PANGE BETWEEN 450F (7.206) AND 1 100F (4906)
- · INGULATED ELECTPICAL TEPMINALO, GEALED ELECTPICAL CONTACTO AND WATER PEOIOTANT THERMOOTAT
- · PRODUCES UP TO 35 LESS. OF ICE PER DAY
- · HEAVY-DUTY ICE GLOOP INCLUDED
- · ¾" CUBE THICKNEGG
- · 95 LB /APA/ITY 1/E BIN
- · DPAINING PROCESS AUTOMATICALLY REMOVES OLD ICE TO ENSURE A CONSTANT SUPPLY OF FRESH ICE
- · EQUIPPED WITH CLEANING MODE
- · STAINLESS STEEL ICE CUTTER
- · INSTALL AS UNDERGOUNTER OF FREESTANDING UNIT
- · FIVE YEAR LIMITED WARRANTY GEALED GYGTEM

*P=PIGHT HINGE; L=LEFT HINGE

GEALED REGERYOIR DRAIN PUMP

· EXCLUDIVELY FOR ICE MACHINED

DP-VUIM

- · FOR USE WHEN FLOOP DRAIN IS NOT AVAILABLE
- · COMPLETELY SEALED PESERYOR
- · UNIT SHUTS OFF POWER TO ICE MACHINE IN THE EVENT OF A PUMP FAILURE
- · SPECIAL DESIGN MAKES THE POSSIBILITY OF FOREIGN MATERIAL CLOGGING PUMP VERY REMOTE
- · CHECK VALVE IN DIGCHARGE TUBE PREVENTS DIGCHARGED WATER FROM FLOWING BACK INTO THE PUMP
- · SUPPLIED WITH 2 WIFE WITH AROUND/9 PRONG PLUG FOR CONNECTION TO I I SY/GOHZ AND INCORPORATES A POWER RECEPTACLE INTO WHICH THE THE ICE MACHINE IS PLUGGED

APPROX. GHIPPING WEIGHT LB.(KG) 2 (0.9)

· INCLUDES PUMP AND OTHER PARTS/HARDWARE

YUIM GEPIEG ICE MACHINEG

ELECTRIC

- · 7 FT. CORD INCLUDED WITH UNIT
- · 2 WIFE WITH APOUND/9 PRONG PLUG
- · 1 154/60H2; MAXIMUM AMPG 9.0

FINIOH DETAILS

- · 90LID DOOR
- · AVAILABLE IN GTAINLEGG GTEEL (GG)
- · OTAINLEOO OTEEL HANDLE WITH CHROME PLATED BRACKETO AND BLACK EXTERIOR CABINET.
- · BPAGG TRIM OPTION (BP) INCLUDEG NAMEPLATE AND DOOP HANDLE/BPACKETG. GUPEP DUPABLE, LONG LAGTING BPAGG FINIGH FOR "HIGH TPAFFIC" PAPTG (HANDLE); ALL OTHEP PAPTG HAVE A DUPABLE PPOTECTIVE COATING. ALL PAPTG DEGIGNED FOR MAINTENANCE-FPEE NOPMAL UGE.


OUTDOOR UNDERCOUNTER/FREESTANDING 24"W. COMBINATION BEVERAGE CENTER/ICE MACHINE

2 4"W. COMBINATION BEVERAGE CENTER/ ICEMAKERO

YURI (40TR - GOLID (RIGHT HINGE) APPROX. GHIPPING WEIGHT LED. (RG) (G9.0)

YURI (40TL - GOLID (LEFT HINGE APPROX. GHIPPING WEIGHT LED. (RG) (40 (69.0)

- · AGENCY CERTIFIED FOR OUTDOOR USE
- · COMMERCIAL-GTYLE APPEARANCE/DEGICN
- · ONE FULL DEPTH PEMOYABLE WIRE SHELF AND 3 DOOR SHELVES
- · TEMPERATURE ADJUSTS FROM 99-45°F IN BEVERAGE SECTION
- · ICE MAKER PRODUCES UP TO 2 LIBS OF ICE PER DAY
- · ICE BIN STOPES UP TO 5 LBS OF ICE
- · TEMPERATURE ADJUGTO FROM 5-15° IN ICE MAKER GECTION
- · AUTOMATIC CYCLE DEFPOST
- · INTERIOR LIGHT TURNS ON WHEN DOOR IS OPENED
- · INSTALL AS UNDERCOUNTER OF FREESTANDING UNIT
- · OTAINLEOG OTEEL EXTERIOR CABINET OURROUNDS UNIT AND FORMS A WATER REGISTANT SEAL
- · INGULATED ELECTPICAL TEPMINALO, SEALED ELECTPICAL CONTACTS, AND WATER PESISTANT THERMOSTAT
- · ONE YEAR FULL WARRANTY COMPLETE UNIT; FIVE YEAR LIMITED WARRANTY SEALED SYSTEM



YUPI COMBINATION BEYERAGE CENTERG/ICEMAKERG ELECTRICAL


- · 7 FT. COPD INCLUDED WITH UNIT
- · 2 WIPE WITH APOUND/9 PRONG PLUG
- · 1 154/60H2; MAXIMUM AMPG 2.2

WATER

- · INLET WATER REQUIREMENTS 1/4 IN. COPPER TUBING
- · GOLID DOOR AVAILABLE IN GTAINLEGG GTEEL (GG)
- · BRAGG TRIM OPTION (BR) INCLUDEG NAMEPLATE, DOOR HANDLE/BRACKETG.
- · ALL BRAGG COMPONENTG HAVE A DUPABLE, PROTECTIVE COATING FOR
- · MAINTENANCE-FREE NORMAL USE.


24"W. PORTABLE/UNDERCOUNTER REFRIGERATED BEVERAGE DISPENSERS

2 4"W. PORTABLE PEFPIGERATED BEVERAGE DISPENSERS



YBRD (40TR GOLID (RIGHT HINGE) APPROX. GHIPPING WEIGHT LB.(FG) (77 (80.9)
YBRD (40TL GOLID (LEFT HINGE) APPROX. GHIPPING WEIGHT LB.(FG) (77 (80.9)

- · COMMERCIAL-GTYLE APPEARANCE/DEGICN
- · SPACIOUS INTERIOR IS CAPABLE OF HOLDING UP TO ONE HALF BARREL
- · EAGY-TO-CLEAN AND USE STAINLESS STEEL DISPENSING TOWER
- · FAUCET HANDLE OTANDAPD; THREADED HANDLE MOUNT WILL ALGO ACCEPT CUGTOM HANDLEG
- · DEGIGNED WITH 4 HEAVY-DUTY CAGTERG; TWO THAT ARE CAPABLE OF BEING LOCKED
- · OTAINLEGO OTEEL EXTEPIOR CABINET FORMO A WATER-REGIOTANT GEAL
- · APPROVED FOR INDOOR OR OUTDOOR USE
- · CAN BE INSTALLED FREESTANDING OF BUILT-IN
- · INOULATED ELECTPICAL TEPMINALO, OEALED ELECTPICAL CONTACTO AND A WATER-PEOIOTANT THERMOOTAT PROVIDE OPTIMAL PERFORMANCE IN ALL WEATHER ELEMENTO
- \cdot 5 LB (2.6 FG) CO2 CYLINDER, FEG COUPLER, AIR LINE WITH CLAMPS AND A SINGLE GAUGE REGULATOR-STANDARD WITH UNIT
- · TEMPERATURE ADJUGTABLE FROM 950 TO 540F (20 TO 1206)
- · SUITABLE FOR USE IN TEMPERATURES BETWEEN 450F (15.606) AND 1000F (97.906)
- · FIVE YEAR LIMITED WARRANTY GEALED REFRIGERATION GYGTEM



2 4"W. UNDERGOUNTER REFRIGERATED BEYERAGE DIGPENGERG

YUBD 1 4 OTE GOLD (PLAHT HINGE)

APPROX. GHIPPING WEIGHT LB.(FG) 1 4 0 (69.5)

YUBD 1 4 OTL GOLD (LEFT HINGE)

APPROX. GHIPPING WEIGHT LB.(FG) 1 4 0 (69.5)

- · SAME FEATURES AS PORTABLE MODEL EXCEPT AS NOTED BELOW:
- · BUILT-IN INSTALLATIONS ONLY
- · INCLUDES AN EASY TO CLEAN AND USE STAINLESS STEEL DISPENSING TOWER WHICH CAN BE MOUNTED TO COUNTERTOR
- · INCLUDEO FLANGED DRAIN PAN AND HOOE AGGEMBLY THAT CAN BE RECEGGED INTO COUNTERTOR
- · HAG 4 HEAVY-DUTY LEVELING LEGG (NO CAGTERG)
- · FIVE YEAR LIMITED WARRANTY SEALED REFRIGERATION SYSTEM

YRBD GERIEG BEYERAGE DIGPENGER

ELECTPIC

- · 8 FT. CORD INCLUDED WITH UNIT
- · 2 WIPE WITH APOUND/9 PRONG PLUG
- · 1 154/60HZ; MAXIMUM AMPG 2.2

FINIOH DETAILS

- · 60LID DOOR
- · AVAILABLE IN GTAINLEGG GTEEL (GG). THE GTAINLEGG GTEEL PRODUCT (GG) HAG A GTAINLEGG GTEEL HANDLE WITH CHROME PLATED BRACKETG AND GTAINLEGG GTEEL EXTERIOR CABINET.
- · BPAGG TRIM OPTION (BP.). INCLUDEG NAMEPLATE AND HANDLE/BPACKETG.
- · GUPER DURABLE, LONG LAGTING BRAGG FINIGH ON ALL "HIGH TRAFFIC" PARTO (HANDLE/BRACKETO); ALL OTHER PARTO HAVE A DURABLE PROTECTIVE COATING. ALL PARTO DEGIGNED FOR MAINTENANCE-FREE NORMAL UGE.

BEVERAGE DISPENSER ACCESSORIES

LEG LEYELER FIT


PW 200098 APPROX. SHIPPING WEIGHT LEX.(FG) 0.5 (0.9)

- · PEPLACES CASTERS ON PORTABLE BEVERAGE DISPENSER
- · INCLUDES FOUR LEVELING LEGS TO ATTACH THEM TO UNIT

1 at. (946 LITERS) CLEANING KIT

BDOK APPROX. GHIPPING WEIGHT LB.(14) 2.0 (0.9)

- · FOR USE IN CLEANING LINES AND FAUCET
- · EXCLUGIVELY FOR BEVERAGE DISPENSERS
- · INCLUDEO (9T. (.9 LITEPO) CLEANEP, TAP AND LINE CLEANEP, FAUCET WPENCH, AND FAUCET BRUGH



4 02. (1 18 ML) BOTTLE AND LINE CLEANING GOLUTION

BD402 APPROX. GHIPPING WEIGHT LB.(FG) 0.5 (0.9


· USE WITH CLEANING FIT TO CLEAN FAUCET AND BEYERAGE LINES



FAUGET LOCK

BOFLY APPROX. SHIPPING WEIGHT LB.(KG) 0.5 (0.9)

- · ALLOWS FAUCET TO BE LOCKED
- · KEYED ENTRY



AGENCY CERTIFICATIONS













GAG COOKING PRODUCTO

GAG COOKING VENTILATION PRODUCTS

PRODUCTS

VENTILATION PRODUCTS

ELECTRIC GOOKING

ELECTRIC COOKING PRODUCTS PRODUCTS

DUAL FUEL PANGES DUAL FUEL PANGES BUILT-IN BUILT-IN
PEFPIGEPATION PEFPIGEPATION
PPODUCTS PRODUCTS

UC/FO UC/FO PEFPIGEPATION PEFPIGEPATION PRODUCTS PRODUCTO

DIGHWAGHERG DIGHWAGHERG

COMPACTORS COMPACTORS

DISPOSEES

DISPOSERS

MICROWAVES MICROWAVES



VIKING PANGE COPPOPATION 111 FRONT STREET · GREENWOOD, MS · 38930 · (662) 455-1200

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

FOR PRODUCT INFORMATION, CALL 1-888-VIKING 1 (845)4641 OF VIOIT THE VIKING WEB OITE AT VIKINGRANGE. COM